

EXHIBIT 1. RF EXPOSURE REQUIREMENTS [§§ 15.247(i), 1.1310 & 2.1091]

1.1. Limits

§ 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500			f/300	<6
1500-100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500			f/1500	<30
1500-100,000			1.0	<30

f = frequency in MHz

* = Plane-wave equivalent power density

Note 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

1.2. Method of Measurements

Calculation Method of Power Density/RF Safety Distance:

$$S = \frac{PG}{4\pi \cdot r^2} = \frac{EIRP}{4\pi \cdot r^2}$$

Where,

P: power input to the antenna in mW

EIRP: Equivalent (effective) isotropic radiated power.

S: power density mW/cm²

G: numeric gain of antenna relative to isotropic radiator

r: distance to centre of radiation in cm

1.3. RF Evaluation

47 CFR 1.1307(b)(3)(ii) For multiple RF sources: Multiple RF sources are exempt if:

- (A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in [paragraph \(b\)\(3\)\(i\)\(A\)](#) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).
- (B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for P_{th} , including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$ = the exemption threshold power (P_{th}) according to [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for fixed, mobile, or portable RF source i .

ERP_j = the ERP of fixed, mobile, or portable RF source j .

$ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source j , at a distance of at least $\lambda/2\pi$ according to the applicable formula of [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section.

$Evaluated_k$ = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

$Exposure Limit_k$ = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k , as applicable from [§ 1.1310 of this chapter](#).

1.3.1. MPE for RFID Standalone (13.56 MHz)

Below is the Standalone RF Exposure from the 13.56 MHz Tx of the Terminal without factoring any collocation with Integration of approved Radio module:

Calculated Exposure Ratio for NBS Payment Solutions Inc. RFID Reader					
Frequency (MHz)	¹ EIRP (mW)	Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)	Exposure Ratio
13.56	0.000188	20	0.000000037	0.979	0.00000004
¹ The EIRP is computed with the measured field strength of 13.56 MHz Transmitter (47.51 at dBµV/m at 10m) using the following formula: $\text{EIRP} = (E \times d)^2 / 30$, where E = electric field strength in V/m, d = measurement distance in meters (m)					

1.3.2. MPE for Co-location with RF Module

The following addresses the co-location of the transmitters within the EUT at a minimum 20 cm evaluation separation distance, which consist of NBS Payment Solutions Inc. RFID Reader and Murata Manufacturing Co., Ltd. WLAN+Bluetooth Module (FCC ID: VPYLB2AE)

Source Option	Maximum MPE Ratio		Sum of the MPE ratios from all sources
	NBS Payment Solutions Inc. RFID Reader	Murata Manufacturing Co., Ltd. WLAN+Bluetooth Module (FCC ID: VPYLB2AE)	
1	0.00000004	0.047	0.047

The sum of the MPE ratios from all sources is < 1. Thus, in compliant with general public (uncontrolled environment) MPE limit.

For detailed MPE ratios calculation, refer to the following tables.

Calculated Exposure Ratio for NBS Payment Solutions Inc. RFID Reader					
Frequency (MHz)	¹ EIRP (mW)	Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)	Exposure Ratio
13.56	0.000188	20	0.000000037	0.979	0.00000004
¹ The EIRP is computed with the measured field strength of 13.56 MHz Transmitter (47.51 at dBµV/m at 10m) using the following formula: $\text{EIRP} = (E \times d)^2 / 30$, where E = electric field strength in V/m, d = measurement distance in meters (m)					

¹Calculated MPE Ratio for Murata Manufacturing Co., Ltd. WLAN+Bluetooth Module
(FCC ID: VPYLB2AE, IC: 772C-LB2AE)

WIFI 2.4G (Worst case)							
Operating Mode	Output Power with tolerance		Antenna Gain		Power density (mW/cm ²)	Limit	MPE Ratio
	(dBm)	(mW)	(dBi)	(num)			
802.11b	19	79.43	2.2	1.66	0.026	1	0.026
802.11g	18	63.1	2.2	1.66	0.021	1	0.021
802.11n20	18	63.1	2.2	1.66	0.021	1	0.021

WIFI 5G (Worst case)							
Operating Mode	Output Power with tolerance		Antenna Gain		Power density (mW/ cm ²)	Limit	MPE Ratio
	(dBm)	(mW)	(dBi)	(num)			
802.11a	18.5	70.79	5.2	3.31	0.047	1	0.047
802.11ac20	17.5	56.23	5.2	3.31	0.037	1	0.037
802.11n20	17.5	56.23	5.2	3.31	0.037	1	0.037
802.11ac40	16	39.81	5.2	3.31	0.026	1	0.026
802.11n40	16	39.81	5.2	3.31	0.026	1	0.026
802.11ac80	13	19.95	5.2	3.31	0.013	1	0.013

¹ The test data of the radio module represented in this table is derived from Murata Manufacturing Co., Ltd. WLAN+Bluetooth Module MPE report. Refer to the report for details under FCC ID: VPYLB2AE. Report Number: 4790016144.1-AE-5. Calculations are an estimate based on proposed antenna gains and disabling of BLE/BT function)