



849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA
PH: 888.472.2424 OR
352.472.5500
FAX: 352.472.2030
EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

RF Exposure Evaluation Report

APPLICANT	CRESCEND TECHNOLOGIES, LLC
	140 E. State Parkway SCHAUMBURG IL 60173 USA
FCC ID	CWWDSDTUH50
MODEL NUMBER	DSDUH50
PRODUCT DESCRIPTION	UHF AMPLIFIER
STANDARD APPLIED	CFR 47 Part 2.1091
PREPARED BY	Franklin Rose

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

GENERAL REMARKS

Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

**Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669**

Authorized Signatory Name:



Franklin Rose, Project Manager / Testing Technician

Date: 02/27/2018

RF Exposure Requirements

General information

Device type: UHF AMPLIFIER

Antenna

The manufacturer does not specify an antenna, but a typical antenna has a gain of 5 dBi.

Configuration	Antenna p/n	Type	Max. Gain (dBi)
Fixed mounted	Any	omni	5

Operating configuration and exposure conditions:

The conducted output power is shown in the table below. Typical use qualifies for a maximum duty cycle factor of 100%.

MPE Calculation:

The minimum separation distance is calculated as follows:

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power density: } P_d(mW/cm^2) = \frac{E^2}{3770}$$

The limit for general uncontrolled exposure environment is shown in FCC rule Part 1.1310, Table 1.

Minimum Separation Distance for Mobile or Fixed Devices General Population/Uncontrolled Exposure

Insert values in yellow highlighted boxes to determine Minimum Separation Distance

Max Power	50	W	<i>equals</i>	Max Power	50000	mW
Duty Cycle	100	%	<i>equals</i>	Duty Factor	1	numeric
Antenna Gain	5	dBi	<i>equals</i>	Gain numeric	3.162278	numeric
Coax Loss	0	dB		Gain - Coax Loss	3.162278	numeric
Power Density	0.3	mW/cm ²				
Frequency	512	MHz				

Enter power Density from the chart to the right

Rule Part 1.1310, Table 1 (B)

Frequency range	Power den	Enter this value
MHz	mW/cm ²	mW/cm ²
0.3-1.34	100	100
1.34-30	180/f ²	0.0
30-300	0.2	0.2
300-1,500	f/1500	0.3
1,500-100,000	1	1

f = frequency in MHz

Minimum Separation Distance	205 cm	2.05 m
------------------------------------	---------------	---------------