

EMC TEST REPORT



Standard(s):

**47 CFR FCC Part 15.247
RSS 247, Issue 4, 2025**

**FCC ID: DGFPD202406
IC: 458A-PSD202406**


**Product: 3M™ Scott™ XT PRO PASS Alarm (AoA Beacon BLE)
Model(s): 202406-01**

**Company Name:
3M Company**

**Address:
Fire & SCBA Solutions
4320 Goldmine Road, Monroe, NC 28110**

**Report Number: HRE202510498-7
Report Issue Date: October 1, 2026**

Report Prepared by:

Signature: 
**Yuriy Litvinov
Lead EMC Engineer**

**Tested by:
3M Company, Hardgoods Regulatory Engineering Laboratory
410 E. Fillmore Avenue, Building 76
St. Paul, Minnesota 55107-1208, USA**



TABLE OF CONTENTS

Item		Description	Page
1.0		Test Summary	3
	1.1	Measurement Uncertainty	3
	1.2	Test Facility	3
2.0		Equipment Description	4
	2.1	Equipment Under Test	4
3.0		EUT Configuration	5
	3.1	System Configuration	5
	3.2	Input/Output Ports of EUT	5
	3.3	Cables	5
	3.4	Measurement Arrangements of EUT	5
	3.5	Exercising of EUT and Interfaces	5
4.0		Test Conditions and Results	6
	4.1	DTS Bandwidth	6
	4.2	Maximum Peak Conducted Output Power	8
	4.3	Maximum Power Spectral Density level	10
	4.4	Radiated Emissions in restricted band	12
	4.5	Radiated Emissions in non-restricted band	30
	4.6	DTS Band-edge Emissions Measurements	32
	4.7	Conducted Emissions	33
5.0		Test Equipment	34
6.0		Revision History	34

3M	3M EMC Laboratory	Report Number: HRE202510498-7 Date: October 1, 2026	Page 3 of 34
-----------	--------------------------	--	--------------

1.0 Test Summary

Based on the results of our investigation, we have concluded the product tested **comply** with the requirements of the standard(s) indicated. The results obtained in this test report pertain only to the item(s) tested.

	Requirement – Test	Test Description	Result	Comments
4.1	FCC Part 15.247(a)(2)/ RSS-247(6.3.1(a))/RSS-Gen (6.7)	DTS Bandwidth	pass	
4.2	FCC Part 15.247(b)(3)/ RSS-247(6.3.2)	Maximum Peak Conducted Output Power	pass	
4.3	FCC Part 15.247(e)/ RSS-247(6.3.1(b))	Maximum Power Spectral Density level	pass	
4.4	FCC Part 15.209 RSS-Gen, 8.9	Radiated Emissions in restricted band	pass	
4.5	FCC Part 15.247(d)/ RSS-247(6.6)	Radiated Emissions in non-restricted band	pass	
4.6	FCC Part 15.247(d)(1)/ RSS-247(6.6)	DTS Band-edge Emissions Measurements	pass	
4.7	FCC Part 15.207/ RSS-Gen (8.8)	Conducted Emissions	N/A	

Note:	Device is battery operated.
--------------	-----------------------------

1.1 Measurement Uncertainty

The measured value related to the corresponding limit will be used to decide whether the equipment meets the requirements. The measurement uncertainty figures were calculated and correspond to a coverage factor of k=2, providing a confidence level of respectively 95.45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian).

Radiated emissions 30MHz to 1000MHz	4.9 dB
Radiated emissions 1GHz to 18GHz	4.6 dB
Conducted emissions 150KHz to 30MHz (AMN)	2.7 dB
Conducted emissions 150KHz to 30MHz (AAN)	1.92 dB
RF frequency	$\pm 3 \times 10^{-8}$
RF power, conducted	1.4 dB
RF Power Spectral Density	0.96 dB

1.2 Test Facility

Test Facility Accreditations:	ISO/IEC 17025:2017, NVLAP LAB CODE: 200033-0
	FCC US502
	ISED Canada CAB identifier: US0012



2.0 Equipment Description

2.1	Equipment Under Test			
Description:	Sensor Module Assembly: Electronics control module for battery power, audio (alarm tones), the Integrated Pak-Tracker 2.0 PCBA, Ultra-Wide Band PCBA, data logging, and the motion sensor. Sensor Module contains two antennas (IPT&BFE) controlled by RF Switch.			
Model(s):	202406-01			
Serial number:	N/A			
3M Division:	Personal Safety			
Modifications and Special Measures:	none			
Frequency Range:	2402-2480MHz			
Channel No.:	39			
Modulation Type:	GFSK			
FCC Classification:	Digital Transmission System (DTS)			
Conducted RF Output Power:	20.2 dBm (104.7mW)			
Antenna Type and Antenna Assembly Gain:	☐ External	☒ Integral PCB Antenna	☐ Dedicated	
	☒ 4dBi (IPT) ☒ 4dBi (BFE)	☐ Declared by the Manufacturer	☒ Measured	
Test Deviations or Exclusions	☐ Yes	☒ No		
Rated Power:	Voltage:	☐ 120VAC	☐ 230VAC	☒ 7.4VDC
	Phase:	☐ 1ph	☐ 3ph	☒ Li-ion Battery
	Frequency:	☐ 50Hz	☐ 60Hz	
	Current:	N/A		
Test Dates:	14/07-14/08/2026			
Received Date:	13/07/2026			
Received Conditions:	☐ Poor	☒ Good		
	☒ Prototype	☐ Production		

3.0 EUT Configuration

3.1 System Configuration

No.	Product Type	Manufacturer	Model	Comments
1	EUT	3M	202406-01	
2	Battery	Inventus Power	902-09531-001	Li-ion/7.4VDC
3	Notebook PC	HP	Zbook	Support Equipment

3.2 Input/Output Ports of EUT

No.	Description	Type	Comments
1	Pressure Transducer	12 pin	Bulkhead Mount Circular Connector
2	Sensor Module, Console	11 pin	Bulkhead Mount Circular Connector

3.3 Cables

No.	Description	Type	Length	Shielding	Comments
1	Control Cables	Twisted Pair	1m	Yes	
2					

3.4 Measurement Arrangements of EUT

	Intended Operational Arrangement(s)	Comments
☒	Table-top only	
☐	Floor-standing only	
☐	Floor-standing or table-top	
☒	Other	Body-worn


3.5 Exercising of EUT and Interfaces

No.	Mode of Operation
1	Transmitting at lowest, middle and highest channels of operation using modulated carrier at each operation mode according to applicable Bluetooth test protocol (BLE AoA Beacon 1mbps)
2	Device programming over Python 3.14.0 Terminal Software using SCBA Radio Testing GUI ver. 1.2.0 provided by the manufacturer for continuous transmission of modulated carrier at maximum rated RF output power and Duty Cycle.


4.0 Test Conditions and Results

4.1	DTS Bandwidth		
	Laboratory Ambient Temperature:	23°C	
	Relative Humidity:	48%	
	Atmospheric Pressure:	1011 mbars	
Reference Standard(s):	☒ ANSI C63.10:2020, Section 11.8.2 ☒ FCC Part 15.247/RSS 247 ☒ KDB 558074	Measurement Point ☒ Conducted ☐ Radiated	
Frequency Range:	☒ 2402-2480.0MHz	RBW = 51KHz/100KHz VBW ≥ 3 x RBW	
Nominal Voltage:	☐ 120VAC ☒ 7.4VDC		
Test Personnel:	Yuriy Litvinov <i>Yuriy Litvinov</i>		Date: 07/28/2026


Frequency (MHz)	Data Rate	RSS Gen 99% dB Bandwidth (KHz)	FCC Part 15.247 6 dB Bandwidth (KHz)	6dB OBW Limit (KHz)	Results
2402	1mbps	1067	709.8	> 500	pass
2440	1mbps	1073	744.3	> 500	pass
2480	1mbps	1089	721.8	> 500	pass




FCC Part 15.247 OBW – BLE Low Channel




RSS Gen OBW – BLE Low Channel




FCC Part 15.247 OBW – BLE Mid Channel



RSS Gen OBW – BLE Mid Channel



FCC Part 15.247 OBW – BLE High Channel






RSS Gen OBW – BLE High Channel

3M	3M EMC Laboratory	Report Number: HRE202510498-7 Date: October 1, 2026	Page 8 of 34
-----------	--------------------------	--	--------------

4.2	Maximum Output Power		
Method:	Measurements was performed with CW carrier at the highest power level at which the transmitter is intended to operate. The analyzer offset was adjusted to compensate for the attenuator and other losses.		
		Laboratory Ambient Temperature:	23°C
		Relative Humidity:	48%
		Atmospheric Pressure:	1011 mbars
Reference Standard(s):	☒ ANSI C63.10:2020, Section 11.9 ☒ FCC Part 15.247/RSS 247 ☒ KDB 558074	Measurement Point ☒ Conducted ☐ Radiated	
Frequency Range:	☒ 2402-2480.0MHz		
Antenna Gain:	4.0dBi	Maximum Conducted RMS Power:	
Limit:	30 dBm	20.2 dBm (104.7mW)	
Nominal Voltage:		☐ 120VAC ☒ 7.4VDC	
Test Personnel:	Yuriy Litvinov <i>Yuriy Litvinov</i>		Date: 07/28/2026




Note:	EIRP (dBm) = Conducted Power (dBm) +Antenna Gain (dBi)= 20.2+4.0=24.2dBm
--------------	--



Conducted RF Power



3M	3M EMC Laboratory	Report Number: HRE202510498-7 Date: October 1, 2026	Page 10 of 34
-----------	--------------------------	--	---------------

4.3	Maximum Power Spectral Density level		
Method:	Measurements was performed with modulated carrier at the highest power level at which the transmitter is intended to operate. The analyzer offset was adjusted to compensate for the attenuator and other losses.		
	Laboratory Ambient Temperature:	23°C	
	Relative Humidity:	48%	
	Atmospheric Pressure:	1011 mbars	
Reference Standard(s):	☒ ANSI C63.10:2020, Section 11.10.2 ☒ FCC Part 15.247/RSS 247 ☒ KDB 558074	Measurement Point ☒ Conducted ☐ Radiated	
Frequency Range:	☒ 2425.0 MHz	PSD Results	
PSD Limit:	8 dBm in any 3KHz band	6.1dBm	
Nominal Voltage:	☐ 120VAC ☒ 7.4VDC		
Test Personnel:	Yuriy Litvinov <i>Yuriy Litvinov</i>	Date: 07/28/2026	





4.4	Radiated Emissions in restricted band					
Method:	Measurements were made in a 3-meter semi-anechoic chamber that complies to CISPR 16/ANSI C63.4 standards. EUT was rotated through three orthogonal axes to determine which attitude (orientation) and arrangement produces the highest emission relative to the limit; the attitude and device arrangement that produces the highest emission relative to the limit was used in making final radiated emission measurements. Spurious Radiated emissions measurements were performed with external preamp and a high pass filter. Final measurements were then performed by rotating the EUT 360° and adjusting the receive antenna height from 1 to 4 m. All frequencies were investigated in both horizontal and vertical antenna polarity, where applicable.					
Test Verification: ☒		Laboratory Ambient Temperature:		23°C		
		Relative Humidity:		55%		
		Atmospheric Pressure:		1011 mbars		
Reference Standard(s):		☒ ANSI C63.10:2020, Section 11.12.1 ☒ FCC Part 15.205/15.209/RSS Gen (8.9) ☒ KDB 558074		Measurement Distance		
				☒ 3 Meters ☐		
Frequency Range:		☒ 30 MHz to 1 GHz		RBW = 100KHz, VBW ≥ 3 x RBW		
		☒ 1 GHz to 25 GHz		RBW = 1MHz, VBW ≥ 3 x RBW		
Nominal Voltage:		☐ 120VAC ☒ 7.4VDC				
Test Personnel:		Jayden Alstad <i>J.A.</i>			Date: 07/30/2026	
Limits –15.209 and RSS Gen						
Frequency (MHz)		Limit dB (µV/m)			Distance	Results
		Quasi-Peak	Average	Peak		
0.009-0.490			2400/F(KHz)		300	N/A
0.490-1.705		24000/F(KHz)			30	N/A
1.705-30		30			30	N/A
30 to 88		40			3	pass
88 to 216		43.5			3	pass
216 to 960		46			3	pass
Above 960			54	74	3	pass



Modifications:	
Note:	The lower limit applies at the transition frequency. An inverse proportionality factor of 20 dB per decade has been used to normalize the measured data to the specified distance for determining compliance For emission in the restricted bands, the limit of 15.209 was used. There are no emissions were detected in the 15.205 restricted band within 30dB below 15.209 limit adjacent or nearby to 2400-2483.5MHz frequency band during operation at the high channel. No radiated spurious emissions were detected above 18GHz





FCC Part 15.209 Radiated Emissions in restricted band - BFE Antenna, Low Ch.




FCC Part 15.209 Radiated Emissions in restricted band - BFE Antenna, Low Ch.





FCC Part 15.209 Radiated Emissions in restricted band - BFE Antenna, Mid Ch.



FCC Part 15.209 Radiated Emissions in restricted band - BFE Antenna, Mid Ch.



FCC Part 15.209 Radiated Emissions in restricted band - BFE Antenna, High Ch.



FCC Part 15.209 Radiated Emissions in restricted band - BFE Antenna, High Ch.



Tables - Radiated Emissions in restricted band



Frequency (MHz)	Pol.	QP Reading dB μ V/m	Total CF dB	Net at 3 m dB μ V/m	Limit (dB μ V/m)	Margin dB
35.63	H	4.1	17	21.1	40	-18.9
197.72	H	8.1	15	23.1	43.5	-20.4
330.11	H	7.1	19.7	26.8	46	-19.2
984.02	H	3.6	30.4	34	54	-20
Notes:	Net Reading (dB μ V) = Reading (dB μ V) + Antenna CF(dB)+Cable CF(dB) – Amp Gain(dB) BLE Low Channel – BFE Antenna					

Frequency (MHz)	Pol.	QP Reading dB μ V/m	Total CF dB	Net at 3 m dB μ V/m	Limit (dB μ V/m)	Margin dB
35	H	4.1	17	21.1	40	-18.9
201.08	H	7.8	14.9	22.7	43.5	-20.8
330.32	H	6.1	19.7	25.8	46	-20.2
956.27	H	3.6	30.4	34	46	-12
Notes:	Net Reading (dB μ V) = Reading (dB μ V) + Antenna CF(dB)+Cable CF(dB) – Amp Gain(dB) BLE Mid Channel – BFE Antenna					



Frequency (MHz)	Pol.	QP Reading dB μ V/m	Total CF dB	Net at 3 m dB μ V/m	Limit (dB μ V/m)	Margin dB
36.74	V	4	17.1	21.1	40	-18.9
198.41	H	8.2	14.9	23.2	43.5	-20.3
333.68	H	7.9	19.7	27.6	46	-18.4
963.5	H	3.6	30.4	34	54	-20
Notes:	Net Reading (dB μ V) = Reading (dB μ V) + Antenna CF(dB)+Cable CF(dB) – Amp Gain(dB) BLE High Channel – BFE Antenna					

Tables - Radiated Emissions in restricted band



[illegible][illegible][illegible]





FCC Part 15.209 Radiated Emissions in restricted band - IPT Antenna, Low Ch.





FCC Part 15.209 Radiated Emissions in restricted band - IPT Antenna, Low Ch.





FCC Part 15.209 Radiated Emissions in restricted band - IPT Antenna, Mid Ch.



FCC Part 15.209 Radiated Emissions in restricted band - IPT Antenna, Mid Ch.



FCC Part 15.209 Radiated Emissions in restricted band - IPT Antenna, High Ch.



FCC Part 15.209 Radiated Emissions in restricted band - IPT Antenna, High Ch.



Tables - Radiated Emissions in restricted band

Frequency (MHz)	Pol.	QP Reading dB μ V/m	Total CF dB	Net at 3 m dB μ V/m	Limit (dB μ V/m)	Margin dB
114.17	H	4.2	15.2	19.4	43.5	-24.1
195.59	H	4.5	15.4	19.9	43.5	-23.6
347.84	H	3.9	19.9	23.8	46	-22.2
545.72	V	2.9	24.3	27.2	46	-18.8
Notes:	Net Reading (dB μ V) = Reading (dB μ V) + Antenna CF(dB)+Cable CF(dB) – Amp Gain(dB) BLE Low Channel – IPT Antenna					

Frequency (MHz)	Pol.	QP Reading dB μ V/m	Total CF dB	Net at 3 m dB μ V/m	Limit (dB μ V/m)	Margin dB
44.18	V	2.8	18	20.8	40	-19.2
195.62	H	6.4	15.4	21.8	43.5	-21.7
348.32	H	5	19.9	24.8	46	-21.2
545.14	V	3.1	24.3	27.4	46	-18.6
Notes:	Net Reading (dB μ V) = Reading (dB μ V) + Antenna CF(dB)+Cable CF(dB) – Amp Gain(dB) BLE Mid Channel – IPT Antenna					

Frequency (MHz)	Pol.	QP Reading dB μ V/m	Total CF dB	Net at 3 m dB μ V/m	Limit (dB μ V/m)	Margin dB
36.32	H	3.8	17.1	20.9	40	-19.1
196.01	H	7	15.3	22.3	43.5	-21.2
349.1	H	3.8	19.8	23.6	46	-22.4
550.85	V	4.7	24.3	29	46	-17
Notes:	Net Reading (dB μ V) = Reading (dB μ V) + Antenna CF(dB)+Cable CF(dB) – Amp Gain(dB) BLE High Channel – IPT Antenna					

Tables - Radiated Emissions in restricted band

[illegible][illegible][illegible]

**Duty Cycle Correction factor**

AoA Beacon (BLE 1Mbit PHY)

Data Rate 1 Mbps/125 kbytes/sec
Bit Timing 1 usec/bit
Byte Timing 8 sec/byte

ADV_EXT_IND PDU type 23 bytes/184 usec
Preamble 1 byte
Access address 4 bytes
Packet header 2 bytes
Ext header len 1 byte
Ext header flags 1 byte
Adv address 6 bytes
Adv data info 2 bytes
Adv aux pointer 3 bytes
CRC 3 bytes
Carrier on to PDU start 6 usec
PDU end to carrier off 10 usec

AUX_ADV_IND PDU type 106 bytes, max 848 usec
Preamble 1 byte
Access address 4 bytes
Packet header 2 bytes
Ext header len 1 byte
Ext header flags 1 byte
Adv data info 2 bytes
Adv sync info 18 bytes
Advertising data 24 bytes
Opt. adv data 50 bytes, max
CRC 3 bytes
Carrier on to PDU start 6 usec
PDU end to carrier off 10 usec

AUX_SYNC_IND PDU type 16 bytes 128 usec
Preamble 1 byte
Access address 4 bytes
Packet header 2 bytes
Ext header len 1 byte
Ext header flags 1 byte
CTE info 1 byte
Adv aux pointer 3 bytes, max
CRC 3 bytes
CTE 160 usec
Carrier on to PDU start 6 usec
CTE end to carrier off 10 usec



Max time (per PDU type)
ADV_EXT_IND 200 usec
AUX_ADV_IND 864 usec
AUX_SYNC_IND 304 usec
Max PDU count (in 100 msec interval)
ADV_EXT_IND 6 advertisements/100 msec
AUX_ADV_IND 2 advertisements/100 msec
AUX_SYNC_IND 25 transmissions/100 msec
Max time TX (in 100 msec interval)
ADV_EXT_IND 1200 usec
AUX_ADV_IND 1728 usec
AUX_SYNC_IND 7600 usec
Total 10528 usec

Duty cycle = Time On /100 msec **$20 \cdot \log_{10}(10.5/100) = -19.6\text{dB}$ which was be applied to the Peak measurement for a corrected Average value**



3M	3M EMC Laboratory	Report Number: HRE202510498-7 Date: October 1, 2026	Page 30 of 34
-----------	--------------------------	--	---------------

4.5	Radiated Emissions in non-restricted band		
Method:	The measurements were made with transmitter set to transmit continuously.		
	Laboratory Ambient Temperature:	23°C	
	Relative Humidity:	48%	
	Atmospheric Pressure:	1011 mbars	
Reference Standard(s):	☒ ANSI C63.10:2020, Section 11.11 ☒ FCC Part 15.247/RSS 247 ☒ KDB 558074	Measurement Point ☒ Conducted ☐ Radiated	
Frequency Range:	☒ 2402-2480.0 MHz		
In-band power in 100KHz:	☒ 20.9dBm	Results:	
Limit:	☒ -10dBm (30dBc below in-band power)	>60dBc	
Nominal Voltage:	☐ 120VAC ☒ 7.4VDC		
Test Personnel:	Yuriy Litvinov <i>Yuriy Litvinov</i>	Date: 07/28/2026	



Note:	A notch filter was installed to prevent system overload at 2.4GHz
--------------	---



Conducted Spurious – Low Ch.




Conducted Spurious – Mid Ch.




Conducted Spurious- High Ch.

4.6	Band-Edge Compliance		
Method:	The measurements were made with transmitter set to transmit continuously with modulated signal at low and high channels.		
	Laboratory Ambient Temperature:	23°C	
	Relative Humidity:	48%	
	Atmospheric Pressure:	1011 mbars	
Reference Standard(s):	☒ ANSI C63.10:2020, Section 11.13.2 ☒ FCC Part 15.247/RSS 247 ☒ KDB 558074	Measurement Point ☒ Conducted ☐ Radiated	
Frequency Range:	☒ 2402-2480.0MHz	Results	
Limit:	☒ >30dBc	Low, 2402 MHz > 53dBc High, 2480 MHz > 60dBc	
Nominal Voltage:	☐ 120VAC ☒ 7.4VDC		
Test Personnel:	Yuriy Litvinov <i>Yuriy Litvinov</i>		Date: 07/28/2026

Note:	
--------------	--



Band Edge - Low
Center Freq. 2.400GHz



Band Edge - High
Center Freq. 2.4835GHz

4.7	Conducted Emissions Data			
Method:	The AMN was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane. This distance was between the closest points of the AMN and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the AMN. All power was connected to the system through Artificial Mains Network (AMN). Conducted voltage measurements on mains lines were made at the output of the AMN.			
	All power was connected to the system through Artificial Mains Network (AMN). All tested telecommunications lines were connected to an Asymmetric Artificial Network (AAN) and conducted voltage measurements on telecommunications lines were made at the output of the ISN. Where an AAN was not appropriate or available measurements were made using a Capacitive Voltage Probe.			
Test Verification: ☐		Laboratory Ambient Temperature:		
		Relative Humidity:		
		Atmospheric Pressure:		
Reference Standard(s):		☐ RSS Gen/FCC 15.207 ☐ ANSI C63.4:2014 ☐ ANSI C63.10:2020	Measurement Point ☐ Mains ☐ Telecommunication ports ☐	
Nominal Voltage:		☐ 120VAC ☐ 230VAC ☐ VDC		
Test Personnel:			Date:	
Limits – Part 15.207/RSS Gen – AC Mains				
Frequency (MHz)	Limit dB (µV)			
	Quasi-Peak	Average	Result	Comments
0.15 to 0.50	66 to 56	56 to 46	N/A	
0.50 to 5	56	46	N/A	
5 to 30	60	50	N/A	

Modifications:	
Note:	

5.0	Test Equipment				
Test Equipment Used					
Description	Manufacturer	Model	Identifier	Last Cal. Date	Check
Biconilog Antenna	Schwarzbeck	VULB 9168	9168-1070	10/20/2025	☒
Horn Antenna	A.H. Systems	SAS 571	1010	10/20/2025	☒
Loop Antenna	A.H. Systems	EHA-51B	1213E	10/20/2025	☐
EMI Receiver	Rohde & Schwarz	ESW26	101412	10/20/2025	☒
Signal Analyzer	Agilent	N9000A	MY53031040	10/20/2025	☒
EMI Receiver	Agilent	E4448A	1530975	10/20/2025	☒
LISN	TESEQ	NNB51	1130	10/20/2025	☐
Coaxial Cable	Insulated Wire	2803	CBL2039	10/20/2025	☒
EMC Software	ETS-Lindgren	TILE 7		N/A	☒
Equipment Calibration Interval:		☒ 12 months ☐ 24 months			

6.0	Report revision history		
Revision Level	Date	Report Number	Notes
0	10/01/2026	HRE202510498-7	Original Issue