

RF Exposure Statement: JP21R26X 002

Page 1 of 2

Client: **NEC Corporation**
 1753 Shimonumabe, Nakahara-ku, Kawasaki City, Kanagawa, 211-8666
 Japan

Test item: **5G NR FR1 Base Station Sub6 Massive MIMO RU**

Identification: **MB5420-m5770-62**

FCC Requirement

According to FCC 1.1307(b), fixed RF source must comply with the following applicable limit for maximum permissible exposure (MPE) specified in FCC 1.1310:

Equipment Use	Frequency Range	Power Density [mW/cm ²]	Average Time [min]
General Population / Uncontrolled Exposure	1.5 – 100GHz	1	30
Occupational / Controlled Exposure	1.5 – 100GHz	5	30

Assessment Result

The distance where the MPE limit for General Population / Uncontrolled Exposure is met is given in the following table:

Maximum EIRP [dBm]	Maximum EIRP [mW]	Distance [cm] Power Density = 1mW/cm ²	Proposed Minimum RF Safety Distance [cm]
68.44	6982324.041	745.41	746

Note:

The distance [cm] is calculated according to the Friis formula: $D = \sqrt{EIRP / (4\pi \cdot S)}$, where

S = power density in mW/cm²

EIRP = Effective Isotropically Radiated Power in mW

The distance where the MPE limit for Occupational / Controlled Exposure is met is given in the following table:

Maximum EIRP [dBm]	Maximum EIRP [mW]	Distance [cm] Power Density = 5mW/cm ²	Proposed Minimum RF Safety Distance [cm]
68.44	6982324.041	333.36	334

Note:

The distance [cm] is calculated according to the Friis formula: $D = \sqrt{EIRP / (4\pi \cdot S)}$, where

S = power density in mW/cm²

EIRP = Effective Isotropically Radiated Power in mW

Prüfbericht - Nr.: 12603897 001

Test Report No.:

Seite 2 von 2

Page 2 of 2

Conclusion

The device complies with the FCC RF exposure requirements with minimum RF safety distance of 746cm for General Population / Uncontrolled Exposure and 334cm for Occupational / Controlled Exposure.

Refer to test report JP21R26X 001 for more details.

TÜV Rheinland Japan Ltd. – Global Technology Assessment Center

4-25-2 Kita-Yamata, Tsuzuki-ku, Yokohama 224-0021, Japan