



EMC Test Data

Client: TOA	Job Number: J41858
Model: WM-3310	T-Log Number: T43245
	Proj Eng: David Bare
Contact: Hisayuki Okuoka	
Spec: FCC & Canada	Class: N/A

Section 2.1055: Frequency Stability

Test Specifics

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 7/7/01	Config. Used: 1
Test Engineer: jmartinez	Config Change: None
Test Location: Enviromental Chamber	EUT Voltage: 9Vdc

General Test Configuration

A spectrum analyzer and support equipment were all place on top of a table, located outside the temperature chamber. A pick-up antenna was used to receive the CW carrier. The pick-up probe was connected to a spectrum analyzer, which was used ot measure

Ambient Conditions: Temperature: N/A
 Rel. Humidity: N/A

Summary of Results

Run #	Test Performed	Limit	Result	Comments
1	Temperature Vs. Frequency	90.265	Pass	

Modifications Made During Testing: None



EMC Test Data

Client: TOA

Job Number: J41858

Model: WM-3310

T-Log Number: T43245

Proj Eng: David Bare

Contact: Hisayuki Okuoka

Spec: FCC & Canada

Class: N/A

Run# 1: Temperature Vs. Frequency

Frequency: 171.04 MHz

Temperature	Drift	99% Occupied BW	Limit
Celsius	(Hz)	(kHz)	(kHz)
-30	-750	49.2	+/-32.5
-20	0	49.4	+/-32.5
-10	750	49.9	+/-32.5
0	1300	49.5	+/-32.5
10	1000	50	+/-32.5
20	800	49.7	+/-32.5
30	800	49.5	+/-32.5
40	500	49.2	+/-32.5
50	200	49.2	+/-32.5

Note:

For this test the modulation test tone (2.5 kHz) was injected directly into the belt-strap microphone (Max input was -26 dBm). The Occupied Bandwidth was measured for each temperature change.