

FCC Part 15 Subpart C
EMI TEST REPORT
of

E.U.T. : Remote Control Signal Sender

FCC ID. : DT9T-8000

MODEL : T-8000

Working Frequency : 432.970 MHz

for

APPLICANT : JEBSEE ELECTRONICS CO., LTD.

ADDRESS : 24-3, SIN-LO ROAD, P.O. BOX 57, TAINAN,
TAIWAN, R.O.C.

Test Performed by

ELECTRONICS TESTING CENTER, TAIWAN

NO. 8 LANE 29, WENMIMG ROAD,
LOSHAN TSUN, KWEISHAN HSIANG,
TAOYUAN, TAIWAN, R.O.C.

Tel:(03)3280026-32

Fax:(03)3280034

Report Number : ET89R-09-079-01

TEST REPORT CERTIFICATION

Applicant : JEBSEE ELECTRONICS CO., LTD.
24-3, SIN-LO ROAD, P. O. BOX 57, TAINANN, TAIWAN,
R.O.C.

Manufacturer : JEBSEE ELECTRONICS CO., LTD.
24-3, SIN-LO ROAD, P. O. BOX 57, TAINANN, TAIWAN,
R.O.C.

Description of EUT :

a) Type of EUT : Remote Control Signal Sender
b) Trade Name : JEBSEE
c) Model No. : T-8000
d) FCC ID : DT9T-8000
e) Working Frequency : 432.970 MHz
f) Power Supply : Adaptor Model : U180010D12
I/P : AC 120V/60Hz; O/P : 18VDC, 100mA

Regulation Applied : FCC Rules and Regulations Part 15 Subpart C (1999)

I HEREBY CERTIFY THAT; The data shown in this report were made in accordance with the procedures given in ANSI C63.4 and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

Note : 1. The results of the testing report relate only to the items tested.
2. The testing report shall not be reproduced except in full, without the written approval of ETC.

Issued Date : Dec. 02, 2000

Test Engineer : Jeff Chuang
(Jeff Chuang)

Approve & Authorized Signer : Will Yauo
Will Yauo, Supervisor
EMI Test Site of ELECTRONICS
TESTING CENTER, TAIWAN

<i>Table of Contents</i>	<i>Page</i>
1. GENERAL INFORMATION	1
1.1 PRODUCT DESCRIPTION	1
1.2 CHARACTERISTICS OF DEVICE:	1
1.3 TEST METHODOLOGY	1
1.4 TEST FACILITY.....	1
2. DEFINITION AND LIMITS	2
2.1 DEFINITION	2
2.2 RESTRICTED BANDS OF OPERATION.....	2
2.3 LIMITATION	2
2.4 LABELING REQUIREMENT.....	4
2.5 USER INFORMATION	4
3. RADIATED EMISSION MEASUREMENT.....	5
3.1 APPLICABLE STANDARD	5
3.2 MEASUREMENT PROCEDURE	5
3.3 TEST DATA	7
3.4 FIELD STRENGTH CALCULATION	8
3.5 TRANSMISSION TIME MEASUREMENT	8
3.6 ACTIVATE TIME	8
3.7 CALCULATION OF DUTY FACTOR.....	8
3.8 RADIATED TEST EQUIPMENT.....	9
3.9 MEASURING INSTRUMENT SETUP	9
3.10 RADIATED MEASUREMENT PHOTOS	10
4. BANDWIDTH OF EMISSION	11
4.1 APPLICABLE STANDARD PLOT GRAPHIC OF BANDWIDTH	11
4.2 BANDWIDTH TEST EQUIPMENT	11
4.3 PLOT GRAPHIC OF BANDWIDTH	11
5. CONDUCTED EMISSION MEASUREMENT	12
5.1 STANDARD APPLICABLE	12
5.2 MEASUREMENT PROCEDURE	12
5.3 CONDUCTED EMISSION DATA.....	13
5.4 RESULT DATA CALCULATION	13
5.5 CONDUCTED MEASUREMENT EQUIPMENT.....	13
5.6 PHOTOS OF CONDUCTION MEASURING SETUP	14
APPENDIX 1 : PLOTTED DATA FOR DUTY FACTOR.....	15
APPENDIX 2 : PLOTTED DATA FOR BANDWIDTH.....	16
APPENDIX 3 : PLOTTED DATA FOR CONDUCTED EMISSION.....	17

1. GENERAL INFORMATION

1.1 Product Description

a) Type of EUT	: Remote Control Signal Sender
b) Trade Name	: JEBSEE
c) Model No.	: T-8000
d) FCC ID	: DT9T-8000
e) Working Frequency	: 432.970 MHz
f) Power Supply	: Adaptor Model : U180010D12 I/P : AC 120V/60Hz; O/P : 18VDC, 100mA

1.2 Characteristics of Device:

The EUT is a transmitter of remote control. This device apply to light control (On/Off), also with a timer function.

1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in chapter 13 of ANSI C63.4.

The Transmitter under test was operated continuously in its normal operating mode for the purpose of the measurements. In order to secure the continuous operation of the device under test, rewiring in the circuit was done by the manufacturer so as to affect its intended operation.

The receiving antenna polarized horizontally was varied from 1 to 4 meters and the wooden turntable was rotated through 360 degrees to obtain the highest reading on the field strength meter or on the display of the spectrum analyzer. And also, each emission was to be maximized by changing the orientation of the Transmitter under test.

In order to determining the average value during one pulse train of the radiated power generated from the Transmitter under test, the encoded wave form in the time domain was used.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the roof top of Building at No.34, Lin 5, Ding Fu Tsun, Linkou Hsiang, Taipei Hsien, Taiwan, R.O.C.

This site has been fully described in a report submitted to your office, and accepted in a letter dated Feb. 10, 2000.

2. DEFINITION AND LIMITS

2.1 Definition

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

2.2 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.25
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3360-4400	Above 38.6
13.36-13.41			

Remark “**” : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2.3 Limitation

(1) Conducted Emission Limits :

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the conducted limit is the following:

Frequency (MHz)	Emission (μ V)	Emission (dB μ V)
0.45 - 30.0	250	48.0

(2) Radiated Emission Limits :

According to 15.231 ,Periodic operation in the band 40.66-40.70 MHz and above 70 MHz, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Frequency Band (MHz)	Field strength of Fundamental (uV/m)	Field strength of Spurious (uV/m)
40.66-40.70	2250	225
70-130	1250	125
130-174	*1,250 to 3,750	*125 to 375
174-260	3750	375
260-470	*3,750 to 12,500	*375 to 1250
Above 470	12500	1250

* Linear interpolations.

According to 15.235, the field strength of emissions from intentional radiators operated under these frequency bands shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental $\mu\text{V}/\text{meter}$	$\text{dB}\mu\text{V}/\text{meter}$
49.82 - 49.90	10000	80

Field strength limits are at the distance of 3 meters, emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209,as following table:

Other Frequencies (MHz)	Field Strength of Fundamental $\mu\text{V}/\text{meter}$	$\text{dB}\mu\text{V}/\text{meter}$
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above 960	500	54.0

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

(3) Limit of transmission time

- a) A manually operated Transmitter shall employ a switch that will automatically deactivate the Transmitter (Transmitter) within not more than 5 seconds of being released.
- b) A Transmitter activated automatically shall cease transmission within 5 seconds after activation.

2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

3. RADIATED EMISSION MEASUREMENT

3.1 Applicable Standard

For periodic operation intentional radiator, the radiated emission shall comply with § 15.231(b).

3.2 Measurement Procedure

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively. Turn on EUT and make sure that it is in normal function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.
7. Check the three frequencies of highest emission with varying the placement of cables (if any) associated with EUT to obtain the worse case and record the result.

Figure 1 : Frequencies measured below 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



3.3 Test Data

A. Fundamental Emission Measurement

Test Date: SEP. 27 2000Temperature : 23 °CHumidity: 50 %

Frequency (MHz)	Ant Pol H/V	Reading (dBuV) Peak	Factor (dB)		Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (m)
			C	D	Peak	Ave.	Peak	Ave.			
432.970	H	84.3	-5.5	-9.6	78.8	69.2	100.8	80.8	-11.6	360	1.50
865.940	V	53.1	2.3	-9.6	55.4	45.8	80.8	60.8	-15.0	180	1.00
1298.910	V	59.5	-8.4	-9.6	51.1	41.5	80.8	60.8	-19.3	0	1.00
1731.880	H/V	---	-6.2	-9.6	---	---	80.8	60.8	---	---	---
2164.850	H/V	---	-4.0	-9.6	---	---	80.8	60.8	---	---	---
2597.820	H/V	---	-2.4	-9.6	---	---	80.8	60.8	---	---	---
3030.790	H/V	---	-1.1	-9.6	---	---	80.8	60.8	---	---	---
*3463.760	H/V	---	-0.1	-9.6	---	---	74.0	54.0	---	---	---
*3896.730	H/V	---	1.6	-9.6	---	---	74.0	54.0	---	---	---
4329.700	H/V	---	2.0	-9.6	---	---	80.8	60.8	---	---	---

Note :

1. Factor C means “corrected”, and that includes antenna factor, cable loss, amplifier gain (if any). And Factor D means “Duty”, that is for calculating the average value and derived from section 3.6 in this test report.
2. Peak Result = Reading + C. Factor
Ave. Result = Peak Value + D Factor
3. “*” means the frequency fall in the restricted frequency band, and the limit of emission is referred to FCC class B
4. The limit for spurious emissions refers to FCC§ 15.231.

If the measured frequencies fall in the restricted frequency band, the limit employed is § 15.209 general requirement when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function, no duty factor applied.

B. Other EmissionTest Date : Nov. 27, 2000 Temperature : 23 °C Humidity: 50 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
30.000	H/V	---	-9.8	---	40.0	---	---	---
100.000	H/V	---	-13.9	---	43.5	---	---	---
200.000	H/V	---	-7.1	---	43.5	---	---	---
300.000	H/V	---	-0.8	---	46.0	---	---	---
500.000	H/V	---	-4.4	---	46.0	---	---	---
1000.000	H/V	---	3.9	---	54.0	---	---	---

3.4 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

$$\text{Peak} = \text{Reading} + \text{Corrected Factor}$$

where

Corr. Factor = Antenna Factor + Cable Factor - Amplifier Gain (if any)

And the average value is

$$\text{Average} = \text{Peak Value} + \text{Duty Factor}$$

Note : If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function.

3.5 Transmission Time Measurement

The EUT is operated manually. It will be deactivated within not more than 5 seconds after being released.

3.6 Activate Time

This Remote Control Signal Sender is operated by Manual, and Activate Time is less than 5 second after being released.

3.7 Calculation of Duty Factor

The duty factor is calculated with following formula :

3.8 Radiated Test Equipment

Equipment	Manufacturer	Model No.	Next Cal. Date
Spectrum Analyzer	Hewlett-Packard	8568B	01/05/2001
Pre-selector	Hewlett-Packard	85685A	01/10/2001
Quasi Peak Detector	Hewlett-Packard	85650A	01/10/2001
Spectrum Analyzer	Adventest	R3271	09/09/2001
RF Test Receiver	Rohde & Schwarz	ESVS 30	01/10/2001
Horn Antenna	EMCO	3115	05/09/2001
Log periodic Antenna	EMCO	3146	11/03/2000
Biconical Antenna	EMCO	3110B	11/03/2000
Preamplifier	Hewlett-Packard	8449B	05/09/2001
Preamplifier	Hewlett-Packard	8447D	01/18/2001

3.9 Measuring Instrument Setup

Explanation of measuring instrument setup in frequency band measured is as following :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi Peak	120 kHz	N/A
	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz

3.10 Radiated Measurement Photos

Please see setup photos in Exhibit F.

4. BANDWIDTH OF EMISSION

4.1 Applicable Standard Plot Graphic of Bandwidth

Per FCC rule § 15.231(c), the permitted emission bandwidth is no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz.

4.2 Bandwidth Test Equipment

Equipment	Manufacturer	Model No.	Next Cal. Date
EMI Test Receiver	Rohde & Schwarz	ESBI	10/01/2001
Plotter	Hewlett-Packard	7550A	N/A

4.3 Plot Graphic of Bandwidth

The emission bandwidth limit for this transmitter is

$$432.970 \text{ MHz} \times 0.25\% = 1082.430 \text{ KHz}$$

Note : Please see appendix 2 for Plotted Data

5. CONDUCTED EMISSION MEASUREMENT


5.1 Standard Applicable

For intentional device, Line Conducted Emission Limits are in accordance to § 15.207(a), any emissions level shall not exceed 48 dBuV.

5.2 Measurement Procedure

1. Setup the configuration per figure 3.
2. A preliminary scan with a spectrum monitor is performed to identify the frequency of emission that has the highest amplitude relative to the limit by operating the EUT in selected modes of operation, typical cable positions, and with a typical system configuration.
3. Record the 6 or 8 highest emissions relative to the limit.
4. Measure each frequency obtained from step 3 by a test receiver set on quasi peak detector function, and then record the accuracy frequency and emission level. If all emissions measured in the specified band are attenuated more than 20 dB from the limit, this step would be ignored, and the peak detector function would be used.
5. Confirm the highest three emissions with variation of the EUT cable configuration and record the final data.
6. Repeat all above procedures on measuring each operation mode of EUT.

Figure 3 : Conducted emissions measurement configuration



5.3 Conducted Emission Data

Operation Mode : Transmitting

Test Date : SEP. 27, 2000

Temperature : 23 °C

Humidity: 50 %

Frequency (MHz)	Reading (dBuV)		Factor (dB)	Result (dBuV)		Limit (dBuV)	Margin (dB)
	Va	Vb		Va	Vb		
0.5128	29.4	30.4	0.2	29.6	30.6	48.0	-17.4
0.5474	33.8	35.6	0.2	34.0	35.8	48.0	-12.2
0.5762	23.2	37.4	0.2	23.4	37.6	48.0	-10.4
0.6880	31.6	25.2	0.2	31.8	25.4	48.0	-16.2
0.7414	28.2	39.8	0.3	28.5	40.1	48.0	-7.9
0.7841	24.2	38.4	0.3	24.5	38.7	48.0	-9.3

Note : Please see appendix 3 for Plotted Data

5.4 Result Data Calculation

The result data is calculated by adding the LISN Factor to the measured reading. The basic equation with a sample calculation is as follows:

$$RESULT = READING + LISN FACTOR$$

Assume a receiver reading of 22.5 dB μ V is obtained, and LISN Factor is 0.1 dB, then the total of disturbance voltage is 22.6 dB μ V.

$$RESULT = 22.5 + 0.1 = 22.6 \text{ dB } \mu \text{ V}$$

$$\begin{aligned} \text{Level in } \mu \text{ V} &= \text{Common Antilogarithm}[(22.6 \text{ dB } \mu \text{ V})/20] \\ &= 13.48 \mu \text{ V} \end{aligned}$$

5.5 Conducted Measurement Equipment

The following test equipment are used during the conducted test .

Equipment	Manufacturer	Model No.	Next Cal. Date
RF Test Receiver	Rohde and Schwarz	ESH3	01/10/2001
Spectrum Monitor	Rohde and Schwarz	EZM	N.C.R.
Line Impedance Stabilization network	Kyoritsu	KNW-407	11/30/2000
Plotter	Hewlett-Packard	7440A	N/A
Shielded Room	Riken	N/A	N.C.R.

5.6 Photos of Conduction Measuring Setup

Please see setup photos in Exhibit F.

APPENDIX 1 : PLOTTED DATA FOR DUTY FACTOR

$$20\log \frac{(8.65 \times 1) + (0.7 \times 18)}{64.25} = -9.6 \text{ dB}$$

*ATTEN 10dB

Δ MKR 0dB

RL 107.0dB μ V

10dB/

8.650ms

D

Δ MKR
8.650 ms
0 dB

CENTER 432.980000MHz


SPAN 0Hz

*RBW 1.0MHz

*VBW 1.0MHz

*SWP 30.0ms

*ATTEN 10dB
BPD0.701V
RL 107.0dB μ V
10dB/
700 μ s
BPD0.33dB
 Δ MKR



CENTER 432.980000MHz
SPAN 0Hz
*RBW 1.0MHz *VBW 1.0MHz *SWP 30.0ms

*ATTEN 10dB

$\Delta MKR -1.00dB$

RL 107.0dB μV

10dB/

64.25ms

D

ΔMKR
64.25
-1.00 dB

CENTER 432.980000MHz

SPAN 0Hz

*RBW 1.0MHz

*VBW 1.0MHz

*SWP 150ms

APPENDIX 2 : PLOTTED DATA FOR BANDWIDTH

*ATTEN 10dB


MKR 84.50dB μ V

RL 107.0dB μ V

10dB/

432.970MHz

D



CENTER 432.980MHz

SPAN 2.000MHz

*RBW 30kHz


*VBW 100kHz

*SWP 100ms

$\Delta MKR = 33 \text{ dB}$

10dB/

530KHz



CENTER 432.980MHZ

SPAN 2.000MHz


*RBW 30KHz

```
*VBW 100KHz
```

```
*SWP 100ms
```

APPENDIX 3 : PLOTTED DATA FOR CONDUCTED EMISSION

dBuV




FCC CONDUCTED TEST
MODEL: TR-B000 MODE: TX

EUT: Infrared Remote Extender
POWER: 120V/60Hz

2: QP; CLASS B LIMIT
LISN: Va ETC EMI LAB.

dBuV



FCC CONDUCTED TEST
MODEL: TR-8000 MODE: TX
EUT: Infrared Remote Extender 2: GP; CLASS B LIMIT
POWER: 120V/60Hz LISN: Vb ETC EMI LAB.