

Radiated Emission Measurement Data

Date of Tested	: 2001-9-11	Polarization	: Horizontal
Temperature	: 27	Humidity	: 65%
Tested Mode	: Walkman Play (Channel 10)		

Frequency (MHz)	Factor (dB)	Meter Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV/m)	Margin (dB)
61.525	-15.30	37.21	21.91	40.00	-18.09
153.675	-10.62	32.34	21.72	43.50	-21.78
362.225	-5.31	32.69	27.38	46.02	-18.64
892.475	-6.01	35.23	29.22	46.02	-16.80
904.900 +	-5.83	90.07	84.24	93.98	-9.74
917.025	-5.82	40.65	34.83	46.02	-11.19
1809.800 *	-29.02	59.45	30.43	73.98	-43.55
2714.700 *	-27.87	56.73	28.86	73.98	-45.12
3619.600 *	-26.29	56.55	30.26	73.98	-43.72
4524.500 *	-24.51	53.90	29.39	73.98	-44.59
5429.400 *	-23.33	52.67	29.34	73.98	-44.64
6334.300 *	-21.07	50.41	29.34	73.98	-44.64
7239.200 *	-19.18	49.27	30.09	73.98	-43.89
8144.100 *	-17.81	47.34	29.53	73.98	-44.45
9049.000 *	-16.27	45.96	29.69	73.98	-44.29

Remark :

- 1 All readings are Quasi-Peak values.
- 2 “+” Means Fundamental Frequency.
- 3 “*” Means Peak Value. Peak Limit = Average + 20 dB.
- 4 Factor = Antenna Factor + Cable Loss – Pre-amplifier

Radiated Emission Measurement Data

Date of Tested	: 2001-9-11	Polarization	: Vertical
Temperature	: 27	Humidity	: 65%
Tested Mode	: Walkman Play (Channel 10)		

Frequency (MHz)	Factor (dB)	Meter Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV/m)	Margin (dB)
37.275	-15.48	42.33	26.85	40.00	-13.15
61.525	-19.99	43.43	23.44	40.00	-16.56
76.075	-16.65	38.39	21.74	40.00	-18.26
308.875	-12.42	38.36	25.94	46.02	-20.08
471.350	0.00	32.90	32.90	46.02	-13.12
904.900 +	-5.43	37.75	32.32	93.98	-61.66
917.025	-5.18	86.71	81.53	46.02	35.51
1809.800 *	-29.02	59.48	30.46	73.98	-43.52
2714.700 *	-27.87	56.27	28.40	73.98	-45.58
3619.600 *	-26.29	56.93	30.64	73.98	-43.34
4524.500 *	-24.51	54.02	29.51	73.98	-44.47
5429.400 *	-23.33	51.81	28.48	73.98	-45.50
6334.300 *	-21.07	50.33	29.26	73.98	-44.72
7239.200 *	-19.18	48.51	29.33	73.98	-44.65
8144.100 *	-17.81	47.76	29.95	73.98	-44.03

Remark :

- 1 All readings are Quasi-Peak values.
- 2 "+" Means Fundamental Frequency.
- 3 "*" Means Peak values. Peak Limit = Average + 20 dB.
- 4 Factor = Antenna Factor + Cable Loss – Pre-amplifier