

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.225)
Report No.: RFBEDV-WTW-P26040671
FCC ID: E2K-DWRFID2402
Product: RFID 13.56MHz Wireless Module
Brand: DELL
Model No.: DWRFID2402
Received Date: 2026/5/7
Test Date: 2026/5/21 ~ 2026/5/25
Issued Date: 2026/6/11
Applicant: Dell Inc.
Address: One Dell Way, Round Rock, Texas 78682, USA
Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories
Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan
FCC Registration / 788550 / TW0003
Designation Number:

Approved by: _____

Jeremy Lin

Jeremy Lin / Project Engineer

, Date: _____

2026/6/11

This test report consists of 32 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Vera Huang / Specialist



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate.....	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty	5
2.2 Supplementary Information	5
3 General Information	6
3.1 General Description.....	6
3.2 Antenna Description of EUT.....	7
3.3 Channel List.....	7
3.4 Test Mode Applicability and Tested Channel Detail.....	7
3.5 Test Program Used and Operation Descriptions	8
3.6 Connection Diagram of EUT and Peripheral Devices	8
3.7 Configuration of Peripheral Devices and Cable Connections	8
4 Test Instruments	9
4.1 AC Power Conducted Emissions	9
4.2 Radiated Emissions below 30 MHz.....	10
4.3 Radiated Emissions above 30 MHz	10
4.4 Frequency Stability	11
4.5 20 dB Bandwidth	11
5 Limits of Test Items.....	12
5.1 AC Power Conducted Emissions	12
5.2 Radiated Emissions below 30 MHz.....	12
5.3 Radiated Emissions above 30 MHz	13
5.4 Frequency Stability	13
5.5 20 dB Bandwidth	13
6 Test Arrangements.....	14
6.1 AC Power Conducted Emissions	14
6.1.1 Test Setup	14
6.1.2 Test Procedure	14
6.2 Radiated Emissions below 30 MHz.....	15
6.2.1 Test Setup	15
6.2.2 Test Procedure	15
6.3 Radiated Emissions above 30 MHz	16
6.3.1 Test Setup	16
6.3.2 Test Procedure	16
6.4 Frequency Stability	17
6.4.1 Test Setup	17
6.4.2 Test Procedure	17
6.5 20 dB Bandwidth	18
6.5.1 Test Setup	18
6.5.2 Test Procedure	18
7 Test Results of Test Item	19
7.1 AC Power Conducted Emissions	19
7.2 Radiated Emissions below 30 MHz.....	21
7.3 Radiated Emissions above 30 MHz	27
7.4 Frequency Stability	29
7.5 20 dB Bandwidth	30
8 Pictures of Test Arrangements	31
9 Information of the Testing Laboratories	32

Release Control Record

Issue No.	Description	Date Issued
RFBEDV-WTW-P26040671	Original Release	2026/6/11

1 Certificate

Product: RFID 13.56MHz Wireless Module

Brand: DELL

Test Model: DWRFID2402

Sample Status: Engineering sample

Applicant: Dell Inc.

Test Date: 2026/5/21 ~ 2026/5/25

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.225)

**Measurement
procedure:** ANSI C63.10-2020

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.225)			
Standard / Clause	Test Item	Result	Remark
15.207	AC Power Conducted Emissions	Pass	Minimum passing margin is -11.73 dB at 0.53800 MHz
15.225 (a)	The field strength of any emissions within the band 13.553-13.567 MHz	Pass	Meet the requirement of limit.
15.225 (b)	The field strength of any emissions within the bands 13.410-13.553 MHz and 13.567-13.710 MHz	Pass	Meet the requirement of limit.
15.225 (c)	The field strength of any emissions within the bands 13.110-13.410 MHz and 13.710-14.010 MHz	Pass	Meet the requirement of limit.
15.225 (d)	The field strength of any emissions appearing outside of the 13.110-14.010 MHz band below 30MHz	Pass	Meet the requirement of limit.
15.225 (d)	The field strength of any emissions appearing outside of the 13.110-14.010 MHz band above 30MHz	Pass	Minimum passing margin is -6.3 dB at 52.31 MHz
15.225 (e)	Frequency Stability	Pass	Meet the requirement of limit.
15.215 (c)	20 dB Bandwidth	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	No antenna connector is used.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) (±)
AC Power Conducted Emissions	9 kHz ~ 30 MHz	2.90 dB
Radiated Emissions below 30 MHz	9 kHz ~ 30 MHz	2.44 dB
Radiated Emissions above 30 MHz	30 MHz ~ 1 GHz	2.95 dB
Frequency Stability	-	0.176 ppm

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description

Product	RFID 13.56MHz Wireless Module
Brand	DELL
Test Model	DWRFID2402
Host Marketing Name (HMN)	P149G
Status of EUT	Engineering sample
Power Supply Rating	3.3 Vdc (from host equipment) 11.4 Vdc (from battery of End-product)
Modulation Type	ASK
NFC Technology Type	NFC-A (ISO/IEC 14443 Type A) NFC-B (ISO/IEC 14443 Type B) NFC-F (ISO/IEC 18092 or FeliCa) NFC-V (ISO/IEC 15693)
Data Rate	Type A: 106 kbit/s Type B: 106 kbit/s Type F: 212 kbit/s, 424 kbit/s Type V: 26.48 kbit/s
Operating Frequency	13.56 MHz
Number of Channel	1
Field Strength Of Fundamental	12.5 dBuV/m (Quasi-Peak) at 30 meters

Note:

1. The EUT is authorized for use in specific End-product. Please refer to below for more details.

Product	Brand	Model
Notebook Computer	DELL	P149G

2. The End-product contains following accessory devices.

AC Adapter	Brand	DELL
	Model	LA65NM251
	AC Input	100-240Vac; 50-60Hz; 1.7A
	DC Output	5.0Vdc; 3.0A/15.0W, 9.0Vdc; 3.0A/27.0W, 15.0Vdc; 3.0A/45.0W, 20.0Vdc; 3.25A/65.0W, 5.0Vdc-21.0Vdc; 4.0A/65.0W
	DC Output Cable	175cm
	Manufacturer	Lite-on Technology Corp.
AC Power cord	Brand	HONGLIN
	Model	HL-052D
	Signal line	0.83m
Battery	Brand	DELL
	Model	XVJNP
	Power Rating	11.4V, 4457mAh, 53.5Wh

3. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Antenna Brand	Antenna Model No.	Antenna Type	Antenna Connector
HongBo	1415-08EG0DE	Loop Antenna	N/A

* Due to radiated measurements are made and the antenna gain is already accounted for this device, so provide an antenna datasheet and/or antenna measurement report is not required. The antenna dimensions and pictures (include antenna wire length if have) are stated in EUT photo exhibit.

3.3 Channel List

1 channel is provided to this EUT:

Channel	Frequency (MHz)
1	13.56

3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. The EUT had been pre-tested on Type A, Type B, Type F, and Type V. Pre-scan these operations / usages and find the worst case as a representative test condition.
Worst Case:	1. EUT Type: Type A 2. EUT is designed to be positioned on the NB mode only.


Following channel(s) was (were) selected for the final test as listed below:

Test Item	Type	Tested Channel	Modulation	Data Rate Parameter
AC Power Conducted Emissions	A	1	100%, ASK	106 kbit/s
Radiated Emissions below 30 MHz	A	1	100%, ASK	106 kbit/s
Radiated Emissions above 30 MHz	A	1	100%, ASK	106 kbit/s
Frequency Stability	-	1	unmodulated	-
20 dB Bandwidth	A	1	100%, ASK	106 kbit/s

3.5 Test Program Used and Operation Descriptions

Set the EUT under transmission condition continuously at specific channel frequency.

3.6 Connection Diagram of EUT and Peripheral Devices



Under Table

Remote Site

3.7 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Monitor	DELL	A14S2421HSXmTW	CN-01KFWF-WSL00-24C-711B	N/A	Provided by Lab
B	Earphone	APPLE	MB77PFEB	N/A	N/A	Provided by Lab
C	Load	BV	LP-04	N/A	N/A	Provided by Lab
D	USB Flash*1	SanDisk	SDDDC3-032G	N/A	N/A	Provided by Lab
E	USB Flash*3	SanDisk	SDDDC3-032G	N/A	N/A	Provided by Lab
F	NFC Card	BV	NFC TYPE-A	N/A	N/A	Provided by Lab
G	Notebook Computer	DELL	P149G	N/A	N/A	Provided by applicant
H	AC Adapter	DELL	LA65NM251	N/A	N/A	Provided by applicant

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	HDMI Cable	1	1.8	Yes	0	Provided by Lab
2	Audio Cable	1	1.2	No	0	Provided by Lab
3	LAN Cable	1	1.5	No	0	Provided by Lab
4	RS-232 to LAN cable	1	1.5	No	0	Provided by Lab
5	DC Power cable	1	1.75	No	0	Provided by applicant
6	Power Cord	1	0.83	No	0	Provided by applicant

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance	E1-011279	04	2025/12/4	2026/12/3
	E1-011280	05	2025/12/4	2026/12/3
	E1-011311	09	2025/12/4	2026/12/3
DC LISN Schwarzbeck	NNBM 8126G	8126G-069	2025/11/3	2026/11/2
Diode Pulse Limiter Schwarzbeck	VTSD 9561 F-N	01617	2025/8/23	2026/8/22
EMI Test Receiver R&S	ESR3	102783	2025/12/15	2026/12/14
LISN R&S	ESH2-Z5	100100	2026/3/4	2027/3/3
	ESH3-Z5	100312	2025/8/29	2026/8/28
RF Coaxial Cable Woken	5D-FB	Cable-cond2-01	2025/8/23	2026/8/22
Software BVADT	BVADT_Conc_ V7.4.1.0	N/A	N/A	N/A
V-LISN Schwarzbeck	NNBL 8226-2	8226-142	2025/8/27	2026/8/26

Notes:

1. The test was performed in HY - Conduction 2.
2. Tested Date: 2026/5/25

4.2 Radiated Emissions below 30 MHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn Max-Full	MFA-440H	AT93021705	N/A	N/A
Loop Antenna TESEQ	HLA 6121	45745	2025/9/1	2026/8/31
MXE EMI Receiver Agilent	N9038A	MY51210203	2025/8/27	2026/8/26
Preamplifier EMCI	EMC001340	980201	2025/9/21	2026/9/20
RF Coaxial Cable Woken	8D-FB	Cable-Ch10-01	2025/9/21	2026/9/20
Signal & Spectrum Analyzer R&S	FSVA3044	100904	2025/7/1	2026/6/30
Software BV ADT	ADT_Radiated_ V7.7.1.1.1	N/A	N/A	N/A
Turn Table Max-Full	MFT-201SS	N/A	N/A	N/A
Turn Table Controller Max-Full	MG-7802	N/A	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 5(Hwaya).
2. Tested Date: 2026/5/21

4.3 Radiated Emissions above 30 MHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn Max-Full	MFA-440H	AT93021705	N/A	N/A
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-472	2025/9/16	2026/9/15
MXE EMI Receiver Agilent	N9038A	MY51210203	2025/8/27	2026/8/26
Preamplifier EMCI	EMC 330H	980112	2025/9/21	2026/9/20
RF Coaxial Cable Woken	8D-FB	Cable-Ch10-01	2025/9/21	2026/9/20
Signal & Spectrum Analyzer R&S	FSVA3044	100904	2025/7/1	2026/6/30
Software BV ADT	ADT_Radiated_ V7.7.1.1.1	N/A	N/A	N/A
Turn Table Max-Full	MFT-201SS	N/A	N/A	N/A
Turn Table Controller Max-Full	MG-7802	N/A	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 5(Hwaya).
2. Tested Date: 2026/5/21

4.4 Frequency Stability

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
3-channel DC power supply OWON	ODP3033	ODP30332128138	N/A	N/A
Digital Multimeter Fluke	8050A	4660081	2025/6/6	2026/6/5
Fixed Attenuator Woken	00800A1K01A-10	00800A1K01A-10-01	2026/5/21	2027/5/20
Loop Antenna TESEQ	HLA 6121	45745	2025/9/1	2026/8/31
Preamplifier EMCI	EMC001340	980201	2025/9/21	2026/9/20
RF Coaxial Cable Woken	8D-FB	Cable-Ch10-01	2025/9/21	2026/9/20
Signal & Spectrum Analyzer R&S	FSV3044	101504	2025/6/18	2026/6/17
Software BV	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A
Temperature & Humidity Chamber Terchy	MHU-225AU	920842	2025/6/25	2026/6/24

Notes:

1. The test was performed in HY - Oven room(Hwaya).
2. Tested Date: 2026/5/22

4.5 20 dB Bandwidth

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn Max-Full	MFA-440H	AT93021705	N/A	N/A
Loop Antenna TESEQ	HLA 6121	45745	2025/9/1	2026/8/31
MXE EMI Receiver Agilent	N9038A	MY51210203	2025/8/27	2026/8/26
Preamplifier EMCI	EMC001340	980201	2025/9/21	2026/9/20
RF Coaxial Cable Woken	8D-FB	Cable-Ch10-01	2025/9/21	2026/9/20
Signal & Spectrum Analyzer R&S	FSVA3044	100904	2025/7/1	2026/6/30
Software BV ADT	ADT_Radiated_ V7.7.1.1.1	N/A	N/A	N/A
Turn Table Max-Full	MFT-201SS	N/A	N/A	N/A
Turn Table Controller Max-Full	MG-7802	N/A	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 5(Hwaya).
2. Tested Date: 2026/5/22

5 Limits of Test Items

5.1 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.2 Radiated Emissions below 30 MHz

- (a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209 as below table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detect or except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, and the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

5.3 Radiated Emissions above 30 MHz

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.4 Frequency Stability

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency over a temperature variation of -20 degrees to 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.


5.5 20 dB Bandwidth

The 20dB bandwidth shall be specified in operating frequency band.

6 Test Arrangements

6.1 AC Power Conducted Emissions

6.1.1 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.1.2 Test Procedure


- Exploratory ac power-line conducted emission measurements: The EUT shall be operated on the mid channel and in the mode with highest output power unless the fundamental operates in the AC power-line emission test range then the EUT shall be operated in the range of typical modes of operation.
- The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.

6.2 Radiated Emissions below 30 MHz

6.2.1 Test Setup

For Radiated emission below 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.2.2 Test Procedure

For Radiated emission below 30 MHz

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode (however, peak detector measurements may be used to determine compliance with QP requirements), except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.


Notes:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
- All modes of operation were investigated and the worst-case emissions are reported.
- KDB 414788 OATS and Chamber Correlation Justification.
 - Based on FCC 15.31(f)(2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.
 - OATs and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

6.3 Radiated Emissions above 30 MHz

6.3.1 Test Setup

For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.3.2 Test Procedure

For Radiated emission above 30 MHz


- The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz (however, peak detector measurements may be used to determine compliance with QP requirements).

Notes:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequencies less than or equal to 1 GHz (however, peak detector measurements may be used to determine compliance with QP requirements).
- All modes of operation were investigated and the worst-case emissions are reported.

6.4 Frequency Stability

6.4.1 Test Setup




6.4.2 Test Procedure

- The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
- Turn the EUT on and couple its output to a spectrum analyzer.
- Turn the EUT off and set the chamber to the highest temperature specified.
- Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 Minutes.
- Repeat step (d) with the temperature chamber set to the next desired temperature until measurements down to the lowest specified temperature have been completed.
- The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 Minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

6.5 20 dB Bandwidth

6.5.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo)

6.5.2 Test Procedure

Radiated Measurement:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-spectrum system was set to Peak Detect Function and Maximum Hold.
- Set resolution bandwidth (RBW) = 1% to 5% of the OBW.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

7 Test Results of Test Item


7.1 AC Power Conducted Emissions

RF Mode	NFC-13.56MHz	Channel	CH 1 : 13.56 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Adair Peng		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15800	10.21	39.13	23.27	49.34	33.48	65.57	55.57	-16.23	-22.09
2	0.17800	10.20	36.82	21.52	47.02	31.72	64.58	54.58	-17.56	-22.86
3	0.40200	10.34	24.11	9.43	34.45	19.77	57.81	47.81	-23.36	-28.04
4	0.55400	10.36	33.36	16.98	43.72	27.34	56.00	46.00	-12.28	-18.66
5	1.55800	10.42	7.28	1.55	17.70	11.97	56.00	46.00	-38.30	-34.03
6	13.56200	10.80	24.43	24.12	35.23	34.92	60.00	50.00	-24.77	-15.08

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	NFC-13.56MHz	Channel	CH 1 : 13.56 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Adair Peng		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.22	39.68	23.98	49.90	34.20	66.00	56.00	-16.10	-21.80
2	0.17000	10.21	34.76	19.31	44.97	29.52	64.96	54.96	-19.99	-25.44
3	0.35000	10.31	19.93	6.78	30.24	17.09	58.96	48.96	-28.72	-31.87
4	0.53800	10.37	33.90	19.88	44.27	30.25	56.00	46.00	-11.73	-15.75
5	1.59000	10.43	4.09	1.96	14.52	12.39	56.00	46.00	-41.48	-33.61
6	13.56200	10.85	22.34	21.98	33.19	32.83	60.00	50.00	-26.81	-17.17

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




7.2 Radiated Emissions below 30 MHz

RF Mode	NFC-13.56MHz	Channel	CH 1 : 13.56 MHz
Frequency Range	13.11 MHz ~ 14.01 MHz	Detector Function & Bandwidth	Quasi-Peak (QP), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 62% RH
Tested By	Thomas Cheng		

Antenna Polarity : Parallel								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*13.56	12.5 QP	84.0	-71.5	1.00	2	31.2	-18.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.
Distance factor@3 m = $40 \cdot \log(3/30) = -40$ dB




RF Mode	NFC-13.56MHz	Channel	CH 1 : 13.56 MHz
Frequency Range	13.11 MHz ~ 14.01 MHz	Detector Function & Bandwidth	Quasi-Peak (QP), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 62% RH
Tested By	Thomas Cheng		

Antenna Polarity : Perpendicular								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*13.56	7.3 QP	84.0	-76.7	1.00	98	26.0	-18.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.
Distance factor@3 m = $40 \cdot \log(3/30) = -40$ dB




RF Mode	NFC-13.56MHz	Channel	CH 1 : 13.56 MHz
Frequency Range	13.11 MHz ~ 14.01 MHz	Detector Function & Bandwidth	Quasi-Peak (QP), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 62% RH
Tested By	Thomas Cheng		

Antenna Polarity : Ground-parallel								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*13.56	8.5 QP	84.0	-75.5	1.00	2	27.2	-18.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.
Distance factor@3 m = $40 \cdot \log(3/30) = -40$ dB




RF Mode	NFC-13.56MHz	Channel	CH 1 : 13.56 MHz
Frequency Range	9 kHz ~ 150 kHz; 150 kHz ~ 30 MHz	Detector Function & Bandwidth	Quasi-Peak (QP), 200 Hz; Quasi-Peak (QP), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 62% RH
Tested By	Thomas Cheng		

Antenna Polarity : Parallel								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	3.40	-7.6 QP	29.5	-37.1	1.00	241	12.8	-20.4
2	6.52	-5.7 QP	29.5	-35.2	1.00	102	13.3	-19.0
3	10.51	-4.4 QP	29.5	-33.9	1.00	84	14.2	-18.6
4	16.26	-5.4 QP	29.5	-34.9	1.00	308	13.1	-18.5
5	19.65	-5.3 QP	29.5	-34.8	1.00	202	12.5	-17.8
6	27.12	-6.4 QP	29.5	-35.9	1.00	55	11.7	-18.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.
Distance factor@3 m = $40 \cdot \log(3/30) = -40$ dB




RF Mode	NFC-13.56MHz	Channel	CH 1 : 13.56 MHz
Frequency Range	9 kHz ~ 150 kHz; 150 kHz ~ 30 MHz	Detector Function & Bandwidth	Quasi-Peak (QP), 200 Hz; Quasi-Peak (QP), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 62% RH
Tested By	Thomas Cheng		

Antenna Polarity : Perpendicular								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2.26	-2.6 QP	29.5	-32.1	1.00	151	17.8	-20.4
2	6.13	-6.7 QP	29.5	-36.2	1.00	122	12.2	-18.9
3	9.88	-3.6 QP	29.5	-33.1	1.00	42	15.3	-18.9
4	18.60	-2.5 QP	29.5	-32.0	1.00	38	15.3	-17.8
5	22.71	-5.7 QP	29.5	-35.2	1.00	152	12.9	-18.6
6	27.12	-6.4 QP	29.5	-35.9	1.00	355	11.7	-18.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.
Distance factor@3 m = $40 \cdot \log(3/30) = -40$ dB




RF Mode	NFC-13.56MHz	Channel	CH 1 : 13.56 MHz
Frequency Range	9 kHz ~ 150 kHz; 150 kHz ~ 30 MHz	Detector Function & Bandwidth	Quasi-Peak (QP), 200 Hz; Quasi-Peak (QP), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 62% RH
Tested By	Thomas Cheng		

Antenna Polarity : Ground-parallel								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2.62	-7.4 QP	29.5	-36.9	1.00	145	13.1	-20.5
2	6.70	-5.8 QP	29.5	-35.3	1.00	110	13.2	-19.0
3	11.26	-5.6 QP	29.5	-35.1	1.00	16	12.9	-18.5
4	15.39	-4.3 QP	29.5	-33.8	1.00	272	14.5	-18.8
5	20.22	-3.6 QP	29.5	-33.1	1.00	149	14.3	-17.9
6	27.12	-6.2 QP	29.5	-35.7	1.00	2	11.9	-18.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + Distance Factor
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. The test distance for 0.49 ~ 30 MHz is 3 m, extrapolate the measured field strength to a distance of 30 meters.
Distance factor@3 m = $40 \cdot \log(3/30) = -40$ dB




7.3 Radiated Emissions above 30 MHz

RF Mode	NFC-13.56MHz	Channel	CH 1 : 13.56 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 62% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	52.31	28.0 QP	40.0	-12.0	2.50 H	93	40.0	-12.0
2	78.50	27.7 QP	40.0	-12.3	2.00 H	197	44.5	-16.8
3	152.22	27.4 QP	43.5	-16.1	2.50 H	235	39.6	-12.2
4	302.57	26.6 QP	46.0	-19.4	1.50 H	10	38.1	-11.5
5	424.79	26.7 QP	46.0	-19.3	1.00 H	325	35.0	-8.3
6	728.40	28.3 QP	46.0	-17.7	1.50 H	42	30.0	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.




RF Mode	NFC-13.56MHz	Channel	CH 1 : 13.56 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	21 °C, 62% RH
Tested By	Thomas Cheng		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	34.85	27.4 QP	40.0	-12.6	1.50 V	251	40.1	-12.7
2	52.31	33.7 QP	40.0	-6.3	1.00 V	67	45.7	-12.0
3	208.48	24.5 QP	43.5	-19.0	2.00 V	158	39.9	-15.4
4	429.64	25.8 QP	46.0	-20.2	1.50 V	121	33.9	-8.1
5	626.55	27.8 QP	46.0	-18.2	1.00 V	37	31.6	-3.8
6	730.34	37.8 QP	46.0	-8.2	2.50 V	194	39.3	-1.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.



7.4 Frequency Stability

Environmental Conditions:	24°C, 68% RH	Tested By:	Thomas Cheng
---------------------------	--------------	------------	--------------

Frequency Stability Versus Temperature									
Operating Frequency: 13.56 MHz									
Temp. (°C)	Power Supply (Vdc)	0 Minute		2 Minutes		5 Minutes		10 Minutes	
		Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)
50	11.4	13.55999	-0.00007	13.55998	-0.00015	13.55999	-0.00007	13.55999	-0.00007
40	11.4	13.55995	-0.00037	13.55995	-0.00037	13.55995	-0.00037	13.55995	-0.00037
30	11.4	13.55994	-0.00044	13.55994	-0.00044	13.55994	-0.00044	13.55995	-0.00037
20	11.4	13.55998	-0.00015	13.55997	-0.00022	13.55998	-0.00015	13.55996	-0.00029
10	11.4	13.56	0.00000	13.56	0.00000	13.56	0.00000	13.56	0.00000
0	11.4	13.55999	-0.00007	13.55999	-0.00007	13.55999	-0.00007	13.56	0.00000
-10	11.4	13.56003	0.00022	13.56003	0.00022	13.56004	0.00029	13.56004	0.00029
-20	11.4	13.56005	0.00037	13.56004	0.00029	13.56003	0.00022	13.56004	0.00029

Frequency Stability Versus Voltage									
Operating Frequency: 13.56 MHz									
Temp. (°C)	Power Supply (Vdc)	0 Minute		2 Minutes		5 Minutes		10 Minutes	
		Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)
20	13.35	13.55998	-0.00015	13.55997	-0.00022	13.55998	-0.00015	13.55996	-0.00029
	11.4	13.55998	-0.00015	13.55997	-0.00022	13.55998	-0.00015	13.55996	-0.00029
	9	13.55998	-0.00015	13.55997	-0.00022	13.55998	-0.00015	13.55996	-0.00029


7.5 20 dB Bandwidth

Environmental Conditions:	24°C, 68% RH	Tested By:	Thomas Cheng
---------------------------	--------------	------------	--------------

Channel	Channel Frequency (MHz)	20 dB Bandwidth (MHz)	Measured Frequencies		Operating Frequency Band (MHz)	Test Result
			FL (MHz)	FH (MHz)		
1	13.56	0.0279	13.5464	13.5743	13.11 ~ 14.01	Pass

Notes:

1. FL is the lowest frequency of the 20 dB bandwidth of power envelope.
2. FH is the highest frequency of the 20 dB bandwidth of power envelope.



8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---