



AEGIS LABS INC.



Class II Permissive Change
Test Report
And Application for Grant of Equipment Authorization

Pertaining To:

EUT	FCC ID:
Intel PRO/Wireless 2200BG Network Connection, MN: WM3B2200BG (PPT)	E2K24BNHM

Configuration
Tested installed in a Dell Latitude D400 Notebook Computer, MN: PPT With a set of Wistron Neweb Corp. Antennas

MEASUREMENTS PERFORMED IN ACCORDANCE WITH

Regulatory Standard(s)
47 CFR Part 15, Subpart C Section 15.247
Test Method: ANSI C63.4: 2003 American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz



Certificate Number: 1111.01

APPLICANT:

Dell Computer Corporation
One Dell Way
Round Rock, TX 78682

Contact(s): Mr. Jason Limoges

PREPARED BY:

Aegis Labs, Inc.
22431 Antonio Parkway B160-417
Rancho S. Margarita, CA 92688

Agent(s): Mr. Steve Kuiper
Mr. Rick Candelas
Mr. Johnny Candelas

Test Report #: INTEL-050207F
Test Report Revision: Rev. A, 04/27/05

	REPORT BODY	APPENDICES	TOTAL PAGES
		A	
PAGES	17	73	90

The contents of this report shall not be reproduced except in full, without the written approval of Aegis Labs, Inc.

Page 1 of 17
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

TABLE OF CONTENTS

SECTION	TITLE	PAGE
	COVER SHEET.....	01
	TABLE OF CONTENTS.....	02
1.0	CERTIFICATION OF TEST DATA.....	03
2.0	SUMMARY OF TEST RESULTS.....	04
3.0	ADMINISTRATIVE DATA AND TEST DESCRIPTION.....	06
4.0	DESCRIPTION OF EUT.....	07
4.1	EUT Description.....	07
4.1.1	Channel Number and Frequencies.....	08
4.2	EUT Configuration.....	09
4.3	List of EUT Sub-Assemblies and Host Equipment.....	10
4.4	I/O Cabling Diagram and Description.....	11
5.0	TEST EQUIPMENT AND TEST SETUPS.....	12
5.1	AC Power Line Conducted Emissions.....	12
5.2	Spurious Radiated Emissions.....	13
5.3	Conducted Emissions At The Antenna Port.....	13
5.4	Test and Measurement Equipment Used.....	14
6.0	SAMPLE CALCULATIONS.....	15
7.0	MODIFICATIONS AND RECOMMENDATIONS.....	17

APPENDICES

A	Test Data
---	-----------



AEGIS LABS INC.

1.0 CERTIFICATION OF TEST DATA

Aegis Labs, Inc. operates as both a Nevada and California Corporation with no organizational or financial relationship with any company, institution, or private individual.

Testing and engineering functions provided by Aegis Labs are furnished through the use of part-time, full-time or consulting engineers with the appropriate qualifications to carry out their duties. The intended purpose of this test report is to describe the measurement procedure and to determine whether the equipment under test "EUT" complies with both the conducted and radiated limits. Limits for emissions testing are described under Subpart C of Part 15 of the FCC rules.

The data, data evaluation and equipment configuration represented herein are a true and accurate representation of the Equipment Under Test (EUT) under the requirements specified in the emissions standard as described below. The test results contained in this report are only representative of the test sample tested as described in Section 3.0 of this report. Certification of the EUT is required as a prerequisite to marketing as defined in Part 2 of the FCC Rules.

Prepared By:



Johnny Candelas
Test Technician
Aegis Labs, Inc.

04/27/05

Date:

Reviewed By:



Rick Candelas
Lab Manager
Aegis Labs, Inc.

04/27/05

Date:

Report Approved By:



Steve J. Kuiper
Quality Assurance Manager
Aegis Labs, Inc.

04/27/05

Date:

Page 3 of 17

Report Number: INTEL-050207F

FCC ID: E2K24BNHM



AEGIS LABS INC.

2.0 SUMMARY OF TEST RESULTS

The test results provided within this report, indicate that the EUT has been found to be in **COMPLIANCE** with the test specifications based upon the following RF compliance standards:

Pass/Fail determination is based upon the nominal values of the test data.

802.11b Mode (2412-2462 MHz)

EMISSIONS STANDARD			
FCC Part 15 Section	Description	Results	Comments
15.247(a)(2)	The minimum 6dB bandwidth shall be at least 500 kHz.	PASSED	2412 MHz = 9.58 MHz 2437 MHz = 9.58 MHz 2462 MHz = 9.58 MHz
15.247(b)(1)	The maximum peak output power of the intentional radiator shall not exceed 1 watt.	PASSED	2412 MHz = 16.20 dBm = 41.69 mW 2437 MHz = 17.40 dBm = 54.95 mW 2462 MHz = 16.40 dBm = 43.65 mW
15.247(b)(4)	The intentional radiator shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the FCC guidelines per Section 1.1307(b)(1).	PASSED	Refer to SAR Test Report
15.247(c)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.	PASSED	See Data Sheets
15.247(c)	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.	PASSED	See Data Sheets
15.247(d)	The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	PASSED	2412 MHz = -8.50 dB 2437 MHz = -6.83 dB 2462 MHz = -7.00 dB
15.207	AC Conducted Emissions	PASSED	See Data Sheet
15.209	Radiated Emissions (30-1000 MHz)	PASSED	See Data Sheet

Page 4 of 17

Report Number: INTEL-050207F

FCC ID: E2K24BNHM



AEGIS LABS INC.

2.0 Summary of Test Results (Continued)

The test results provided within this report, indicate that the EUT has been found to be in **COMPLIANCE** with the test specifications based upon the following RF compliance standards:

Pass/Fail determination is based upon the nominal values of the test data.

802.11g Mode (2412-2462 MHz)

EMISSIONS STANDARD			
FCC Part 15 Section	Description	Results	Comments
15.247(a)(2)	The minimum 6dB bandwidth shall be at least 500 kHz.	PASSED	2412 MHz = 16.58 MHz 2437 MHz = 16.67 MHz 2462 MHz = 16.67 MHz
15.247(b)(1)	The maximum peak output power of the intentional radiator shall not exceed 1 watt.	PASSED	2412 MHz = 16.10 dBm = 40.74 mW 2437 MHz = 16.10 dBm = 40.74 mW 2462 MHz = 16.00 dBm = 39.81 mW
15.247(b)(4)	The intentional radiator shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the FCC guidelines per Section 1.1307(b)(1).	PASSED	Refer to SAR Test Report
15.247(c)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.	PASSED	See Data Sheets
15.247(c)	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.	PASSED	See Data Sheets
15.247(d)	The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	PASSED	2412 MHz = -17.83 dB 2437 MHz = -15.83 dB 2462 MHz = -17.00 dB
15.207	AC Conducted Emissions	PASSED	See Data Sheet
15.209	Radiated Emissions (30-1000 MHz)	PASSED	See Data Sheet

Page 5 of 17

Report Number: INTEL-050207F

FCC ID: E2K24BNHM



AEGIS LABS INC.

3.0 ADMINISTRATIVE DATA AND TEST DESCRIPTION

DEVICE TESTED:	ITE Type: Intel PRO/Wireless 2200BG Network Connection Model Number(s): WM3B2200BG (PPT) Serial Number: 0814C0094ADC54906006 FCC ID: E2K24BNHM
TEST DATE(S):	February 7 - 17, 2005
DATE EUT RECEIVED:	July 28, 2004
ORIGIN OF TEST SAMPLE(S):	Production Unit
RESPONSIBLE PARTY:	Dell Computer Corporation One Dell Way Round Rock, TX 78682
CLIENT CONTACT:	Mr. Jason Limoges
MANUFACTURER:	Dell Computer Corporation
TEST LOCATION:	Aegis Labs, Inc. 32231 Trabuco Creek Road Trabuco Canyon, CA 92678 Conducted Site #2 Radiated Site #2
A2LA CERTIFICATE:	1111.01, Valid through February 28, 2006
PURPOSE OF TEST:	To demonstrate compliance with the relevant standards described in Section 2.0 of this report.
TEST(S) PERFORMED:	Refer to Table in Section 2.0 of this report.

All calibration vendors were responsible for certifying Aegis Labs, Inc. test equipment as per the manufacturer's specifications and that the equipment is calibrated using instruments and standards where the accuracy is traceable to the National Institute of Standards and Technology (NIST). Calibration of all test equipment conforms to ANSI/NCSL Z540-1 and ISO 10012-1 and/or ISO/IEC Guide 17025 compliance (Additionally, other pertinent test equipment will carry MIL-STD-45662A). All calibration documents are on file with Aegis Labs, Inc., with copies provided upon request.

Page 6 of 17
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

4.0 DESCRIPTION OF EUT

4.1 EUT Description

Equipment Under Test (EUT)	
Trade Name:	Intel PRO/Wireless 2200BG Network Connection
Model Number:	WM3B2200BG (PPT) tested installed in a Dell Latitude D400 Notebook Computer
Frequency Range:	2.412 – 2.462 GHz
Type of Transmission:	Direct Sequence Spread Spectrum
Transfer Rate:	1/2/5.5/11 Mbps for 802.11b mode 6/36/54 Mbps for 802.11g mode
Number of Channels:	11
Modulation Type:	DBPSK, DQPSK, CCK
Antenna Type (See Note 1):	PIFA (Main), PIFA (Aux)
Antenna Gain (See Note 2):	<u>Wistron:</u> 2.4 GHz = 2.59dBi
Transmit Output Power:	17 dBm (Typical) for 802.11b mode 16 dBm (Typical) for 802.11g mode Please see Appendix A (Data Sheets) for actual output power.
Power Supply:	3.3VDC from computer MPCPI slot.
Number of External Test Ports Exercised:	2 Antenna Ports (1 Main & 1 Auxiliary)

The Intel PRO/Wireless 2200BG Network Connection was tested installed in the Mini PCI slot of a Dell Latitude | D400 Notebook Computer MN: PPT. The Intel PRO/Wireless 2200BG Network Connection is an embedded 2.4 GHz Wireless Local Area Network Mini-PCI adapter. The Mini-PCI Type 3B form factor is designed for notebook computer systems where overall thickness must be kept to an absolute minimum and connect to antennas internal to the notebook computer. It is capable of a data rate of up to 11 Mbps in 802.11b mode and 54Mbps in 802.11g mode. Please refer to section 4.2 of this report for a further description.

NOTE 1: For a more detailed description, please refer to the manufacture's specifications or User's Manual.

NOTE 2: Refer to the antenna specifications for a further description of the antennas. Antennas will be professionally installed inside the laptop computer by the laptop vendor. The antenna gain was subtracted from the antenna cable loss to come up with the total antenna gain.

Page 7 of 17

Report Number: INTEL-050207F

FCC ID: E2K24BNHM



AEGIS LABS INC.

4.1.1 Channel Number and Frequencies

802.11b Mode		802.11g Mode	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	1	2412
2	2417	2	2417
3	2422	3	2422
4	2427	4	2427
5	2432	5	2432
6	2437	6	2437
7	2442	7	2442
8	2447	8	2447
9	2452	9	2452
10	2457	10	2457
11	2462	11	2462



AEGIS LABS INC.

4.2 EUT Configuration

The EUT was tested installed in the Mini PCI slot of a Dell Latitude | D400 Notebook Computer MN: PPT and was connected to a set of Wistron Neweb Corp. triple band antennas via its main and auxiliary antenna ports. Data can be found in Appendix A.

For conducted emissions at the AC mains port and radiated emissions, the EUT was connected to a Zoom modem, Canon printer, Dell monitor, and Logitech mouse via its serial, parallel, video, and USB ports respectively.

The low (channel 1), middle (channel 6), and high (channel 11) were tested in 802.11b & g modes. Also, the EUT was tested once transmitting from the MAIN antenna port and once transmitting from the AUX antenna port. The EUT was transmitting and receiving on a continuous basis.



AEGIS LABS INC.

4.3 List of EUT, Sub-Assemblies, and Host Equipment


LIST OF EUT AND SUB-ASSEMBLIES			
Equipment Name	Manufacturer	Model Number	Serial Number
Intel PRO/Wireless 2200BG Network Connection	Intel Corporation	WM3B2200BG	0814C0094ADC54906006
EUT Sub-Assemblies			
Latitude D400 Notebook Computer	Dell Computer Corporation	PPT	8142Y010093260105DM000
Auxiliary Triple Band Antenna	Wistron NeWeb Corp.	CAB-A	N/A
Main Triple Band Antenna	Wistron NeWeb Corp.	CAB-A	N/A

HOST EQUIPMENT LIST			
Equipment Name	Manufacturer	Model Number	Serial Number
LCD Monitor	Dell	E151FPp	CN-06R644-47804-34R-LATL
Mouse	Logitech	M-BJ58	LNA22802012

NOTE: All the power cords of the above support equipment are standard non-shielded, 1.8 meters long.



4.4 I/O Cabling Diagram and Description



- Cable 1: This is a 6-foot braid and foil shielded round cable connecting the Latitude | D400 Notebook Computer with the Dell LCD monitor. It has metallic DB-15 type connector at the computer end and is hardwired to the monitor. The cable is bundled to a length of one meter and the shield of the cable is grounded to the chassis of both devices via the connector shells.
- Cable 2: This is a 6-foot braid and foil shielded round cable connecting the Latitude | D400 Notebook Computer to the Logitech mouse. It has a metallic USB-B type connector at the computer end and is hardwired to the mouse. The shield of the cable is grounded to the chassis of the computer via the connector shell.



AEGIS LABS INC.

5.0 TEST EQUIPMENT AND TEST SETUPS

The test equipment settings and functions are selected using the guidance of ANSI C63.4-2003. All test equipment setups and operations during conducted and radiated emissions testing are in accordance with this reference document.

5.1 AC Power Line Conducted Emissions

During conducted emissions measurements, a spectrum analyzer was used as the measuring instrument along with a preselector and quasi-peak detector. A 10 dB attenuation pad was used for the protection of the spectrum analyzer input stage. The conducted emissions from the EUT in the frequency range from 150 kHz to 30 MHz were captured for graphical display through the use of automated LABVIEW EMI measurement software. All graphical readings were measured in the “Peak” mode only to reduce testing time. Upon completion of the graphical scan, the test lab personnel performed the conducted measurement scan manually using the spectrum analyzer front panel keys. The spectrum analyzer bandwidth settings for measuring “Peak”, “Average”, and/or “Quasi-Peak” conducted emissions were set at 9 kHz. The Frequency Span was set at 300 kHz, Resolution Bandwidth = 100 kHz, Video Bandwidth = 100 kHz, Sweep Time = 200msec with a reference level set at 97.0 dBuV. Attenuation was set at 10dB, Positive Peak. All peak measurements coming within 3 dB of the limit line were “Averaged” and/or “Quasi-Peaked” and denoted appropriately in the EXCEL spreadsheet.

The Equipment Under Test (EUT) was configured as a system with peripherals connected, so that at least one interface port of each type is connected to one external peripheral when tested for conducted emissions according to ANSI C63.4: 2003. Excess power cord length was wrapped in a bundle 30 to 40 centimeters in length near the center of the cord. The EUT was tested in a tabletop configuration.

The emission readings for Line 1 and Line 2 are highlighted on the data sheets in Appendix A. The graphical scans only reflects peak readings while the tabulated data sheets reflect peak, average, and/or quasi-peak readings which ever applies.



AEGIS LABS INC.

5.2 Spurious Radiated Emissions

A spectrum analyzer was used as the measuring instrumentation along with a preselector and quasi-peak-detector. The pre-amplifiers were used to increase the sensitivity of the instrument. The spectrum analyzer was used in the peak detector mode with the “max-hold” feature activated and in Positive Peak mode. In this mode, the spectrum analyzer records the highest measured reading over all the sweeps. The quasi-peak detector was used only for those readings, which are marked accordingly in the data sheet. The effective measurement bandwidth used for the radiated emissions test was 120 kHz for (30 MHz- 1000 MHz). The Frequency Span was set at 1 MHz Resolution Bandwidth = 1MHz, Video Bandwidth = 1 MHz, Sweep Time = 20msec with a reference level set at 97.0 dBuV. Attenuation was set at 0dB, Positive Peak. The spectrum analyzer operated such that the modulation of the signal was filtered out to set the analyzer in linear mode. For testing beyond 1000 MHz a spectrum analyzer capable of taking reading above 1000 MHz was connected to the high frequency amplifier, where these measurement readings were taken with the transducer placed at a 3-meter test distance from the EUT. The spectrum analyzer settings for testing beyond 1000 MHz included Resolution and Video Bandwidths set at 1 MHz, Sweep Time = 50 msec.

The Open Area Test Sites (OATS) was used for radiated emission testing. These test sites are designed according to ANSI C63.4: 2003 and ANSI C63.7: 1992 guidelines. The Measurements were conducted in accordance with ANSI C63.4: 2003 and ANSI C63.7: 1992 requirements.

Broadband biconical, log periodic, and horn antennas were used as transducers during the measurement reading phase. The frequency spans were wide (30 MHz-88 MHz, 88 MHz- 216 MHz, 216 MHz- 300 MHz, and 300 MHz- 1000 MHz). After 1000 MHz the horn antenna was used to measure emissions. The emission readings in both horizontal and vertical polarities are highlighted on the data sheets in Appendix A.

5.3 Conducted Emissions at the Antenna Port

A spectrum analyzer or power meter was used as the measuring instrumentation along with an attenuator and/or filter connected to the EUT antenna port. The attenuator and filters are used to ensure that the front end of the measurement instrument is not overloaded by the fundamental transmission. . The instruments recorded the measured readings with the bandwidths (video and resolution) set in accordance with the FCC Rules and regulations.

For the power out measurements an oscilloscope along with a schottky detector diode, 12dB attenuator, and a signal generator were used to perform the measurements.

The measured readings are on the data sheets in Appendix A.



AEGIS LABS INC.

5.4 Test and Measurement Equipment Used

TEST EQUIPMENT USED					
Equipment Name	Manufacturer	Model Number	Serial Number	Calibration Due Date	Calibration Cycle
EMI Receiver - RF Section	Hewlett Packard	85462A	3325A00137	03/29/05	1 Year
EMI Receiver – RF Filter Section	Hewlett Packard	85460A	3330A00138	03/29/05	1 Year
Attenuator - 5W-10dB	Pasternack	PE7014-10	N/A	11/03/05	2 Year
LISN (EUT)	FCC	FCC-LISN-50-25-2	9931	02/06/06	2 Year
LISN (Access)	Com-Power	LI-200	12019	01/25/06	2 Year
LISN (Access)	Com-Power	LI-200	12018	01/25/06	2 Year
Spectrum Analyzer	Agilent	8564EC	4046A00387	02/06/06	2 Years
Preamplifier	Miteq	JS42-01001800-25-10P	815980 & 884968 & 885090	12/09/05	2 Years
2400-2483.5 MHz Notch Filter	Micro-Tronics	BRM50702-02	003	04/21/06	2 Years
5725-5850 MHz Notch Filter	Microwave Circuits, Inc.	N0257881	3173-01	06/27/05	2 Years
Antenna - Biconical	EMCO	3110	9108-1421	02/11/05	1 Year
Antenna - Log Periodic	EMCO	3148	4947	02/11/05	1 Year
1-18 GHz Antenna - Horn	Com-Power	AH-118	10069	12/09/05	2 Years
18-26.5 GHz Preamplified Antenna – Horn	Custom Microwave	H042	001	11/04/05	2 Year
26.5-40 GHz Preamplified Antenna – Horn	Custom Microwave	H028	GM1260-10	11/04/05	2 Year
Power Meter	Anritsu	ML2487A	6K00001785	04/05/05	2 Years
Wide Bandwidth Sensor	Anritsu	MA2491A	31193	04/05/05	2 Years

Page 14 of 17
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

6.0 SAMPLE CALCULATIONS

If a preamplifier is used during the Radiated Emissions Testing, it is required that the amplifier gain be subtracted from the Spectrum Analyzer (Meter) Reading. In addition, a correction factor for the antenna, cable and a distance factor, if any, must be applied to the Meter Reading before a true field strength reading can be obtained. In the case of manual measurements and for greater efficiency and convenience, usage of the calibration correction factors is necessary to calculate the Corrected Meter Reading. These correlation factors for each meter reading shall be modified to reflect these correlation factors at each frequency value so that the meter readings can be compared directly to the modified specification limit. This modified specification limit is referred to as the "Corrected Meter Reading Limit" (CML).

The equation shall be derived in the following manner:

$$\text{Corrected Meter Reading} = \text{Meter Reading} + F + C - G - D$$

Where, F = Antenna Factor

C = Cable Factor

G = Amplifier Gain

D = Distance Factor

Therefore, the equation for determining the Corrected Meter Reading Limit (CML) is:

$$\text{CML} = \text{Specification Limit} - F - C + G + D$$

For the manual mode of measurement, a table of corrected meter reading limits shall be used to permit immediate comparison of the meter reading to determine if the measured emission amplitude exceeded the specification limit at that specific frequency. There shall be two calculation sheets done, one for three meter and one for ten-meter measurement distances, where applicable.



AEGIS LABS INC.

6.0 Sample Calculations (Continued)

Peak Transmit Power Output:

A correction factor for the cable must be applied to the Conducted Power before a true power reading can be obtained. This is referred to as the “Corrected Power” (CP).

The equation shall be derived in the following manner:

Corrected Power Reading = Conducted Power Reading + C

Where, C = Cable Factor

The conducted power is taken in units of dBm. To obtain units of mW the following equation is used:

$$\text{mW} = 10^{(\text{dBm}/10)}$$



AEGIS LABS INC.

7.0 MODIFICATIONS AND RECOMMENDATIONS

No modifications were made to the EUT.



AEGIS LABS INC.

APPENDIX A

TEST DATA

Page 1 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

WLAN = ON, Bluetooth = OFF
TEST DATA

Page 2 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

AC POWER LINE CONDUCTED EMISSIONS TEST RESULTS

CLIENT:	Dell Computer Corporation	DATE:	10/07/04
EUT:	Intel PRO/Wireless 2200BG Network Connection	PROJECT NUMBER:	INTEL-050207
MODEL NUMBER:	WM3B2200BG (PPT)	TEST ENGINEER:	RC
SERIAL NUMBER:	0814C009ADC54906006	SITE #:	2
CONFIGURATION:	Tested installed in the Mini PCI slot of the Dell Latitude D400 Notebook computer connected to a set of Wistron Neweb Corp. antennas.	TEMPERATURE:	18 C
		HUMIDITY:	38% RH
		TIME:	4:00 PM

Standard:	FCC CFR 47, Part 15.207
Description:	AC Power Line Conducted Emissions
Results:	Passes the conducted limits by -2.24@ 0.1521 MHz

Conducted Limits		
Frequency (MHz)	Quasi-Peak Limit (dBuV)	Average Limit (dBuV)
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

NOTE: During preliminary scans, there wasn't any difference which channel or data rate was used with the EUT; therefore only Channel 1 at a data rate of 1 Mbps was used for final testing. Also, the scan was only done with the Wistron NeWeb Corp. set of antennas.


Page 3 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AC Power Line Conducted Emissions Test Results (Continued)

AEGIS LABS INC.

CONDUCTED EMISSIONS – LINE 1						
Freq. (MHz)	Meter Reading (dBuV)	Detector (PK/QP/AV)	Average Limit (dBuV)	Average Delta (dB)	Quasi-Peak Limit (dBuV)	Quasi-Peak Delta (dB)
0.1521	52.90	PK	55.94	-3.04	65.94	-13.04
0.1650	52.50	PK	55.57	-3.07	65.57	-13.07
0.1902	49.80	PK	54.85	-5.05	64.85	-15.05
0.2412	46.40	PK	53.39	-6.99	63.39	-16.99
5.0600	36.40	PK	50.00	-13.60	60.00	-23.60
13.4450	40.70	PK	50.00	-9.30	60.00	-19.30



RBW = 100 kHz, VBW = 100 kHz


Page 4 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AC Power Line Conducted Emissions Test Results (Continued)

AEGIS LABS INC.

CONDUCTED EMISSIONS - LINE 2						
Freq. (MHz)	Meter Reading (dBuV)	Detector (PK/QP/AV)	Average Limit (dBuV)	Average Delta (dB)	Quasi-Peak Limit (dBuV)	Quasi-Peak Delta (dB)
0.1521	53.70	PK	55.94	-2.24	65.94	-12.24
0.1650	52.40	PK	55.57	-3.17	65.57	-13.17
0.1803	51.30	PK	55.13	-3.83	65.13	-13.83
0.2028	49.30	PK	54.49	-5.19	64.49	-15.19
1.1150	33.90	PK	46.00	-12.10	56.00	-22.10
11.8600	39.60	PK	50.00	-10.40	60.00	-20.40



RBW = 100 kHz, VBW = 100 kHz

Page 5 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

SPURIOUS RADIATED EMISSIONS TEST RESULTS

CLIENT:	Dell Computer Corporation	DATE:	10/07/04
EUT:	Intel PRO/Wireless 2200BG Network Connection	PROJECT NUMBER:	INTEL-050207
MODEL NUMBER:	WM3B2200BG (PPT)	TEST ENGINEER:	RC
SERIAL NUMBER:	0814C009ADC54906006	SITE #:	2
CONFIGURATION:	Tested installed in the Mini PCI slot of the Dell Latitude D400 Notebook computer connected to a set of Wistron Neweb Corp. antennas.	TEMPERATURE:	15 C
		HUMIDITY:	34% RH
		TIME:	11:30 AM

Standard:	FCC Pt. 15.209
Description:	Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in Sec. 15.209.
Results:	Passes the radiated limits by $-3.02@ 464.00\text{MHz}$ (Horizontal antenna polarization)

Radiated Limits	
Frequency (MHz)	Quasi-Peak Limit (dBuV) @ 10m
30-88	40
88-216	43.5
216-960	46
960-1000	54

NOTE 1: During preliminary scans, there wasn't any difference which channel or data rate was used with the EUT; therefore only Channel 1 at a data rate of 1 Mbps was used for final testing. Also, the scan was only done with the Wistron NeWeb Corp. set of antennas.

NOTE 2: RBW/VBW = 1 MHz

Page 6 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Peak, Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	10 Meter Distance Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
60.13	34.90	300	180		PK	34.40	1.20	8.38	10.46	20.54	40.00	-19.46
129.67	35.30	400	135		PK	34.35	1.93	14.27	10.46	27.61	43.50	-15.89
144.38	43.00	400	90	40.12	QP	34.32	2.00	14.92	10.46	33.17	43.50	-10.33
336.05	35.20	250	90		PK	34.10	3.22	15.06	10.46	29.84	46.00	-16.16
364.85	35.70	250	135		PK	34.06	3.36	15.11	10.46	30.57	46.00	-15.43
388.73	46.00	200	270	41.56	QP	34.03	3.45	15.13	10.46	36.57	46.00	-9.43

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Peak, Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	10 Meter Distance Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
60.50	47.80	100	180		PK	34.40	1.21	8.60	10.46	33.67	40.00	-6.33
129.11	43.80	100	135		PK	34.35	1.92	12.54	10.46	34.37	43.50	-9.13
143.90	43.60	100	90	40.33	QP	34.33	2.00	14.39	10.46	32.85	43.50	-10.65
336.04	35.20	100	0		PK	34.10	3.22	15.54	10.46	30.31	46.00	-15.69
364.58	33.70	100	90		PK	34.06	3.36	15.34	10.46	28.80	46.00	-17.20
388.89	44.40	100	90	39.57	QP	34.03	3.46	15.86	10.46	35.31	46.00	-10.69

NOTE: The measurements were taken at 10 meters and extrapolated to 3 meters.

NOTE 2: The measurements are Peak readings unless otherwise specified.

Page 7 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

CLIENT:	Dell Computer Corporation	DATE:	02/07/05
EUT:	Intel PRO/Wireless 2200BG Network Connection	PROJECT NUMBER:	INTEL-050207
MODEL NUMBER:	WM3B2200BG (PPT)	TEST ENGINEER:	JC
SERIAL NUMBER:	0814C009ADC54906006	SITE #:	2
CONFIGURATION:	Tested installed in the Mini PCI slot of the Dell Latitude D400 Notebook computer connected to a set of Wistron Neweb Corp. antennas in 802.11b (2412-2462 MHz) mode.	TEMPERATURE:	13 C
		HUMIDITY:	72% RH
		TIME:	4:00 PM

Standard:	FCC CFR 47, Part 15.247(c)
Description:	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.
Results:	Passes (See Data Sheets)

Unwanted Spurious Emissions Limits			
Frequency (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m) (Emissions in the restricted bands)	Field Strength (dBm/MHz) (Emissions outside the restricted bands)
Above 960	500	54.00 (Average) 74.00 (Peak)	< -20 dBc

NOTE 1: RBW/VBW = 1 MHz

Page 8 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Fundamental Measurements in 802.11b mode
Channels 1, 6, & 11
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-04

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
2412.00	69.33	100	225				3.02	29.22	101.58		
2412.00				65.77	A		3.02	29.22	98.02		
2437.00	70.33	100	225				3.04	29.27	102.64		
2437.00				66.75	A		3.04	29.27	99.06		
2462.00	68.17	100	225				3.06	29.32	100.55		
2462.00				64.04	A		3.06	29.32	96.42		

RADIATED EMISSIONS – Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
2412.00	68.67	100	0				3.02	29.42	101.12		
2412.00				62.89	A		3.02	29.42	95.34		
2437.00	69.00	100	90				3.04	29.47	101.51		
2437.00				60.98	A		3.04	29.47	93.49		
2462.00	66.83	100	225				3.06	29.52	99.41		
2462.00				63.03	A		3.06	29.52	95.61		

Page 9 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Band Edge Field Strength Measurements in 802.11b mode
Channels 1, 6, & 11
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-04

RADIATED EMISSIONS - Horizontal Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
2390.00									45.41	74.00	-28.59
2390.00									36.86	54.00	-17.14
2385.30									49.25	74.00	-24.75
2385.30									43.86	54.00	-10.14
2400.00	35.00	100	225				3.02	29.20	67.22	81.58	-14.36
2483.50									49.22	74.00	-24.78
2483.50									41.09	54.00	-12.91
2488.70									50.88	74.00	-23.12
2488.70									42.75	54.00	-11.25
RADIATED EMISSIONS – Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
2390.00									44.95	74.00	-29.05
2390.00									34.18	54.00	-19.82
2385.30									48.79	74.00	-25.21
2385.30									41.18	54.00	-12.82
2400.00	34.83	100	0				3.02	29.40	67.25	81.12	-13.87
2483.50									48.08	74.00	-25.92
2483.50									40.28	54.00	-13.72
2488.70									49.74	74.00	-24.26
2488.70									41.94	54.00	-12.06

NOTE: The “Band Edge Field Strength” was calculated using the “Fundamental” and “Conducted Band Edge” measurements per the “Marker-Delta Method” with the following formula:

$$BE = Fm - \Delta m$$

Where

BE = Band Edge Field Strength

Fm = Measured Fundamental (Peak or Average)

Δm = Measured Conducted Band Edge Delta (Peak or Average)

Page 10 of 73 (Appendix A)

Report Number: INTEL-050207F

FCC ID: E2K24BNHM




AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

(Marker Delta Conducted Band Edge Plots)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)



Page 11 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM




AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

(Marker Delta Conducted Band Edge Plots)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)



Page 12 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11b mode
Channels 1, 6, & 11
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-05

RADIATED EMISSIONS - Horizontal Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		1 Meter Distance Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)											
2312.00	32.00	100	135			9.54	2.96	29.02	54.44	74.00	-19.56
2312.00				19.25	A	9.54	2.96	29.02	41.69	54.00	-12.31
EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)											
2336.00	32.17	100	135			9.54	2.98	29.07	54.68	74.00	-19.32
2336.00				19.89	A	9.54	2.98	29.07	42.40	54.00	-11.60
EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)											
2360.00	31.17	100	135			9.54	2.99	29.12	53.74	74.00	-20.26
2360.00				17.10	A	9.54	2.99	29.12	39.67	54.00	-14.33
RADIATED EMISSIONS - Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		1 Meter Distance Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)											
2312.00	32.50	100	225			9.54	2.96	29.22	55.14	74.00	-18.86
2312.00				21.15	A	9.54	2.96	29.22	43.79	54.00	-10.21
EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)											
2336.00	32.33	100	225			9.54	2.98	29.27	55.04	74.00	-18.96
2336.00				20.31	A	9.54	2.98	29.27	43.02	54.00	-10.98
EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)											
2360.00	31.33	100	225			9.54	2.99	29.32	54.10	74.00	-19.90
2360.00				17.79	A	9.54	2.99	29.32	40.56	54.00	-13.44

NOTE: These spurious emissions measurements were taken without a preamp at a distance on 1 meter to avoid saturating the preamp and analyzer because the signals were close to the fundamental frequency. The readings were extrapolated to 1 meter.

Page 13 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11b mode
Channels 1, 6, & 11
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-06

RADIATED EMISSIONS - Horizontal Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)											
1000.03	50.50	100	270			42.66	1.93	24.90	34.67	74.00	-39.33
1000.03				40.19	A	42.66	1.93	24.90	24.36	54.00	-29.64
3216.00	48.83	100	225			43.07	3.51	30.98	40.24	81.58	-41.34
4823.95	45.67	100	225			43.27	4.35	34.10	40.85	74.00	-33.15
4823.95				33.54	A	43.27	4.35	34.10	28.72	54.00	-25.28
6432.00	44.83	100	225			43.82	5.03	35.37	41.42	81.58	-40.16
9647.99	48.83	100	180			43.22	6.19	38.11	49.91	81.58	-31.67
EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)											
1000.00	48.67	100	270			42.66	1.93	24.90	32.84	74.00	-41.16
1000.00				39.53	A	42.66	1.93	24.90	23.70	54.00	-30.30
3249.32	47.83	100	225			43.08	3.53	31.05	39.32	82.64	-43.32
4874.02	42.17	100	225			43.29	4.37	34.27	37.53	74.00	-36.47
4874.02				32.46	A	43.29	4.37	34.27	27.82	54.00	-26.18
6498.70	43.67	100	225			43.84	5.06	35.40	40.29	82.64	-42.35
9747.90	49.50	100	135			43.25	6.23	38.25	50.72	82.64	-31.92
EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)											
1000.00	48.67	100	225			42.66	1.93	24.90	32.84	74.00	-41.16
1000.00				40.00	A	42.66	1.93	24.90	24.17	54.00	-29.83
3282.66	46.83	100	225			43.10	3.55	31.12	38.40	80.55	-42.15
4923.98	44.83	100	225			43.30	4.40	34.44	40.36	74.00	-33.64
4923.98				34.34	A	43.30	4.40	34.44	29.87	54.00	-24.13
6565.37	41.83	100	225			43.84	5.08	35.62	38.70	80.55	-41.85
9847.89	49.17	100	135			43.29	6.27	38.39	50.54	80.55	-30.01

Page 14 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

RADIATED EMISSIONS - Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)											
1000.00	52.17	100	180			42.66	1.93	25.00	36.44	74.00	-37.56
1000.00				42.49	A	42.66	1.93	25.00	26.76	54.00	-27.24
3216.00	47.00	100	180			43.07	3.51	31.09	38.53	81.12	-42.59
4823.98	44.50	100	180			43.27	4.35	34.07	39.65	74.00	-34.35
4823.98				34.93	A	43.27	4.35	34.07	30.08	54.00	-23.92
6432.01	44.50	100	315			43.82	5.03	35.35	41.06	81.12	-40.06
9648.03	55.17	125	270			43.22	6.19	38.17	56.31	81.12	-24.81
EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)											
1000.01	49.33	100	45			42.66	1.93	25.00	33.60	74.00	-40.40
1000.01				41.01	A	42.66	1.93	25.00	25.28	54.00	-28.72
3249.33	49.00	100	225			43.08	3.53	31.15	40.59	81.51	-40.92
4874.04	44.17	100	225			43.29	4.37	34.22	39.48	74.00	-34.52
4874.04				35.11	A	43.29	4.37	34.22	30.42	54.00	-23.58
6498.64	44.00	100	225			43.84	5.06	35.40	40.62	81.51	-40.89
9747.99	55.17	100	90			43.25	6.23	38.35	56.49	81.51	-25.02
EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)											
1000.00	50.00	100	180			42.66	1.93	25.00	34.27	74.00	-39.73
1000.00				41.15	A	42.66	1.93	25.00	25.42	54.00	-28.58
3282.66	47.17	100	225			43.10	3.55	31.21	38.83	79.41	-40.58
4923.91	44.83	100	225			43.30	4.40	34.37	40.29	74.00	-33.71
4923.91				36.97	A	43.30	4.40	34.37	32.43	54.00	-21.57
6565.40	42.50	100	225			43.84	5.08	35.60	39.34	79.41	-40.07
9848.05	54.17	100	45			43.29	6.27	38.53	55.68	79.41	-23.73

Page 15 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11b mode
Channels 1, 6, & 11
Continuous RX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-06

RADIATED EMISSIONS - Horizontal Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Receive Mode on Channel 1 (2.412 GHz)											
3216.00	47.67	100	135			43.07	3.51	30.98	39.08	80.00	-40.92
3216.00				41.37	A	43.07	3.51	30.98	32.78	60.00	-27.22
6432.05	42.17	100	225			43.82	5.03	35.37	38.76	80.00	-41.24
6432.05				32.32	A	43.82	5.03	35.37	28.91	60.00	-31.09
9648.00	42.83	100	225			43.22	6.19	38.11	43.91	80.00	-36.09
9648.00				32.85	A	43.22	6.19	38.11	33.93	60.00	-26.07
EUT in Continuous Receive Mode on Channel 6 (2.437 GHz)											
3249.35	47.67	100	225			43.08	3.53	31.05	39.16	80.00	-40.84
3249.35				41.75	A	43.08	3.53	31.05	33.24	60.00	-26.76
6498.65	42.67	100	315			43.84	5.06	35.40	39.29	80.00	-40.71
6498.65				33.26	A	43.84	5.06	35.40	29.88	60.00	-30.12
9748.02	42.00	100	315			43.25	6.23	38.25	43.22	80.00	-36.78
9748.02				32.78	A	43.25	6.23	38.25	34.00	60.00	-26.00
EUT in Continuous Receive Mode on Channel 11 (2.462 GHz)											
3282.61	46.33	100	180			43.10	3.55	31.12	37.90	80.00	-42.10
3282.61				39.36	A	43.10	3.55	31.12	30.93	60.00	-29.07
6565.46	42.00	100	225			43.84	5.08	35.62	38.87	80.00	-41.13
6565.46				32.14	A	43.84	5.08	35.62	29.01	60.00	-30.99
9848.03	43.67	100	225			43.29	6.27	38.39	45.04	80.00	-34.96
9848.03				33.67	A	43.29	6.27	38.39	35.04	60.00	-24.96

Page 16 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

RADIATED EMISSIONS - Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Receive Mode on Channel 1 (2.412 GHz)											
3216.00	48.17	100	225			43.07	3.51	31.09	39.70	80.00	-40.30
3216.00				42.42	A	43.07	3.51	31.09	33.95	60.00	-26.05
6432.05	42.83	100	225			43.82	5.03	35.35	39.39	80.00	-40.61
6432.05				32.61	A	43.82	5.03	35.35	29.17	60.00	-30.83
9648.00	43.67	100	225			43.22	6.19	38.17	44.81	80.00	-35.19
9648.00				32.85	A	43.22	6.19	38.17	33.99	60.00	-26.01
EUT in Continuous Receive Mode on Channel 6 (2.437 GHz)											
3249.35	49.00	100	225			43.08	3.53	31.15	40.59	80.00	-39.41
3249.35				43.78	A	43.08	3.53	31.15	35.37	60.00	-24.63
6498.65	44.00	100	45			43.84	5.06	35.40	40.62	80.00	-39.38
6498.65				33.35	A	43.84	5.06	35.40	29.97	60.00	-30.03
9748.02	42.67	125	315			43.25	6.23	38.35	43.99	80.00	-36.01
9748.02				32.89	A	43.25	6.23	38.35	34.21	60.00	-25.79
EUT in Continuous Receive Mode on Channel 11 (2.462 GHz)											
3282.61	47.50	100	225			43.10	3.55	31.21	39.16	80.00	-40.84
3282.61				42.44	A	43.10	3.55	31.21	34.10	60.00	-25.90
6565.46	42.17	100	45			43.84	5.08	35.60	39.01	80.00	-40.99
6565.46				32.32	A	43.84	5.08	35.60	29.16	60.00	-30.84
9848.03	45.17	100	225			43.29	6.27	38.53	46.68	80.00	-33.32
9848.03				35.17	A	43.29	6.27	38.53	36.68	60.00	-23.32



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

CLIENT:	Dell Computer Corporation	DATE:	02/07/05
EUT:	Intel PRO/Wireless 2200BG Network Connection	PROJECT NUMBER:	INTEL-050207
MODEL NUMBER:	WM3B2200BG (PPT)	TEST ENGINEER:	JC
SERIAL NUMBER:	0814C009ADC54906006	SITE #:	2
CONFIGURATION:	Tested installed in the Mini PCI slot of the Dell Latitude D400 Notebook computer connected to a set of Wistron Neweb Corp. antennas in 802.11g (2412-2462 MHz) mode.	TEMPERATURE:	13 C
		HUMIDITY:	72% RH
		TIME:	4:00 PM

Standard:	FCC CFR 47, Part 15.247(c)
Description:	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.
Results:	Passes (See Data Sheets)

Unwanted Spurious Emissions Limits			
Frequency (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m) (Emissions in the restricted bands)	Field Strength (dBm/MHz) (Emissions outside the restricted bands)
Above 960	500	54.00 (Average) 74.00 (Peak)	< -20 dBc

NOTE 1: RBW/VBW = 1 MHz

Page 18 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Fundamental Measurements in 802.11g mode
Channels 1, 6, & 11
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-04

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
2412.00	63.00	100	225				3.02	29.22	95.25		
2412.00				51.78	A		3.02	29.22	84.03		
2437.00	62.17	100	225				3.04	29.27	94.48		
2437.00				51.86	A		3.04	29.27	84.17		
2462.00	61.67	100	225				3.06	29.32	94.05		
2462.00				52.54	A		3.06	29.32	84.92		

RADIATED EMISSIONS – Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
2412.00	62.67	100	90				3.02	29.42	95.12		
2412.00				52.75	A		3.02	29.42	85.20		
2437.00	62.17	100	90				3.04	29.47	94.68		
2437.00				52.46	A		3.04	29.47	84.97		
2462.00	60.50	100	270				3.06	29.52	93.08		
2462.00				51.48	A		3.06	29.52	84.06		

Page 19 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Band Edge Field Strength Measurements in 802.11g mode
Channels 1, 6, & 11
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-04

RADIATED EMISSIONS - Horizontal Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
2390.00									51.42	74.00	-22.58
2390.00									38.36	54.00	-15.64
2400.00	38.83	100	225				3.02	29.20	71.05	75.25	-4.20
2483.50									53.71	74.00	-20.29
2483.50									41.09	54.00	-12.91
RADIATED EMISSIONS - Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
2390.00									51.29	74.00	-22.71
2390.00									39.53	54.00	-14.47
2400.00	38.33	100	90				3.02	29.40	70.75	75.12	-4.37
2483.50									52.74	74.00	-21.26
2483.50									40.23	54.00	-13.77

NOTE: The “Band Edge Field Strength” was calculated using the “Fundamental” and “Conducted Band Edge” measurements per the “Marker-Delta Method” with the following formula:

$$BE = F_m - \Delta m$$

Where

BE = Band Edge Field Strength

F_m = Measured Fundamental (Peak or Average)

Δm = Measured Conducted Band Edge Delta (Peak or Average)

Page 20 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM




AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

(Marker Delta Conducted Band Edge Plots)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)



Page 21 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM




AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

(Marker Delta Conducted Band Edge Plots)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)



Page 22 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11g mode
Channels 1, 6, & 11
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-05

RADIATED EMISSIONS - Horizontal Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		1 Meter Distance Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)											
2312.00	32.17	100	135			9.54	2.96	29.02	54.61	74.00	-19.39
2312.00				19.13	A	9.54	2.96	29.02	41.57	54.00	-12.43
EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)											
2336.00	32.00	100	135			9.54	2.98	29.07	54.51	74.00	-19.49
2336.00				19.86	A	9.54	2.98	29.07	42.37	54.00	-11.63
EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)											
2360.00	31.17	100	135			9.54	2.99	29.12	53.74	74.00	-20.26
2360.00				16.25	A	9.54	2.99	29.12	38.82	54.00	-15.18
RADIATED EMISSIONS - Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		1 Meter Distance Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)											
2312.00	32.83	100	225			9.54	2.96	29.22	55.47	74.00	-18.53
2312.00				21.44	A	9.54	2.96	29.22	44.08	54.00	-9.92
EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)											
2336.00	32.67	100	225			9.54	2.98	29.27	55.38	74.00	-18.62
2336.00				20.15	A	9.54	2.98	29.27	42.86	54.00	-11.14
EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)											
2360.00	31.00	100	225			9.54	2.99	29.32	53.77	74.00	-20.23
2360.00				16.58	A	9.54	2.99	29.32	39.35	54.00	-14.65

NOTE: These spurious emissions measurements were taken without a preamp at a distance on 1 meter to avoid saturating the preamp and analyzer because the signals were close to the fundamental frequency. The readings were extrapolated to 1 meter.

Page 23 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11g mode
Channels 1, 6, & 11
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-06

RADIATED EMISSIONS - Horizontal Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)											
1000.00	50.50	100	270			42.66	1.93	24.90	34.67	74.00	-39.33
1000.00				41.70	A	42.66	1.93	24.90	25.87	54.00	-28.13
3216.03	47.17	100	225			43.07	3.51	30.98	38.58	75.25	-36.67
4823.97	43.00	100	135			43.27	4.35	34.10	38.18	74.00	-35.82
4823.97				32.51	A	43.27	4.35	34.10	27.69	54.00	-26.31
6432.02	44.83	100	225			43.82	5.03	35.37	41.42	75.25	-33.83
9748.00	43.83	100	315			43.25	6.23	38.25	45.05	75.25	-30.20
EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)											
1000.00	50.67	100	270			42.66	1.93	24.90	34.84	74.00	-39.16
1000.00				41.40	A	42.66	1.93	24.90	25.57	54.00	-28.43
3249.35	47.50	125	225			43.08	3.53	31.05	38.99	74.48	-35.49
4873.96	44.17	100	135			43.29	4.37	34.27	39.53	74.00	-34.47
4873.96				31.75	A	43.29	4.37	34.27	27.11	54.00	-26.89
6498.67	43.17	100	135			43.84	5.06	35.40	39.79	74.48	-34.69
9748.02	44.17	100	315			43.25	6.23	38.25	45.39	74.48	-29.09
EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)											
1000.00	49.50	100	270			42.66	1.93	24.90	33.67	74.00	-40.33
1000.00				41.04	A	42.66	1.93	24.90	25.21	54.00	-28.79
3282.66	44.33	100	225			43.10	3.55	31.12	35.90	74.05	-38.15
4924.00	42.83	100	135			43.30	4.40	34.44	38.36	74.00	-35.64
4924.00				32.68	A	43.30	4.40	34.44	28.21	54.00	-25.79
6565.32	42.50	100	135			43.84	5.08	35.62	39.37	74.05	-34.68
9848.02	44.00	100	315			43.29	6.27	38.39	45.37	74.05	-28.68

Page 24 of 73 (Appendix A)
 Report Number: INTEL-050207F
 FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

RADIATED EMISSIONS - Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)											
1000.00	51.17	100	180			42.66	1.93	25.00	35.44	74.00	-38.56
1000.00				41.81	A	42.66	1.93	25.00	26.08	54.00	-27.92
3216.01	47.50	100	225			43.07	3.51	31.09	39.03	75.12	-36.09
4823.98	43.17	100	135			43.27	4.35	34.07	38.32	74.00	-35.68
4823.98				32.37	A	43.27	4.35	34.07	27.52	54.00	-26.48
6532.02	43.17	100	225			43.84	5.07	35.50	39.90	75.12	-35.22
9747.98	43.50	100	315			43.25	6.23	38.35	44.82	75.12	-30.30
EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)											
1000.20	50.33	100	45			42.66	1.93	25.00	34.60	74.00	-39.40
1000.20				42.24	A	42.66	1.93	25.00	26.51	54.00	-27.49
3249.33	47.83	100	225			43.08	3.53	31.15	39.42	74.68	-35.26
4874.02	42.33	100	135			43.29	4.37	34.22	37.64	74.00	-36.36
4874.02				32.06	A	43.29	4.37	34.22	27.37	54.00	-26.63
6498.69	43.17	100	225			43.84	5.06	35.40	39.79	74.68	-34.89
9748.06	44.00	100	315			43.25	6.23	38.35	45.32	74.68	-29.36
EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)											
1000.00	52.33	100	180			42.66	1.93	25.00	36.60	74.00	-37.40
1000.00				42.54	A	42.66	1.93	25.00	26.81	54.00	-27.19
3282.65	46.50	100	225			43.10	3.55	31.21	38.16	73.08	-34.92
4923.98	44.50	100	135			43.30	4.40	34.37	39.96	74.00	-34.04
4923.98				32.51	A	43.30	4.40	34.37	27.97	54.00	-26.03
6565.36	42.83	100	225			43.84	5.08	35.60	39.67	73.08	-33.41
9848.10	44.33	100	270			43.29	6.27	38.53	45.84	73.08	-27.24

Page 25 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11g mode
Channels 1, 6, & 11
Continuous RX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-06

RADIATED EMISSIONS - Horizontal Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Receive Mode on Channel 1 (2.412 GHz)											
3216.00	48.83	100	225			43.07	3.51	30.98	40.24	80.00	-39.76
3216.00				43.71	A	43.07	3.51	30.98	35.12	60.00	-24.88
6432.05	42.83	100	45			43.82	5.03	35.37	39.42	80.00	-40.58
6432.05				32.37	A	43.82	5.03	35.37	28.96	60.00	-31.04
9648.00	43.83	100	315			43.22	6.19	38.11	44.91	80.00	-35.09
9648.00				32.89	A	43.22	6.19	38.11	33.97	60.00	-26.03
EUT in Continuous Receive Mode on Channel 6 (2.437 GHz)											
3249.35	49.17	100	225			43.08	3.53	31.05	40.66	80.00	-39.34
3249.35				44.30	A	43.08	3.53	31.05	35.79	60.00	-24.21
6498.65	44.67	100	45			43.84	5.06	35.40	41.29	80.00	-38.71
6498.65				33.63	A	43.84	5.06	35.40	30.25	60.00	-29.75
9748.02	43.00	100	225			43.25	6.23	38.25	44.22	80.00	-35.78
9748.02				32.71	A	43.25	6.23	38.25	33.93	60.00	-26.07
EUT in Continuous Receive Mode on Channel 11 (2.462 GHz)											
3282.61	46.17	125	225			43.10	3.55	31.12	37.74	80.00	-42.26
3282.61				41.21	A	43.10	3.55	31.12	32.78	60.00	-27.22
6565.46	41.83	100	45			43.84	5.08	35.62	38.70	80.00	-41.30
6565.46				32.22	A	43.84	5.08	35.62	29.09	60.00	-30.91
9848.03	43.50	100	315			43.29	6.27	38.39	44.87	80.00	-35.13
9848.03				33.19	A	43.29	6.27	38.39	34.56	60.00	-25.44

Page 26 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

RADIATED EMISSIONS - Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Receive Mode on Channel 1 (2.412 GHz)											
3216.00	48.33	100	225			43.07	3.51	31.09	39.86	80.00	-40.14
3216.00				42.56	A	43.07	3.51	31.09	34.09	60.00	-25.91
6432.05	41.50	100	45			43.82	5.03	35.35	38.06	80.00	-41.94
6432.05				32.09	A	43.82	5.03	35.35	28.65	60.00	-31.35
9648.00	44.17	100	225			43.22	6.19	38.17	45.31	80.00	-34.69
9648.00				32.80	A	43.22	6.19	38.17	33.94	60.00	-26.06
EUT in Continuous Receive Mode on Channel 6 (2.437 GHz)											
3249.35	49.00	100	225			43.08	3.53	31.15	40.59	80.00	-39.41
3249.35				44.07	A	43.08	3.53	31.15	35.66	60.00	-24.34
6498.65	43.00	100	45			43.84	5.06	35.40	39.62	80.00	-40.38
6498.65				33.17	A	43.84	5.06	35.40	29.79	60.00	-30.21
9748.02	44.33	100	225			43.25	6.23	38.35	45.65	80.00	-34.35
9748.02				34.04	A	43.25	6.23	38.35	35.36	60.00	-24.64
EUT in Continuous Receive Mode on Channel 11 (2.462 GHz)											
3282.61	47.17	100	225			43.10	3.55	31.21	38.83	80.00	-41.17
3282.61				42.37	A	43.10	3.55	31.21	34.03	60.00	-25.97
6565.46	43.17	100	45			43.84	5.08	35.60	40.01	80.00	-39.99
6565.46				32.22	A	43.84	5.08	35.60	29.06	60.00	-30.94
9848.03	45.33	125	225			43.29	6.27	38.53	46.84	80.00	-33.16
9848.03				36.87	A	43.29	6.27	38.53	38.38	60.00	-21.62



AEGIS LABS INC.

PEAK TRANSMIT POWER

CLIENT:	Dell Computer Corporation	DATE:	02/07/05
EUT:	Intel PRO/Wireless 2200BG Network Connection	PROJECT NUMBER:	INTEL-050207-01
MODEL NUMBER:	WM3B2200BG (PPT)	TEST ENGINEER:	JC
SERIAL NUMBER:	0814C009ADC54906006	SITE #:	2
CONFIGURATION:	Tested installed in the Mini PCI slot of the Dell Latitude D400 Notebook computer.	TEMPERATURE:	13 C
		HUMIDITY:	77% RH
		TIME:	2:45 PM

Standard:	FCC CFR 47, Part 15.247(b)(1)
Description:	The maximum peak output power of the intentional radiator shall not exceed 1 watt.
Results:	See Data Sheet

Peak Transmit Power Limits	
Frequency (MHz)	Output Power (W)
2412-2462	1

Page 28 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



Peak Transmit Power (Continued)

Mode	Channel	Frequency (MHz)	Rate (Mbps)	Average Power (dBm)	Average Power (mW)	Peak Power (dBm)	Peak Power (mW)
802.11b	1	2412	1	14.00	25.12	16.20	41.69
802.11b	1	2412	5.5	13.40	21.88	16.20	41.69
802.11b	1	2412	11	12.80	19.05	16.20	41.69
802.11b	2	2417	1	15.10	32.36	17.30	53.70
802.11b	2	2417	5.5	14.20	26.30	17.00	50.12
802.11b	2	2417	11	13.50	22.39	17.00	50.12
802.11b	6	2437	1	15.10	32.36	17.40	54.95
802.11b	6	2437	5.5	14.30	26.92	17.20	52.48
802.11b	6	2437	11	13.60	22.91	17.20	52.48
802.11b	10	2457	1	14.90	30.90	17.10	51.29
802.11b	10	2457	5.5	14.00	25.12	16.80	47.86
802.11b	10	2457	11	13.40	21.88	16.90	48.98
802.11b	11	2462	1	14.20	26.30	16.40	43.65
802.11b	11	2462	5.5	13.30	21.38	16.10	40.74
802.11b	11	2462	11	12.70	18.62	16.10	40.74
802.11g	1	2412	6	6.20	4.17	16.10	40.74
802.11g	1	2412	36	4.70	2.95	16.10	40.74
802.11g	1	2412	54	4.20	2.63	16.00	39.81
802.11g	6	2437	6	6.10	4.07	16.10	40.74
802.11g	6	2437	36	4.70	2.95	16.00	39.81
802.11g	6	2437	54	4.20	2.63	16.00	39.81
802.11g	11	2462	6	5.80	3.80	16.00	39.81
802.11g	11	2462	36	4.30	2.69	15.90	38.90
802.11g	11	2462	54	3.80	2.40	16.00	39.81

NOTE: The output power measurement is conducted.



AEGIS LABS INC.

6 dB EMISSIONS BANDWIDTH

CLIENT:	Dell Computer Corporation	DATE:	02/17/05
EUT:	Intel PRO/Wireless 2200BG Network Connection	PROJECT NUMBER:	INTEL-050207
MODEL NUMBER:	WM3B2200BG (PPT)	TEST ENGINEER:	JC
SERIAL NUMBER:	0814C009ADC54906006	SITE #:	2
CONFIGURATION:	Tested installed in the Mini PCI slot of the Dell Latitude D400 Notebook computer.	TEMPERATURE:	11 C
		HUMIDITY:	83% RH
		TIME:	9:15 AM

Standard:	FCC CFR 47, Part 15.247(a)(2)
Description:	The minimum 6dB bandwidth shall be at least 500 kHz.
Results:	See Data Sheets



Page 30 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

6 dB Emissions Bandwidth (Continued)

802.11b Mode

Test Date	Data	Test Eng.
02/17/05	2.412 GHz (INTEL-050207-02b1)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ ΔMKR 0dB 9.58MHz  CENTER 2.41200GHz SPAN 50.00MHz *RBW 100kHz *VBW 300kHz SWP 50.0ms		
Test Date	Data	Test Eng.
02/17/05	2.437 GHz (INTEL-050207-02b3)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ ΔMKR -.67dB 9.58MHz  CENTER 2.43700GHz SPAN 50.00MHz *RBW 100kHz *VBW 300kHz SWP 50.0ms		


Page 31 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

6 dB Emissions Bandwidth (Continued)

802.11b Mode







AEGIS LABS INC.

6 dB Emissions Bandwidth (Continued)

802.11g Mode

Test Date	Data	Test Eng.
02/17/05	2.412 GHz (INTEL-050207-03b1)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ ΔMKR .33dB 16.58MHz  CENTER 2.41200GHz SPAN 50.00MHz *RBW 100kHz *VBW 300kHz SWP 50.0ms		
Test Date	Data	Test Eng.
02/17/05	2.437 GHz (INTEL-050207-03b2)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ ΔMKR -.33dB 16.67MHz  CENTER 2.43700GHz SPAN 50.00MHz *RBW 100kHz *VBW 300kHz SWP 50.0ms		


Page 33 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

6 dB Emissions Bandwidth (Continued)

802.11g Mode



Page 34 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

PEAK POWER SPECTRAL DENSITY

CLIENT:	Dell Computer Corporation	DATE:	02/17/05
EUT:	Intel PRO/Wireless 2200BG Network Connection	PROJECT NUMBER:	INTEL-050207
MODEL NUMBER:	WM3B2200BG (PPT)	TEST ENGINEER:	JC
SERIAL NUMBER:	0814C009ADC54906006	SITE #:	2
CONFIGURATION:	Tested installed in the Mini PCI slot of the Dell Latitude D400 Notebook computer.	TEMPERATURE:	11 C
		HUMIDITY:	83% RH
		TIME:	9:15 AM

Standard:	FCC CFR 47, Part 15.247(d)
Description:	The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.
Results:	See Data Sheets

Peak Power Spectral Density Limits	
Frequency (MHz)	Limit (dBm)
2412-2462	8



Page 35 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Peak Power Spectral Density (Continued)

802.11b Mode

Test Date	Data	Test Eng.
02/17/05	2.412 GHz (INTEL-050207-02d1)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -8.50dBm 2.412700GHz  CENTER 2.412000GHz SPAN 1.500MHz *RBW 3.0kHz *VBW 3.0kHz *SWP 500sec		
Test Date	Data	Test Eng.
02/17/05	2.437 GHz (INTEL-050207-02d3)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -6.83dBm 2.436333GHz  CENTER 2.437000GHz SPAN 1.500MHz *RBW 3.0kHz *VBW 3.0kHz *SWP 500sec		


Page 36 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Peak Power Spectral Density (Continued)

802.11b Mode




Page 37 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Peak Power Spectral Density (Continued)

802.11g Mode




Page 38 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Peak Power Spectral Density (Continued)

802.11g Mode





AEGIS LABS INC.

CONDUCTED OUT OF BAND EMISSIONS

CLIENT:	Dell Computer Corporation	DATE:	02/17/05
EUT:	Intel PRO/Wireless 2200BG Network Connection	PROJECT NUMBER:	INTEL-050207
MODEL NUMBER:	WM3B2200BG (PPT)	TEST ENGINEER:	JC
SERIAL NUMBER:	0814C009ADC54906006	SITE #:	2
CONFIGURATION:	Tested installed in the Mini PCI slot of the Dell Latitude D400 Notebook computer.	TEMPERATURE:	11 C
		HUMIDITY:	83% RH
		TIME:	9:15 AM

Standard:	FCC CFR 47, Part 15.407(b)(1) and 15.407(b)(2)
Description:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.





Page 40 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11b Mode

Test Date	Data	Test Eng.
02/17/05	2.412 GHz (INTEL-050207-02e01)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -55.50dBm 457MHz  START 30MHz STOP 2.000GHz *RBW 100kHz *VBW 300kHz SWP 1.10sec *ATTEN 20dB RL 10.0dBm 10dB/ MKR -43.50dBm 9.653GHz  START 2.000GHz STOP 10.000GHz *RBW 100kHz *VBW 300kHz SWP 4.40sec		
Test Date	Data	Test Eng.
02/17/05	2.412 GHz (INTEL-050207-02e02)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -43.50dBm 9.653GHz  START 2.000GHz STOP 10.000GHz *RBW 100kHz *VBW 300kHz SWP 4.40sec *ATTEN 20dB RL 10.0dBm 10dB/ MKR -43.50dBm 9.653GHz  START 2.000GHz STOP 10.000GHz *RBW 100kHz *VBW 300kHz SWP 4.40sec		

Page 41 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11b Mode

Test Date	Data	Test Eng.
02/17/05	2.412 GHz (INTEL-050207-02e03)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -59.50dBm 13.33GHz START 10.00GHz STOP 20.00GHz *RBW 100kHz *VBW 300kHz SWP 5.50sec *ATTEN 20dB RL 10.0dBm 10dB/ MKR -56.83dBm 24.650GHz START 20.000GHz STOP 26.000GHz *RBW 100kHz *VBW 300kHz SWP 3.30sec		
Test Date	Data	Test Eng.
02/17/05	2.412 GHz (INTEL-050207-02e04)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -56.83dBm 24.650GHz START 20.000GHz STOP 26.000GHz *RBW 100kHz *VBW 300kHz SWP 3.30sec *ATTEN 20dB RL 10.0dBm 10dB/ MKR -56.83dBm 24.650GHz START 20.000GHz STOP 26.000GHz *RBW 100kHz *VBW 300kHz SWP 3.30sec		





Page 42 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11b Mode

Test Date	Data	Test Eng.
02/17/05	2.437 GHz (INTEL-050207-02e09)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -50.83dBm 483MHz  START 30MHz STOP 2.000GHz *RBW 100kHz *VBW 300kHz SWP 1.10sec *ATTEN 20dB RL 10.0dBm 10dB/ MKR -40.33dBm 9.747GHz  START 2.000GHz STOP 10.000GHz *RBW 100kHz *VBW 300kHz SWP 4.40sec		
Test Date	Data	Test Eng.
02/17/05	2.437 GHz (INTEL-050207-02e10)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -40.33dBm 9.747GHz  START 2.000GHz STOP 10.000GHz *RBW 100kHz *VBW 300kHz SWP 4.40sec *ATTEN 20dB RL 10.0dBm 10dB/ MKR -40.33dBm 9.747GHz  START 2.000GHz STOP 10.000GHz *RBW 100kHz *VBW 300kHz SWP 4.40sec		



Page 43 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11b Mode

Test Date	Data	Test Eng.
02/17/05	2.437 GHz (INTEL-050207-02e11)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -59.17dBm 13.37GHz  START 10.00GHz STOP 20.00GHz *RBW 100kHz *VBW 300kHz SWP 5.50sec 		
Test Date	Data	Test Eng.
02/17/05	2.437 GHz (INTEL-050207-02e12)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -56.83dBm 24.510GHz  START 20.000GHz STOP 26.000GHz *RBW 100kHz *VBW 300kHz SWP 3.30sec 		



Page 44 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11b Mode

Test Date	Data	Test Eng.
02/17/05	2.462 GHz (INTEL-050207-02e17)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -52.33dBm 506MHz  START 30MHz STOP 2.000GHz *RBW 100kHz *VBW 300kHz SWP 1.10sec		
Test Date	Data	Test Eng.
02/17/05	2.462 GHz (INTEL-050207-02e18)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -37.67dBm 9.853GHz  START 2.000GHz STOP 10.000GHz *RBW 100kHz *VBW 300kHz SWP 4.40sec		



Page 45 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11b Mode

Test Date	Data	Test Eng.
02/17/05	2.462 GHz (INTEL-050207-02e19)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -59.67dBm 14.22GHz  START 10.00GHz STOP 20.00GHz *RBW 100kHz *VBW 300kHz SWP 5.50sec		
Test Date	Data	Test Eng.
02/17/05	2.462 GHz (INTEL-050207-02e20)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -56.67dBm 25.310GHz  START 20.000GHz STOP 26.000GHz *RBW 100kHz *VBW 300kHz SWP 3.30sec		



Page 46 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11g Mode

Test Date	Data	Test Eng.
02/17/05	2.412 GHz (INTEL-050207-03e01)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -64.83dBm 503MHz  START 30MHz STOP 2.000GHz *RBW 100kHz *VBW 300kHz SWP 1.10sec		
Test Date	Data	Test Eng.
02/17/05	2.412 GHz (INTEL-050207-03e02)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -44.83dBm 2.307GHz  START 2.000GHz STOP 10.000GHz *RBW 100kHz *VBW 300kHz SWP 4.40sec		



Page 47 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11g Mode

Test Date	Data	Test Eng.
02/17/05	2.412 GHz (INTEL-050207-03e03)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -58.83dBm 14.20GHz  START 10.00GHz STOP 20.00GHz *RBW 100kHz *VBW 300kHz SWP 5.50sec 		
Test Date	Data	Test Eng.
02/17/05	2.412 GHz (INTEL-050207-03e04)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -56.33dBm 24.610GHz  START 20.000GHz STOP 26.000GHz *RBW 100kHz *VBW 300kHz SWP 3.30sec 		



Page 48 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11g Mode

Test Date	Data	Test Eng.
02/17/05	2.437 GHz (INTEL-050207-03e05)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -65.17dBm 480MHz  START 30MHz STOP 2.000GHz *RBW 100kHz *VBW 300kHz SWP 1.10sec		
Test Date	Data	Test Eng.
02/17/05	2.437 GHz (INTEL-050207-03e06)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -45.33dBm 2.333GHz  START 2.000GHz STOP 10.000GHz *RBW 100kHz *VBW 300kHz SWP 4.40sec		





Page 49 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11g Mode

Test Date	Data	Test Eng.
02/17/05	2.437 GHz (INTEL-050207-03e07)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -59.50dBm 13.38GHz  START 10.00GHz STOP 20.00GHz *RBW 100kHz *VBW 300kHz SWP 5.50sec *ATTEN 20dB RL 10.0dBm 10dB/ MKR -56.17dBm 25.430GHz  START 20.000GHz STOP 26.000GHz *RBW 100kHz *VBW 300kHz SWP 3.30sec		
Test Date	Data	Test Eng.
02/17/05	2.437 GHz (INTEL-050207-03e08)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -56.17dBm 25.430GHz  START 20.000GHz STOP 26.000GHz *RBW 100kHz *VBW 300kHz SWP 3.30sec *ATTEN 20dB RL 10.0dBm 10dB/ MKR -56.17dBm 25.430GHz  START 20.000GHz STOP 26.000GHz *RBW 100kHz *VBW 300kHz SWP 3.30sec		



Page 50 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11g Mode

Test Date	Data	Test Eng.
02/17/05	2.462 GHz (INTEL-050207-03e09)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -64.83dBm 463MHz  START 30MHz *RBW 100kHz STOP 2.000GHz *VBW 300kHz SWP 1.10sec 		
Test Date	Data	Test Eng.
02/17/05	2.462 GHz (INTEL-050207-03e10)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -47.17dBm 2.253GHz  START 2.000GHz *RBW 100kHz STOP 10.000GHz *VBW 300kHz SWP 4.40sec 		



Page 51 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11g Mode

Test Date	Data	Test Eng.
02/17/05	2.462 GHz (INTEL-050207-03e11)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -58.17dBm 13.38GHz  START 10.00GHz STOP 20.00GHz *RBW 100kHz *VBW 300kHz SWP 5.50sec		
Test Date	Data	Test Eng.
02/17/05	2.462 GHz (INTEL-050207-03e12)	JC
*ATTEN 20dB RL 10.0dBm 10dB/ MKR -56.17dBm 25.340GHz  START 20.000GHz STOP 26.000GHz *RBW 100kHz *VBW 300kHz SWP 3.30sec		

Page 52 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

WLAN = ON, Bluetooth = ON
TEST DATA

Page 53 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

CLIENT:	Dell Computer Corporation	DATE:	02/09/05
EUT:	Intel PRO/Wireless 2200BG Network Connection	PROJECT NUMBER:	INTEL-050207
MODEL NUMBER:	WM3B2200BG (PPT)	TEST ENGINEER:	JC
SERIAL NUMBER:	0814C009ADC54906006	SITE #:	2
CONFIGURATION:	Tested installed in the Mini PCI slot of the Dell Latitude D400 Notebook computer connected to a set of Wistron Neweb Corp. antennas in 802.11b (2412-2462 MHz) mode.	TEMPERATURE:	7 C
		HUMIDITY:	90% RH
		TIME:	8:00 AM

Standard:	FCC CFR 47, Part 15.247(c)
Description:	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.
Results:	Passes (See Data Sheets)

Unwanted Spurious Emissions Limits			
Frequency (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m) (Emissions in the restricted bands)	Field Strength (dBm/MHz) (Emissions outside the restricted bands)
Above 960	500	54.00 (Average) 74.00 (Peak)	< -20 dBc

NOTE 1: RBW/VBW = 1 MHz

Page 54 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Fundamental Measurements in 802.11b mode
Channels 1, 6, & 11
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-07

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
2412.00	69.83	100	225				3.02	29.22	102.08		
2412.00				66.03	A		3.02	29.22	98.28		
2437.00	70.00	100	225				3.04	29.27	102.31		
2437.00				66.26	A		3.04	29.27	98.57		
2462.00	67.67	100	225				3.06	29.32	100.05		
2462.00				63.54	A		3.06	29.32	95.92		

RADIATED EMISSIONS – Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
2412.00	69.50	100	0				3.02	29.42	101.95		
2412.00				65.94	A		3.02	29.42	98.39		
2437.00	69.50	100	45				3.04	29.47	102.01		
2437.00				65.74	A		3.04	29.47	98.25		
2462.00	68.00	100	45				3.06	29.52	100.58		
2462.00				64.13	A		3.06	29.52	96.71		

Page 55 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Band Edge Field Strength Measurements in 802.11b mode
Channels 1, 6, & 11
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-07

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
2390.00								45.91	74.00	-28.09
2390.00								37.12	54.00	-16.88
2385.30								49.75	74.00	-24.25
2385.30								44.12	54.00	-9.88
2400.00	35.17	100	225			3.02	29.20	67.39	82.08	-14.69
2483.50								48.72	74.00	-25.28
2483.50								40.59	54.00	-13.41
2488.70								50.38	74.00	-23.62
2488.70								42.25	54.00	-11.75

RADIATED EMISSIONS – Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
2390.00								45.78	74.00	-28.22
2390.00								37.23	54.00	-16.77
2385.30								49.62	74.00	-24.38
2385.30								44.23	54.00	-9.77
2400.00	34.67	100	0			3.02	29.40	67.09	81.95	-14.86
2483.50								49.25	74.00	-24.75
2483.50								41.38	54.00	-12.62
2488.70								50.91	74.00	-23.09
2488.70								43.04	54.00	-10.96

NOTE: The “Band Edge Field Strength” was calculated using the “Fundamental” and “Conducted Band Edge” measurements per the “Marker-Delta Method” with the following formula:

$$BE = F_m - \Delta m$$

Where

BE = Band Edge Field Strength

F_m = Measured Fundamental (Peak or Average)

Δm = Measured Conducted Band Edge Delta (Peak or Average)

Page 56 of 73 (Appendix A)

Report Number: INTEL-050207F

FCC ID: E2K24BNHM




AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

(Marker Delta Conducted Band Edge Plots)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)



Page 57 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM




AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

(Marker Delta Conducted Band Edge Plots)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)



Page 58 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11b mode
Channels 1, 6, & 11
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-08

RADIATED EMISSIONS - Horizontal Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		1 Meter Distance Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)											
2312.00	31.50	100	135			9.54	2.96	29.02	53.94	74.00	-20.06
2312.00				18.82	A	9.54	2.96	29.02	41.26	54.00	-12.74
EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)											
2336.00	31.67	100	135			9.54	2.98	29.07	54.18	74.00	-19.82
2336.00				19.91	A	9.54	2.98	29.07	42.42	54.00	-11.58
EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)											
2360.00	30.83	100	135			9.54	2.99	29.12	53.40	74.00	-20.60
2360.00				16.16	A	9.54	2.99	29.12	38.73	54.00	-15.27
RADIATED EMISSIONS - Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		1 Meter Distance Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)											
2312.00	32.50	100	225			9.54	2.96	29.22	55.14	74.00	-18.86
2312.00				21.04	A	9.54	2.96	29.22	43.68	54.00	-10.32
EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)											
2336.00	32.67	100	225			9.54	2.98	29.27	55.38	74.00	-18.62
2336.00				20.32	A	9.54	2.98	29.27	43.03	54.00	-10.97
EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)											
2360.00	31.00	100	225			9.54	2.99	29.32	53.77	74.00	-20.23
2360.00				16.95	A	9.54	2.99	29.32	39.72	54.00	-14.28

NOTE: These spurious emissions measurements were taken without a preamp at a distance on 1 meter to avoid saturating the preamp and analyzer because the signals were close to the fundamental frequency. The readings were extrapolated to 1 meter.

Page 59 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11b mode
Channels 1, 6, & 11
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-09

RADIATED EMISSIONS - Horizontal Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)											
1000.03	47.67	100	90			42.66	1.93	24.90	31.84	74.00	-42.16
1000.03				38.89	A	42.66	1.93	24.90	23.06	54.00	-30.94
3216.00	44.83	100	180			43.07	3.51	30.98	36.24	82.08	-45.84
4823.95	41.67	100	225			43.27	4.35	34.10	36.85	74.00	-37.15
4823.95				32.27	A	43.27	4.35	34.10	27.45	54.00	-26.55
6432.00	42.33	100	225			43.82	5.03	35.37	38.92	82.08	-43.16
9647.99	48.00	100	180			43.22	6.19	38.11	49.08	82.08	-33.00
EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)											
1000.00	48.00	100	135			42.66	1.93	24.90	32.17	74.00	-41.83
1000.00				37.92	A	42.66	1.93	24.90	22.09	54.00	-31.91
3249.32	46.50	100	225			43.08	3.53	31.05	37.99	82.31	-44.32
4874.02	42.00	100	225			43.29	4.37	34.27	37.36	74.00	-36.64
4874.02				32.34	A	43.29	4.37	34.27	27.70	54.00	-26.30
6498.70	43.00	100	225			43.84	5.06	35.40	39.62	82.31	-42.69
9747.90	49.17	100	180			43.25	6.23	38.25	50.39	82.31	-31.92
EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)											
1000.00	49.17	100	135			42.66	1.93	24.90	33.34	74.00	-40.66
1000.00				40.16	A	42.66	1.93	24.90	24.33	54.00	-29.67
3282.66	44.17	100	135			43.10	3.55	31.12	35.74	80.05	-44.31
4923.98	44.50	100	225			43.30	4.40	34.44	40.03	74.00	-33.97
4923.98				32.22	A	43.30	4.40	34.44	27.75	54.00	-26.25
6565.37	44.67	100	225			43.84	5.08	35.62	41.54	80.05	-38.51
9847.89	49.50	100	135			43.29	6.27	38.39	50.87	80.05	-29.18

Page 60 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

RADIATED EMISSIONS - Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)											
1000.00	53.00	100	180			42.66	1.93	25.00	37.27	74.00	-36.73
1000.00				41.62	A	42.66	1.93	25.00	25.89	54.00	-28.11
3216.00	47.67	100	225			43.07	3.51	31.09	39.20	81.95	-42.75
4823.98	43.67	100	225			43.27	4.35	34.07	38.82	74.00	-35.18
4823.98				34.32	A	43.27	4.35	34.07	29.47	54.00	-24.53
6432.01	44.50	100	315			43.82	5.03	35.35	41.06	81.95	-40.89
9648.03	50.67	100	270			43.22	6.19	38.17	51.81	81.95	-30.14
EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)											
1000.01	56.33	125	270			42.66	1.93	25.00	40.60	74.00	-33.40
1000.01				43.80	A	42.66	1.93	25.00	28.07	54.00	-25.93
3249.33	47.00	100	225			43.08	3.53	31.15	38.59	82.01	-43.42
4874.04	44.67	100	225			43.29	4.37	34.22	39.98	74.00	-34.02
4874.04				35.59	A	43.29	4.37	34.22	30.90	54.00	-23.10
6498.64	44.17	100	225			43.84	5.06	35.40	40.79	82.01	-41.22
9747.99	54.17	125	270			43.25	6.23	38.35	55.49	82.01	-26.52
EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)											
1000.00	53.83	150	180			42.66	1.93	25.00	38.10	74.00	-35.90
1000.00				42.51	A	42.66	1.93	25.00	26.78	54.00	-27.22
3282.66	47.50	100	225			43.10	3.55	31.21	39.16	80.58	-41.42
4923.91	44.17	100	225			43.30	4.40	34.37	39.63	74.00	-34.37
4923.91				34.65	A	43.30	4.40	34.37	30.11	54.00	-23.89
6565.40	42.50	100	225			43.84	5.08	35.60	39.34	80.58	-41.24
9848.05	52.33	125	180			43.29	6.27	38.53	53.84	80.58	-26.74

Page 61 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11b mode
Channels 1, 6, & 11
Continuous RX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-09

RADIATED EMISSIONS - Horizontal Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Receive Mode on Channel 1 (2.412 GHz)											
3216.00	46.67	100	180			43.07	3.51	30.98	38.08	80.00	-41.92
3216.00				40.68	A	43.07	3.51	30.98	32.09	60.00	-27.91
6432.05	42.50	100	225			43.82	5.03	35.37	39.09	80.00	-40.91
6432.05				31.88	A	43.82	5.03	35.37	28.47	60.00	-31.53
9648.00	43.17	100	225			43.22	6.19	38.11	44.25	80.00	-35.75
9648.00				32.37	A	43.22	6.19	38.11	33.45	60.00	-26.55
EUT in Continuous Receive Mode on Channel 6 (2.437 GHz)											
3249.35	46.17	125	225			43.08	3.53	31.05	37.66	80.00	-42.34
3249.35				39.90	A	43.08	3.53	31.05	31.39	60.00	-28.61
6498.65	43.83	100	315			43.84	5.06	35.40	40.45	80.00	-39.55
6498.65				33.12	A	43.84	5.06	35.40	29.74	60.00	-30.26
9748.02	43.17	100	315			43.25	6.23	38.25	44.39	80.00	-35.61
9748.02				32.22	A	43.25	6.23	38.25	33.44	60.00	-26.56
EUT in Continuous Receive Mode on Channel 11 (2.462 GHz)											
3282.61	45.17	125	225			43.10	3.55	31.12	36.74	80.00	-43.26
3282.61				37.76	A	43.10	3.55	31.12	29.33	60.00	-30.67
6565.46	42.33	100	225			43.84	5.08	35.62	39.20	80.00	-40.80
6565.46				32.09	A	43.84	5.08	35.62	28.96	60.00	-31.04
9848.03	43.00	100	225			43.29	6.27	38.39	44.37	80.00	-35.63
9848.03				32.99	A	43.29	6.27	38.39	34.36	60.00	-25.64

Page 62 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

RADIATED EMISSIONS - Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Receive Mode on Channel 1 (2.412 GHz)											
3216.00	49.50	100	225			43.07	3.51	31.09	41.03	80.00	-38.97
3216.00				44.84	A	43.07	3.51	31.09	36.37	60.00	-23.63
6432.05	41.67	100	225			43.82	5.03	35.35	38.23	80.00	-41.77
6432.05				31.96	A	43.82	5.03	35.35	28.52	60.00	-31.48
9648.00	42.67	100	225			43.22	6.19	38.17	43.81	80.00	-36.19
9648.00				32.32	A	43.22	6.19	38.17	33.46	60.00	-26.54
EUT in Continuous Receive Mode on Channel 6 (2.437 GHz)											
3249.35	47.67	100	225			43.08	3.53	31.15	39.26	80.00	-40.74
3249.35				42.27	A	43.08	3.53	31.15	33.86	60.00	-26.14
6498.65	43.33	100	45			43.84	5.06	35.40	39.95	80.00	-40.05
6498.65				33.30	A	43.84	5.06	35.40	29.92	60.00	-30.08
9748.02	42.17	125	315			43.25	6.23	38.35	43.49	80.00	-36.51
9748.02				32.29	A	43.25	6.23	38.35	33.61	60.00	-26.39
EUT in Continuous Receive Mode on Channel 11 (2.462 GHz)											
3282.61	46.83	100	225			43.10	3.55	31.21	38.49	80.00	-41.51
3282.61				40.99	A	43.10	3.55	31.21	32.65	60.00	-27.35
6565.46	42.50	100	45			43.84	5.08	35.60	39.34	80.00	-40.66
6565.46				31.96	A	43.84	5.08	35.60	28.80	60.00	-31.20
9848.03	45.00	125	225			43.29	6.27	38.53	46.51	80.00	-33.49
9848.03				35.76	A	43.29	6.27	38.53	37.27	60.00	-22.73



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

CLIENT:	Dell Computer Corporation	DATE:	02/09/05
EUT:	Intel PRO/Wireless 2200BG Network Connection	PROJECT NUMBER:	INTEL-050207
MODEL NUMBER:	WM3B2200BG (PPT)	TEST ENGINEER:	JC
SERIAL NUMBER:	0814C009ADC54906006	SITE #:	2
CONFIGURATION:	Tested installed in the Mini PCI slot of the Dell Latitude D400 Notebook computer connected to a set of Wistron Neweb Corp. antennas in 802.11g (2412-2462 MHz) mode.	TEMPERATURE:	7 C
		HUMIDITY:	90% RH
		TIME:	8:00 AM

Standard:	FCC CFR 47, Part 15.247(c)
Description:	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.
Results:	Passes (See Data Sheets)

Unwanted Spurious Emissions Limits			
Frequency (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m) (Emissions in the restricted bands)	Field Strength (dBm/MHz) (Emissions outside the restricted bands)
Above 960	500	54.00 (Average) 74.00 (Peak)	< -20 dBc

NOTE 1: RBW/VBW = 1 MHz

Page 64 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Fundamental Measurements in 802.11g mode
Channels 1, 6, & 11
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-07

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
2412.00	62.00	100	225				3.02	29.22	94.25		
2412.00				53.41	A		3.02	29.22	85.66		
2437.00	62.17	100	225				3.04	29.27	94.48		
2437.00				52.85	A		3.04	29.27	85.16		
2462.00	62.17	100	225				3.06	29.32	94.55		
2462.00				51.88	A		3.06	29.32	84.26		

RADIATED EMISSIONS – Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
2412.00	62.33	100	225				3.02	29.42	94.78		
2412.00				56.34	A		3.02	29.42	88.79		
2437.00	63.33	100	45				3.04	29.47	95.84		
2437.00				53.96	A		3.04	29.47	86.47		
2462.00	60.67	100	270				3.06	29.52	93.25		
2462.00				51.18	A		3.06	29.52	83.76		

Page 65 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Band Edge Field Strength Measurements in 802.11g mode
Channels 1, 6, & 11
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-07

RADIATED EMISSIONS - Horizontal Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
2390.00									50.42	74.00	-23.58
2390.00									39.99	54.00	-14.01
2400.00	39.67	100	225				3.02	29.20	71.89	74.25	-2.36
2483.50									54.21	74.00	-19.79
2483.50									40.43	54.00	-13.57
RADIATED EMISSIONS – Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
2390.00									50.95	74.00	-23.05
2390.00									43.12	54.00	-10.88
2400.00	39.17	100	225				3.02	29.40	71.59	74.78	-3.19
2483.50									52.91	74.00	-21.09
2483.50									39.93	54.00	-14.07

NOTE: The “Band Edge Field Strength” was calculated using the “Fundamental” and “Conducted Band Edge” measurements per the “Marker-Delta Method” with the following formula:

$$BE = F_m - \Delta m$$

Where

BE = Band Edge Field Strength

F_m = Measured Fundamental (Peak or Average)

Δ_m = Measured Conducted Band Edge Delta (Peak or Average)

Page 66 of 73 (Appendix A)
 Report Number: INTEL-050207F
 FCC ID: E2K24BNHM




AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

(Marker Delta Conducted Band Edge Plots)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)



Page 67 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM




AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

(Marker Delta Conducted Band Edge Plots)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)



Page 68 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11g mode
Channels 1, 6, & 11
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-08

RADIATED EMISSIONS - Horizontal Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		1 Meter Distance Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)											
2312.00	32.00	100	135			9.54	2.96	29.02	54.44	74.00	-19.56
2312.00				19.65	A	9.54	2.96	29.02	42.09	54.00	-11.91
EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)											
2336.00	31.83	100	135			9.54	2.98	29.07	54.34	74.00	-19.66
2336.00				19.27	A	9.54	2.98	29.07	41.78	54.00	-12.22
EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)											
2360.00	31.17	100	135			9.54	2.99	29.12	53.74	74.00	-20.26
2360.00				16.56	A	9.54	2.99	29.12	39.13	54.00	-14.87
RADIATED EMISSIONS - Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		1 Meter Distance Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)											
2312.00	33.50	100	225			9.54	2.96	29.22	56.14	74.00	-17.86
2312.00				21.61	A	9.54	2.96	29.22	44.25	54.00	-9.75
EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)											
2336.00	32.50	100	225			9.54	2.98	29.27	55.21	74.00	-18.79
2336.00				20.23	A	9.54	2.98	29.27	42.94	54.00	-11.06
EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)											
2360.00	31.00	100	225			9.54	2.99	29.32	53.77	74.00	-20.23
2360.00				16.71	A	9.54	2.99	29.32	39.48	54.00	-14.52

NOTE: These spurious emissions measurements were taken without a preamp at a distance on 1 meter to avoid saturating the preamp and analyzer because the signals were close to the fundamental frequency. The readings were extrapolated to 1 meter.

Page 69 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11g mode
Channels 1, 6, & 11
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-09

RADIATED EMISSIONS - Horizontal Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)											
1000.00	51.33	100	135			42.66	1.93	24.90	35.50	74.00	-38.50
1000.00				41.07	A	42.66	1.93	24.90	25.24	54.00	-28.76
3216.03	45.33	100	180			43.07	3.51	30.98	36.74	74.25	-37.51
4823.97	42.50	100	135			43.27	4.35	34.10	37.68	74.00	-36.32
4823.97				32.54	A	43.27	4.35	34.10	27.72	54.00	-26.28
6432.02	42.83	100	225			43.82	5.03	35.37	39.42	74.25	-34.83
9748.00	43.50	100	315			43.25	6.23	38.25	44.72	74.25	-29.53
EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)											
1000.00	50.33	100	225			42.66	1.93	24.90	34.50	74.00	-39.50
1000.00				40.56	A	42.66	1.93	24.90	24.73	54.00	-29.27
3249.35	47.50	125	225			43.08	3.53	31.05	38.99	74.48	-35.49
4873.96	42.67	100	135			43.29	4.37	34.27	38.03	74.00	-35.97
4873.96				32.61	A	43.29	4.37	34.27	27.97	54.00	-26.03
6498.67	43.83	100	135			43.84	5.06	35.40	40.45	74.48	-34.03
9748.02	42.83	100	315			43.25	6.23	38.25	44.05	74.48	-30.43
EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)											
1000.00	50.33	100	135			42.66	1.93	24.90	34.50	74.00	-39.50
1000.00				40.92	A	42.66	1.93	24.90	25.09	54.00	-28.91
3282.66	46.50	125	225			43.10	3.55	31.12	38.07	74.55	-36.48
4924.00	42.33	100	135			43.30	4.40	34.44	37.86	74.00	-36.14
4924.00				32.12	A	43.30	4.40	34.44	27.65	54.00	-26.35
6565.32	43.00	100	135			43.84	5.08	35.62	39.87	74.55	-34.68
9848.02	44.17	100	315			43.29	6.27	38.39	45.54	74.55	-29.01

Page 70 of 73 (Appendix A)
 Report Number: INTEL-050207F
 FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

RADIATED EMISSIONS - Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)											
1000.00	51.50	125	180			42.66	1.93	25.00	35.77	74.00	-38.23
1000.00				41.73	A	42.66	1.93	25.00	26.00	54.00	-28.00
3216.01	49.33	100	225			43.07	3.51	31.09	40.86	74.78	-33.92
4823.98	43.33	100	135			43.27	4.35	34.07	38.48	74.00	-35.52
4823.98				32.46	A	43.27	4.35	34.07	27.61	54.00	-26.39
6532.02	41.67	100	225			43.84	5.07	35.50	38.40	74.78	-36.38
9747.98	42.33	100	315			43.25	6.23	38.35	43.65	74.78	-31.13
EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)											
1000.20	55.00	100	180			42.66	1.93	25.00	39.27	74.00	-34.73
1000.20				45.77	A	42.66	1.93	25.00	30.04	54.00	-23.96
3249.33	48.33	100	225			43.08	3.53	31.15	39.92	75.84	-35.92
4874.02	42.83	100	135			43.29	4.37	34.22	38.14	74.00	-35.86
4874.02				32.46	A	43.29	4.37	34.22	27.77	54.00	-26.23
6498.69	43.83	100	225			43.84	5.06	35.40	40.45	75.84	-35.39
9748.06	42.33	100	315			43.25	6.23	38.35	43.65	75.84	-32.19
EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)											
1000.00	50.83	100	180			42.66	1.93	25.00	35.10	74.00	-38.90
1000.00				42.01	A	42.66	1.93	25.00	26.28	54.00	-27.72
3282.65	48.00	100	225			43.10	3.55	31.21	39.66	73.25	-33.59
4923.98	42.67	100	135			43.30	4.40	34.37	38.13	74.00	-35.87
4923.98				31.91	A	43.30	4.40	34.37	27.37	54.00	-26.63
6565.36	42.33	100	225			43.84	5.08	35.60	39.17	73.25	-34.08
9848.10	45.83	100	270			43.29	6.27	38.53	47.34	73.25	-25.91

Page 71 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11g mode
Channels 1, 6, & 11
Continuous RX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050207-09

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Receive Mode on Channel 1 (2.412 GHz)										
3216.00	49.00	100	225			43.07	3.51	30.98	40.41	80.00 -39.59
3216.00				42.22	A	43.07	3.51	30.98	33.63	60.00 -26.37
6432.05	43.50	100	45			43.82	5.03	35.37	40.09	80.00 -39.91
6432.05				32.06	A	43.82	5.03	35.37	28.65	60.00 -31.35
9648.00	44.00	100	315			43.22	6.19	38.11	45.08	80.00 -34.92
9648.00				32.09	A	43.22	6.19	38.11	33.17	60.00 -26.83
EUT in Continuous Receive Mode on Channel 6 (2.437 GHz)										
3249.35	46.83	100	135			43.08	3.53	31.05	38.32	80.00 -41.68
3249.35				40.16	A	43.08	3.53	31.05	31.65	60.00 -28.35
6498.65	44.67	100	45			43.84	5.06	35.40	41.29	80.00 -38.71
6498.65				32.78	A	43.84	5.06	35.40	29.40	60.00 -30.60
9748.02	41.50	100	225			43.25	6.23	38.25	42.72	80.00 -37.28
9748.02				32.09	A	43.25	6.23	38.25	33.31	60.00 -26.69
EUT in Continuous Receive Mode on Channel 11 (2.462 GHz)										
3282.61	46.67	100	225			43.10	3.55	31.12	38.24	80.00 -41.76
3282.61				39.18	A	43.10	3.55	31.12	30.75	60.00 -29.25
6565.46	43.50	100	45			43.84	5.08	35.62	40.37	80.00 -39.63
6565.46				31.29	A	43.84	5.08	35.62	28.16	60.00 -31.84
9848.03	44.67	100	315			43.29	6.27	38.39	46.04	80.00 -33.96
9848.03				32.54	A	43.29	6.27	38.39	33.91	60.00 -26.09

Page 72 of 73 (Appendix A)
Report Number: INTEL-050207F
FCC ID: E2K24BNHM



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

RADIATED EMISSIONS - Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Receive Mode on Channel 1 (2.412 GHz)											
3216.00	48.83	100	225			43.07	3.51	31.09	40.36	80.00	-39.64
3216.00				45.13	A	43.07	3.51	31.09	36.66	60.00	-23.34
6432.05	44.33	100	45			43.82	5.03	35.35	40.89	80.00	-39.11
6432.05				32.54	A	43.82	5.03	35.35	29.10	60.00	-30.90
9648.00	43.83	100	225			43.22	6.19	38.17	44.97	80.00	-35.03
9648.00				32.37	A	43.22	6.19	38.17	33.51	60.00	-26.49
EUT in Continuous Receive Mode on Channel 6 (2.437 GHz)											
3249.35	48.33	100	225			43.08	3.53	31.15	39.92	80.00	-40.08
3249.35				42.32	A	43.08	3.53	31.15	33.91	60.00	-26.09
6498.65	45.33	100	45			43.84	5.06	35.40	41.95	80.00	-38.05
6498.65				32.94	A	43.84	5.06	35.40	29.56	60.00	-30.44
9748.02	44.00	100	225			43.25	6.23	38.35	45.32	80.00	-34.68
9748.02				31.83	A	43.25	6.23	38.35	33.15	60.00	-26.85
EUT in Continuous Receive Mode on Channel 11 (2.462 GHz)											
3282.61	48.00	100	225			43.10	3.55	31.21	39.66	80.00	-40.34
3282.61				41.81	A	43.10	3.55	31.21	33.47	60.00	-26.53
6565.46	44.00	100	45			43.84	5.08	35.60	40.84	80.00	-39.16
6565.46				31.26	A	43.84	5.08	35.60	28.10	60.00	-31.90
9848.03	45.83	100	225			43.29	6.27	38.53	47.34	80.00	-32.66
9848.03				34.46	A	43.29	6.27	38.53	35.97	60.00	-24.03