

## Nemko Korea CO., Ltd.

300-2, Osan-Ri, Mohyun-Myun, Yongin-City, Kyungki-Do, KOREA

TEL:+82 31 322 2333

FAX:+82 31 322 2332

### FCC EVALUATION REPORT FOR CERTIFICATION

**Applicant :**

Samsung Electro-Mechanics Co., Ltd.

314, Maetan3-dong, Paldal-gu, Suwon-shi

Kyunggi-do, Korea, (Post code : 442-743)

Attn. : Mr. Junhwan Lim

Dates of Issue : August 30, 2003

Test Report No. : NK2DE531

Test Site : Nemko Korea Co., Ltd.

EMC site, Korea

FCC ID

**E2XSDR5000K**

Brand Name

**SAMSUNG**

CONTACT PERSON

**Samsung Electro-Mechanics Co., Ltd.**  
**314, Maetan3-dong, Paldal-gu, Suwon-shi**  
**Kyunggi-do, Korea , 442-743.**  
**Mr. Junhwan Lim**  
**Telephone No. : +82 32 210 6497**

Applied Standard:

FCC 47 CFR Part 15, Subpart C : 2000

Classification :

FCC Class B Device

EUT Type:

27MHz Wireless Internet Keyboard

The device bearing the brand name and FCC ID specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-1992.

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



**Tested By : S. K. Lee**  
**Senior Engineer**



**Reviewed By : H.H. Kim**  
**Manager & Chief Engineer**

# **TABLE OF CONTENTS**

---

|                                                 |           |
|-------------------------------------------------|-----------|
| <b>SCOPE</b>                                    | <b>3</b>  |
| <b>INTRODUCTION (Site Description)</b>          | <b>4</b>  |
| <b>TEST CONDITIONS &amp; EUT INFORMATION</b>    | <b>5</b>  |
| <b>SUMMARY OF TEST RESULTS</b>                  | <b>6</b>  |
| <b>RECOMMANDATION / CONCLUSION</b>              | <b>6</b>  |
| <b>SAMPLE CALCULATION</b>                       | <b>6</b>  |
| <b>DESCRIPTION OF TEST (Radiated Emissions)</b> | <b>7</b>  |
| <b>TEST DATA (Radiated Emissions)</b>           | <b>8</b>  |
| <b>PLOT OF EMISSION</b>                         | <b>10</b> |
| <b>ACCURACY OF MEASUREMENT</b>                  | <b>11</b> |
| <b>TEST EQUIPMENT</b>                           | <b>12</b> |
| <b>APPENDIX A - LABELLING REQUIREMENTS</b>      | <b>13</b> |
| <b>APPENDIX B - CIRCUIT DIAGRAM</b>             | <b>14</b> |
| <b>APPENDIX C - PHOTOGRAPHS OF TEST SET-UP</b>  | <b>15</b> |
| <b>APPENDIX D - EUT PHOTOGRAPHS</b>             | <b>16</b> |
| <b>APPENDIX E - USER'S MANUAL</b>               | <b>21</b> |
| <b>APPENDIX F - SCHEMATIC DIAGRAM</b>           | <b>22</b> |
| <b>APPENDIX G – OPERATING DESCRIPTION</b>       | <b>23</b> |

## SCOPE

---

*Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission under FCC part 15.*

|                             |                                                                                                                                                                                                                                                                 |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Responsible Party* :</b> | Samsung Electro-Mechanics Co., Ltd.                                                                                                                                                                                                                             |
| <b>Contact Person :</b>     | Mr. Junhwan Lim                                                                                                                                                                                                                                                 |
| <b>Manufacturer :</b>       | 1. Samsung Electro-Mechanics Co., Ltd.<br>314, Maetan3-dong, Paldal-gu, Suwon-shi, Kyunggi-do,<br>Korea , 442-743.<br>2. Dongguan Samsung Electro-Mechanics Co.,Ltd.<br>Quan-Tang Village,Liao-Bu Town,Dong-guan City,<br>Guang-Dong Province P.R CHINA, 523425 |

- FCC ID: E2XSDR5000K
- Model: SDR5000K
- Brand Name: SAMSUNG
- EUT Type: 27MHz Wireless Internet Keyboard
- Classification: FCC Class B
- Applied Standard: FCC 47 CFR Part 15 , Subpart C
- Test Procedure(s): ANSI C63.4 (1992)
- Dates of Test: August 14, 2003 to August 19, 2003
- Place of Tests: Nemko Korea Co., Ltd. EMC Site
- Test Report No.: NK2DE531

## INTRODUCTION

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-1992) was used in determining radiated and conducted emissions emanating from **Samsung Electro-Mechanics Co., Ltd.**

FCC ID : **E2XSDR5000K, 27MHz Wireless Internet Keyboard.**

These measurement tests were conducted at **Nemko Korea Co., Ltd. EMC Laboratory**.

The site address is 300-2, Osan-Ri, Mohyun-Myun, Yongin-City, Kyungki-Do, KOREA

The area of Nemko Korea Corporation LTD. EMC Test Site is located in a mountain area at 80 kilometers (48 miles) southeast and Incheon International Airport (Incheon Airport), 30 kilometers (18miles) south-southeast from central Seoul.

It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures.

The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 1992.



Nemko Korea Co., Ltd.  
EMC Lab.  
300-2, Osan-Ri, Mohyun-Myun, Yongin-  
City Kyungki-Do, KOREA 449-852  
Tel)+82-31-322-2333  
Fax)+82-31-322-2332

Fig. 1. The map above shows the Seoul in Korea vicinity area.

The map also shows Nemko Korea Corporation Ltd. EMC Lab. and Incheon Airport.

## TEST CONDITIONS & EUT INFORMATION

---

### Operating During Test

The EUT is part of transmitter and transmitted specific frequency(27.045MHz) continuously.

### Support Equipment

|               |                                                                                              |                  |
|---------------|----------------------------------------------------------------------------------------------|------------------|
| PC            | Dell computer, FCC DoC<br>Model: Dimension 4600<br>1.8m unshielded AC power cable            | S/N: B56481S     |
| Monitor       | Hansol, FCC ID: MSAB17DF<br>1.8m unshielded AC power cord<br>1.2m shielded D-sub cable       | S/N: N/A         |
| RF Receiver   | Samsung, FCC ID: E2XSDR5000R<br>1.2m shielded Din cable                                      | S/N: N/A         |
| Keyboard(EUT) | Samsung, FCC ID: E2XSDR5000K                                                                 | S/N: N/A         |
| Mouse         | Samsung, FCC ID: E2XSDR5000M                                                                 | S/N: N/A         |
| Printer       | HP, Model No: C4562K , FCC DoC<br>1.8m unshielded AC power cord<br>1.2m Shielded D-sub cable | S/N: SG74T1C206  |
| Joystick      | Logitech , M/N:J-ZA10, FCC DoC<br>1.8m Shielded D-sub cable                                  | S/N: YED20300268 |
| Serial Mouse  | IO Tec , M/N: Laser mouse<br>1.2m unshielded D-sub cable                                     | S/N: N/A         |
| USB Mouse     | Immanuel . M/N: Magicsecure3100<br>1.5m Shielded D-sub cable                                 | S/N: N/A         |

### EUT Information

|                     |                              |
|---------------------|------------------------------|
| Clock:              | 2MHz(X2) , 13.5225MHz(X_2)   |
| Chipset:            | EM83P100P(U3)                |
| Working Frequency:  | 27.045MHz (1 CH)             |
| Modulation:         | FSK                          |
| RF output power:    | > -10dBm                     |
| Current Dissipation | < 7mA                        |
| Power Supply:       | 3.0V , AA size Battery 2 pcs |

## SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specification:

| Name of Test                         | Paragraph No. | Result   | Remark                          |
|--------------------------------------|---------------|----------|---------------------------------|
| Power line<br>Conducted Emission     | 15.207        | N/A      | EUT is operated by 3V batteries |
| Radiated Emission<br>( Fundamental ) | 15.227        | Complies |                                 |
| Radiated Emission<br>( Spurious )    | 15.209        | Complies |                                 |

## RECOMMENDATION/CONCLUSION

The data collected shows that the **Samsung Electro-Mechanics Co., Ltd.**

FCC ID : **E2XSDR5000K, 27MHz Wireless Internet Keyboard.**

The highest emission observed was at **40.53 MHz** for radiated emissions with a margin of **5.5 dB**.

## SAMPLE CALCULATION

$$\text{dB } \mu\text{V} = 20 \log_{10} (\mu\text{V}/\text{m})$$

$$\mu\text{V} = 10^{(\text{dB } \mu\text{V}/20)}$$

### EX. 1.

@57.7 MHz

Class B limit = 100  $\mu\text{V}/\text{m}$  = 40.0 dB  $\mu\text{V}/\text{m}$

Reading = 19.1 dB  $\mu\text{V}$  (calibrated level)

Antenna factor + Cable Loss = 10.12 dB

Total = 29.22 dB  $\mu\text{V}/\text{m}$

Margin = 40.0 - 29.22 = 10.78

10.78 dB below the limit

## DESCRIPTION OF TEST

### Radiated Emissions

Preliminary measurement were made indoors at 3 meter using broad band antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The Technology configuration, clock speed, mode of operation or video resolution, turntable azimuth with respect to the antenna was note for each frequency found.

The spectrum was scanned from 30 to 1000MHz using Biconical log Antenna(ARA, LPB-2520/A). Above 1GHz, log periodic antenna (Rohde Schwarz HL025:upto 18GHz) was used.

Final Measurements were made outdoors at 3 or 10m test range using Logbicon Super Antenna(Schwarzbeck, VULB9166) or log periodic antenna.( Rohde Schwarz HL025)

The test equipment was placed on a wooden table.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

Each frequency found during pre-scan measurements was reexamined and investigated using EMI test receiver.(ESCS30)

The detector function was set to CISPR quasi-peak mode or Average mode and the bandwidth of the receiver was set to 120KHz or 1MHz depending on the frequency or type of signal.

The half wave dipole antenna was tuned to the frequency found during preliminary radiated measurements.

The EUT support equipment and interconnecting cables were re configured to the setup producing the maximum emission for the frequency and were placed on top of a 0.8m high non- metallic 1.0X 1.5 meter table.

The EUT, support equipment and interconnecting cables were re-arranged and manipulated to maximize each EME emission.

The turn table containing the Technology was rotated; the antenna height was varied 1 to 4meter and stopped at the azimuth or height producing the maximum emission Each emission was maximized by : switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and of support equipment, and powering the monitor from the floor mounted outlet box and computer aux AC outlet, if applicable; which ever determined the worst case emission.

Each EME reported was calibrated using the R/S signal generator.




Fig. 2. Dimensions of Outdoor Test Site

## TEST DATA

### Radiated Emissions; general requirements (15.209)


FCC ID : E2XSDR5000K

Working Frequency : 27.045MHz

| Frequency (MHz) | Reading (dB $\mu$ N) | Pol* (H/V) | AF+CL+Amp (dB)** | Result (dB $\mu$ N/m) | Limit (dB $\mu$ N/m) | Margin (dB) |
|-----------------|----------------------|------------|------------------|-----------------------|----------------------|-------------|
| 40.53           | 55.6                 | H          | -21.1            | 34.5                  | 40.0                 | 5.5         |
| 121.70          | 43.8                 | H          | -17.0            | 26.8                  | 43.5                 | 16.7        |
| 135.27*         | 40.6                 | H          | -14.9            | 25.7                  | 43.5                 | 17.8        |
| 175.78          | 44.7                 | H          | -13.2            | 31.5                  | 43.5                 | 12.0        |
| 189.30*         | 43.8                 | H          | -13.5            | 30.3                  | 43.5                 | 13.2        |
| 351.57          | 40.8                 | H          | -10.0            | 30.8                  | 46.0                 | 15.2        |

\* : Harmonics of the highest fundamental frequency.

**Table 1. Radiated Measurements at 3meters**



**Fig. 3. Limits at 3 meters**

#### NOTES:

1. All modes of operation were investigated the worst-case emission are reported.
2. The radiated limits are shown on Figure 3.

Above 1GHz the limit is 500  $\mu$ N/m.

#### NOTES:

1. \*Pol. H =Horizontal V=Vertical
2. \*\*AF+CL+Amp. = Antenna Factor + Cable Loss + Amplifier.
3. Up to the 10<sup>th</sup> harmonics were investigated according to § 15.33 and the worst –case is reported.

*S. K. Lee*

Tested by **S. K. Lee**

## TEST DATA

### Radiated Emissions ; within the band 26.96-27.28MHz (15.227)

FCC ID : E2XSDR5000K

Working Frequency : 27.045MHz

| Channel | Frequency | *)Pol.<br>(H/V) | Reading(dB $\mu$ V) |      | **)A.F<br>(dB) | **)C.L+Amp<br>(dB) | Result(dB $\mu$ V/m) |      | Limit(dB $\mu$ V/m) |       |
|---------|-----------|-----------------|---------------------|------|----------------|--------------------|----------------------|------|---------------------|-------|
|         | (MHz)     |                 | AV                  | PK   |                |                    | AV                   | PK   | AV                  | PK    |
| 1       | 27.045    | H               | 13.4                | 13.6 | 5.0            | 30.7               | 49.1                 | 49.3 | 80.0                | 100.0 |
|         | 27.045    | V               | 20.5                | 20.9 | 5.0            | 30.7               | 56.2                 | 56.6 | 80.0                | 100.0 |

**Table 2. Radiated Measurements at 3meters**


#### NOTES:

1. \*Pol. H =Horizontal V=Vertical
2. \*\*CL+Amp. = Cable Loss + Amplifier. A.F= Antenna Factor
3. The limit at fundamental frequency is 10,000uV/m @3m, using Average detector.
4. The emissions radiated outside of this band shall not exceed the general radiated emission limit in §15.209.
5. The emissions are maximized by changing polarity of the antenna.



Tested by **S. K. Lee**

PLOTS OF EMISSION



## ACCURACY OF MEASUREMENT

The Measurement Uncertainties stated were calculated in accordance with the requirements of NIST Technical Note 1297 with the confidence level of 95%

### 1. Radiation Uncertainty Calculation

| Contribution                                                                                                       | Probability Distribution | Uncertainty(+/-dB) |
|--------------------------------------------------------------------------------------------------------------------|--------------------------|--------------------|
| Antenna Factor                                                                                                     | Normal (k=2)             | $\pm 0.5$          |
| Cable Loss                                                                                                         | Normal (k=2)             | $\pm 0.04$         |
| Receiver Specification                                                                                             | Rectangular              | $\pm 2.0$          |
| Antenna directivity                                                                                                | Rectangular              | $\pm 1.0$          |
| Antenna Factor variation with Height                                                                               |                          |                    |
| Antenna Phase Center Variation                                                                                     |                          |                    |
| Antenna Factor Frequency Interpolation                                                                             |                          |                    |
| Measurement Distance Variation                                                                                     |                          |                    |
| Site Imperfections                                                                                                 | Rectangular              | $\pm 2.0$          |
| Mismatch:Receiver VRC $r_i=0.3$<br>Antenna VRC $r_R=0.1(B_i)0.4(L_p)$<br>Uncertainty Limits $20\log(1\pm r_i r_R)$ | U-Shaped                 | $+ 0.25 / - 0.26$  |
| System Repeatibility                                                                                               | Std.deviation            | $\pm 0.05$         |
| Repeatability of EUT                                                                                               | -                        | -                  |
| Combined Standard Uncertainty                                                                                      | Normal                   | $\pm 1.77$         |
| Expended Uncertainty U                                                                                             | Normal (k=2)             | $\pm 3.5$          |

### 2. Conducted Uncertainty Calculation

| Contribution                                                                                       | Probability Distribution | Uncertainty(+/-dB) |
|----------------------------------------------------------------------------------------------------|--------------------------|--------------------|
| Receiver Specification                                                                             | Normal (k=2)             | $\pm 2.0$          |
| LISN coupling spec.                                                                                | Normal (k=2)             | $\pm 0.4$          |
| Cable and input attenuator cal.                                                                    | Rectangular              | $\pm 0.4$          |
| Mismatch:Receiver VRC $r_i=0.3$<br>LISN vrc $r_g=0.1$<br>Uncertainty Limits $20\log(1\pm r_i r_R)$ | U-Shaped                 | $\pm 0.26$         |
| System Repeatibility                                                                               | Std.deviation            | $\pm 0.68$         |
| Repeatability of EUT                                                                               | -                        | -                  |
| Combined Standard Uncertainty                                                                      | Normal                   | $\pm 1.18$         |
| Expended Uncertainty U                                                                             | Normal (k=2)             | $\pm 2.4$          |

## TEST EQUIPMENT

| No. | Instrument              | Manufacturer | Model          | Calibration Date |
|-----|-------------------------|--------------|----------------|------------------|
| 1   | *Test Receiver          | R & S        | ESCS 30        | 2002.09          |
| 2   | Test Receiver           | PMM          | PMM9000        | 2003.06          |
| 3   | Amplifier               | HP           | 8447F          | 2003.07          |
| 4   | *Amplifier              | HP           | 8447F          | 2002.11          |
| 5   | *Amplifier              | HP           | 8447F          | 2003.01          |
| 6   | *Spectrum Analyzer      | Advantest    | R4136          | 2003.03          |
| 7   | Spectrum Analyzer       | H.P          | 8566B          | 2003.03          |
| 8   | *Spectrum Analyzer      | Anritsu      | MS2668C        | 2002.12          |
| 9   | *Logbicon Super Antenna | Schwarzbeck  | VULB9166       | 2003.05          |
| 10  | Log-Periodic Antenna    | R & S        | HL025          | 2003.01          |
| 11  | Dipole Antenna          | R & S        | VHA9103        | 2003.05          |
| 12  | Dipole Antenna          | R & S        | UHA9105        | 2003.05          |
| 13  | *Biconical Log Antenna  | ARA          | LPB-2520/A     | 2003.05          |
| 14  | Absorbing Clamp         | R & S        | MDS21          | 2003.06          |
| 15  | High Voltage Probe      | R & S        | ESH2-Z3        | 2002.09          |
| 16  | Signal Generator        | R & S        | SMP02          | 2002.12          |
| 17  | Matching Pad            | R & S        | RAM358.5414.02 | 2003.05          |
| 18  | LISN                    | R & S        | ESH3-Z5        | 2002.10          |
| 19  | LISN                    | Kyoritsu     | KNW-408        | 2002.12          |
| 20  | LISN                    | Kyoritsu     | KNW-407        | 2003.04          |
| 21  | *Position Controller    | EM Eng.      | N/A            | N/A              |
| 22  | *Turn Table             | EM Eng.      | N/A            | N/A              |
| 23  | *Antenna Mast           | EM Eng.      | N/A            | N/A              |
| 24  | *Anechoic Chamber       | EM Eng.      | N/A            | N/A              |

\*) Test equipment used during the test