

Client:	GE MDS LLC	Job Number:	J97156
Model:	ENET-L2T	T-Log Number:	T97159
Contact:	Dennis McCarthy	Project Manager:	Christine Krebill
Standard:	FCC part 80 and 95, RSS-131	Project Coordinator:	-
		Class:	N/A

Maximum Permissible Exposure

Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 3/5/2015

Test Engineer: David Bare

General Test Configuration

Calculation uses the free space transmission formula:

$$S = (PG)/(4 \pi d^2)$$

Where: S is power density (W/m^2), P is output power (W), G is antenna gain relative to isotropic, d is separation distance from the transmitting antenna (m).

Summary of Results

Device complies with Power Density requirements at 20cm separation:	No
If not, required separation distance (in cm):	

Use: General

Antenna: Various depending on License

USE THIS FOR 300-1500 MHz single transmitters

Freq. MHz	EUT Power		Cable Loss Loss dB	Ant Gain dBi	Power at Ant dBm	EIRP mW	Power Density (S) at 20 cm mW/cm^2	MPE Limit at 20 cm mW/cm^2
216	45.6	36307.8	0	2.2	45.6	60255.96	11.988	0.144

For the cases where $S >$ the MPE Limit

Freq. MHz	Power Density (S) at 20 cm mW/cm^2	MPE Limit at 20 cm mW/cm^2	Distance where $S \leq$ MPE Limit cm
216	11.988	0.144	182.5