



PRODUCTS FOR TESTING,
ASSEMBLING & REPAIRING
ELECTRONIC EQUIPMENT™

Product Search

[Express Order](#) [Shopping Cart](#)

Enter Keyword(s) or Part #

Search

[Keyword Search Tips](#)

[Browse Brands](#)

Click here to
see our
New Products!

Product Categories

- [Adhesives & Dispensers](#)
- [Aerosols & Cleaning Equipment](#)
- [Deals](#)
- [Lamps & Magnifiers](#)
- [Miscellaneous](#)
- [Networking](#)
- [Product Identification & Cable Ties](#)
- [Soldering & Desoldering](#)
- [Static Protection & Clean Room](#)
- [Storage & Material Handling](#)
- [Test & Measurement](#)
- [Tool Kits & Cases](#)
- [Tools](#)
- [Workbenches & Chairs](#)

[Home](#) [Shop](#) [My Account](#) [About Us](#) [Value Services](#) [Help](#)



Thermal Transfer Printable Thermatab™ Labels, Material 423 (THT2-423-10)

Your Price:
\$65.20

[Add to shopping cart](#)

Model: THT-2-423-10
Part Number: 124-955
Availability: Not in stock
Shipping weight: 1.05 lbs.

Specifications

- **Application:** Bar codes; Circuit boards; Component IDs
- **Color:** White
- **Dimensions:** 0.900" x 0.250"
- **Material Code:** 423
- **Material Type:** Polyester
- **Properties:** Solvent-resistant
- **Specification:** UL/CSA recognized
- **Temp Range:** - 40 °F to + 248 °F
- **Type:** Thermal transfer printable

Free Catalogs!



Copyright 2004,
Contact East, Inc.



WHEN PERFORMANCE MATTERS MOST™

WELCOME TO BRADY [Register/Login](#)

[My Account](#) **888-250-3082** [Contact Us](#)

[Find a Distributor](#)

MY CART

\$0.00 (0 Items)



[All Brady Products](#)

[Solutions by Regulation](#)

[Solutions by Industry](#)

[Professional Services](#)

[Customer & Product Support](#)

[Home](#)

[Products](#)

[Labels, Markers and Tapes](#)

[Circuit Board and Component Identification](#)

[Thermal Transfer Printable Labels](#)

[EMAIL PAGE](#)

[PRINT PAGE](#)





Thermal Transfer Printable Labels - # THT-2-423-10

SIZE:

0.900" W x 0.250" H (22.860 mm W x 6.350 mm H)

MATERIAL:

Permanent Polyester

QTY/UOM:

10,000/Roll

CATALOG #:

THT-2-423-10

PRODUCT #:

30119

\$90.84 MSRP (\$US)

QTY:

QUESTIONS OR COMMENTS

Call our customer service at

 **1-888-250-3082**



PRODUCT SUPPORT

[Portable Label Printers](#)

[Industrial Printers](#)

[Label Design Software](#)

[Printer Ribbons](#)

[JetTab Set Up Sheets](#)

[LaserTab Set Up Sheets](#)

OVERVIEW SPECIFICATIONS

Specification Of Thermal Transfer Printable Labels

Application(s):

Circuit Board & Component ID, Through Hole - Top

Agency Approval (s)/Compliance:

AGA Approved, CSA Approved, Halogen-Free (DIN VDE 0472/parts 815), UL Recognized

Size:

0.900" W x 0.250" H (22.860 mm W x 6.350 mm H)

Printable Area:

0.900" W x 0.250" H (22.860 mm W x 6.350 mm H)

Web Width:

3.350" (85.09 mm)

Label Type/Style:

Label

Vertical Repeat:

0.350" (8.89 mm)

Horizontal Repeat:

1.125" (28.58 mm)

Color:

White

http://www.bradyid.com/bradyid/pdpv/THT-2-423-10.html

8/6/2012

LIVE CHAT

Finish:	Gloss
Qty Per Row:	3
Material Type:	Polyester
Material Description:	Permanent Polyester
Brady Material #:	B-423
General ID Catalog:	pg. 88
Recommended Ribbon Series:	6000
Suggested Ribbon Part#:	R6002
Acceptable Ribbon Series:	4900, 6200
After Process:	Yes, this material will work with this application
Printer Compatibility:	BBP81, Brady 1244, Brady 1344, Brady 200MVP Plus, Brady 2461, Brady 300MVP Plus, Brady 300X-Plus II, Brady 3481, Brady 360X-Plus II, Brady 600X-Plus II, Brady 6441, IP300, IP600, Tagus T200, Tagus T300, Thermal Transfer Printers
Surface:	Smooth
Surface Mount Technology:	No, this material does not work with this application
Through Hole Technology:	Top: Yes. In extreme high temperatures, testing of this material is recommended, Bottom: No
RoHS Compatibility:	Compliant with RoHS Directive. NOTE: All statements concerning RoHS Directive compliance refer to 2005/618/EC MCV amendment to RoHS Directive 2002/95/EC. Product compliance is based upon information provided by suppliers of the raw materials used by Brady to manufacture these products, or by independent laboratory testing of these products. As such, Brady makes no independent representations or warranties, express or implied, and assumes no liability in connection with the use of this information.
QTY/UOM:	10,000/Roll