




DEVICE: MDKP KEYPAD Alarm Transmitter

PHOTOGRAPH: Occupied Bandwidth

CONDITIONS: Transmitter Fundamental. A1D Modulation - Pulse Position Modulation. Fixed Duty Cycle. Surface Acoustic Wave (SAW) Frequency Determining Element.

SPECTRUM ANALYZER CONTROL SETTINGS

CENTER FREQUENCY:	318 MHz	INPUT ATTENUATION:	-10 dB
SCAN WIDTH:	2.0 KHz / Div.	PREAMPLIFIER GAIN:	0 dB
SCAN TIME:	1.0 Sec / Div.	LOG REF. LEVEL:	-10 dBm
RF BANDWIDTH:	0.3 KHz		
ANTENNA:	6" Whip Ant. at Analyzer Input	TUNED TO:	N/A
ANTENNA DISTANCE:	0.25 Meters	ANTENNA HEIGHT:	N/A
SYSTEM NOISE FLOOR:	N/A		

NOTES: Per 15.231(c), Occupied Bandwidth (20 dB down) is less than +/- 8 KHz. This is less than 0.010% of the center frequency. FCC Rules, 15.231(c) devices must be less than 0.25% of center frequency. This device therefore complies with 15.231(c).

LINEAR CORPORATION
FCC ID: EF4 ACP00878