

Date: 1998-12-28
No.: HM1701A/504

TEST REPORT

Page 1 of 7

APPLICANT:

EVENFLO COMPANY , INC.
1801 COMMERCE DRIVE,
PIQUA, OHIO 45356, U.S.A.

DATE OF SAMPLES RECEIVED: 1998.12.23

DATE OF TESTING: 1998.12.24 to 1998.12.26

DESCRIPTION OF SAMPLE(S):

A sample of product said to be:

Product: #615 Ultra-Sensitive Monitor - Receiver
Manufacturer: Barney Technology Ltd.
Model Number: #615
Brand Name: #615 Ultra-Sensitive Monitor
Rating: 120Va.c. 5W 60Hz
Origin: China

INVESTIGATIONS REQUESTED:

Measurement to the relevant clauses of F.C.C. Rules and Regulations Part 15 Subpart B - Unintentional Radiator.

RESULT/ REMARK: Please see attached sheet(s).

CONCLUSION:

From the measurement data obtained, the tested sample was considered to have COMPLIED with the clause 15.109(a) and |ANSI C63.4:1992 section 12.1.1.1-2.of Federal Communications Commission Rules and Regulations Part 15.

TEST EQUIPMENT AUDIT: Please see Appendix A

LAW MAN KIT

Testing Engineer

KITTY CHOY

Verify by

PATRICK WONG

Patrick Wong
for Managing Director

Conditions in issuance of Test Report

1. This Report is issued in confidence to the client and it will be strictly treated as such by the Hong Kong Standards and Testing Centre Ltd. It may not be reproduced either in its entirety or in part and it may not be used for advertising. The client to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Hong Kong Standards and Testing Centre Ltd. to his customer, supplier or other persons directly concerned. The Hong Kong Standards and Testing Centre Ltd. will not, without the consent of the client, enter into any discussion or correspondence with any third party concerning the contents of the Report. 2. The report refers only to the sample tested and does not apply to the bulk, unless the sampling has been carried out by the Hong Kong Standards and Testing Centre Ltd. and is stated as such in the Report. 3. In the event of the improper use of the report, the Hong Kong Standards and Testing Centre Ltd. reserves the rights to withdraw it, and to adopt any other remedies which may be appropriate. 4. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Hong Kong Standards and Testing Centre Ltd. 5. The Hong Kong Standards and Testing Centre Ltd. will not be liable for or accept responsibility for any loss or damage howsoever arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations. 6. Applicants wishing to use the Report in court proceedings or arbitration shall inform the Hong Kong Standards and testing Centre Ltd. to that effect prior to submitting the sample for testing.

Date: 1998-12-28
No.: HM1701A/504

TEST REPORT

Page 2 of 7

TEST SUMMARY

UNINTENTIONAL RADIATOR

- (A) Measurement of Radiated Emissions Satisfactory
- (B) Line Conducted Voltage Test. Satisfactory

TEST DATA

Please refer to the attached result sheets.

Date: 1998-12-28
No.: HM1701A/504

TEST REPORT

Page 3 of 7

UNINTENTIONAL RADIATOR

** RECEIVER SECTION **

(A) Measurement of Radiated Interference

=====

TEST REFERENCE: FCC Rules Part 15 Subpart B section 15.109(a)
TEST CONDITION : Channel A and B
TEST DATE : 1998.12.24

=====

Freq. to which tuned	Freq of the emission	Polarization H-V	Meter reading (at 3m)		Antenna factor	Field Strength (at 3m)	FCC limit @
MHz	MHz		dB()	dB	dB(/m)	/m	/m
49.9	49.9		< 1.0	+	15.0	< 6.4	100
	99.7		< 1.0	+	12.2	< 4.6	150
	149.6		< 1.0	+	9.8	< 3.5	150
	199.4		< 1.0	+	11.5	< 4.2	150
	249.3		< 1.0	+	15.9	< 7.0	200
	299.1		< 1.0	+	17.0	< 7.9	200
	349.0		< 1.0	+	17.2	< 8.1	200
	398.8		< 1.0	+	18.8	< 9.8	200
	448.7		< 1.0	+	19.7	< 10.8	200
	498.6		< 1.0	+	20.6	< 12.0	200
	548.4		< 1.0	+	22.2	< 14.5	200
	598.3		< 1.0	+	23.4	< 16.6	200
	648.1		< 1.0	+	23.5	< 16.8	200
	698.0		< 1.0	+	25.0	< 20.0	200
	747.8		< 1.0	+	26.2	< 22.9	200
	797.7		< 1.0	+	27.2	< 25.7	200
	847.5		< 1.0	+	27.2	< 25.7	200
	897.5		< 1.0	+	27.2	< 25.7	200
	947.2		< 1.0	+	27.8	< 27.5	200
	997.1		< 1.0	+	28.5	< 29.9	500

=====

=====SUMMARY=====

All data is within limits

=====

Broad-band Antennas were used and both polarizations of emissions were measured

Polarizations at highest reading indicated as:

H -- Horizontal V -- Vertical

=====

Date: 1998-12-28

TEST REPORT

Page 4 of 7

No.: HM1701A/504

NOTES FOR THE RADIATION MEASUREMENT

(1) Test site facility:

Open field test site located at Taipo (Hong Kong) with a metal ground plane on filed with the FCC pursuant to section 2.948 of the FCC Rules.

(2) Distance between the ET and measuring antenna:

3 meters.

(3) Measuring instrumentation's:

CISPR Quasi-peak type field strength meter (25 MHz - 1000 MHz.). 6 dB bandwidth set at 120 KHz. Also, peak level of the fundamental emissions was measured in order to determine compliance with the 20dB peak to average limit specified in Section 15.35(b) of the FCC new Rules.

(4) Measuring antenna:

Broad band antenna for the frequency range 25-1000 MHz, connected with 10 meters coaxial cable. Cable loss of the coaxial cable. included in the Antenna Factor for measurement data. The antenna are capable of measuring both horizontal and vertical polarizations.

(5) Frequency range scanned:

The frequency range from 25 MHz to 1000 MHz had been searched. Readings of the highest emissions relating to the limit were reported as above.

(6) Arrangement of EUT:

During the test, the sample was operated at rated supply voltage and arranged for maximum emissions.

(7) Measuring Procedure:

In accordance with the relevant clauses of the FCC Rules Part 15 section 15.109(a) and ANSI C63.4:1992 section 12.1.1.1-2.

(8) Measuring Uncertainty:

The calculated uncertainty for measurement performed at 3M test distance are:-
30MHz to 300MHz = $\pm 3.7\text{dB}$, 300MHz to 1000MHz = $\pm 3.0\text{dB}/-2.7\text{dB}$.

Remark: Purpose of this test is to provide the Applicant with the necessary test data of their device for the submission to FCC with application for Equipment Authorization under FCC's Equipment Authorization Program. This test itself is not an Approval Test.

(B) Measurement of Line-Conducted Voltage onto AC Power Line

Date: 1998-12-28
No.: HM1701A/504

TEST REPORT

Page 5 of 7

TEST REFERENCE : FCC Rules Part 15 Subpart B Section 15.107(a)
(Class B)
TEST CONDITION : Channel A and B
TEST DATE : 1998-12-26

(1) Between "Live" and "Ground"

Frequency Range of Emission			Maximum Measured Radio Noise		FCC Limit (Class B)
MHz			dB()		
0.45	-	0.8	0.00	1.00	250.00
0.8	-	1.6	0.00	1.00	250.00
1.6	-	3.0	0.00	1.00	250.00
3.0	-	5.0	0.00	1.00	250.00
5.0	-	7.0	0.00	1.00	250.00
7.0	-	9.0	0.00	1.00	250.00
9.0	-	11.0	0.00	1.00	250.00
11.0	-	13.0	0.00	1.00	250.00
13.0	-	15.0	0.00	1.00	250.00
15.0	-	17.0	0.00	1.00	250.00
17.0	-	19.0	0.00	1.00	250.00
19.0	-	21.0	0.00	1.00	250.00
21.0	-	23.0	0.00	1.00	250.00
23.0	-	25.0	0.00	1.00	250.00
25.0	-	27.0	0.00	1.00	250.00
27.0	-	30.0	0.00	1.00	250.00

- End -

=====

----- SUMMARY -----

All data is within limits

Date: 1998-12-28
No.: HM1701A/504

TEST REPORT

Page 6 of 7

(B) Measurement of Line-Conducted Voltage onto AC Power Line

TEST REFERENCE : FCC Rules Part 15 Subpart B Section 15.107(a)
(Class B)

TEST CONDITION : Channel A and B

TEST DATE : 1998-12-26

(1) Between "Neutral" and "Ground"

Frequency Range of Emission			Maximum Measured Radio Noise		FCC Limit (Class B)
MHz			dB()		
0.45	-	0.8	0.00	1.00	250.00
0.8	-	1.6	0.00	1.00	250.00
1.6	-	3.0	0.00	1.00	250.00
3.0	-	5.0	0.00	1.00	250.00
5.0	-	7.0	0.00	1.00	250.00
7.0	-	9.0	0.00	1.00	250.00
9.0	-	11.0	0.00	1.00	250.00
11.0	-	13.0	0.00	1.00	250.00
13.0	-	15.0	0.00	1.00	250.00
15.0	-	17.0	0.00	1.00	250.00
17.0	-	19.0	0.00	1.00	250.00
19.0	-	21.0	0.00	1.00	250.00
21.0	-	23.0	0.00	1.00	250.00
23.0	-	25.0	0.00	1.00	250.00
25.0	-	27.0	0.00	1.00	250.00
27.0	-	30.0	0.00	1.00	250.00

----- SUMMARY -----

All data is within limits

Date: 1998-12-28
No.: HM1701A/504

TEST REPORT

Page 7 of 7

NOTES FOR THE CONDUCTED POWER-LINE MEASUREMENT

- (1)LISN (Line Impedance Stabilization Network) used :
50 μ H LISN in accordance with Section of ANSI C63.4:1992.
- (2)Measurement Instrumentations:
CISPR quasi-peak type radio noise meter (9 KHz - 30 MHz), 6 dB bandwidth set at 9 KHz for measurement between 150 KHz & 30MHz.
- (3)Frequency range scanned :
The frequency range from 450 KHz to 30 MHz had been searched. Reading of the highest emissions relating to the limit were reported as above.
- (4)Configuration of EUT
Connection of equipment and operation conditions were same as those in the Radiation measurement.
- (5)Measurement procedure :
In accordance with the relevant sections of ANSI C63.4:1992 "FCC Methods of measurement of Radio Noise Emissions from Computing Devices".
- (6)Measuring Uncertainty:
The calculated uncertainty for conducted power-line measurement is = ± 2.3 dB.

Remark : Purpose of this test is to provide the Applicant with the necessary test data of their device for the submission to FCC with application for Equipment Authorization under FCC's Equipment Authorization Program. This test itself is not an Approval Test.

*****End of Document*****