



Exhibit: RF Exposure – FCC

FCC ID: EHTRFP48

Report File #: 7169004663E-000

Client	Mitel Networks	
Product	RFP48	
Standard(s)	FCC KDB 447498:2015	

RF Exposure – FCC

The EUT contains a 1920-1930 (Licence-Exempt Personal Communications Services) transmitter .

Radiofrequency Radiation Exposure Evaluation: Mobile Devices

Mobile devices shall be evaluated for RF radiation exposure according to the provisions of FCC §2.1091 and the MPE guidelines identified in FCC §1.1310.

As per FCC §1.1310 Table 1(B), the limit for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields for General Population/Uncontrolled Exposure in the frequency range of 300 MHz to 1.5 GHz is $f/1500 \text{ mW/cm}^2$ and in the frequency range of 1.5GHz to 100GHz is 1.0 mW/cm^2 . Where f = frequency in MHz.

The power density formula is given by:

$$P_d = (P_{out} * G) / (4 * \pi * R^2)$$

Where,

P_d = Power density in mW/cm^2

P_{out} = Conducted output power to antenna in mW

G = Numeric Antenna Gain

π = 3.1416

R = Separation distance in cm

MPE Calculation: 1920-1930 MHz FHSS transmitter

The FHSS transmitter has a maximum conducted output power of 19.9 dBm or 98 mW and an antenna gain of -0.4 dBi or 0.91 numerically.

For a distance of 20cm, the power density is:

$$P_d = (98 \text{ mW} * 0.91) / (4 * 3.1416 * (20\text{cm})^2)$$

$$P_d = 0.017731 \text{ mW/cm}^2$$

The device passes the requirement. The calculated power density of 0.017731 mW/cm^2 is below the 1.0 mW/cm^2 limit, and is 1.8 % of this limit.

Page 2 of 2	Report Issued: 10/16/2018	7169004663L-000
-------------	---------------------------	-----------------