

TEST REPORT

Applicant	BLACK BOX Corporation
Address	1000 Park Drive Lawrence, Pennsylvania 15055-1018

Manufacturer or Supplier	BLACK BOX Corporation
Address	1000 Park Drive Lawrence, Pennsylvania 15055-1018
Product	AC750 Wireless Dual Band Gigabit Router
Brand Name	BLACK BOX
Model	WRT750A
Additional Model & Model Difference	N/A
Date of tests	Mar. 23, 2016 ~ Apr. 29, 2016

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 15, Subpart C, Section 15.247**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Harry Li Project Engineer/ EMC Department	Approved by Chris Chen Manager / EMC Department
	 Date: Apr. 29, 2016

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS.....	5
2 MEASUREMENT UNCERTAINTY	5
3 GENERAL INFORMATION	6
3.1 GENERAL DESCRIPTION OF EUT.....	6
3.2 DESCRIPTION OF TEST MODES.....	7
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST	8
3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	8
3.3 DUTY CYCLE OF TEST SIGNAL	10
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	11
3.5 DESCRIPTION OF SUPPORT UNITS.....	11
4 TEST TYPES AND RESULTS.....	12
4.1 CONDUCTED EMISSION MEASUREMENT	12
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	12
4.1.2 TEST INSTRUMENTS.....	12
4.1.3 TEST PROCEDURES	13
4.1.4 DEVIATION FROM TEST STANDARD	13
4.1.5 TEST SETUP.....	14
4.1.6 EUT OPERATING CONDITIONS	14
4.1.7 TEST RESULTS	15
4.2 RADIATED EMISSION MEASUREMENT	17
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	17
4.2.2 TEST INSTRUMENTS.....	18
4.2.3 TEST PROCEDURES	19
4.2.4 DEVIATION FROM TEST STANDARD	19
4.2.5 TEST SETUP.....	20
4.2.6 EUT OPERATING CONDITIONS	20
4.2.7 TEST RESULTS	21
4.3 6DB BANDWIDTH MEASUREMENT.....	35
4.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT	35
4.3.2 TEST INSTRUMENTS.....	35
4.3.3 TEST PROCEDURE.....	35
4.3.4 DEVIATION FROM TEST STANDARD	35



4.3.5	TEST SETUP	36
4.3.6	EUT OPERATING CONDITIONS	36
4.3.7	TEST RESULTS	37
4.4	CONDUCTED OUTPUT POWER	43
4.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	43
4.4.2	TEST SETUP	43
4.4.3	TEST INSTRUMENTS	43
4.4.4	TEST PROCEDURES	44
4.4.5	DEVIATION FROM TEST STANDARD	44
4.4.6	EUT OPERATING CONDITIONS	44
4.4.7	TEST RESULTS	45
4.5	POWER SPECTRAL DENSITY MEASUREMENT	47
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	47
4.5.2	TEST SETUP	47
4.5.3	TEST INSTRUMENTS	47
4.5.4	TEST PROCEDURE	47
4.5.5	DEVIATION FROM TEST STANDARD	47
4.5.6	EUT OPERATING CONDITION	48
4.5.7	TEST RESULTS	48
4.6	OUT OF BAND EMISSION MEASUREMENT	52
4.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	52
4.6.2	TEST SETUP	52
4.6.3	TEST INSTRUMENTS	52
4.6.4	TEST PROCEDURE	52
4.6.5	DEVIATION FROM TEST STANDARD	53
4.6.6	EUT OPERATING CONDITION	53
4.6.7	TEST RESULTS	54
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	66
6	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	67



Test Report No.: RF160323N065-1

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF160323N065-1	Original release	Apr. 29, 2016

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit.
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is RSMA not a standard connector.

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.70dB
Radiated emissions	9KHz ~ 30MHz	2.90dB
	30MHz ~ 1GMHz	3.55dB
	1GHz ~ 18GHz	4.84dB
	18GHz ~ 40GHz	4.84dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	AC750 Wireless Dual Band Gigabit Router
MODEL NO.	WRT750A
FCC ID	EHX-WRT750A
NOMINAL VOLTAGE	AC 100-240V 50/60Hz
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
OPERATING FREQUENCY	2412-2462MHz for 11b/g/n(HT20) 2422-2452MHz for 11n(HT40)
AVERAGE POWER	22.59dBm (Measured Average Power)
ANTENNA TYPE	Dipole Antenna; 2.7dBi gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A

NOTE:

1. The EUT incorporates a MIMO function. Physically, the EUT provides two transmitters and two receivers.

MODULATION MODE	FUNCTION
802.11b	2TX/2RX
802.11g	2TX/2RX
802.11n (HT20)	2TX/2RX
802.11n (HT40)	2TX/2RX

2. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
4. Please refer to the EUT photo document (Reference No.: 160323N065) for detailed product photo.
5. The EUT was powered by the following adapters:

ADAPTER	
BRAND:	LEADER ELECTRONICSINC.
MODEL:	MU18A2120150-A1
INPUT:	AC 100-240V, 50/60Hz, 0.5A Max
OUTPUT:	DC 12.0V, 1.5A
DC CABLE:	Unshielded, without core Non-detachable, 1.5m

3.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n(HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.
The worst case was found when positioned on X axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	Powered by AC 120V with WIFI function

Where **RE<1G**: Radiated Emission below 1GHz **RE≥1G**: Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

POWER LINE CONDUCTED EMISSION TEST:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CONDITION
-	WIFI (2.4G) Link

- ☒ Compare highest, middle and lowest of the data rate, EUT transmitting using the lowest data rate will generate highest transmitting power. so determine the worst-case data rate in the report.

RADIATED EMISSION TEST (BELOW 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	AXIS
802.11g	1 to 11	1	OFDM	BPSK	6.0	X

RADIATED EMISSION TEST (ABOVE 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	AXIS
802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0	X
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0	X
802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5	X
802.11n HT40	3 to 9	3, 6, 9	OFDM	BPSK	13.5	X

☒ Compare highest, middle and lowest of the data rate, EUT transmitting using the lowest data rate will generate highest power. so determine the worst-case data rate in the report.

BANDEDGE MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n HT40	3 to 9	3, 6, 9	OFDM	BPSK	13.5

☒ Compare highest, middle and lowest of the data rate, EUT transmitting using the lowest data rate will generate highest power. so determine the worst-case data rate in the report.

ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode and the worst data rate.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
802.11n HT20	1 to 11	1, 11	OFDM	BPSK	6.5
802.11n HT40	3 to 9	3, 9	OFDM	BPSK	13.5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	22deg. C, 57%RH	AC 120V 60Hz	Kery He
RE≥1G	22deg. C, 57%RH	AC 120V 60Hz	Kery He
PLC	20deg. C, 56%RH	AC 120V 60Hz	Kery He
APCM	20deg. C, 55%RH	AC 120V 60Hz	Harry Li

3.3 DUTY CYCLE OF TEST SIGNAL

Chain 0:

Duty cycle of test signal is 100 %

Chain 1:

Duty cycle of test signal is 100 %



3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

558074 D01 DTS Meas Guidance v03r05

662911 D01 Multiple Transmitter v02r01

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

NOTE: It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B(DoC). The test report has been issued separately.

3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	N/A	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:** 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESCS30	100340	May 11,15	May 10,16
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	Mar. 04,16	Mar. 03,17
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	Apr. 05,16	Apr. 04,17
Voltage probe	SCHWARZBECK	TK 9421	TK 9421-176	Jan. 08,16	Jan. 07,17
Test software	ADT	ADT_Cond_V7.3.7	N/A	N/A	N/A

- NOTE:**
1. The test was performed in shielded room 553.
2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.



4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

**2.Both of LISNs (AMN) are 80 cm from EUT and at least 80
from other units and other metal planes**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.


4.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA: WIFI link

PHASE	Line	6dB BANDWIDTH	9kHz
-------	------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18	9.73	44.40	28.76	54.13	38.49	64.61	54.61	-10.48	-16.12
2	0.19	9.72	37.94	19.16	47.66	28.88	64.08	54.08	-16.42	-25.20
3	0.51	9.78	20.46	11.08	30.24	20.86	56.00	46.00	-25.76	-25.14
4	0.76	9.76	25.16	18.42	34.92	28.18	56.00	46.00	-21.08	-17.82
5	1.38	9.74	32.12	10.10	41.86	19.84	56.00	46.00	-14.14	-26.16
6	18.65	9.98	28.72	19.66	38.70	29.64	60.00	50.00	-21.30	-20.36


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



PHASE	Neutral	6dB BANDWIDTH	9kHz
-------	---------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18	9.48	44.70	30.28	54.18	39.76	64.61	54.61	-10.43	-14.85
2	0.19	9.48	37.54	18.88	47.02	28.36	64.08	54.08	-17.06	-25.72
3	0.25	9.48	32.88	15.12	42.36	24.60	61.84	51.84	-19.48	-27.24
4	3.22	9.51	21.86	13.48	31.37	22.99	56.00	46.00	-24.63	-23.01
5	16.01	9.63	22.60	10.34	32.23	19.97	60.00	50.00	-27.77	-30.03
6	19.27	9.68	24.12	15.06	33.80	24.74	60.00	50.00	-26.20	-25.26

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Apr. 05,16	Apr. 04,17
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV40	101003	Apr. 05,16	Apr. 04,17
Bilog Antenna	Teseq	CBL 6111D	30643	Jul. 16, 15	Jul. 15, 16
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	May 30, 14	May 29, 16
GPS Generator+ Antenna	TOJOIN	GNSS-5000A	E1-010119	Aug. 08, 14	Aug. 07, 16
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Mar. 12,16	Mar. 11,18
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170242	Mar. 12,16	Mar. 11,17
Amplifier (9kHz-1GHz)	SONOMA	310D	186955	Mar. 04,16	Mar. 03, 17
Pre-Amplifier(1-18G)	HP	8449B	3008A00409	Mar. 04,16	Mar. 03, 17
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 20,15	Nov. 19,16
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Sep. 01,15	Aug. 31,16

NOTE:

1. The test was performed in 966 Chamber.
2. The calibration interval of the above test instruments is 12 or 24months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 494399.

4.2.3 TEST PROCEDURES

- a. Below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. Above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- c. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- d. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- e. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be performed using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $> 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file Test Setup Photo.

4.2.4 DEVIATION FROM TEST STANDARD


No deviation.

4.2.5 TEST SETUP

3.1.6.1 TEST SETUP ABOVE 1GHz



3.1.6.2 TEST SETUP BELOW 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



**BUREAU
VERITAS**

Test Report No.: RF160323N065-1

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:


802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	124.19	29.00	43.50	-14.50	100	0	46.70	-17.70
2	249.30	32.60	46.00	-13.40	100	0	48.50	-15.90
3	374.42	27.50	46.00	-18.50	100	0	39.30	-11.80
4	624.65	35.10	46.00	-10.90	100	0	39.90	-4.80
5	773.67	35.80	46.00	-10.20	100	0	37.40	-1.60
6	874.88	37.70	46.00	-8.30	100	0	38.20	-0.50

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.




CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.00	27.80	40.00	-12.20	100	0	40.10	-12.30
2	124.19	30.50	43.50	-13.00	100	0	48.20	-17.70
3	249.30	33.00	46.00	-13.00	100	0	48.90	-15.90
4	374.42	39.10	46.00	-6.90	100	0	50.90	-11.80
5	558.58	27.90	46.00	-18.10	100	0	33.20	-5.30
6	624.65	30.10	46.00	-15.90	100	0	34.90	-4.80

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.





ABOVE 1GHz DATA

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2412.00	106.1 PK			2.23 H	267	68.70	37.40
2	*2412.00	103.1 AV			2.23 H	267	65.70	37.40
3	2390.00	64.5 PK	74.0	-9.5	1.11 H	327	27.10	37.40
4	2390.00	45.3 AV	54.0	-8.7	1.11 H	327	7.90	37.40
5	4824.00	47.8 PK	74.0	-26.2	2.20 H	42	39.40	8.40
6	4824.00	40.4 AV	54.0	-13.6	2.20 H	42	32.00	8.40
7	#7236.00	50.8 PK	76.1	-25.3	1.32 H	264	37.60	13.20
8	#7236.00	37.6 AV	73.1	-35.5	1.32 H	264	24.40	13.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2412.00	112.7 PK			1.85 V	19	75.30	37.40
2	*2412.00	109.6 AV			1.85 V	19	72.20	37.40
3	2390.00	73.9 PK	74.0	-0.1	1.01 V	274	36.50	37.40
4	2390.00	48.5 AV	54.0	-5.5	1.01 V	274	11.10	37.40
5	4824.00	48.1 PK	74.0	-25.9	2.00 V	349	39.70	8.40
6	4824.00	42.0 AV	54.0	-12.0	2.00 V	349	33.60	8.40
7	#7236.00	52.7 PK	82.7	-30.0	1.00 V	0	39.50	13.20
8	#7236.00	43.3 AV	79.6	-36.3	1.00 V	0	30.10	13.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	108.1 PK			1.40 H	297	70.60	37.50
2	*2437.00	104.5 AV			1.40 H	297	67.00	37.50
3	2390.00	63.9 PK	74.0	-10.1	1.20 H	11	26.50	37.40
4	2390.00	44.6 AV	54.0	-9.4	1.20 H	11	7.20	37.40
5	2483.50	66.8 PK	74.0	-7.2	2.48 H	45	29.10	37.70
6	2483.50	47.2 AV	54.0	-6.8	2.48 H	45	9.50	37.70
7	4874.00	49.7 PK	74.0	-24.3	1.00 H	39	41.20	8.50
8	4874.00	43.7 AV	54.0	-10.3	1.00 H	39	35.20	8.50
9	7311.00	54.5 PK	74.0	-19.5	1.14 H	165	41.30	13.20
10	7311.00	46.3 AV	54.0	-7.7	1.14 H	165	33.10	13.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	115.9 PK			1.85 V	87	78.40	37.50
2	*2437.00	112.1 AV			1.85 V	87	74.60	37.50
3	2390.00	69.1 PK	74.0	-4.9	1.36 V	117	31.70	37.40
4	2390.00	47.1 AV	54.0	-6.9	1.36 V	117	9.70	37.40
5	2483.50	73.4 PK	74.0	-0.6	1.22 V	12	35.70	37.70
6	2483.50	49.2 AV	54.0	-4.8	1.22 V	12	11.50	37.70
7	4874.00	49.8 PK	74.0	-24.2	1.56 V	192	41.30	8.50
8	4874.00	43.8 AV	54.0	-10.2	1.56 V	192	35.30	8.50
9	7311.00	58.6 PK	74.0	-15.4	2.15 V	169	45.40	13.20
10	7311.00	53.4 AV	54.0	-0.6	2.15 V	169	40.20	13.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	106.3 PK			3.00 H	294	68.70	37.60
2	*2462.00	103.9 AV			3.00 H	294	66.30	37.60
3	2483.50	60.5 PK	74.0	-13.5	1.04 H	298	22.80	37.70
4	2483.50	47.2 AV	54.0	-6.8	1.04 H	298	9.50	37.70
5	4924.00	48.4 PK	74.0	-25.6	1.51 H	220	39.90	8.50
6	4924.00	42.2 AV	54.0	-11.8	1.51 H	220	33.70	8.50
7	7386.00	50.7 PK	74.0	-23.3	1.01 H	71	37.40	13.30
8	7386.00	40.9 AV	54.0	-13.1	1.01 H	71	27.60	13.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	113.2 PK			2.05 V	15	75.60	37.60
2	*2462.00	109.2 AV			2.05 V	15	71.60	37.60
3	2483.50	73.9 PK	74.0	-0.1	1.75 V	147	36.20	37.70
4	2483.50	53.5 AV	54.0	-0.5	1.75 V	147	15.80	37.70
5	4924.00	49.2 PK	74.0	-24.8	1.33 V	50	40.70	8.50
6	4924.00	42.3 AV	54.0	-11.7	1.33 V	50	33.80	8.50
7	7386.00	53.9 PK	74.0	-20.1	1.38 V	174	40.60	13.30
8	7386.00	45.3 AV	54.0	-8.7	1.38 V	174	32.00	13.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2412.00	102.2 PK			1.51 H	300	65.00	37.20
2	*2412.00	93.0 AV			1.51 H	300	55.80	37.20
3	2390.00	67.4 PK	74.0	-6.6	1.00 H	174	30.30	37.10
4	2390.00	50.4 AV	54.0	-3.6	1.00 H	174	13.30	37.10
5	4824.00	46.5 PK	74.0	-27.5	1.17 H	159	38.80	7.70
6	4824.00	33.6 AV	54.0	-20.4	1.17 H	159	25.90	7.70
7	#7236.00	54.3 PK	72.2	-17.9	1.88 H	11	40.80	13.50
8	#7236.00	36.9 AV	63.0	-26.1	1.88 H	11	23.40	13.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2412.00	110.3 PK			1.74 V	200	73.10	37.20
2	*2412.00	99.7 AV			1.74 V	200	62.50	37.20
3	2390.00	71.7 PK	74.0	-2.3	1.14 V	124	34.60	37.10
4	2390.00	53.9 AV	54.0	-0.1	1.14 V	124	16.80	37.10
5	4824.00	49.0 PK	74.0	-25.0	1.00 V	148	41.30	7.70
6	4824.00	37.3 AV	54.0	-16.7	1.00 V	148	29.60	7.70
7	#7236.00	51.6 PK	80.3	-28.7	1.71 V	20	38.10	13.50
8	#7236.00	34.8 AV	69.7	-34.9	1.71 V	20	21.30	13.50

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	103.9 PK			1.00 H	196	66.60	37.30
2	*2437.00	95.9 AV			1.00 H	196	58.60	37.30
3	2390.00	51.9 PK	74.0	-22.1	1.54 H	184	14.80	37.10
4	2390.00	42.8 AV	54.0	-11.2	1.54 H	184	5.70	37.10
5	2483.50	55.1 PK	74.0	-18.9	1.18 H	27	17.70	37.40
6	2483.50	44.3 AV	54.0	-9.7	1.18 H	27	6.90	37.40
7	4874.00	44.3 PK	74.0	-29.7	1.59 H	69	36.50	7.80
8	4874.00	36.2 AV	54.0	-17.8	1.59 H	69	28.40	7.80
9	7311.00	51.5 PK	74.0	-22.5	1.23 H	87	37.90	13.60
10	7311.00	36.2 AV	54.0	-17.8	1.23 H	87	22.60	13.60
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	111.8 PK			1.33 V	310	74.50	37.30
2	*2437.00	103.3 AV			1.33 V	310	66.00	37.30
3	2390.00	57.1 PK	74.0	-16.9	1.58 V	78	20.00	37.10
4	2390.00	45.8 AV	54.0	-8.2	1.58 V	78	8.70	37.10
5	2483.50	58.3 PK	74.0	-15.7	1.35 V	328	20.90	37.40
6	2483.50	47.0 AV	54.0	-7.0	1.35 V	328	9.60	37.40
7	4874.00	41.3 PK	74.0	-32.7	1.64 V	189	33.50	7.80
8	4874.00	34.5 AV	54.0	-19.5	1.64 V	189	26.70	7.80
9	7311.00	55.2 PK	74.0	-18.8	1.23 V	72	41.60	13.60
10	7311.00	42.3 AV	54.0	-11.7	1.23 V	72	28.70	13.60

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	102.9 PK			1.91 H	228	65.50	37.40
2	*2462.00	92.4 AV			1.91 H	228	55.00	37.40
3	2483.50	63.8 PK	74.0	-10.2	1.91 H	228	26.40	37.40
4	2483.50	47.7 AV	54.0	-6.3	1.91 H	228	10.30	37.40
5	4924.00	43.5 PK	74.0	-30.5	1.52 H	134	35.60	7.90
6	4924.00	32.3 AV	54.0	-21.7	1.52 H	134	24.40	7.90
7	7386.00	48.3 PK	74.0	-25.7	1.42 H	12	34.60	13.70
8	7386.00	34.3 AV	54.0	-19.7	1.42 H	12	20.60	13.70
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	108.3 PK			1.07 V	317	70.90	37.40
2	*2462.00	100.0 AV			1.07 V	317	62.60	37.40
3	2483.50	72.9 PK	74.0	-1.1	1.00 V	78	35.50	37.40
4	2483.50	53.4 AV	54.0	-0.6	1.00 V	78	16.00	37.40
5	4924.00	42.3 PK	74.0	-31.7	1.54 V	89	34.40	7.90
6	4924.00	33.2 AV	54.0	-20.8	1.54 V	89	25.30	7.90
7	7386.00	48.6 PK	74.0	-25.4	1.12 V	35	34.90	13.70
8	7386.00	38.5 AV	54.0	-15.5	1.12 V	35	24.80	13.70

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

802.11n 20MHz

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2412.00	103.0 PK			1.91 H	276	65.80	37.20
2	*2412.00	93.7 AV			1.91 H	276	56.50	37.20
3	2390.00	67.1 PK	74.0	-6.9	1.91 H	276	30.00	37.10
4	2390.00	49.2 AV	54.0	-4.8	1.91 H	276	12.10	37.10
5	4824.00	43.6 PK	74.0	-30.4	1.64 H	56	35.90	7.70
6	4824.00	33.3 AV	54.0	-20.7	1.64 H	56	25.60	7.70
7	#7236.00	46.2 PK	73.0	-26.8	1.23 H	120	32.70	13.50
8	#7236.00	35.4 AV	63.7	-28.3	1.23 H	120	21.90	13.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2412.00	106.5 PK			1.14 V	76	69.30	37.20
2	*2412.00	97.5 AV			1.14 V	76	60.30	37.20
3	2390.00	69.8 PK	74.0	-4.2	2.21 V	286	32.70	37.10
4	2390.00	53.4 AV	54.0	-0.6	2.21 V	286	16.30	37.10
5	4824.00	41.5 PK	74.0	-32.5	1.67 V	100	33.80	7.70
6	4824.00	32.3 AV	54.0	-21.7	1.67 V	100	24.60	7.70
7	#7236.00	50.1 PK	76.5	-26.4	1.46 V	39	36.60	13.50
8	#7236.00	36.3 AV	67.5	-31.2	1.46 V	39	22.80	13.50

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	103.7 PK			2.19 H	218	66.40	37.30
2	*2437.00	93.9 AV			2.19 H	218	56.60	37.30
3	2390.00	52.8 PK	74.0	-21.2	1.57 H	224	15.70	37.10
4	2390.00	42.9 AV	54.0	-11.1	1.57 H	224	5.80	37.10
5	2483.50	53.8 PK	74.0	-20.2	1.17 H	26	16.40	37.40
6	2483.50	44.8 AV	54.0	-9.2	1.17 H	26	7.40	37.40
7	4874.00	43.1 PK	74.0	-30.9	1.65 H	153	35.30	7.80
8	4874.00	34.5 AV	54.0	-19.5	1.65 H	153	26.70	7.80
9	7311.00	52.5 PK	74.0	-21.5	1.34 H	98	38.90	13.60
10	7311.00	38.4 AV	54.0	-15.6	1.34 H	98	24.80	13.60
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	110.2 PK			1.45 V	336	72.90	37.30
2	*2437.00	102.8 AV			1.45 V	336	65.50	37.30
3	2390.00	54.3 PK	74.0	-19.7	1.00 V	20	17.20	37.10
4	2390.00	43.1 AV	54.0	-10.9	1.00 V	20	6.00	37.10
5	2483.50	56.0 PK	74.0	-18.0	1.51 V	74	18.60	37.40
6	2483.50	50.1 AV	54.0	-3.9	1.51 V	74	9.70	40.40
7	4874.00	42.9 PK	74.0	-31.1	1.32 V	235	35.10	7.80
8	4874.00	31.4 AV	54.0	-22.6	1.32 V	235	23.60	7.80
9	7311.00	64.1 PK	74.0	-9.9	1.65 V	352	50.50	13.60
10	7311.00	43.7 AV	54.0	-10.3	1.65 V	352	30.10	13.60

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	99.4 PK			2.21 H	287	62.00	37.40
2	*2462.00	90.5 AV			2.21 H	287	53.10	37.40
3	2483.50	65.1 PK	74.0	-8.9	2.21 H	287	27.70	37.40
4	2483.50	47.2 AV	54.0	-6.8	2.21 H	287	9.80	37.40
5	4924.00	41.3 PK	74.0	-32.7	1.30 H	20	33.40	7.90
6	4924.00	31.8 AV	54.0	-22.2	1.30 H	20	23.90	7.90
7	7386.00	46.4 PK	74.0	-27.6	1.68 H	22	32.70	13.70
8	7386.00	34.1 AV	54.0	-19.9	1.68 H	22	20.40	13.70
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	107.9 PK			4.00 V	79	70.50	37.40
2	*2462.00	99.4 AV			4.00 V	79	62.00	37.40
3	2483.50	73.3 PK	74.0	-0.7	1.62 V	303	35.90	37.40
4	2483.50	53.8 AV	54.0	-0.2	1.62 V	303	16.40	37.40
5	4924.00	41.0 PK	74.0	-33.0	1.50 V	352	33.10	7.90
6	4924.00	30.2 AV	54.0	-23.8	1.50 V	352	22.30	7.90
7	7386.00	47.2 PK	74.0	-26.8	1.34 V	35	33.50	13.70
8	7386.00	34.0 AV	54.0	-20.0	1.34 V	35	20.30	13.70

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

802.11n 40MHz

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2422.00	98.6 PK			2.52 H	275	61.40	37.20
2	*2422.00	89.1 AV			2.52 H	275	51.90	37.20
3	2390.00	63.2 PK	74.0	-10.8	2.52 H	275	26.10	37.10
4	2390.00	49.1 AV	54.0	-4.9	2.52 H	275	12.00	37.10
5	4844.00	40.7 PK	74.0	-33.3	1.13 H	8	32.90	7.80
6	4844.00	32.1 AV	54.0	-21.9	1.13 H	8	24.30	7.80
7	7266.00	45.2 PK	74.0	-28.8	1.51 H	10	31.70	13.50
8	7266.00	34.7 AV	54.0	-19.3	1.51 H	10	21.20	13.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2422.00	103.1 PK			1.67 V	73	65.90	37.20
2	*2422.00	94.3 AV			1.67 V	73	57.10	37.20
3	2390.00	70.5 PK	74.0	-3.5	2.24 V	217	33.40	37.10
4	2390.00	53.9 AV	54.0	-0.1	2.24 V	217	16.80	37.10
5	4844.00	41.6 PK	74.0	-32.4	1.65 V	40	33.80	7.80
6	4844.00	30.6 AV	54.0	-23.4	1.65 V	40	22.80	7.80
7	7266.00	45.8 PK	74.0	-28.2	1.06 V	108	32.30	13.50
8	7266.00	34.3 AV	54.0	-19.7	1.06 V	108	20.80	13.50

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	100.6 PK			1.96 H	271	63.30	37.30
2	*2437.00	90.5 AV			1.96 H	271	53.20	37.30
3	2390.00	63.3 PK	74.0	-10.7	1.45 H	87	26.20	37.10
4	2390.00	48.9 AV	54.0	-5.1	1.45 H	87	11.80	37.10
5	2483.50	66.3 PK	74.0	-7.7	1.58 H	227	28.90	37.40
6	2483.50	50.9 AV	54.0	-3.1	1.58 H	227	13.50	37.40
7	4874.00	41.8 PK	74.0	-32.2	1.62 H	135	34.00	7.80
8	4874.00	31.6 AV	54.0	-22.4	1.62 H	135	23.80	7.80
9	7311.00	47.3 PK	74.0	-26.7	1.17 H	48	33.70	13.60
10	7311.00	35.6 AV	54.0	-18.4	1.17 H	48	22.00	13.60
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	105.1 PK			1.23 V	95	67.80	37.30
2	*2437.00	96.1 AV			1.23 V	95	58.80	37.30
3	2390.00	67.1 PK	74.0	-6.9	1.66 V	235	30.00	37.10
4	2390.00	52.0 AV	54.0	-2.0	1.66 V	235	14.90	37.10
5	2483.50	69.8 PK	74.0	-4.2	1.54 V	229	32.40	37.40
6	2483.50	53.3 AV	54.0	-0.7	1.54 V	229	15.90	37.40
7	4874.00	43.2 PK	74.0	-30.8	1.36 V	284	35.40	7.80
8	4874.00	32.5 AV	54.0	-21.5	1.36 V	284	24.70	7.80
9	7311.00	50.7 PK	74.0	-23.3	1.58 V	347	37.10	13.60
10	7311.00	34.1 AV	54.0	-19.9	1.58 V	347	20.50	13.60

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	97.4 PK			1.75 H	304	60.10	37.30
2	*2452.00	88.5 AV			1.75 H	304	51.20	37.30
3	2483.50	64.2 PK	74.0	-9.8	1.75 H	304	26.80	37.40
4	2483.50	48.2 AV	54.0	-5.8	1.75 H	304	10.80	37.40
5	4904.00	42.6 PK	74.0	-31.4	1.63 H	117	34.70	7.90
6	4904.00	32.8 AV	54.0	-21.2	1.63 H	117	24.90	7.90
7	7356.00	46.8 PK	74.0	-27.2	1.69 H	57	33.10	13.70
8	7356.00	34.7 AV	54.0	-19.3	1.69 H	57	21.00	13.70
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	102.9 PK			1.56 V	75	65.60	37.30
2	*2452.00	93.7 AV			1.56 V	75	56.40	37.30
3	2483.50	70.8 PK	74.0	-3.2	1.63 V	317	33.40	37.40
4	2483.50	53.4 AV	54.0	-0.6	1.63 V	317	16.00	37.40
5	4904.00	43.6 PK	74.0	-30.4	1.08 V	9	35.70	7.90
6	4904.00	32.7 AV	54.0	-21.3	1.08 V	9	24.80	7.90
7	7356.00	47.1 PK	74.0	-26.9	1.16 V	246	33.40	13.70
8	7356.00	34.8 AV	54.0	-19.2	1.16 V	246	21.10	13.70

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	Feb. 18,16	Feb. 17,17
Power Sensor	Keysight	U2021XA	MY55060018	Feb. 18,16	Feb. 17,17
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 12, 15	Oct.11, 16
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.07,15	Sep. 06,16
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 28,15	Nov. 27,16
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 09,15	Nov. 08,16
Signal Generator	Agilent	N5183A	MY50140980	Nov. 09,15	Nov. 08,16
ESG Vector Signal Generator	Agilent	E4438C	MY49072505	Nov. 09,15	Nov. 08,16
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Sep. 01,15	Aug. 31,16

NOTE:

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRG/CHINA and NIM/CHINA.


4.3.3 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 100KHz
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
1	2412	10.13	10.08	0.5	PASS
6	2437	10.07	10.08	0.5	PASS
11	2462	10.09	10.12	0.5	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
1	2412	16.40	16.39	0.5	PASS
6	2437	16.37	16.39	0.5	PASS
11	2462	16.39	16.38	0.5	PASS

802.11n 20MHz

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
1	2412	17.14	17.09	0.5	PASS
6	2437	17.34	17.06	0.5	PASS
11	2462	17.11	17.09	0.5	PASS

802.11n 40MHz


CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
3	2422	35.91	35.90	0.5	PASS
6	2437	35.94	36.10	0.5	PASS
9	2452	36.12	36.36	0.5	PASS



BUREAU
VERITAS

Test Report No.: RF160323N065-1

CHAIN 0



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China


Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



BUREAU
VERITAS

Test Report No.: RF160323N065-1

CHAIN 1



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com

802.11b 20MHz

CHANNEL	FREQUENCY (MHz)	99% OCCUPANCY BANDWIDTH (MHz)		PASS / FAIL
		CHAIN 0	CHAIN 1	
1	2412	12.78	12.71	PASS
6	2437	13.04	13.10	PASS
11	2462	12.73	12.80	PASS

802.11b 20MHz

CHANNEL	FREQUENCY (MHz)	99% OCCUPANCY BANDWIDTH (MHz)		PASS / FAIL
		CHAIN 0	CHAIN 1	
1	2412	17.04	17.03	PASS
6	2437	18.74	18.80	PASS
11	2462	16.90	17.00	PASS

802.11n 20MHz

CHANNEL	FREQUENCY (MHz)	99% OCCUPANCY BANDWIDTH (MHz)		PASS / FAIL
		CHAIN 0	CHAIN 1	
1	2412	18.00	17.76	PASS
6	2437	19.40	19.37	PASS
11	2462	17.79	17.80	PASS


802.11n 40MHz

CHANNEL	FREQUENCY (MHz)	99% OCCUPANCY BANDWIDTH (MHz)		PASS / FAIL
		CHAIN 0	CHAIN 1	
3	2422	36.80	36.67	PASS
6	2437	37.00	37.00	PASS
9	2452	36.83	36.66	PASS



BUREAU
VERITAS

Test Report No.: RF160323N065-1



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China


Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com

4.4 CONDUCTED OUTPUT POWER

4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm).

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	Feb. 18,16	Feb. 17,17
Power Sensor	Keysight	U2021XA	MY55060018	Feb. 18,16	Feb. 17,17
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 12, 15	Oct.11, 16
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.07,15	Sep. 06,16
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 28,15	Nov. 27,16
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 09,15	Nov. 08,16
Signal Generator	Agilent	N5183A	MY50140980	Nov. 09,15	Nov. 08,16
ESG Vector Signal Generator	Agilent	E4438C	MY49072505	Nov. 09,15	Nov. 08,16
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Sep. 01,15	Aug. 31,16

NOTE:

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



4.4.4 TEST PROCEDURES

An Average power sensor was used on the output port of the EUT. An Average power meter was used to read the response of the Average power sensor. Record the Average power level.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.4.7 TEST RESULTS

802.11b

CHAN.	FREQ (MHz)	AVG. POWER (dBm)		AVG. POWER (mW)		TOTAL POWER (mW)	TOTAL POWER (dBm)	AVG. POWER LIMIT (W)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1				
1	2412	15.93	15.86	39.174	38.548	77.722	18.91	30	PASS
6	2437	19.70	19.46	93.325	88.308	181.633	22.59	30	PASS
11	2462	16.74	16.85	47.206	48.417	95.623	19.81	30	PASS

802.11g

CHAN.	FREQ (MHz)	AVG. POWER (dBm)		AVG. POWER (mW)		TOTAL POWER (mW)	TOTAL POWER (dBm)	AVG. POWER LIMIT (W)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1				
1	2412	13.12	12.96	20.512	19.770	40.282	16.05	30	PASS
6	2437	18.67	18.52	73.621	71.121	144.742	21.61	30	PASS
11	2462	13.08	12.88	20.324	19.409	39.733	15.99	30	PASS

802.11n 20MHz

CHAN.	FREQ (MHz)	AVG. POWER (dBm)		AVG. POWER (mW)		TOTAL POWER (mW)	TOTAL POWER (dBm)	AVG. POWER LIMIT (W)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1				
1	2412	13.10	12.65	20.417	18.408	38.825	15.89	30	PASS
6	2437	18.49	18.58	70.632	72.111	142.743	21.55	30	PASS
11	2462	12.07	12.42	16.106	17.458	33.564	15.26	30	PASS

802.11n 40MHz


CHAN.	FREQ (MHz)	AVG. POWER (dBm)		AVG. POWER (mW)		TOTAL POWER (mW)	TOTAL POWER (dBm)	AVG. POWER LIMIT (W)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1				
3	2422	10.61	10.32	11.508	10.765	22.273	13.48	30	PASS
6	2437	14.02	13.79	25.235	23.933	49.168	16.92	30	PASS
9	2452	9.15	9.27	8.222	8.453	16.675	12.22	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: 3 kHz.
- d) Set VBW $\geq 3 \times$ RBW.
- e) Detector = peak
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times$ span/RBW.
- g) Sweep time = auto couple.
- h) Use the peak marker function to determine the maximum amplitude level.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

Same as item 4.3.6.

4.5.7 TEST RESULTS

802.11b

TX chain	Channel	Freq. (MHz)	PSD (dBm)	10 log (N=2) dB	TOTAL PSD (dBm)	Limit (dBm)	PASS /FAIL
0	1	2412	-9.10	3.01	-6.09	8	PASS
	6	2437	-6.70	3.01	-3.69	8	PASS
	11	2462	-10.14	3.01	-7.13	8	PASS
1	1	2412	-9.67	3.01	-6.66	8	PASS
	6	2437	-6.28	3.01	-3.27	8	PASS
	11	2462	-7.88	3.01	-4.87	8	PASS

Note:

1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain = $2.7\text{dBi} + 10\log(2) = 5.71$, so the power density limit no need to reduce.

802.11g

TX chain	Channel	Freq. (MHz)	PSD (dBm)	10 log (N=2) dB	TOTAL PSD (dBm)	Limit (dBm)	PASS /FAIL
0	1	2412	-13.76	3.01	-10.75	8	PASS
	6	2437	-10.65	3.01	-7.64	8	PASS
	11	2462	-15.78	3.01	-12.77	8	PASS
1	1	2412	-14.41	3.01	-11.40	8	PASS
	6	2437	-10.12	3.01	-7.11	8	PASS
	11	2462	-14.29	3.01	-11.28	8	PASS

Note:

1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain = $2.7\text{dBi} + 10\log(2) = 5.71$, so the power density limit no need to reduce.

802.11n 20MHz

TX chain	Channel	Freq. (MHz)	PSD (dBm)	10 log (N=2) dB	TOTAL PSD (dBm)	Limit (dBm)	PASS /FAIL
0	1	2412	-18.97	3.01	-15.96	8	PASS
	6	2437	-11.42	3.01	-8.41	8	PASS
	11	2462	-21.60	3.01	-18.59	8	PASS
1	1	2412	-19.19	3.01	-16.18	8	PASS
	6	2437	-9.39	3.01	-6.38	8	PASS
	11	2462	-19.11	3.01	-16.10	8	PASS

Note:

1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain = $2.7\text{dBi} + 10\log(2) = 5.71$, so the power density limit no need to reduce.

802.11n 40MHz

TX chain	Channel	Freq. (MHz)	PSD (dBm)	10 log (N=2) dB	TOTAL PSD (dBm)	Limit (dBm)	PASS /FAIL
0	3	2422	-18.11	3.01	-15.10	8	PASS
	6	2437	-16.28	3.01	-13.27	8	PASS
	9	2452	-19.63	3.01	-16.62	8	PASS
1	3	2422	-17.42	3.01	-14.41	8	PASS
	6	2437	-14.96	3.01	-11.95	8	PASS
	9	2452	-17.72	3.01	-14.71	8	PASS

Note:


1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain = $2.7\text{dBi} + 10\log(2) = 5.71$, so the power density limit no need to reduce.



BUREAU
VERITAS

Test Report No.: RF160323N065-1

CHAIN 0






BUREAU
VERITAS

Test Report No.: RF160323N065-1

CHAIN 1



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com

4.6 OUT OF BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

Measurement Procedure - Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



Test Report No.: RF160323N065-1

Measurement Procedure –Unwanted Emission Level

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

Same as item 4.3.6




BUREAU
VERITAS

Test Report No.: RF160323N065-1

4.6.7 TEST RESULTS

802.11b

CHAIN 0



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com




BUREAU
VERITAS


Test Report No.: RF160323N065-1

CHAIN 1


CH 1



CH 6



CH 11



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com




BUREAU
VERITAS

Test Report No.: RF160323N065-1


802.11g

CHAIN 0


CH 1



CH 6



CH 11



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com




BUREAU
VERITAS


Test Report No.: RF160323N065-1

CHAIN 1


CH 1



CH 6



CH 11






BUREAU
VERITAS

Test Report No.: RF160323N065-1


802.11n 20MHz

CHAIN 0


CH 1



CH 6



CH 11



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com




BUREAU
VERITAS


Test Report No.: RF160323N065-1

CHAIN 1


CH 1



CH 6



CH 11






BUREAU
VERITAS

Test Report No.: RF160323N065-1


802.11n 40MHz

CHAIN 0


CH 3



CH 6



CH 9



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com




BUREAU
VERITAS


Test Report No.: RF160323N065-1

CHAIN 1


CH 3



CH 6



CH 9



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com




BUREAU
VERITAS


Test Report No.: RF160323N065-1

802.11b

CHAIN 0



CHAIN 1






BUREAU
VERITAS

Test Report No.: RF160323N065-1


802.11g

CHAIN 0

CH 1 Band edge




CH 11 Band edge




CHAIN 1

CH 1 Band edge



CH 11 Band edge






BUREAU
VERITAS

Test Report No.: RF160323N065-1


802.11n 20MHz

CHAIN 0

CH 1 Band edge




CH 11 Band edge




CHAIN 1

CH 1 Band edge



CH 11 Band edge






BUREAU
VERITAS

Test Report No.: RF160323N065-1


802.11n 40MHz

CHAIN 0

CH 3 Band edge




CH 9 Band edge




CHAIN 1

CH 3 Band edge



CH 9 Band edge



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



Test Report No.: RF160323N065-1

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: RF160323N065-1

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---