

**#01\_WLAN2.4GHz\_802.11b 1Mbps\_Bottom Face\_0mm\_Ch11;Ant 1**

Communication System: 802.11b ; Frequency: 2462 MHz;Duty Cycle: 1:1.021

Medium: MSL\_2450\_170505 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.968$  S/m;  $\epsilon_r = 54.174$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.1 °C ; Liquid Temperature : 22.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3931; ConvF(7.73, 7.73, 7.73); Calibrated: 2016/10/3;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2016/9/28
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1131
- Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7373)

**Area Scan (101x61x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.15 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.21 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 1.79 W/kg

**SAR(1 g) = 0.685 W/kg; SAR(10 g) = 0.272 W/kg**

Maximum value of SAR (measured) = 1.31 W/kg



0 dB = 1.31 W/kg = 1.17 dBW/kg

**#02\_WLAN5GHz\_802.11ac-VHT80 MCS0\_Bottom Face\_0mm\_Ch58;Ant 1**

Communication System: 802.11ac ; Frequency: 5290 MHz; Duty Cycle: 1:1.083

Medium: MSL\_5G\_170505 Medium parameters used:  $f = 5290$  MHz;  $\sigma = 5.618$  S/m;  $\epsilon_r = 46.757$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.2 °C ; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3931; ConvF(4.57, 4.57, 4.57); Calibrated: 2016/10/3;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2016/9/28
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1131
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

**Area Scan (121x81x1):** Interpolated grid:  $dx=1.000$  mm,  $dy=1.000$  mm

Maximum value of SAR (interpolated) = 0.648 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=4$ mm,  $dy=4$ mm,  $dz=1.4$ mm

Reference Value = 11.27 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 2.64 W/kg

**SAR(1 g) = 0.323 W/kg; SAR(10 g) = 0.069 W/kg**

Maximum value of SAR (measured) = 1.55 W/kg



0 dB = 1.55 W/kg = 1.90 dBW/kg

**#03\_WLAN5GHz\_802.11ac-VHT80 MCS0\_Bottom Face\_0mm\_Ch106;Ant 1**

Communication System: 802.11ac ; Frequency: 5530 MHz;Duty Cycle: 1:1.083

Medium: MSL\_5G\_170505 Medium parameters used:  $f = 5530$  MHz;  $\sigma = 5.928$  S/m;  $\epsilon_r = 46.34$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.2 °C ; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3931; ConvF(3.71, 3.71, 3.71); Calibrated: 2016/10/3;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2016/9/28
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1131
- Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7373)

**Area Scan (121x81x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.225 W/kg


**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 6.797 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 4.29 W/kg

**SAR(1 g) = 0.770 W/kg; SAR(10 g) = 0.173 W/kg**

Maximum value of SAR (measured) = 2.29 W/kg



0 dB = 2.29 W/kg = 3.60 dBW/kg

**#04\_WLAN5GHz\_802.11ac-VHT80 MCS0\_Bottom Face\_0mm\_Ch155;Ant 1**

Communication System: 802.11ac ; Frequency: 5775 MHz;Duty Cycle: 1:1.083

Medium: MSL\_5G\_170505 Medium parameters used:  $f = 5775$  MHz;  $\sigma = 6.258$  S/m;  $\epsilon_r = 45.958$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.2 °C; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3931; ConvF(4.01, 4.01, 4.01); Calibrated: 2016/10/3;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2016/9/28
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1131
- Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7373)

**Area Scan (121x81x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.333 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 6.086 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 5.83 W/kg

**SAR(1 g) = 0.860 W/kg; SAR(10 g) = 0.169 W/kg**

Maximum value of SAR (measured) = 2.79 W/kg



**#05\_Bluetooth\_1Mbps\_Bottom Face\_0mm\_Ch39;Ant 2**

Communication System: Bluetooth ; Frequency: 2441 MHz;Duty Cycle: 1:1.297

Medium: MSL\_2450\_170505 Medium parameters used :  $f = 2441$  MHz;  $\sigma = 1.943$  S/m;  $\epsilon_r = 54.252$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.1 °C ; Liquid Temperature : 22.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3931; ConvF(7.73, 7.73, 7.73); Calibrated: 2016/10/3;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2016/9/28
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1131
- Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7373)

**Area Scan (91x61x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.161 W/kg


**Zoom Scan (7x7x5)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.441 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.195 W/kg

**SAR(1 g) = 0.058 W/kg; SAR(10 g) = 0.020 W/kg**

Maximum value of SAR (measured) = 0.121 W/kg



0 dB = 0.121 W/kg = -9.17 dBW/kg