

RF Exposure Calculation

Applicant: RTX Telecom Inc

FCC ID: ELIRTX3055

The internal / external antennas used for this mobile transmitter must provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter.

A safety statement concerning minimum separation distances from enclosure of the **RTX3055.1** will be integrated in the user's manual to provide end-users with transmitter operating conditions for satisfying RF exposure compliance.

The appropriate Max conducted power can be drawn from the test report no. G0M20503-9313-C-1.

For transmitter operating in the 1920-1930 Mhz range, paragraph 1.1310 Table 1 limits maximum permissible exposure (MPE) to 1.0 mW/cm² for uncontrolled environments and 5.0 mW/cm² for controlled environments.

The far field on-axis power flux density (W/m²) is calculated using the following formula:

S = Power density (mW/cm²)

EIRP = isotropically radiated power (mW)

ERP = effective radiated power (mW)

r = Distance in cm

Calculations

$$S = \frac{PG}{4\pi R^2} \quad S = \frac{EIRP}{4\pi R^2} = \frac{1.64 ERP}{4\pi R^2} = \frac{0.41 ERP}{\pi R^2}$$

name			nature value	log value
conducted power			118,58 mW	20,74 dBm
max Antenna gain dBi			2,00	3,00 dBi
max Antenna gain dBd			1,52	1,83 dBd
		r	20 cm	
calculated		S	0,047 mW/cm ²	
Limit		S	1,00 mW/cm ²	for f >1500 MHz
calculated radiated power	EIRP		236,59 mW	23,74
	ERP		180,69 mW	22,57
measured radiated power	EIRP		mW	
	ERP		mW	



Kurt Damm

Head of Radio Communication

ETS

Electronic Technology Systems Dr. Genz GmbH
Storkower Strasse 38c
D-15526 Reichenwalde b. Berlin

Handelsregister:

Amtsgericht Frankfurt/Oder HRB 5151
Geschäftsführung: Dr. Dietmar Genz
Norbert Kaspar

Bankverbindung:

Sparkasse Oder-Spree
BLZ 170 550 50
Kto. Nr. 3105165974