

Project No: TM-2602000330P
Report No.: TMWK2606002677KS

FCC ID: ELVATR6B

Page 1 / 15
Rev. 00

RF Exposure Evaluation Report

FCC 47 CFR § 2.1091

for

Vehicle Security and Remote Start System

Model Name.: 4361215, 4361223

Prepared for:

NUTEK CORPORATION

No.167, Lane 235, Bauchiau Rd., Xindian District, New Taipei City, 23145, Taiwan

Prepared by

Compliance Certification Services Inc.

Wugu Laboratory

No.11, Wugong 6th Rd., Wugu Dist.,

New Taipei City, Taiwan.

Issue Date: July 06, 2026

Note: This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, NIST or any government agencies. The test results in the report only apply to the tested sample.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Project No: TM-2602000330P
Report No.: TMWK2606002677KS

Page 2 / 15
Rev. 00

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	July 06, 2026	Initial Issue	ALL	Allison Chen



Project No: TM-2602000330P
Report No.: TMWK2606002677KS

Page 3 / 15
Rev. 00

Table of Contents

1	ATTESTATION OF TEST RESULTS	4
2	TEST SPECIFICATION, METHODS AND PROCEDURES	5
3	DEVICE UNDER TEST (DUT) INFORMATION	6
3.1	DUT DESCRIPTION	6
3.2	WIRELESS TECHNOLOGIES	7
4	MEASUREMENT UNCERTAINTY	9
5	MAXIMUM PERMISSIBLE EXPOSURE	10
5.1	LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	10
5.2	MPE CALCULATION METHOD	11
5.3	MPE EXEMPTION	12
5.4	MULTIPLE RF SOURCES	13
6	MPE EXEMPTION OPTION B	14
7	FACILITIES	15

Project No: TM-2602000330P
Report No.: TMWK2606002677KS

Page 4 / 15
Rev. 00

1 Attestation of Test Results

Applicant Name	NUTEK CORPORATION		
Model Name	4361215, 4361223		
Applicable Standards	FCC 47 CFR § 2.1091 FCC 47 CFR § 1.1310 Published RF exposure KDB procedures		
Receive EUT Date:	March 08, 2026		
Date of Test:	May 11, 2026		
Compliance Certification Services Inc. , tested the above equipment in accordance with the requirements set forth in the above standards. Determination of compliance is based on the results of the compliance measurement,not taking into account measurement instrumentation uncertainty.All indications of Pass/Fail in this report are opinions expressed by Compliance Certification Services Inc, based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.			
Approved & Released By:		Tested by:	
			
Sky Zhou Asst. Section Manager Compliance Certification Services Inc.		KW Huang Engineer Compliance Certification Services Inc.	



Project No: TM-2602000330P
Report No.: TMWK2606002677KS

Page 5 / 15
Rev. 00

2 Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1091, the following FCC Published RF exposure [KDB](#) procedures:

- 447498 D04 Interim General RF Exposure Guidance v01
- 865664 D02 RF Exposure Reporting v01r02



Project No: TM-2602000330P
Report No.: TMWK2606002677KS

Page 6 / 15
Rev. 00

3 Device Under Test (DUT) Information

3.1 DUT Description

Product	Vehicle Security and Remote Start System
Trade Name	N/A
Model No.	4361215, 4361223
Model Discrepancy	Hardware/software is identical on 4361215, 4361223. Separate P/N's for specific customer, processing location & inventory (for marketing purpose only).
Hardware Version	AQ11C
Software Version	NSP44
Sample Stage	Identical prototype

3.2 Wireless Technologies

Frequency bands	☐ Bluetooth: 2402MHz-2480MHz WIFI 2.4GHz ☐ 802.11b/g/n HT20/ax HE20 mode:: 2412MHz ~ 2462 MHz ☐ 802.11n HT40 mode:: 2422MHz ~ 2452 MHz WIFI 5GHz ☐ 802.11a/n HT20 / ac VHT20 / ax HE20 mode: 5180MHz ~ 5240MHz / 5260 ~ 5320MHz / 5500 ~ 5700MHz / 5745MHz ~ 5825MHz ☐ 802.11n HT40 / ac VHT40 / ax HE40 mode: 5190 MHz ~ 5230 MHz / 5270 MHz ~ 5310 MHz / 5510 MHz ~ 5670 MHz / 5755 MHz ~ 5795 MHz ☐ 802.11ac VHT80 / ax HE80 mode: 5210 MHz / 5290 MHz / 5530 ~ 5610 MHz / 5775 MHz WWAN: ☐ WCDMA Band II: 1850 ~ 1910 MHz ☐ WCDMA Band IV: 1710 ~ 1755 MHz ☐ WCDMA Band V: 824 ~ 849 MHz ☐ LTE Band 2: 1850 ~ 1910 MHz ☐ LTE Band 4: 1710 ~ 1755 MHz ☐ LTE Band 5: 824 ~ 849 MHz ☐ LTE Band 7: 2500 ~ 2570 MHz ☐ LTE Band 12: 699 ~ 716 MHz ☐ LTE Band 13: 777 ~ 787 MHz ☐ LTE Band 25: 1850 ~ 1915 MHz ☐ LTE Band 26: 814 ~ 849 MHz ☐ LTE Band 38: 2570 ~ 2620 MHz ☐ LTE Band 41: 2496 ~ 2690 MHz ☐ LTE Band 66: 1710 ~ 1780 MHz ☒ Others: 904 MHz ~ 923.6 MHz
Exposure classification	☐ Occupational/Controlled exposure ☒ General Population/Uncontrolled exposure

Antenna Specification	(1) Brand / Model: Nutek Corpation. / AQ11_Antenna			
	Type: PCB Antenna			
	Gain: -1.58 dBi			
	(2) Brand / Model: Chinmore Industry CO.LTD / HWE00271			
	Type: Dipole Antenna			
	Gain: 2.5 dBi			
	PCB Antenna	Gain :	-1.58 dBi	(Numeric gain: 0.70)
	Dipole Antenna	Gain :	2.50 dBi	(Numeric gain: 1.78)
				Worst
Maximum tune up power	904-923.6MHz16.50 dBm(44.67 mW)			

Notes:

1. For more details, please refer to the User's manual of the EUT.
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.
3. Disclaimer: The variant model numbers are assessed as identical in hardware and software to each other, hence all variants are fully covered by the test results in this test report without further verification test.
4. The tune up power referred the AVG power of the test report TMWK2602000904KR for RF Exposure assessment purpose.



Project No: TM-2602000330P
Report No.: TMWK2606002677KS

Page 9 / 15
Rev. 00

4 Measurement Uncertainty

904-923.6 MHz

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	±2.37dB
Channel Bandwidth	±2.85dB
Power Spectral density	±2.74dB
Conducted Bandedge	±2.74dB
Conducted Spurious Emission	±2.74dB
Radiated Emission_9kHz-30MHz	± 2.750 dB
Radiated Emission_30MHz-200MHz	± 3.874 dB
Radiated Emission_200MHz-1GHz	± 4.065 dB
Radiated Emission_1GHz-6GHz	± 5.594 dB
Radiated Emission_6GHz-18GHz	± 5.556 dB



Project No: TM-2602000330P
Report No.: TMWK2606002677KS

Page 10 / 15
Rev. 00

5 Maximum Permissible Exposure

5.1 Limits for Maximum Permissible Exposure (MPE)

Table 1 - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	* 100	6
3.0-30	1842/f	4.89/f	* 900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* 100	30
1.34-30	824/f	2.19/f	* 180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
<u>1,500-100,000</u>			1.0	30

5.2 MPE Calculation Method

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \text{ Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

If, Substituting the MPE safe distance using d = 20 cm into Equation 1:

$$S = 0.000199 \times P \times G$$

5.3 MPE EXEMPTION

- (A) The available maximum time-averaged power is no more than 1 mW
- (B) The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

- (C) Using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.
Note: R is in meters, f is in MHz.	

5.4 Multiple RF sources

In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation),

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$



Project No: TM-2602000330P
Report No.: TMWK2606002677KS

Page 14 / 15
Rev. 00

6 MPE Exemption Option B

Frequency (MHz)	R(m)	Max Tune-up power (dBm)	G(dBi)	Max Tune-up EIRP (dBm)	Max Tune-up ERP (dBm)	Max Tune-up ERP (mW)	ERP Threshold (mW)	MPE Exemption
904	0.2	16.5	2.50	19.00	16.85	48.417	1844	Complies



Project No: TM-2602000330P
Report No.: TMWK2606002677KS

Page 15 / 15
Rev. 00

7 Facilities

All measurement facilities used to collect the measurement data are located at

☒ No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan.

END OF REPORT