

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

FCC ID: ELVATRPG
IC: 3671B-43605680

Page: 1 / 61
Rev.: 02

RADIO TEST REPORT

FCC 47 CFR PART 15 SUBPART C INDUSTRY CANADA RSS-247 (CLASS II PERMISSIVE CHANGE)

Test Standard	FCC Part 15.247 IC RSS-247 issue 4 and IC RSS-GEN issue 5
Product name	In Vehicle Unit
Brand Name	NA
Model No.	4361216 、 4361218
Test Result	Pass
Statements of Conformity	Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10-2020 (FCC), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024 (IC) and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.

The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc. (Wugu Laboratory)

Approved by:

Sehni, Hu

Sehni Hu
Supervisor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	May 28, 2026	Initial Issue	ALL	Peggy Tsai
01	July 6, 2026	See the following Note Rev.(01)	P. 32	Peggy Tsai
02	July 14, 2026	See the following Note Rev.(02)	P. 4	Peggy Tsai

Rev. (01)

1. Modify test result in section 4.7.4.

Rev. (02)

1. Modify model discrepancy in section 1.1.

Table of contents

1.	GENERAL INFORMATION	4
1.1	EUT INFORMATION	4
1.2	EUT CHANNEL INFORMATION	5
1.3	ANTENNA INFORMATION	6
1.4	MEASUREMENT UNCERTAINTY.....	7
1.5	FACILITIES AND TEST LOCATION	7
1.6	INSTRUMENT CALIBRATION	8
1.7	SUPPORT AND EUT ACCESSORIES EQUIPMENT	9
1.8	TEST SET UP DIAGRAM.....	9
1.9	TEST PROGRAM	10
1.10	TEST METHODOLOGY AND APPLIED STANDARDS	10
2.	TEST SUMMARY	11
3.	DESCRIPTION OF TEST MODES.....	12
3.1	THE WORST MODE OF OPERATING CONDITION	12
3.2	THE WORST MODE OF MEASUREMENT	13
3.3	EUT DUTY CYCLE.....	15
4.	TEST RESULT	16
4.1	AC POWER LINE CONDUCTED EMISSION	16
4.2	20DB BANDWIDTH AND OCCUPIED BANDWIDTH (99%)	17
4.3	OUTPUT POWER MEASUREMENT	21
4.4	FREQUENCY SEPARATION	23
4.5	NUMBER OF HOPPING.....	26
4.6	CONDUCTED BANDEDGE AND SPURIOUS EMISSION.....	28
4.7	TIME OF OCCUPANCY (DWELL TIME)	31
4.8	RADIATION BANDEDGE AND SPURIOUS EMISSION	33
APPENDIX 1 - PHOTOGRAPHS OF EUT		

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	NUTEK CORPORATION No.167, Lane 235, Bauchiau Rd., Xindian District, New Taipei City, 23145, Taiwan
Manufacturer	NUTEK CORPORATION No.167, Lane 235, Bauchiau Rd., Xindian District, New Taipei City, 23145, Taiwan
Equipment	In Vehicle Unit
Model Name / HVIN	4361216 、 4361218
Model Discrepancy	The product models listed below are identical in design, circuitry, PCB layout, RF module, and electrical components, the only difference between the models is the enclosure design. Model List: 4361216: enclosure with mounting ears 4361218: enclosure without mounting ears
Trade name	NA
Received Date	March 8, 2026
Date of Test	May 4 ~ 13, 2026
Power Operation	Power by Power Supply (DC 12V)
PMN	4361216 、 4361218
EUT Serial #	001
HW Version	AR01C
SW Version	NSP44
Class II Permissive Change	1. Add model name / HVIN: 4361216 、 4361218. 2. The RF chip IC is changed from Si1080-A-GM to S1061-A-GM, with the same brand, model series, and specifications as the original.

Remark:

- For more details, please refer to the User's manual of the EUT.
- Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.
- Disclaimer: The variant model numbers are assessed as identical in hardware and software to each other, hence all variants are fully covered by the test results in this test report without further verification test.

1.2 EUT CHANNEL INFORMATION

Frequency Range	904 MHz – 923.6 MHz									
Modulation Type	GFSK									
Number of channels	50 Channels									
Channel List	CH	Freq. (MHz)	CH	Freq. (MHz)	CH	Freq. (MHz)	CH	Freq. (MHz)	CH	Freq. (MHz)
	1	904	11	908	21	912	31	916	41	920
	2	904.4	12	908.4	22	912.4	32	916.4	42	920.4
	3	904.8	13	908.8	23	912.8	33	916.8	43	920.8
	4	905.2	14	909.2	24	913.2	34	917.2	44	921.2
	5	905.6	15	909.6	25	913.6	35	917.6	45	921.6
	6	906	16	910	26	914	36	918	46	922
	7	906.4	17	910.4	27	914.4	37	918.4	47	922.4
	8	906.8	18	910.8	28	914.8	38	918.8	48	922.8
	9	907.2	19	911.2	29	915.2	39	919.2	49	923.2
	10	907.6	20	911.6	30	915.6	40	919.6	50	923.6

Remark:

Refer as ANSI C63.10-2020 (FCC), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024 (IC) and RSS-GEN for test channels.

Number of frequencies to be tested		
Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
☐ 1 MHz or less	1	Middle
☐ 1 MHz to 10 MHz	2	1 near top and 1 near bottom
☒ More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

1.3 ANTENNA INFORMATION

External antenna:

Antenna Type	☐ CHIP ☐ PCB ☒ Dipole ☐ Integral Antenna
Antenna Model	HWE00271
Antenna Gain	Gain: 2.5 dBi

Internal antenna:

Antenna Type	☐ CHIP ☒ PCB Trace ☐ Dipole ☐ Integral Antenna
Antenna Model	AR01
Antenna Gain	Gain: -2.28 dBi

Notes:

1. The antenna(s) of the EUT are permanently attached and there are no provisions for connection to an external antenna. So the EUT complies with the requirements of §15.203 and RSS-GEN 6.8.

1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	±2.37dB
Channel Bandwidth	±2.85dB
Power Spectral density	±2.74dB
Conducted Bandedge	±2.74dB
Conducted Spurious Emission	±2.74dB
Radiated Emission_9kHz-30MHz	± 2.750 dB
Radiated Emission_30MHz-200MHz	± 3.874 dB
Radiated Emission_200MHz-1GHz	± 4.065 dB
Radiated Emission_1GHz-6GHz	± 5.594 dB
Radiated Emission_6GHz-18GHz	± 5.556 dB

Remark:

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

☒ No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan.

CAB identifier: TW1309

Test site	Test Engineer	Remark
AC Conduction Room	-	Not applicable, because EUT doesn't connect to AC Main Source direct.
Radiation	Ben Yang 、 Tony Chao	-
RF Conducted	Jerry Chang	-

Remark: The lab has been recognized as the FCC accredited lab. under the KDB 974614 D01 and is listed in the FCC public Access Link (PAL) database, FCC Registration No. :444940, the FCC Designation No.:TW1309

1.6 INSTRUMENT CALIBRATION

Conducted_FCC/IC/NCC (All)					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Loop Probe	LANGER EMV-TECHNIK	RF-R 50-1	02-2644	2025-12-10	2026-12-09
PXA Signal Analyzer	Keysight	N9030B	MY62291089	2025-09-24	2026-09-23
Power Sensor	Anritsu	MA2411B	1911387	2025-08-21	2026-08-20
Power Sensor	Anritsu	MA2411B	1911386	2025-07-07	2026-07-06
Power Meter	Anritsu	ML2496A	2136002	2025-07-07	2026-07-06
DC Blocks	Marvelous Microwave	MVE6411	MVE-001	2025-08-06	2026-08-05
Attenuator	Marvelous Microwave Inc	MVE2213-10	08	2025-11-06	2026-11-05
DC Power Source	GWINSTEK	GPC-3030D	8070184	2025-09-15	2026-09-14
Software	Radio Test Software Ver. 21				

966A_Radiated					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Signal Analyzer	Agilent	N9010A	MY52220817	2026-03-13	2027-03-12
Active Loop Antenna	COM-POWER	AL-130	121051	2026-02-04	2027-02-03
Thermo-Hygro Meter	HTC	HTC-1	HTC-D06	2025-05-26	2026-05-25
Bi-Log Antenna	Sunol Sciences	JB3	A030105&532	2025-06-26	2026-06-25
Preamplifier	EMEC	EM330	060609	2026-02-13	2027-02-12
Cable	Huber+Suhner	104PEA	20995+21000+182330	2025-08-06	2026-08-05
Horn Antenna	ETC	MCTD 1209	DRH13M02003	2025-12-19	2026-12-18
Preamplifier	HP	8449B	3008A00965	2025-12-17	2026-12-16
Cable	EMCI	EMC101G	1508S0193+230205+250412	2026-01-14	2027-01-13
High Pass Filters	Titan Microwave	T04N90292850S01	24090402-3	2025-10-28	2026-10-27
High Pass Filters	Titan Microwave	HPF-1200-18000	10231034	2026-01-14	2027-01-13
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Software	e3 V9-210616c				

Remark:

- Each piece of equipment is scheduled for calibration once a year.
- N.C.R. = No Calibration Required.


1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT

EUT Accessories Equipment					
No.	Equipment	Brand	Model	Series No.	FCC ID
	N/A				

Support Equipment (Conducted)					
No.	Equipment	Brand	Model	Series No.	FCC ID
1	AC Power Cable	N/A	N/A	N/A	N/A

Support Equipment (Radiated)					
No.	Equipment	Brand	Model	Series No.	FCC ID
1	DC CABLE	MISUMI	MCR3S-RE	N/A	N/A
A	2 Pin -Power Cable	N/A	N/A	N/A	N/A
B	Antenna	N/A	N/A	N/A	N/A

1.8 TEST SET UP DIAGRAM



1.9 TEST PROGRAM

The EUT connection corresponds to the surrounding fixture control board.
This EUT uses switches to set the frequency, modulation, and power to allow the sample to continuously transmit.

1.10 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10-2020, FCC Part 2, FCC Part 15.247, KDB 558074 D01, ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024, RSS-247 Issue 4 and RSS-GEN Issue 5.

2. TEST SUMMARY

FCC Standard Section	IC Standard Section	Report Section	Test Item	Result
15.203	RSS-GEN 6.8	1.3	Antenna Requirement	Pass
15.207(a)	RSS-GEN 8.8	4.1	AC Conducted Emission	N/A
15.247(a)(1)	RSS-247(6.2.1) RSS-247(6.2.2.1)	4.2	20 dB Bandwidth	Pass
-	RSS-GEN 6.7	4.2	Occupied Bandwidth (99%)	Pass
15.247(b)(2)	RSS-247(6.2.2.2)	4.3	Output Power Measurement	Pass
15.247(a)(1)	RSS-247(6.2.1)	4.4	Frequency Separation	Pass
15.247(b)(2)	RSS-247(6.2.2.1)	4.5	Number of Hopping	Pass
15.247(d)	RSS-247(6.6)	4.6	Conducted Band Edge	Pass
15.247(d)	RSS-247(6.6)	4.6	Conducted Spurious Emission	Pass
15.247(a)(1)	RSS-247(6.2.2.1)	4.7	Time of Occupancy	Pass
15.247(d), 15.205(a), 15.209(a)	RSS-GEN 8.9, 8.10 RSS-247(6.6)	4.8	Radiation Band Edge	Pass
15.247(d), 15.205(a), 15.209(a)	RSS-GEN 8.9, 8.10 RSS-247(6.6)	4.8	Radiation Spurious Emission	Pass

3. DESCRIPTION OF TEST MODES

3.1 THE WORST MODE OF OPERATING CONDITION

Operation mode	GFSK
Test Channel Frequencies	1.Lowest Channel: 904 MHz 2.Middle Channel: 914 MHz 3.Highest Channel: 923.6 MHz

3.2 THE WORST MODE OF MEASUREMENT

External antenna:

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by Power Supply(4361216)
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4
Worst Position	☐ Placed in fixed position. ☐ Placed in fixed position at X-Plane (E2-Plane) ☐ Placed in fixed position at Y-Plane (E1-Plane) ☒ Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by Power Supply(4361216) Mode 2: EUT power by Power Supply(4361218)
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(Z-Plane) were recorded in this report
3. Variations between models are evaluated by laboratories and the test results reported here apply to the worst model: 4361216.

Internal antenna:

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by Power Supply(4361216)
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4
Worst Position	☐ Placed in fixed position. ☒ Placed in fixed position at X-Plane (E2-Plane) ☐ Placed in fixed position at Y-Plane (E1-Plane) ☐ Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by Power Supply(4361216) Mode 2: EUT power by Power Supply(4361218)
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(X-Plane) were recorded in this report.
3. Variations between models are evaluated by laboratories and the test results reported here apply to the worst model: 4361216.

3.3 EUT DUTY CYCLE


Temperature: 23.1 ~ 26.3°C

Test date: May 4 ~ 13, 2026

Humidity: 56 ~ 60% RH

Tested by: Jerry Chang

Mode	Duty Cycle (%) = Ton / (Ton+Toff)	Duty Factor (dB) =10*log (1/Duty Cycle)	1/T (kHz)	VBW setting (kHz)
GFSK	100.00	0.00	0.00	0.01



4. TEST RESULT

4.1 AC POWER LINE CONDUCTED EMISSION

4.1.1 Test Limit

According to §15.207(a) and RSS-GEN section 8.8,

Frequency Range (MHz)	Limits(dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50


* Decreases with the logarithm of the frequency.

4.1.2 Test Procedure

Test method Refer as ANSI C63.10-2020 (FCC), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024 (IC),

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

4.1.3 Test Setup



4.1.4 Test Result

Not applicable, because EUT not connect to AC Main Source direct.

4.2 20dB BANDWIDTH AND OCCUPIED BANDWIDTH (99%)

4.2.1 Test Limit

According to §15.247(a) (1), RSS-247(6.2.1)(a) , RSS 247(6.2.2.1) and RSS-GEN 6.7,

20 dB Bandwidth : For reporting purposes only.

Occupied Bandwidth(99%) : For reporting purposes only.

4.2.2 Test Procedure

Test method Refer as ANSI C63.10-2020 (FCC), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024 (IC),

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 3kHz, VBW = 10kHz and Detector = Peak, to measurement 20 dB Bandwidth and 99% Bandwidth.
4. Measure and record the result of 20 dB Bandwidth and 99% Bandwidth. in the test report.

4.2.3 Test Setup

Refer to section 1.8.

4.2.4 Test Result

Temperature: 23.1 ~ 26.3°C **Test date:** May 4 ~ 13, 2026
Humidity: 56 ~ 60% RH **Tested by:** Jerry Chang

20dB BANDWIDTH


CH	20 dB BW (kHz)
1	86.09
26	86.55
50	86.12

BANDWIDTH 99%


CH	99% BW (kHz)
1	84.499
26	84.766
50	84.515

Test Data


20dB BANDWIDTH



904MHz




914MHz




923.6MHz


BANDWIDTH 99%



904MHz



914MHz



923.6MHz

4.3 OUTPUT POWER MEASUREMENT

4.3.1 Test Limit

According to §15.247(b)(2),

For frequency hopping systems operating in the 902-928 MHz band: 1 watt.

According to RSS-247 section 6.2.2.2,

The hopset uses 50 or more hopping channels, the maximum peak conducted output power shall not exceed 1.0 W, and the e.i.r.p. shall not exceed 4 W.

Limit	☒ Antenna not exceed 6 dBi : 30dBm ☐ Antenna with DG greater than 6 dBi [Limit = 30 – (DG – 6)] ☐ Point-to-point operation
-------	---

4.3.2 Test Procedure

1. The EUT RF output connected to the power meter by RF cable.
2. Setting maximum power transmit of EUT.
3. The path loss was compensated to the results for each measurement.
4. Measure and record the result of Peak output power and Average output power. in the test report.

4.3.3 Test Setup

Refer to section 1.8.

4.3.4 Test Result

Temperature: 23.1 ~ 26.3°C
Humidity: 56 ~ 60% RH

Test date: May 4 ~ 13, 2026
Tested by: Jerry Chang

Peak & Average output power :

GFSK mode (Peak):

Freq. (MHz)	Power Setting	Peak Output Power (dBm)	Output Power (mW)	Limit (mW)
904.000	default	16.24	42.073	1000
914.000	default	15.97	39.537	1000
923.600	default	15.39	34.594	1000

GFSK mode (Average):

Freq. (MHz)	Power Setting	Avg. Output Power (dBm)	Output Power (mW)	Limit (mW)
904.000	default	16.16	41.305	1000
914.000	default	15.95	39.355	1000
923.600	default	15.33	34.119	1000

*Note: Avg. output power has been calculated with duty factor.

EIRP Power:

GFSK mode EIRP

Frequency (MHz)	Power Setting	Avg. Output Power (dBm)	Antenna Gain (dBi)	EIRP (mW)	Limit (mW)
904.000	default	16.16	2.50	73.451	4000
914.000	default	15.95	2.50	69.984	4000
923.600	default	15.33	2.50	60.674	4000

* Note:

1. EIRP = Average Power + Gain
2. This product supports two antenna types, selecting the maximum gain for evaluation and recording the worst-case scenario in the report.

4.4 FREQUENCY SEPARATION

4.4.1 Test Limit

According to §15.247(a)(1) and RSS-247 (6.2.1),

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Limit	> 20dB bandwidth
-------	------------------

4.4.2 Test Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. EUT RF output port connected to the SA by RF cable.
3. Set the spectrum analyzer as RBW = 10kHz, VBW = 30kHz, Sweep = auto.
Max hold, mark 3 peaks of hopping channel and record the 3 peaks frequency.

4.4.3 Test Setup

Refer to section 1.8.

4.4.4 Test Result

Temperature: 23.1 ~ 26.3°C


Test date: May 4 ~ 13, 2026

Humidity: 56 ~ 60% RH

Tested by: Jerry Chang

Hopping Frequency Separation					
Mode	Main Channel (MHz)	Adjacent Channel (MHz)	Separation (kHz)	Min Separation Limit (kHz)	Pass/Fail
GFSK	904.00	904.40	400	86.09	Pass
	913.60	914.00	400	86.55	Pass
	923.20	923.60	400	86.12	Pass

Test Data



4.5 NUMBER OF HOPPING

4.5.1 Test Limit

According to §15.247(a)(1) and RSS-247 (6.2.2.1),
The system shall use at least 50 hopping channels.

4.5.2 Test Procedure

Test method Refer as ANSI C63.10-2020 (FCC), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024 (IC),

1. Place the EUT on the table and set it in transmitting mode.
2. EUT RF output port connected to the SA by RF cable.
3. Set spectrum analyzer Start Freq. = 899 MHz, Stop Freq. = 929 MHz, RBW=82KHz, VBW =300kHz.
4. Max hold, view and count how many channel in the band.

4.5.3 Test Setup

Refer to section 1.8.


4.5.4 Test Result

Temperature: 23.1 ~ 26.3°C
Humidity: 56 ~ 60% RH

Test date: May 4 ~ 13, 2026
Tested by: Jerry Chang

Number of Hopping				
Mode	Frequency (MHz)	Hopping Channel Number	Hopping Channel Number Limits	Result
GFSK	904-923.6	50	≥ 50	Pass

Test Data



4.6 CONDUCTED BANDEDGE AND SPURIOUS EMISSION

4.6.1 Test Limit

According to §15.247(d), RSS-247 section 6.6,

Limit	-20 dBc
-------	---------

4.6.2 Test Procedure

1. EUT RF output port connected to the SA by RF cable, and the path loss was compensated to result.
2. SA setting, RBW=100kHz, VBW=300kHz, Detector=Peak, Trace mode = max hold, SWT = Auto.
3. The Band Edge at 902MHz and 928MHz are investigated with both hopping "ON" and "OFF" modes ".

4.6.3 Test Setup

Refer to section 1.8.

4.6.4 Test Result

Temperature: 23.1 ~ 26.3°C


Humidity: 56 ~ 60% RH

Test date: May 4 ~ 13, 2026


Tested by: Jerry Chang

Test Data


Hopping mode




Non-hopping mode




Spurious Emission



904MHz



914MHz



923.6MHz

4.7 TIME OF OCCUPANCY (DWELL TIME)

4.7.1 Test Limit

According to §15.247 (a)(1), RSS-247 section 6.2.2.1,

The average time of occupancy on any channel shall not be greater than 0.4 s within a 20 s period.

4.7.2 Test Procedure

1. EUT RF output port connected to the SA by RF cable.
2. Set center frequency of spectrum analyzer = operating frequency.
3. Set the spectrum analyzer as RBW=100kHz, VBW=300kHz, Sweep = 20 s.

4.7.3 Test Setup

Refer to section 1.8.

4.7.4 Test Result

Temperature: 23.1 ~ 26.3°C
Humidity: 56 ~ 60% RH



Test date: May 4 ~ 13, 2026
Tested by: Jerry Chang

GFSK

Channel	PACKET TYPE	Dwell time of each pulse (ms)	Number of pulses within period	Total dwell time within period (ms)	Limit (ms)
26	GFSK	62.30	6	373.8	400

NOTE: Measurement Period is 20 s

Test Data



4.8 RADIATION BANDEDGE AND SPURIOUS EMISSION

4.8.1 Test Limit

FCC according to §15.247(d), §15.209(a) and §15.205(a),

In any 100 kHz bandwidth outside the authorized frequency band, all harmonic and spurious must be least 20 dB below the highest emission level with the authorized frequency band. Radiation emission which fall in the restricted bands must also follow the FCC section 15.209 as below limit in table.

Below 30 MHz

Frequency	Field Strength (microvolts/m)	Magnetic H-Field (microamperes/m)	Measurement Distance (metres)
9-490 kHz	2,400/F (F in kHz)	2,400/F (F in kHz)	300
490-1,705 kHz	24,000/F (F in kHz)	24,000/F (F in kHz)	30
1.705-30 MHz	30	N/A	30

Above 30 MHz

Frequency (MHz)	Field Strength microvolts/m at 3 metres (watts, e.i.r.p.)	
	Transmitters	Receivers
30-88	100 (3 nW)	100 (3 nW)
88-216	150 (6.8 nW)	150 (6.8 nW)
216-960	200 (12 nW)	200 (12 nW)
Above 960	500 (75 nW)	500 (75 nW)

Remark:

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

IC according to RSS-247 section 6.6, RSS-Gen, Section 8.9 and 8.10.

RSS-Gen Table 3 and Table 5 – General Field Strength Limits for Transmitters and Receivers at Frequencies Above 30 MHz ^(Note)

Frequency (MHz)	Field Strength microvolts/m at 3 metres (watts, e.i.r.p.)	
	Transmitters	Receivers
30-88	100 (3 nW)	100 (3 nW)
88-216	150 (6.8 nW)	150 (6.8 nW)
216-960	200 (12 nW)	200 (12 nW)
Above 960	500 (75 nW)	500 (75 nW)

Note: Measurements for compliance with the limits in table 3 may be performed at distances other than 3 metres, in accordance with Section 6.6.

RSS-Gen Table 6: General Field Strength Limits for Transmitters at Frequencies Below 30 MHz (Transmit)

Frequency	Magnetic field strength (H-Field) (μA/m)	Measurement Distance (m)
9-490 kHz ^{Note}	6.37/F (F in kHz)	300
490-1,705 kHz	63.7/F (F in kHz)	30
1.705-30 MHz	0.08	30

Note: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

4.8.2 Test Procedure

1. The EUT is placed on a turntable, Above 1 GHz is 1.5m and below 1 GHz is 0.8m above ground plane. The EUT Configured un accordance with ANSI C63.10-2020 (FCC), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024 (IC), and the EUT set in a continuous mode.

2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. And EUT is set 3m away from the receiving antenna, which is scanned from 1m to 4m above the ground plane to find out the highest emissions. Measurement are made polarized in both the vertical and the horizontal positions with antenna.

3. Span shall wide enough to full capture the emission measured. The SA from 9kHz to 26.5GHz set to the low, Mid and High channels with the EUT transmit.

4. No emission found between lowest internal used/generated frequency to 30MHz (9KHz~30MHz).

Radiated emission below 30MHz is measured in a 9m*6m*6m semi-ane choic chamber, the measurements correspond to those obtained at an open-field test site. There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

5. The SA setting following :

(1) Below 30MHz :

(1.1) 9KHz-490KHz : RBW=200Hz / VBW=1kHz / Sweep=AUTO

(1.2) 490KHz-30MHz : RBW=10kHz / VBW=30kHz / Sweep=AUTO

(2) 30MHz to 1GHz : RBW = 100kHz, VBW $\geq$ 3*RBW, Sweep = Auto,

Detector = Peak, Trace = Max hold.

(3) Above 1GHz :

(3.1) For Peak measurement : RBW = 1MHz, VBW $\geq$ 3 RBW, Sweep = Auto,

Detector = Peak, Trace = Max hold.

(3.2) For Average measurement : RBW = 1MHz, VBW $\geq$ 3 RBW, Sweep = Auto,

Detector =RMS, Trace = Max hold.

6. Data result


Actual FS=Spectrum Reading Level + Factor

Margin=Actual FS- Limit


Factor = Antenna factor + Cable loss – Amp gain

4.8.3 Test Setup


9kHz ~ 30MHz



30MHz ~ 1GHz




Above 1 GHz



4.8.4 Test Result

Band Edge Test Data-External antenna:

Project No	: TM-2603000074P	Test Date	: 2026-05-06
Operation Band	: 900 MHz	Temp./Humi.	: 25.6/55
Frequency	: 904 MHz	Antenna Pol.	: VERTICAL
Operation Mode	: Bandedge	Engineer	: Tony.Chao
EUT Pol	: H	Test Chamber	: 966A
Setting	: External antenna		




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
901.98	36.02	1.54	37.56	46.00	-8.44	QP
904.02	112.75	1.53	114.28	--	--	Peak
904.02	109.23	1.53	110.76	--	--	Average
929.04	33.41	2.16	35.57	46.00	-10.43	Peak

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 39 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 904 MHz
Operation Mode : Bandedge
EUT Pol : H
Setting : External antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read	Factor	Actual	Limit	Margin	Detector
MHz	Level		FS	@3m		Mode
	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
901.68	39.49	1.54	41.03	46.00	-4.97	Peak
904.02	107.12	1.53	108.65	--	--	Peak
904.02	104.37	1.53	105.90	--	--	Average
928.98	29.47	2.16	31.63	46.00	-14.37	Peak

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 40 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 923.6 MHz
Operation Mode : Bandedge
EUT Pol : H
Setting : External antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : VERTICAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
901.44	31.57	1.54	33.11	46.00	-12.89	Peak
923.61	112.64	1.98	114.62	--	--	Peak
923.61	110.24	1.98	112.22	--	--	Average
928.14	39.61	2.12	41.73	46.00	-4.27	Peak

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 41 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 923.6 MHz
Operation Mode : Bandedge
EUT Pol : H
Setting : External antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A



Freq	Read	Factor	Actual	Limit	Margin	Detector
MHz	Level		FS	@3m		Mode
	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
900.09	29.41	1.55	30.96	46.00	-15.04	Peak
923.61	105.49	1.98	107.47	--	--	Peak
923.61	102.36	1.98	104.34	--	--	Average
928.47	33.86	2.13	35.99	46.00	-10.01	Peak


Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 42 / 61
Rev.: 02

Band Edge Test Data-Internal antenna:

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 904 MHz
Operation Mode : Bandedge
EUT Pol : E2
Setting : Internal antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : VERTICAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
901.98	38.95	1.54	40.49	46.00	-5.51	Peak
903.99	104.41	1.53	105.94	--	--	Peak
903.99	101.28	1.53	102.81	--	--	Average
927.99	29.04	2.12	31.16	46.00	-14.84	Peak

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 43 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 904 MHz
Operation Mode : Bandedge
EUT Pol : E2
Setting : Internal antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
901.89	38.67	1.54	40.21	46.00	-5.79	QP
904.02	112.93	1.53	114.46	--	--	Peak
904.02	109.19	1.53	110.72	--	--	Average
928.05	33.95	2.12	36.07	46.00	-9.93	Peak

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 44 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 923.6 MHz
Operation Mode : Bandedge
EUT Pol : E2
Setting : Internal antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : VERTICAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
900.45	28.94	1.55	30.49	46.00	-15.51	Peak
923.61	103.49	1.98	105.47	--	--	Peak
923.61	100.50	1.98	102.48	--	--	Average
929.04	32.12	2.16	34.28	46.00	-11.72	Peak

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 45 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 923.6 MHz
Operation Mode : Bandedge
EUT Pol : E2
Setting : Internal antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read		Actual	Limit		Detector
MHz	Level	Factor	FS	@3m	Margin	Mode
	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
901.35	34.23	1.54	35.77	46.00	-10.23	Peak
923.58	112.85	1.98	114.83	--	--	Peak
923.58	109.34	1.98	111.32	--	--	Average
928.50	41.44	2.13	43.57	46.00	-2.43	Peak

TX Test Data-External antenna:

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 923.6 MHz
Operation Mode : TX
EUT Pol : H
Setting : External antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : VERTICAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
31.60	28.70	-3.73	24.97	40.00	-15.03	Peak
104.90	32.64	-11.72	20.92	43.50	-22.58	Peak
228.10	31.52	-12.02	19.50	46.00	-26.50	Peak
555.90	30.84	-3.43	27.41	46.00	-18.59	Peak
863.60	38.63	1.21	39.84	46.00	-6.16	Peak
983.60	37.74	2.82	40.56	54.00	-13.44	Peak

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 47 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 923.6 MHz
Operation Mode : TX
EUT Pol : H
Setting : External antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
30.00	28.40	-2.73	25.67	29.54	-3.87	Peak
104.90	33.15	-11.72	21.43	43.50	-22.07	Peak
230.00	36.81	-11.91	24.90	46.00	-21.10	Peak
467.50	31.13	-4.70	26.43	46.00	-19.57	Peak
516.60	32.05	-4.21	27.84	46.00	-18.16	Peak
674.70	30.43	-1.42	29.01	46.00	-16.99	Peak

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 48 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 904 MHz
Operation Mode : TX
EUT Pol : E2
Setting : External antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : VERTICAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
5424.00	58.29	4.13	62.42	74.00	-11.58	Peak
5424.00	34.63	4.13	38.76	54.00	-15.24	Average

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 49 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 904 MHz
Operation Mode : TX
EUT Pol : E2
Setting : External antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : HORIZONTAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
5424.00	56.22	4.13	60.35	74.00	-13.65	Peak
5424.00	34.41	4.13	38.54	54.00	-15.46	Average

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 50 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 914 MHz
Operation Mode : TX
EUT Pol : E2
Setting : External antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : VERTICAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
5484.00	60.01	4.27	64.28	74.00	-9.72	Peak
5484.00	34.28	4.27	38.55	54.00	-15.45	Average

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 51 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 914 MHz
Operation Mode : TX
EUT Pol : E2
Setting : External antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : HORIZONTAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
5484.00	58.08	4.27	62.35	74.00	-11.65	Peak
5484.00	34.54	4.27	38.81	54.00	-15.19	Average

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 52 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 923.6 MHz
Operation Mode : TX
EUT Pol : E2
Setting : External antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : VERTICAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4618.00	52.06	2.83	54.89	74.00	-19.11	Peak
4618.00	35.23	2.83	38.06	54.00	-15.94	Average
5541.60	59.92	4.56	64.48	74.00	-9.52	Peak
5541.60	34.31	4.56	38.87	54.00	-15.13	Average

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 53 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 923.6 MHz
Operation Mode : TX
EUT Pol : E2
Setting : External antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : HORIZONTAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4618.00	52.08	2.83	54.91	74.00	-19.09	Peak
4618.00	35.59	2.83	38.42	54.00	-15.58	Average
5541.60	57.64	4.56	62.20	74.00	-11.80	Peak
5541.60	34.19	4.56	38.75	54.00	-15.25	Average

TX Test Data-Internal antenna:

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 914 MHz
Operation Mode : TX
EUT Pol : E2
Setting : Internal antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : VERTICAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
32.30	29.29	-4.19	25.10	40.00	-14.90	Peak
166.50	32.11	-11.35	20.76	43.50	-22.74	Peak
298.10	29.74	-9.26	20.48	46.00	-25.52	Peak
463.40	30.71	-4.84	25.87	46.00	-20.13	Peak
630.00	30.37	-1.84	28.53	46.00	-17.47	Peak
762.00	29.67	-0.10	29.57	46.00	-16.43	Peak

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 55 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 914 MHz
Operation Mode : TX
EUT Pol : E2
Setting : Internal antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : HORIZONTAL
Engineer : Tony.Chao
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
31.10	28.26	-3.48	24.78	40.00	-15.22	Peak
104.90	34.23	-11.72	22.51	43.50	-20.99	Peak
534.70	31.54	-3.84	27.70	46.00	-18.30	Peak
683.50	34.66	-1.32	33.34	46.00	-12.66	Peak
863.60	42.28	1.21	43.49	46.00	-2.51	Peak
983.60	38.26	2.82	41.08	54.00	-12.92	Peak

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 56 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 904 MHz
Operation Mode : TX
EUT Pol : E2
Setting : Internal antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : VERTICAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
1808.00	61.18	-6.21	54.97	74.00	-19.03	Peak
1808.00	38.32	-6.21	32.11	54.00	-21.89	Average
5424.00	60.35	4.13	64.48	74.00	-9.52	Peak
5424.00	34.66	4.13	38.79	54.00	-15.21	Average

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 57 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 904 MHz
Operation Mode : TX
EUT Pol : E2
Setting : Internal antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : HORIZONTAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
1808.00	63.57	-6.21	57.36	74.00	-16.64	Peak
1808.00	38.59	-6.21	32.38	54.00	-21.62	Average
5424.00	58.36	4.13	62.49	74.00	-11.51	Peak
5424.00	34.41	4.13	38.54	54.00	-15.46	Average

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 58 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 914 MHz
Operation Mode : TX
EUT Pol : E2
Setting : Internal antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : VERTICAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
1828.00	60.78	-6.08	54.70	74.00	-19.30	Peak
1828.00	37.50	-6.08	31.42	54.00	-22.58	Average
5484.00	60.23	4.27	64.50	74.00	-9.50	Peak
5484.00	34.26	4.27	38.53	54.00	-15.47	Average

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 59 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 914 MHz
Operation Mode : TX
EUT Pol : E2
Setting : Internal antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : HORIZONTAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
1828.00	62.63	-6.08	56.55	74.00	-17.45	Peak
1828.00	37.87	-6.08	31.79	54.00	-22.21	Average
5484.00	57.50	4.27	61.77	74.00	-12.23	Peak
5484.00	34.29	4.27	38.56	54.00	-15.44	Average

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 60 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 923.6 MHz
Operation Mode : TX
EUT Pol : E2
Setting : Internal antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : VERTICAL
Engineer : Ben.Yang
Test Chamber : 966A




Freq	Read Level	Factor	Actual FS	Limit @3m	Margin	Detector Mode
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4618.00	55.66	2.83	58.49	74.00	-15.51	Peak
4618.00	36.54	2.83	39.37	54.00	-14.63	Average
5541.60	58.91	4.56	63.47	74.00	-10.53	Peak
5541.60	34.41	4.56	38.97	54.00	-15.03	Average

Project No: TM-2603000074P
Report No.: TMWK2603000998KR

Page: 61 / 61
Rev.: 02

Project No : TM-2603000074P
Operation Band : 900 MHz
Frequency : 923.6 MHz
Operation Mode : TX
EUT Pol : E2
Setting : Internal antenna

Test Date : 2026-05-06
Temp./Humi. : 25.6/55
Antenna Pol. : HORIZONTAL
Engineer : Ben.Yang
Test Chamber : 966A



Freq	Read	Factor	Actual	Limit	Margin	Detector
MHz	Level		FS	@3m		Mode
	dBuV	dB	dBuV/m	dBuV/m	dB	PK/QP/AV
4618.00	53.70	2.83	56.53	74.00	-17.47	Peak
4618.00	36.36	2.83	39.19	54.00	-14.81	Average
5541.60	54.31	4.56	58.87	74.00	-15.13	Peak
5541.60	34.49	4.56	39.05	54.00	-14.95	Average

--End of Test Report--