

FCC TEST REPORT

REPORT NO.: RF930506A05

MODEL NO.: MOBT90UO, MOBT92UO, MOBT32UO

RECEIVED: May 6, 2004

TESTED: May 26, 2004

APPLICANT: PRIMAX ELECTRONICS LTD.

ADDRESS: No. 669, Ruey Kuang Road, Neihu, Taipei,
Taiwan. R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: 47 14th Lin, Chiapau Tsun, Linko, Taipei,
Taiwan, R.O.C.

This test report consists of 56 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA or any government agencies. The test results in the report only apply to the tested sample.



0528
ILAC MRA

TABLE OF CONTENTS

1	CERTIFICATION	4
2	SUMMARY OF TEST RESULTS	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	7
3.4	DESCRIPTION OF SUPPORT UNITS	8
3.5	CONFIGURATION OF SYSTEM UNDER TEST	8
4	TEST PROCEDURES AND RESULTS	9
4.1	CONDUCTED EMISSION MEASUREMENT	9
4.2	NUMBER OF HOPPING FREQUENCY USED	9
4.2.1	LIMIT OF HOPPING FREQUENCY USED	9
4.2.2	TEST INSTRUMENTS	9
4.2.3	TEST PROCEDURES	10
4.2.4	DEVIATION FROM TEST STANDARD	10
4.2.5	TEST SETUP	11
4.2.6	TEST RESULTS	11
4.3	DWELL TIME ON EACH CHANNEL	14
4.3.1	LIMIT OF DWELL TIME USED	14
4.3.2	TEST INSTRUMENTS	14
4.3.3	TEST PROCEDURES	15
4.3.4	DEVIATION FROM TEST STANDARD	15
4.3.5	TEST SETUP	15
4.3.6	TEST RESULTS	16
4.4	CHANNEL BANDWIDTH	21
4.4.1	LIMITS OF CHANNEL BANDWIDTH	21
4.4.2	TEST INSTRUMENTS	21
4.4.3	TEST PROCEDURE	22
4.4.4	DEVIATION FROM TEST STANDARD	22
4.4.5	TEST SETUP	22
4.4.6	EUT OPERATING CONDITION	22
4.4.7	TEST RESULTS	23
4.5	HOPPING CHANNEL SEPARATION	27
4.5.1	LIMIT OF HOPPING CHANNEL SEPARATION	27
4.5.2	TEST INSTRUMENTS	27

4.5.3	TEST PROCEDURES	28
4.5.4	DEVIATION FROM TEST STANDARD	28
4.5.5	TEST SETUP	28
4.5.6	TEST RESULTS	29
4.6	MAXIMUM PEAK OUTPUT POWER –USING POWER METTER.....	33
4.6.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	33
4.6.2	INSTRUMENTS.....	33
4.6.3	TEST PROCEDURES	34
4.6.4	DEVIATION FROM TEST STANDARD	34
4.6.5	TEST SETUP	35
4.6.6	EUT OPERATING CONDITION	35
4.6.7	TEST RESULTS	36
4.7	RADIATED EMISSION MEASUREMENT	40
4.7.1	LIMITS OF RADIATED EMISSION MEASUREMENT	40
4.7.2	TEST INSTRUMENTS.....	41
4.7.3	TEST PROCEDURES	42
4.7.4	DEVIATION FROM TEST STANDARD	42
4.7.5	TEST SETUP	43
4.7.6	TEST RESULTS	44
4.8	BAND EDGES MEASUREMENT	48
4.8.1	LIMITS OF BAND EDGES MEASUREMENT	48
4.8.2	TEST INSTRUMENTS.....	48
4.8.3	TEST PROCEDURE.....	48
4.8.4	DEVIATION FROM TEST STANDARD	48
4.8.5	EUT OPERATING CONDITION	49
4.8.6	TEST RESULTS	49
4.9	ANTENNA REQUIREMENT	54
4.9.1	STANDARD APPLICABLE	54
4.9.2	ANTENNA CONNECTED CONSTRUCTION	54
5	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	55
6	INFORMATION ON THE TESTING LABORATORIES	56

1 CERTIFICATION

PRODUCT : Bluetooth Mouse
BRAND NAME : Targus, Toshiba, Sony, HP, IBM, Belkin,
Kensington, Mirco Innovation
MODEL NO. : MOBT90UO, MOBT92UO, MOBT32UO
APPLICANT : PRIMAX ELECTRONICS LTD.
TESTED: May 26, 2004
TEST ITEM : ENGINEERING SAMPLE
STANDARDS : FCC 47 CFR Part 15, Subpart C (Section 15.247),
ANSI C63.4-2001

The above equipment (model no.: MOBT90UO) has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY: Annie Chang , **DATE:** June 16, 2004
(Annie Chang)

APPROVED BY: Mike Su. , **DATE:** June 16, 2004
(Mike Su, Manager)

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC 47 CFR Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	NA	DC power not applicable
15.247(a)(1)(I)-(ii)	Number of Hopping Frequency Used Spec.: At least 15 channels	PASS	Meet the requirement of limit
15.247(a)(1)(ii)	Dwell Time on Each Channel Spec. : Max. 0.4 second within 31.2 second	PASS	Meet the requirement of limit
15.247(a)(1)(I)-(ii)	Hopping Channel Separation Spec. : Min. 25 kHz or 20 dB bandwidth, whichever is greater.	PASS	Meet the requirement of limit
15.247(a)(2)	Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System Spec.: Max. 1 MHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Spec.: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Spec.: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -1.94 dB at 4804.00MHz
15.247(c)	Band Edge Measurement	PASS	Meet the requirement of limit

Note: The information of measurement uncertainty is available upon the customer's request.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Bluetooth Mouse
MODEL NO.	MOBT90UO, MOBT92UO, MOBT32UO
POWER SUPPLY	3Vdc from battery
MODULATION TYPE	FHSS (GFSK)
FREQUENCY RANGE	2402MHz ~ 2480MHz
NUMBER OF CHANNEL	79
OUTPUT POWER	-1.13dBm
ANTENNA TYPE	Micro String Antenna
ANTENNA GAIN	1dBi
DATA CABLE	NA
I/O PORTS	USB Port
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT is a wireless Mouse, with Bluetooth technology.
2. The EUT has three model names, which are identical to each other in all aspects except for different brand name as the following :

BRAND	MODEL	DESCRIPTION
IBM	MOBT32UO	-
Targus, Toshiba, Sony, HP, Belkin, Kensington, Micro Innovation	MOBT90UO, MOBT92UO	for different outer appearance

During the test, the **MOBT90UO** was chosen as a representative model and therefore only its test data was recorded in this report.

3. For a more detailed features description, please refer to the manufacturer's specifications or User's Manual

3.2 DESCRIPTION OF TEST MODES

Seventy-nine channels are provided to this EUT.

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2431	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

Software used to control the EUT for staying in continuous transmitting and receiving mode is programmed. Channel 0, 39 and 78 are chosen for testing to fulfill the requirement of frequency spectrum usage in each country.

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a Bluetooth Mouse. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:


FCC 47 CFR Part 15, Subpart C. (15.247)
ANSI C63.4 : 2001

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT was tested stand alone.

3.5 CONFIGURATION OF SYSTEM UNDER TEST



4 TEST PROCEDURES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT NA

4.2 NUMBER OF HOPPING FREQUENCY USED

4.2.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 hopping frequencies, and should be equally spaced.

4.2.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SIGNAL GENERATOR / Agilent	E8257C	MY43320668	Dec 31, 2004

NOTE:

The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


4.2.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
4. Set the SA on View mode and then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.2.4 DEVIATION FROM TEST STANDARD


No deviation


4.2.5 TEST SETUP



4.2.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.





4.3 DWELL TIME ON EACH CHANNEL

4.3.1 LIMIT OF DWELL TIME USED

For FHSS, the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 31.6 second period. For hybrid systems, the average time of occupancy on any frequency should not exceed 0.4 seconds within a time period in seconds equal to the number of hopping frequencies employed multiplied by 0.4.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SIGNAL GENERATOR / Agilent	E8257C	MY43320668	Dec 31, 2004

NOTES:

The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
4. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
5. Repeat above procedures until all frequencies measured were complete.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP




4.3.6 TEST RESULTS

Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	47 (times / 5 sec) *6.32=297 times	0.5	148	400
DH3	25 (times / 5 sec) *6.32=158 times	1.733	274	400


Test plots of the transmitting time slot are shown on next four pages

DH1

* Agilent 10:51:57 May 21, 2004




* Agilent 11:05:57 May 21, 2004




DH3

* Agilent 11:54:07 May 21, 2004



* Agilent 11:57:18 May 21, 2004



4.4 CHANNEL BANDWIDTH

4.4.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5 MHz and 5725-5850 MHz bands, the maximum 20 dB bandwidth of the hopping channel is 1 MHz.

4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SIGNAL GENERATOR / Agilent	E8257C	MY43320668	Dec 31, 2004

NOTES:

The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


4.4.3 TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP




4.4.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.


4.4.7 TEST RESULTS

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (kHz)	MAXIMUM LIMIT (MHz)	PASS/FAIL
0	2402	705	1	PASS
39	2441	699	1	PASS
78	2480	699	1	PASS


Channel 0



Channel 39



Channel 78



4.5 HOPPING CHANNEL SEPARATION

4.5.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25KHz or 20dB bandwidth (whichever is greater).

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SIGNAL GENERATOR / Agilent	E8257C	MY43320668	Dec 31, 2004

NOTES:

The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


4.5.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 TEST RESULTS

Channel	Frequency (MHz)	Adjacent Channel Separation	Minimum Limit (kHz)	Pass / Fail
0	2402	1.005 MHz	705	PASS
39	2441	1.000 MHz	699	PASS
78	2480	1.000 MHz	699	PASS

The minimum limit is 20dB bandwidth. Test results please refer to next three pages.

