



Total Solution Provider for Power, EMI and RF

东聚电子-联想鼠标天线测试报告

Prepared by: 韩国军

Data: 2021/08/11

Rev:01

Contents

- **Revised History**
- **Specification**
- **Kunsan Chamber- SATIMO_Starlab**
- **Test Setup for S-parameter Measurement**
- **Antenna Picture**
- **S- Parameter_ Returnloss**
- **Coordinate System**
- **3D Peak Gain & Efficiency List Table**
- **2D Radiation Pattern Results**





Revised History

Date	Version	Revised Record
2021/08/11	01	



Specification

Electrical	
Item	Specification
Test Environment	Free Space
Antenna Type	Chip
Frequency Range	2400-2500MHz
Returnloss	<-10
Polarization	Linear
Gain(Peak Gain)	<-0.62 dBi
Efficiency	>32%
Input Impedance	50 ohm




Kunsan Chamber _SATIMO_Starlab



StarLab

StarLab



Chamber Dimension: 3m*3m*3m

Test Setup for S-parameter Measurement




Keysight E5071C ENA
9 kHz 至 8.5 GHz





Antenna Picture

Ant (BTCA00321608002G4P)



S- Parameter



Coordinate System




3D Peak Gain & Efficiency List Table


Ant		
Frequency(MHz)	Efficiency	Total Gain(dBi)
2400	39%	-0.62
2410	40%	-0.7
2420	39%	-0.83
2430	38%	-0.92
2440	37%	-1.2
2450	36%	-1.51
2460	35%	-1.82
2470	35%	-2.01
2480	34%	-1.7
2490	33%	-1.68
2500	32%	-1.72




3D Peak Gain & Efficiency List Table




2D Gain Pattern Antenna _ZX Cut($\Phi=0$)



2D Gain Pattern Antenna _ZY Cut($\Phi=90^\circ$)



2D Gain Pattern Antenna _XY Cut(Theta=90)





CHILISIN ELECTRONICS CORP.
Total Solution Provider for Power, EMI and RF.



Total Solution Provider for EMI, Power and RF.

Thank you!

