

FCC RF EXPOSURE REPORT

FCC ID: EMOB67

Project No. : 1605C137
Equipment : Bluetooth Speaker
Test Model : Ni-B67RP
Serial Model : Ni-B67LN, Wi-B67GD, Wi-B67PY
Applicant : SDI TECHNOLOGIES INC.
Address : 1299 Main Street, Rahway, NJ 07065, U.S.A

According: : FCC Guidelines for Human Exposure IEEE C95.1

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.
TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

Table for Filed Antenna

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	Printed	N/A	0

GENERAL CONCLUSION:

Maximum measured transmitter power:

OutputPower (dBm)	Output Power (mW)	Limit (mW)
2.18	1.65	10

According to FCC KDB447498 V06, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

The maximum measured output peak power of this EUT is 1.65mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold