EMTEK
Access to the World

ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO FCC PART 15 SUBPART C REQUIREMENT

OF

Bluetooth Wireless Color Changing Dual Alarm FM Clock Radio with USB Charging

Model No.: iBT290, iBT290X (X= A-Z denotes as color of cabinet)

Trademark: iHome

FCC ID: EMOIBT290

Report No.: ED161213028E2

Issue Date: December 16, 2016

Prepared for

SDI Technologies Inc.
1299, Main Street, Rahway, NJ 07065, U.S.A.

Prepared by

EMTEK(DONGGUAN) CO., LTD.

No.281, Guantai Road, Nancheng District,
Dongguan, Guangdong, China
TEL: 86-769-22807078
FAX: 86-769-22807079

This report shall not be reproduced, except in full, without the written approval of EMTEK(DONGGUAN) CO., LTD.

VERIFICATION OF COMPLIANCE

Applicant:	SDI Technologies Inc. 1299, Main Street, Rahway, NJ 07065, U.S.A.
Manufacturer:	SDI Technologies Inc. 1299, Main Street, Rahway, NJ 07065, U.S.A.
Factory:	DongGuan Synst Electronics Co., Ltd. The Science &Technology Industrial Park, Houjie Town, DongGuan, China.
Product Description:	Bluetooth Wireless Color Changing Dual Alarm FM Clock Radio with USB Charging
Trade Mark:	iHome
Model Number:	iBT290, iBT290X (X= A-Z denotes as color of cabinet) (Note: The samples are the same except difference color of appearance and model number. So iBT290 was selected for full test.)

We hereby certify that:

The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2016).

Date of Test : December 13, 2016 to December 16, 2016

Prepared by : _____

Abby Li/Editor

Reviewer : _____

Alan He/Supervisor

Approved & Authorized Signer : _____

Sam Lv/Manager

Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	ED161213028E2

Table of Contents

1. GENERAL INFORMATION 6
1.1 PRODUCT DESCRIPTION 6
1.2 TEST FACILITY 7
2. SYSTEM TEST CONFIGURATION 8
2.1 EUT CONFIGURATION 8
2.2 EUT EXERCISE 8
2.3 TEST PROCEDURE 8
2.4 CONFIGURATION OF TESTED SYSTEM 9
3. SUMMARY OF TEST RESULTS 10
4. DESCRIPTION OF TEST MODES 11
5. TEST SYSTEM UNCERTAINTY 12
6. CONDUCTED EMISSIONS TEST 13
6.1 MEASUREMENT PROCEDURE: 13
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 13
6.3 MEASUREMENT EQUIPMENT USED: 13
6.4 MEASUREMENT RESULT: 13
6.5 CONDUCTED MEASUREMENT PHOTOS: 16
7. RADIATED EMISSION TEST 17
7.1 MEASUREMENT PROCEDURE 17
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 19
7.3 MEASUREMENT EQUIPMENT USED: 20
7.4 RADIATED EMISSION LIMIT 21
7.5 MEASUREMENT RESULT 22
7.5 RADIATED MEASUREMENT PHOTOS: 30
8. CHANNEL SEPARATION TEST 31
8.1 MEASUREMENT PROCEDURE 31
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 31
8.3 MEASUREMENT EQUIPMENT USED: 31
8.4 MEASUREMENT RESULTS: 31
9. 20DB BANDWIDTH TEST 38
9.1 MEASUREMENT PROCEDURE 38
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 38
9.3 MEASUREMENT EQUIPMENT USED: 38
9.4 MEASUREMENT RESULTS: 38
10. QUANTITY OF HOPPING CHANNEL TEST 45

10.1 MEASUREMENT PROCEDURE 45
10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 45
10.3 MEASUREMENT EQUIPMENT USED: 45
10.4 MEASUREMENT RESULTS: 45
11. TIME OF OCCUPANCY (DWELL TIME) TEST 46
11.1 TEST DESCRIPTION 46
11.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 46
11.3 MEASUREMENT EQUIPMENT USED: 46
11.4 TEST REQUIREMENTS / LIMITS 46
11.5 TEST RESULT 47
12. MAXIMUM PEAK OUTPUT POWER TEST 49
12.1 MEASUREMENT PROCEDURE 49
12.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 49
12.3 MEASUREMENT EQUIPMENT USED: 49
12.4 MEASUREMENT RESULTS: 50
13. BAND EDGE TEST 56
13.1 MEASUREMENT PROCEDURE 56
13.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 57
13.3 MEASUREMENT EQUIPMENT USED: 57
13.4 MEASUREMENT RESULTS: 58
14. ANTENNA APPLICATION 60
14.1 ANTENNA REQUIREMENT 60
14.2 RESULT 60
15. PHOTOS OF EUT 60

1.1 Product Description

Characteristics	Description
Product Name	Bluetooth Wireless Color Changing Dual Alarm FM Clock Radio with USB Charging
Model number	iBT290
Power Supply	AC 120V/60Hz for adapter
Adapter	M/N:SW0752000-H04 Input rating: 100-240V~, 50/60Hz, Max. 500mA Output rating:7.5V ⎓ 2000mA
Kind of Device	Bluetooth Ver.3.0
Modulation	GFSK, π/4-DQPSK, 8DPSK
Operating Frequency Range	2402-2480MHz
Number of Channels	79
Transmit Power Max(PK)	2.76dBm(0.001888W)
Antenna Type	Internal PCB antenna
Antenna Gain	0dBi
Product Software Version	9BQ895107.bin
Product Hardware version	REV:03
Radio Software Version	201608240015
Radio Hardware version	BTM8615-V01A

1.2 Test Facility

Site Description

EMC Lab. : Registered on FCC, June 18, 2014
The Certificate Number is 247565.

Registered on Industry Canada, February 19, 2014
The Certificate Number is 9444A

Name of Firm : EMTEK(DONGGUAN) CO., LTD.

Site Location : No.281, Guantai Road, Nancheng District,
Dongguan, Guangdong, China

1. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The Tx frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of EUT was rotated according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

Item	Equipment	Trade Mark	Model No.	FCC ID	Note
1.	Bluetooth Wireless Color Changing Dual Alarm FM Clock Radio with USB Charging	iHome	iBT290	EMOIBT290	***EUT***
2	Adapter	N/A	M/N:SW0752000-H04 Input rating: 100-240V~, 50/60Hz, Max. 500mA Output rating: 7.5V ⎓2000mA	N/A	***Support EUT***

Note:

(1) Unless otherwise denoted as EUT in『Remark』column , device(s) used in tested system is a support equipment.

2. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.207	AC Power Conducted Emission	Compliant
§15.247(d),§15.209	Radiated Emission	Compliant
§15.247(a)(1)	Channel Separation test	Compliant
§15.247(a)(1)	20dB Bandwidth	Compliant
§15.247(a)(1)(iii)	Quantity of Hopping Channel	Compliant
§15.247(a)(1)(iii)	Time of Occupancy(Dwell Time)	Compliant
§15.247(b)	Max Peak output Power test	Compliant
§15.247(d)	Band edge test	Compliant
§15.203	Antenna Requirement	Compliant

3. Description of test modes

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2013 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The 3 channels of lower, medium and higher were chosen for test.

Channel	Frequency(MHz)
1	2402
40	2441
79	2480

4. TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	±1x10^-5
Maximum Peak Output Power Test	±1.0dB
Conducted Emissions Test	±2.0dB
Radiated Emission Test	±2.0dB
Power Density	±2.0dB
Occupied Bandwidth Test	±1.0dB
Band Edge Test	±3dB
All emission, radiated	±3dB
Antenna Port Emission	±3dB
Temperature	±0.5℃
Humidity	±3%

Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%

5. Conducted Emissions Test

6.1 Measurement Procedure:

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Equipment Used:

Conducted Emission Test Site						
EQUIPMENT TYPE	**MFR**	**MODEL NUMBER**	**SERIAL NUMBER**	**Characteristics**	**Last Cal.**	**Due date**
Test Receiver	Rohde & Schwarz	ESCS30	100018	9kHz~3GHz	06/24/2016	06/23/2017
L.I.S.N	Rohde & Schwarz	ENV216	100017	9KHz-300MHz	06/24/2016	06/23/2017
RF Switching Unit	CDS	RSU-M2	38401	9KHz-300MHz	06/24/2016	06/23/2017
Coaxial Cable	CDS	79254	46107086	9kHz~3GHz	06/24/2016	06/23/2017

6.4 Measurement Result:

Pass.

All the modulation modes were tested the data of the worst mode (GFSK TX 2441MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.

Please refer to the following data.



Site site #1 Phase: L1 Temperature: 24
Limit: (CE)FCC PART 15 C_QP Power: AC 120V/60Hz Humidity: 55 %
Mode: DSS(TX2441)
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.5100	34.07	10.10	44.17	56.00	-11.83	QP	
2		0.5100	27.70	10.10	37.80	46.00	-8.20	AVG	
3		1.5340	33.68	10.10	43.78	56.00	-12.22	QP	
4	*	1.5340	28.92	10.10	39.02	46.00	-6.98	AVG	
5		2.5540	33.92	10.10	44.02	56.00	-11.98	QP	
6		2.5540	28.73	10.10	38.83	46.00	-7.17	AVG	
7		3.5620	33.86	10.10	43.96	56.00	-12.04	QP	
8		3.5620	23.07	10.10	33.17	46.00	-12.83	AVG	
9		4.5660	32.61	10.10	42.71	56.00	-13.29	QP	
10		4.5660	22.99	10.10	33.09	46.00	-12.91	AVG	
11		5.6060	33.05	10.10	43.15	60.00	-16.85	QP	
12		5.6060	24.71	10.10	34.81	50.00	-15.19	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Lin



Site site #1 Phase: N Temperature: 24

Limit: (CE)FCC PART 15 C_QP Power: AC 120V/60Hz Humidity: 55 %

Mode: DSS(TX2441)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.5100	38.48	10.10	48.58	56.00	-7.42	QP	
2	*	0.5100	32.67	10.10	42.77	46.00	-3.23	AVG	
3		1.5300	38.09	10.10	48.19	56.00	-7.81	QP	
4		1.5300	29.24	10.10	39.34	46.00	-6.66	AVG	
5		2.5540	37.14	10.10	47.24	56.00	-8.76	QP	
6		2.5540	23.88	10.10	33.98	46.00	-12.02	AVG	
7		3.5620	37.29	10.10	47.39	56.00	-8.61	QP	
8		3.5620	25.65	10.10	35.75	46.00	-10.25	AVG	
9		4.5780	36.01	10.10	46.11	56.00	-9.89	QP	
10		4.5780	24.21	10.10	34.31	46.00	-11.69	AVG	
11		5.5980	36.86	10.10	46.96	60.00	-13.04	QP	
12		5.5980	24.23	10.10	34.33	50.00	-15.67	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Lin

5.5 Conducted Measurement Photos:



6. Radiated Emission Test

7.1 Measurement Procedure

1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10-2013.
2. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a Styrofoam table which is 1.5m above ground plane.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degree) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
7. Test Procedure of measurement (For Above 1GHz):
   1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
   2) Change the antenna polarization and repeat 1) with vertical polarization.
   3) Make a hardcopy of the spectrum.
   4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
   5) Change the analyser mode to Clear/ Write and found the cone of emission.
   6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
   7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
   8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.

Use the following spectrum analyzer settings:

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	120KHz
VB	300KHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	Peak
Trace	Max hold

7.2 Test SET-UP (Block Diagram of Configuration)

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



7.3 Measurement Equipment Used:

Item	Equipment	Manufacturer	Model No.	Serial No.	Characteristics	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI	1166.5950.03	9KHz-3GHz	06/24/2016	1 Year
2.	Loop Antenna	Schwarzbeck	FMZB 1519	012	9 KHz -30MHz	06/24/2016	1 Year
3.	Bilog Antenna	Schwarzbeck	VULB9163	000141	25MHz-2GHz	06/24/2016	1 Year
4.	Power Amplifier	CDS	RSU-M352	818	1MHz-1GHz	06/24/2016	1 Year
5.	Power Amplifier	HP	8447F	OPT H64	1GHz-26.5GHz	06/24/2016	1 Year
6.	Color Monitor	SUNSPO	SP-140A	N/A	--	06/24/2016	1 Year
7.	Single Line Filter	JIANLI	XL-3	N/A	--	06/24/2016	1 Year
8.	Single Phase Power Line Filter	JIANLI	DL-2X100B	N/A	--	06/24/2016	1 Year
9.	3 Phase Power Line Filter	JIANLI	DL-4X100B	N/A	--	06/24/2016	1 Year
10.	DC Power Filter	JIANLI	DL-2X50B	N/A	--	06/24/2016	1 Year
11.	Cable	Schwarzbeck	PLF-100	549489	9KHz-3GHz	06/24/2016	1 Year
12.	Cable	Rosenberger	CIL02	A0783566	9KHz-3GHz	06/24/2016	1 Year
13.	Cable	Rosenberger	RG 233/U	525178	9KHz-3GHz	06/24/2016	1 Year
14.	Signal Analyzer	Rohde & Schwarz	FSV30	103040	9KHz-40GHz	06/24/2016	1 Year
15.	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1272	1GHz-18GHz	06/24/2016	1 Year
16.	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	14GHz -26.5GHz	06/24/2016	1 Year
17.	Power Amplifier	LUNAR EM	LNA1G18-40	J10100000081	1GHz-26.5GHz	06/24/2016	1 Year
18.	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	06/24/2016	1 Year
19.	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	06/24/2016	1 Year
20.	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	06/24/2016	1 Year

7.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1]0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])

Remark : 1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of ξ 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

7.5 Measurement Result

Below 30MHz:

Operation Mode:	TX	Test Date :	December 14, 2016
Frequency Range:	9KHz~30MHz	Temperature :	28℃
Test Result:	PASS	Humidity :	65 %
Measured Distance:	3m	Test By:	Andy

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Below 1000MHz:

Pass.

All the modulation modes were tested the data of the worst mode (GFSK TX 2441MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.

Please refer to the following data.



Site Chamber #1 Polarization: ***Horizontal*** Temperature: 26

Limit: (RE)FCC PART 15 C 3m Power: AC 120V/60Hz Humidity: 55 %

Mode:DSS(TX2441)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		40.6700	30.13	-13.27	16.86	40.00	-23.14	QP			
2		42.6100	30.31	-13.22	17.09	40.00	-22.91	QP			
3		117.3000	38.21	-18.15	20.06	43.50	-23.44	QP			
4	*	119.2400	38.95	-18.04	20.91	43.50	-22.59	QP			
5		143.4900	34.33	-18.37	15.96	43.50	-27.54	QP			
6		152.2200	37.88	-18.79	19.09	43.50	-24.41	QP			

*:Maximum data x:Over limit !:over margin Operator: YE



Site Chamber #1 Polarization: *Vertical* Temperature: 26

Limit: (RE)FCC PART 15 C 3m Power: AC 120V/60Hz Humidity: 55 %

Mode:DSS(TX2441)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	30.0000	49.15	-14.83	34.32	40.00	-5.68	QP			
2		40.7016	38.13	-13.26	24.87	40.00	-15.13	QP			
3		46.5030	39.84	-14.61	25.23	40.00	-14.77	QP			
4		51.3400	39.99	-15.67	24.32	40.00	-15.68	QP			
5		143.4900	43.60	-18.37	25.23	43.50	-18.27	QP			
6		149.3100	43.66	-18.56	25.10	43.50	-18.40	QP			

*:Maximum data x:Over limit !:over margin Operator: YE

Above 1000MHz

Please refer to the following data.

Operation Mode: GFSK (CH1: 2402MHz) Test Date : December 14, 2016

Freq.	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV
4804	V	64.12	44.12	74	54	-9.88	-9.88
7206	V	63.56	42.06	74	54	-10.44	-11.94
9608	V	62.33	41.56	74	54	-11.67	-12.44
12010	V	61.54	40.58	74	54	-12.46	-13.42
14412	V	60.58	40.33	74	54	-13.42	-13.67
16814	V	59.27	39.42	74	54	-14.73	-14.58
4804	H	65.12	45.06	74	54	-8.88	-8.94
7206	H	64.03	44.32	74	54	-9.97	-9.68
9608	H	63.65	43.56	74	54	-10.35	-10.44
12010	H	62.52	42.58	74	54	-11.48	-11.42
14412	H	61.33	41.95	74	54	-12.67	-12.05
16814	H	59.87	40.25	74	54	-14.13	-13.75

Operation Mode: GFSK (CH40: 2441MHz) Test Date : December 14, 2016

Freq.	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV
4882	V	62.12	43.05	74	54	-11.88	-10.95
7323	V	61.05	42.06	74	54	-12.95	-11.94
9764	V	60.33	41.62	74	54	-13.67	-12.38
12205	V	59.54	40.53	74	54	-14.46	-13.47
14646	V	58.63	39.45	74	54	-15.37	-14.55
17087	V	57.66	38.24	74	54	-16.34	-15.76
4882	H	65.12	44.12	74	54	-8.88	-9.88
7323	H	64.38	42.06	74	54	-9.62	-11.94
9764	H	62.42	41.62	74	54	-11.58	-12.38
12205	H	62.05	40.57	74	54	-11.95	-13.43
14646	H	61.42	40.01	74	54	-12.58	-13.99
17087	H	60.85	39.65	74	54	-13.15	-14.35

Operation Mode: GFSK (CH79: 2480MHz) Test Date : December 14, 2016

Freq.	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV
4960	V	64.12	43.15	74	54	-9.88	-10.85
7440	V	63.06	42.06	74	54	-10.94	-11.94
9920	V	62.05	41.33	74	54	-11.95	-12.67
12400	V	61.52	40.25	74	54	-12.48	-13.75
14880	V	60.85	39.65	74	54	-13.15	-14.35
17360	V	59.27	38.27	74	54	-14.73	-15.73
4960	H	63.14	44.12	74	54	-10.86	-9.88
7440	H	62.06	43.62	74	54	-11.94	-10.38
9920	H	61.32	42.58	74	54	-12.68	-11.42
12400	H	60.85	41.58	74	54	-13.15	-12.42
14880	H	59.41	40.95	74	54	-14.59	-13.05
17360	H	58.22	39.88	74	54	-15.78	-14.12

Operation Mode: Pi/4-DQPSK (CH1: 2402MHz) Test Date : December 14, 2016

Freq.	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV
4804	V	65.12	43.62	74	54	-8.88	-10.38
7206	V	64.21	42.15	74	54	-9.79	-11.85
9608	V	63.65	41.85	74	54	-10.35	-12.15
12010	V	63.21	40.52	74	54	-10.79	-13.48
14412	V	62.05	39.27	74	54	-11.95	-14.73
16814	V	61.95	38.62	74	54	-12.05	-15.38
4804	H	64.12	44.12	74	54	-9.88	-9.88
7206	H	63.06	43.06	74	54	-10.94	-10.94
9608	H	62.85	42.65	74	54	-11.15	-11.35
12010	H	61.88	41.52	74	54	-12.12	-12.48
14412	H	60.25	40.58	74	54	-13.75	-13.42
16814	H	59.24	39.56	74	54	-14.76	-14.44

Operation Mode: Pi/4-DQPSK (CH40: 2441MHz) Test Date : December 14, 2016

Freq.	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV
4882	V	64.12	43.06	74	54	-9.88	-10.94
7323	V	62.05	42.05	74	54	-11.95	-11.95
9764	V	61.06	41.33	74	54	-12.94	-12.67
12205	V	60.33	40.57	74	54	-13.67	-13.43
14646	V	59.27	39.12	74	54	-14.73	-14.88
17087	V	58.62	38.06	74	54	-15.38	-15.94
4882	H	62.06	44.16	74	54	-11.94	-9.84
7323	H	61.33	43.62	74	54	-12.67	-10.38
9764	H	60.58	42.95	74	54	-13.42	-11.05
12205	H	59.27	41.32	74	54	-14.73	-12.68
14646	H	58.12	40.51	74	54	-15.88	-13.49
17087	H	57.64	39.52	74	54	-16.36	-14.48

Operation Mode: Pi/4-DQPSK (CH79: 2480MHz) Test Date : December 14, 2016

Freq.	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV
4960	V	64.12	44.12	74	54	-9.88	-9.88
7440	V	63.06	42.06	74	54	-10.94	-11.94
9920	V	62.15	41.65	74	54	-11.85	-12.35
12400	V	60.87	40.95	74	54	-13.13	-13.05
14880	V	59.24	40.36	74	54	-14.76	-13.64
17360	V	58.62	39.27	74	54	-15.38	-14.73
4960	H	65.12	45.16	74	54	-8.88	-8.84
7440	H	64.16	44.32	74	54	-9.84	-9.68
9920	H	63.02	43.65	74	54	-10.98	-10.35
12400	H	61.54	42.05	74	54	-12.46	-11.95
14880	H	60.88	41.85	74	54	-13.12	-12.15
17360	H	60.32	40.87	74	54	-13.68	-13.13

Operation Mode: 8DPSK (CH1: 2402MHz) Test Date : December 14, 2016

Freq.	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV
4804	V	64.12	43.06	74	54	-9.88	-10.94
7206	V	63.06	42.51	74	54	-10.94	-11.49
9608	V	62.85	41.58	74	54	-11.15	-12.42
12010	V	61.33	40.81	74	54	-12.67	-13.19
14412	V	60.25	40.52	74	54	-13.75	-13.48
16814	V	59.12	39.27	74	54	-14.88	-14.73
4804	H	65.12	44.12	74	54	-8.88	-9.88
7206	H	64.12	43.65	74	54	-9.88	-10.35
9608	H	62.05	42.06	74	54	-11.95	-11.94
12010	H	61.52	41.85	74	54	-12.48	-12.15
14412	H	60.95	40.85	74	54	-13.05	-13.15
16814	H	60.22	39.42	74	54	-13.78	-14.58

Operation Mode: 8DPSK (CH40: 2441MHz) Test Date : December 14, 2016

Freq.	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV
4882	V	64.12	42.16	74	54	-9.88	-11.84
7323	V	63.06	41.62	74	54	-10.94	-12.38
9764	V	62.05	40.35	74	54	-11.95	-13.65
12205	V	61.33	39.27	74	54	-12.67	-14.73
14646	V	60.23	38.12	74	54	-13.77	-15.88
17087	V	60.12	36.28	74	54	-13.88	-17.72
4882	H	61.23	43.06	74	54	-12.77	-10.94
7323	H	60.52	42.16	74	54	-13.48	-11.84
9764	H	59.12	41.52	74	54	-14.88	-12.48
12205	H	58.21	40.85	74	54	-15.79	-13.15
14646	H	57.33	39.24	74	54	-16.67	-14.76
17087	H	56.24	38.52	74	54	-17.76	-15.48

Operation Mode: 8DPSK (CH79: 2480MHz) Test Date : December 14, 2016

Freq.	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	PK	AV	PK	AV
4960	V	63.12	45.12	74	54	-10.88	-8.88
7440	V	62.06	42.06	74	54	-11.94	-11.94
9920	V	61.52	41.65	74	54	-12.48	-12.35
12400	V	60.33	40.87	74	54	-13.67	-13.13
14880	V	59.25	39.22	74	54	-14.75	-14.78
17360	V	58.42	38.65	74	54	-15.58	-15.35
4960	H	64.12	43.03	74	54	-9.88	-10.97
7440	H	63.06	42.06	74	54	-10.94	-11.94
9920	H	62.33	41.58	74	54	-11.67	-12.42
12400	H	61.58	40.65	74	54	-12.42	-13.35
14880	H	60.58	40.25	74	54	-13.42	-13.75
17360	H	59.45	38.22	74	54	-14.55	-15.78

Other harmonics emissions are lower than 20dB below the allowable limit.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+ Probe Factor +Cable Loss.
(3) The average measurement was not performed when the peak measured data under the limit of average detection.
(4) Measuring frequencies from 1GHz to 25GHz.

6.5 Radiated Measurement Photos:



7. Channel Separation test

8.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	06/24/2016	06/23/2017
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	06/24/2016	06/23/2017
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	06/24/2016	06/23/2017

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

8.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	December 14, 2016
Test By:	Andy	Temperature :	25 ℃
Test Result:	PASS	Humidity :	50 %
Modulation:	GFSK		

Channel number	Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit 2/3 20dB Down BW(kHz)
1	2402	1003	>738
40	2441	1003	>738
79	2480	1003	>741


Spectrum
Ref Level 10.00 dBm
RBW 100 kHz
Att 10 dB SWT 19 µs VBW 300 kHz Mode Auto FFT
1Pk Max
D1[1] -1.39 dB
M1[1] -1.00290 MHz
-0.71 dBm
2.40300330 GHz
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.402 GHz
691 pts
Span 3.0 MHz
Measuring...


Spectrum
Ref Level 10.00 dBm
RBW 100 kHz
Att 10 dB SWT 19 µs VBW 300 kHz Mode Auto FFT
1Pk Max
D1[1] -0.10 dB
M1[1] 1.00290 MHz
1.10 dBm
2.44119100 GHz
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.441 GHz
691 pts
Span 3.0 MHz
Measuring...



Spectrum Detector:	PK	Test Date :	December 14, 2016
Test By:	Andy	Temperature :	24℃
Test Result:	PASS	Humidity :	53 %
Modulation:	Π/4-DQPSK		

Channel number	Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit 2/3 20dB Down BW(kHz)
1	2402	1003	>912
40	2441	1003	>912
79	2480	1003	>909


Spectrum
Ref Level 10.00 dBm
RBW 100 kHz
Att 10 dB SWT 19 µs VBW 300 kHz Mode Auto FFT
1Pk Max
D1[1] -1.20 dB
-1.00290 MHz
M1[1] -4.02 dBm
2.40302460 GHz
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.402 GHz
691 pts
Span 3.0 MHz
Measuring...


Spectrum
Ref Level 10.00 dBm
RBW 100 kHz
Att 10 dB SWT 19 µs VBW 300 kHz Mode Auto FFT
1Pk Max
D1[1] -0.18 dB
-1.00290 MHz
M1[1] -2.01 dBm
2.44202890 GHz
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.441 GHz
691 pts
Span 3.0 MHz
Measuring...



Spectrum Detector:	PK	Test Date :	December 14, 2016
Test By:	Andy	Temperature :	24℃
Test Result:	PASS	Humidity :	53 %
Modulation:	8DPSK		

Channel number	Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit 2/3 20dB Down BW(kHz)
1	2402	1003	>912
40	2441	1003	>912
79	2480	1003	>912


Spectrum
Ref Level 10.00 dBm
RBW 100 kHz
Att 10 dB SWT 19 µs VBW 300 kHz Mode Auto FFT
1Pk Max
D1[1] -1.27 dB
-1.00290 MHz
M1[1] -4.08 dBm
2.40302890 GHz
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.402 GHz
691 pts
Span 3.0 MHz
Measuring...


Spectrum
Ref Level 10.00 dBm
RBW 100 kHz
Att 10 dB SWT 19 µs VBW 300 kHz Mode Auto FFT
1Pk Max
D1[1] -0.06 dB
1.00290 MHz
M1[1] -2.01 dBm
2.44103040 GHz
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.441 GHz
691 pts
Span 3.0 MHz
Measuring...


Spectrum
Ref Level 10.00 dBm
RBW 100 kHz
Att 10 dB SWT 19 µs VBW 300 kHz Mode Auto FFT
1Pk Max
D1[1] -0.13 dB
-1.00290 MHz
M1 M1[1] -0.17 dBm
2.48019100 GHz
D1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.48 GHz
691 pts
Span 3.0 MHz
Measuring...

8. 20dB Bandwidth test

9.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

9.2 Test SET-UP (Block Diagram of Configuration)



9.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	06/24/2016	06/23/2017
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	06/24/2016	06/23/2017
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	06/24/2016	06/23/2017

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

9.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	December 14, 2016
Test By:	Andy	Temperature :	24℃
Test Result:	PASS	Humidity :	53 %
Modulation:	GFSK		

Channel number	Channel frequency (MHz)	20dB Down BW(kHz)
1	2402	1107
40	2441	1111
79	2480	1111


Spectrum
Ref Level 10.00 dBm
RBW 100 kHz
Att 10 dB SWT 19 µs VBW 300 kHz Mode Auto FFT
1Pk Max
M1[1]
-1.63 dBm
2.40219100 GHz
ndB 20.00 dB
Bw 1.107100000 MHz
Q factor 2169.8
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.402 GHz
691 pts
Span 3.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.402191 GHz -1.63 dBm ndB down 1.1071 MHz
T1 1 2.4014747 GHz -21.63 dBm ndB 20.00 dB
T2 1 2.4025818 GHz -21.41 dBm Q factor 2169.8
Measuring...


Spectrum
Ref Level 10.00 dBm
RBW 100 kHz
Att 10 dB SWT 19 µs VBW 300 kHz Mode Auto FFT
1Pk Max
M1[1]
1.05 dBm
2.44119100 GHz
ndB 20.00 dB
Bw 1.111400000 MHz
Q factor 2196.4
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.441 GHz
691 pts
Span 3.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.441191 GHz 1.05 dBm ndB down 1.1114 MHz
T1 1 2.4404703 GHz -18.73 dBm ndB 20.00 dB
T2 1 2.4415818 GHz -19.05 dBm Q factor 2196.4
Measuring...



Spectrum Detector:	PK	Test Date :	December 14, 2016
Test By:	Andy	Temperature :	24℃
Test Result:	PASS	Humidity :	53 %
Modulation:	Π/4-DQPSK		

Channel number	Channel frequency (MHz)	20dB Down BW(kHz)
1	2402	1368
40	2441	1368
79	2480	1363


Spectrum
Ref Level 10.00 dBm
RBW 100 kHz
Att 10 dB SWT 19 µs VBW 300 kHz Mode Auto FFT
1Pk Max
M1[1]
-5.24 dBm
2.40219100 GHz
ndB 20.00 dB
Bw 1.367600000 MHz
Q factor 1756.5
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.402 GHz
691 pts
Span 3.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.402191 GHz -5.24 dBm ndB down 1.3676 MHz
T1 1 2.4013444 GHz -25.30 dBm ndB 20.00 dB
T2 1 2.402712 GHz -25.14 dBm Q factor 1756.5
Measuring...


Spectrum
Ref Level 10.00 dBm
RBW 100 kHz
Att 10 dB SWT 19 µs VBW 300 kHz Mode Auto FFT
1Pk Max
M1[1]
-2.02 dBm
2.44102600 GHz
ndB 20.00 dB
Bw 1.367600000 MHz
Q factor 1784.9
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.441 GHz
691 pts
Span 3.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.441026 GHz -2.02 dBm ndB down 1.3676 MHz
T1 1 2.4403357 GHz -22.06 dBm ndB 20.00 dB
T2 1 2.4417033 GHz -22.06 dBm Q factor 1784.9
Measuring...



Spectrum Detector:	PK	Test Date :	December 14, 2016
Test By:	Andy	Temperature :	24℃
Test Result:	PASS	Humidity :	53 %
Modulation:	8DPSK		

Channel number	Channel frequency (MHz)	20dB Down BW(kHz)
1	2402	1368
40	2441	1368
79	2480	1368


Spectrum
Ref Level 10.00 dBm
RBW 100 kHz
Att 10 dB SWT 19 µs VBW 300 kHz Mode Auto FFT
1Pk Max
M1[1]
-5.10 dBm
2.40219100 GHz
ndB 20.00 dB
Bw 1.367600000 MHz
Q factor 1756.5
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.402 GHz
691 pts
Span 3.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.402191 GHz -5.10 dBm ndB down 1.3676 MHz
T1 1 2.4013531 GHz -24.95 dBm ndB 20.00 dB
T2 1 2.4027207 GHz -24.92 dBm Q factor 1756.5
Measuring...


Spectrum
Ref Level 10.00 dBm
RBW 100 kHz
Att 10 dB SWT 19 µs VBW 300 kHz Mode Auto FFT
1Pk Max
M1[1]
-1.81 dBm
2.44086110 GHz
ndB 20.00 dB
Bw 1.367600000 MHz
Q factor 1784.8
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.441 GHz
691 pts
Span 3.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.4408611 GHz -1.81 dBm ndB down 1.3676 MHz
T1 1 2.4403444 GHz -21.94 dBm ndB 20.00 dB
T2 1 2.441712 GHz -21.94 dBm Q factor 1784.8
Measuring...


Spectrum
Ref Level 10.00 dBm
RBW 100 kHz
Att 10 dB SWT 19 µs VBW 300 kHz Mode Auto FFT
1Pk Max
M1[1]
0.15 dBm
2.47986110 GHz
ndB 20.00 dB
Bw 1.367600000 MHz
Q factor 1813.3
M1
T1
T2
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.48 GHz
691 pts
Span 3.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.4798611 GHz 0.15 dBm ndB down 1.3676 MHz
T1 1 2.4793444 GHz -19.87 dBm ndB 20.00 dB
T2 1 2.480712 GHz -19.93 dBm Q factor 1813.3
Measuring...

9. Quantity of Hopping Channel Test

10.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

10.2 Test SET-UP (Block Diagram of Configuration)



10.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	06/24/2016	06/23/2017
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	06/24/2016	06/23/2017
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	06/24/2016	06/23/2017

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

10.4 Measurement Results:

Refer to attached data chart.

Worst Test Mode	GFSK	Test Date :	December 14, 2016
Test By:	Andy	Temperature :	25 ℃
Test Result:	PASS	Humidity :	50 %

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel
2402-2480	79	＞15



10. Time of Occupancy (Dwell Time) test

11.1 Test Description

The Equipment Under Test (EUT) was set up to perform the dwell time measurements. The EUT was connected to the spectrum analyzer via a short coax cable. The dwell time is calculated by:

Dwell time = time slot length * hop rate / number of hopping channels * 31.6s

with:
- hop rate = 1600 * 1/s for DH1 packets = 1600 s^{-1}
- hop rate = 1600/3 * 1/s for DH3 packets = 533.33 s^{-1}
- number of hopping channels = 79
- 31.6 s = 0.4 seconds multiplied by the number of hopping channels = 0.4 s * 79

The highest value of the dwell time is reported.

11.2 Test SET-UP (Block Diagram of Configuration)



11.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	06/24/2016	06/23/2017
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	06/24/2016	06/23/2017
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	06/24/2016	06/23/2017

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

11.4 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (a) (1) (iii)

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Since the Bluetooth technology uses 79 channels this period is calculated to be 31.6seconds. Refer to attached data chart.

11.5 Test result

Mode	Number of transmission in a 31.6(79 Hopping*0.4)	Length of transmissions time(msec)	Result (msec)	Limit (msec)
DH1	1600/(2*79) x 31.6 = 320	0.414	132.48	400
DH3	1600/(4*79) x 31.6 =160	1.672	267.52	400
DH5	1600/(6*79) x 31.6 =106.67	2.920	311.47	400

Remark: The results of worst cased was recorded.

.

DH1:



DH3:


Spectrum
Ref Level 10.00 dBm
RBW 1 MHz
Att 10 dB SWT 3 ms VBW 3 MHz
1AP View
D1[1]
-0.74 dB
1.6716562 ms
M1[1]
-29.01 dBm
543.3750 µs
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
M1
D1
CF 2.441 GHz
32001 pts
300.0 µs/
Measuring...

DH5:


Spectrum
Ref Level 10.00 dBm
RBW 1 MHz
Att 10 dB SWT 5 ms VBW 3 MHz
1AP View
D1[1]
0.08 dB
2.920000 ms
M1[1]
-29.31 dBm
1.384219 ms
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
M1
D1
CF 2.48 GHz
32001 pts
500.0 µs/
Measuring...

11. MAXIMUM PEAK OUTPUT POWER TEST

12.1 Measurement Procedure

a. Check the calibration of the measuring instrument(SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using proper RBW and VBW setting.

d. Measure the captured power within the band and recording the plot.

e. Repeat above procedures until all frequencies required were complete.

12.2 Test SET-UP (Block Diagram of Configuration)



12.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	06/24/2016	06/23/2017
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	06/24/2016	06/23/2017
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	06/24/2016	06/23/2017

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

12.4Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	December 14, 2016
Test By:	Leon	Temperature :	25 ℃
Test Result:	PASS	Humidity :	50 %
Modulation:	GFSK		

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
01	2402	-1.56	0.698	1000	PASS
40	2441	1.2	1.318	1000	PASS
79	2480	**2.76**	**1.888**	1000	PASS




Spectrum
Ref Level 10.00 dBm
RBW 3 MHz
Att 10 dB SWT 1.3 µs VBW 10 MHz Mode Auto FFT
1Pk Max
M1[1]
1.20 dBm
2.441141460 GHz
M1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.441 GHz
32001 pts
Span 9.0 MHz
Measuring...


Spectrum
Ref Level 10.00 dBm
RBW 3 MHz
Att 10 dB SWT 1.3 µs VBW 10 MHz Mode Auto FFT
1Pk Max
M1[1]
2.76 dBm
2.479916470 GHz
M1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.48 GHz
32001 pts
Span 9.0 MHz
Measuring...

Spectrum Detector:	PK	Test Date :	December 14, 2016
Test By:	Andy	Temperature :	25 ℃
Test Result:	PASS	Humidity :	50 %
Modulation:	Π/4-DQPSK		

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
01	2402	-4.08	0.391	125	PASS
40	2441	-0.99	0.796	125	PASS
79	2480	0.95	1.245	125	PASS




Spectrum
Ref Level 10.00 dBm
RBW 3 MHz
Att 10 dB SWT 1.3 µs VBW 10 MHz Mode Auto FFT
1Pk Max
M1[1]
-0.99 dBm
2.441190400 GHz
M1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.441 GHz
32001 pts
Span 9.0 MHz
Measuring...


Spectrum
Ref Level 10.00 dBm
RBW 3 MHz
Att 10 dB SWT 1.3 µs VBW 10 MHz Mode Auto FFT
1Pk Max
M1[1]
0.95 dBm
2.479651260 GHz
M1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.48 GHz
32001 pts
Span 9.0 MHz
Measuring...

Spectrum Detector:	PK	Test Date :	December 14, 2016
Test By:	Andy	Temperature :	25 ℃
Test Result:	PASS	Humidity :	50 %
Modulation:	8DPSK		

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
01	2402	-3.7	0.427	125	PASS
40	2441	-0.46	0.899	125	PASS
79	2480	1.46	1.400	125	PASS




Spectrum
Ref Level 10.00 dBm
RBW 3 MHz
Att 10 dB SWT 1.3 µs VBW 10 MHz Mode Auto FFT
1Pk Max
M1[1]
-0.46 dBm
2.441378270 GHz
M1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.441 GHz
32001 pts
Span 9.0 MHz
Measuring...


Spectrum
Ref Level 10.00 dBm
RBW 3 MHz
Att 10 dB SWT 1.3 µs VBW 10 MHz Mode Auto FFT
1Pk Max
M1[1]
1.46 dBm
2.480366740 GHz
M1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
CF 2.48 GHz
32001 pts
Span 9.0 MHz
Measuring...

12. Band EDGE test

13.1 Measurement Procedure

For Conducted Test

1. The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100KHz. The video bandwidth is set to 300KHz.
2. The spectrum from 30MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

For Radiated emission Test

The EUT was placed on a styrofoam table which is 1.5m above ground plane.

The measurement procedure at the ban edges was simplified by performing the measurement in just one plot. Both, the in-band-emission and the unwanted emission were be encompassed by the span. After trace stabilization, the maximum peak was be determined by a peak detector and the value was marked by an appropriate limit line. The second limit line, which is 20dB below the first, marks the limit for the emissions in the unrestricted band. A maximum-peak-detector marks the highest emission in the unrestricted band next to the band edge.

The measurements were performed at the lower end of the 2.4GHz band.

Use the following spectrum analyzer settings:

For Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:

EMI Test Receiver	Setting
Attenuation	Auto
RBW	1MHz
VBW	3MHz
Detector	Peak
Trace	Max hold

For Non-Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 100KHz, video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

13.2 Test SET-UP (Block Diagram of Configuration)

For Conducted Test



For Radiated emission Test



13.3 Measurement Equipment Used:

For Conducted Test

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	06/24/2016	06/23/2017
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	06/24/2016	06/23/2017
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	06/24/2016	06/23/2017

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

For Radiated emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Characteristics	Last Cal.	Cal. Interval
1	Signal Analyzer	Rohde & Schwarz	FSV30	103040	9KHz-40GHz	06/24/2016	1 Year
2	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1272	1GHz-18GHz	06/24/2016	1 Year
3	Power Amplifier	LUNAR EM	LNA1G18-40	J1010000 0081	1GHz-26.5GHz	06/24/2016	1 Year
4	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	06/24/2016	1 Year
5	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	06/24/2016	1 Year
6	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	06/24/2016	1 Year

13.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	December 14, 2016
Test By:	Andy	Temperature :	25 ℃
Test Result:	PASS	Humidity :	50 %

1. Conducted Test

For Non-Hopping Mode:

Frequency (MHz)	Modulation	Peak Power Output(dBm)	Emission read Value(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
2398.9	GFSK	-5.15	-54.79	49.64	>20dBc
2399.77	pi/4-DQPSK	-5.29	-51.15	45.86	>20dBc
2399.31	8DPSK	-5.14	-51.15	46.01	>20dBc
2483.44	GFSK	2.69	-63.69	66.38	>20dBc
2483.72	pi/4-DQPSK	-0.1	-60.09	59.99	>20dBc
2484.51	8DPSK	-0.05	-60.79	60.74	>20dBc

For Hopping Mode:

Frequency (MHz)	Modulation	Peak Power Output(dBm)	Emission read Value(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
2399.36	GFSK	-0.56	-52.86	52.3	>20dBc
2399.76	pi/4-DQPSK	-4.18	-55.09	50.91	>20dBc
2399.48	8DPSK	-3.92	-51.76	47.84	>20dBc
2484.12	GFSK	2.05	-59	61.05	>20dBc
2484.07	pi/4-DQPSK	-2.97	-56.76	53.79	>20dBc
2488.07	8DPSK	-1.31	-58.01	56.7	>20dBc

2. Radiated emission Test

Worst test modulation GFSK

For Non-Hopping Mode:

Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
		PK	AV	PK	AV	PK	AV
2398.05	H	61.25	42.06	74	54	-12.75	-11.94
2398.74	V	62.06	43.82	74	54	-11.94	-10.18
2483.59	H	60.36	41.06	74	54	-13.64	-12.94
2484.95	V	64.15	46.32	74	54	-9.85	-7.68

For Hopping Mode:

Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
		PK	AV	PK	AV	PK	AV
2399.62	H	62.06	42.12	74	54	-11.94	-11.88
2398.89	V	64.52	45.62	74	54	-9.48	-8.38
2484.36	H	61.88	42.82	74	54	-12.12	-11.18
2483.96	V	63.85	45.32	74	54	-10.15	-8.68

13. Antenna Application

14.1 Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247.

FCC part 15C section 15.247 requirements:
Systems operating in the 2402-2480MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

14.2 Result

The EUT's antenna, permanent attached antenna, used a PCB antenna and integrated on PCB, The antenna's gain is 0 dBi and meets the requirement.

14. Photos of EUT

Please refer to external photos and internal photos.