

Applicant/Grantee		Timex Group USA Inc.	
FCC ID:		EP9-TMXM02Q	
IC/HVIN		3348A-TMXM02Q / SMA10T	
Type of Module: Limited Single-modular transmitter			
No.	Requirements	Device Conditions	Comply (Y/N)
1	The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.	NO RF shielding. Refer to the External Photos.	N
2	The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation.	The EUT has buffered modulation/data inputs, it's integrated on the chip U101: NRF52840. Refer to the Schematic Diagram.	Y
3	The modular transmitter must have its own power supply regulation.	The module has its own power supply regulation. It has a DC-DC converter (U103) to supply power. Refer to the Block Diagrams.	Y
4	The modular transmitter must comply with the antenna and transmission system requirements of §§ 15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a “unique” antenna coupler.	The module has no external power amplifier. The Antenna is employ a “Integral” antenna coupler and the antenna gain is -1.5dBi. Refer to the External Photos.	Y
5	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing for compliance with part 15 requirements.	The modular transmitter was tested in a stand-alone configuration via a laptop PC USB Interface. And is not inside another device during testing. Refer to the Test Setup Photos.	Y
6	The modular transmitter must be equipped with either a permanently affixed label.	The FCC ID is permanently on the PCB. Refer to the Label Location and Label.	Y
7	The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization.	The User Manual instruction that the OEM how to use the label. Refer to the User Manual.	Y
8	The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	Refer to the Appendix B of test report.	Y

Signature
Name and title
Email
Tel.
Date


 Sam Everett / Director Quality Assurance & Regulatory
 severett@timexgroup.com
 203-346-5603
 30 May 2019