

Maximum Permissible Exposure Report

FCC ID: EROTS1070

Report No. : BTL-FCCP-5-2003T099
Equipment : 10.1 inch Touch Screen Surface mount
Model Name : M201923006, TS-1070-B-S, TS-1070-W-S
Brand Name : CRESTRON
Applicant : Crestron Electronics, Inc.
Address : 15 Volvo Drive, Rockleigh, NJ 07647

FCC Rule Part(s) : FCC Guidelines for Human Exposure IEEE C95.1


Date of Receipt : 2020/3/20
Date of Test : 2020/3/20 ~ 2020/4/15
Issued Date : 2020/5/4

The above equipment has been tested and found in compliance with the requirement of the above standards by BTL Inc.

Prepared by


Peter Chen, Engineer

**Approved by**


Scott Hsu, Manager

BTL Inc.

No.18, Ln. 171, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City 114, Taiwan

Tel: +886-2-2657-3299

Fax: +886-2-2657-3331

Web: www.newbtl.com

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	2020/5/4

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

For BT, BLE, WLAN:

Ant.	Brand	Test Model	Antenna Type	Connector	Gain (dBi)
1	YAGEO	TS WLAN MAIN	PIFA	IPEX	-1.64

For 5G RLAN:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Note
1	YAGEO	TS WLAN MAIN	PIFA	IPEX	1.86	UNII-1
					4.17	UNII-3

TEST RESULTS

For BT:

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm2)	Limit of Power Density (S) (mW/cm2)	Test Result
-1.64	0.6855	5.95	3.9355	0.00053697	1	Complies

For BLE:

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm2)	Limit of Power Density (S) (mW/cm2)	Test Result
-1.64	0.6855	1.10	1.2882	0.00017577	1	Complies

For 2.4G WLAN:

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm2)	Limit of Power Density (S) (mW/cm2)	Test Result
-1.64	0.6855	19.84	96.3829	0.01315075	1	Complies

For 5G RLAN:

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm2)	Limit of Power Density (S) (mW/cm2)	Test Result
4.17	2.6122	19.24	83.9460	0.04364660	1	Complies

Note:

1. The calculated distance is 20 cm.

COLLOCATED POWER DENSITY CALCULATIONS

So for BT, WIFI simultaneous transmission: $0.00053697/1+0.04364660/1=0.04418357<1$

End of Test Report