

Test report

TA128_01.DOC

EUT: Matrix Needleprinter
Tested type: T2255
Production level: UCL No. 0
S/N: 2532125

Manufacturer: Tally GmbH
Glockeraustr. 4
89275 Elchingen
Germany

Measurement procedure: FCC rules part 15, limit class B
The regulations were ☒ kept
☐ not kept

Applicant: Tally GmbH
Glockeraustr. 4
89275 Elchingen
Germany

Contact person: Mr. Böhm, Mr. Winterhalder

Arrival of EUT: 07/02/2001

ID of EUT: PR127_01

Date(s) of test of EUT: 07/04/2001

Remarks:

The test results effects only to the relate items tested. The test report shall not be reproduced except in full without the written approval of the testing laboratory

Test laboratory: EMCE GmbH Ingenieurbüro für EMV-Prüfungen
und Schaltungsentwicklung
Laupheimer-Str. 25d
88483 Burgrieden / Germany
FCC Registration Nr. 90568
DAR-Registration Nr: TTI-P-G164/98

Test engineer: Mr. Chr. Vogelmann
EMCE GmbH Ingenieurbüro für EMV-Prüfungen
und Schaltungsentwicklung

EUT description: Matrix needle printer, with parallel and serial I/F.

EUT size: 600x300x295mm (LxWxH)

EUT configuration: Printer with attached serial I/F.

Used accessories:

Designation	S/N	FCC-ID	Manufacturer
PC SCENIC 5T/90 PCI	S26361-K345-V711	-	Siemens Nixdorf Informationssysteme AG
Monitor MCM 1702	S26361-K373-V318 S/N BU 908484	FCC-ID ARFKDM1788	Siemens Nixdorf Informationssysteme AG
Keyboard MF2 LC	S26381-K252-V120		Siemens Nixdorf Informationssysteme AG
Mouse Serial Mouse 2.0A	0222829	FCC-ID C3KSMP1	Microsoft Corp.
Additional Printer HP Deskjet 850C	S/N US545110NX	FCC-ID B94C2145X	Hewlett Packard

Additional information: xx

List of valid equipment

	Inv-Nr.	Designation	Type	Manufacturer	S/N
☒	001	Test receiver	ESS 5Hz - 1000 MHz	Rohde & Schwarz	833776/008
	002	Probe	ESH2-Z3	Rohde & Schwarz	-
☒	003	LISN 1	ESH3-Z5	Rohde & Schwarz	835268/007
	004	LISN 2	ESH3-Z5	Rohde & Schwarz	835268/003
	005	LISN 3	NNB 4/32T	Rolf Heine HF-Technik	4/32T-96015
	006	LISN	NNBM 8125	Schwarzbeck	8125371
	007	Absorbing clamp	MDS 21	Schwarzbeck	942436
	008	Antenna 9kHz - 30MHz	HFH2-Z2	Rohde & Schwarz	835776/0002
	009	Antenna 30 - 300MHz	VHBA9123 / BBA9106	Schwarzbeck	435
☒	010	Antenna 250 -1200MHz	UHALP 9108A	Schwarzbeck	108
☒	011	Antenna 30 - 300MHz	VHBA9123 / BBA9106	Schwarzbeck	0408/94
	012	Antenna 250 -1200MHz	UHALP 9108A	Schwarzbeck	166
	013	Antenna 9kHz - 30MHz	Loop antenna 1.5m	EMCE GmbH	-
☒	014	Open area test site	3m	EMCE GmbH	-
	015	Open area test site	10m	EMCE GmbH	-
	019	Burst generator	PEFT / PHV 41.2	Haefely	082948-50
	020	Coupling clamp	IP4A	Haefely	082672-13
	022	ESD-Gun	NSG 435	Schaffner	577
	024	HF-Generator	SMY01	Rohde & Schwarz	844146/046
	025	Current clamp BCI	F-120-2	FCC	47
	026	Coupling device network	CDN 801-M3-25	FCC	92
	027	Surge Generator	Transient 1000	EMC-Partner AG	TRA1000-85
	029	HF Amplifier	10W1000	Amplifier Research	10576
	030	Coupling device network	CDN 801- S1/9pol.DSUB	EMCE GmbH	-
	031	Coupling device network	CDN 801- S1/9pol.DSUB	EMCE GmbH	-

	Inv-Nr.	Designation	Type	Manufacturer	S/N
	032	HF Amplifier	75A250	Amplifier Research	22789
	033	Coupling device network	CDN AF2	EMCE GmbH	
	034	Coupling device network	CDN AF2	EMCE GmbH	
	035	3-Phase Coupling network	CDN-1000	EMC-Partner AG	CDN-1000-45
	036	Coupling device network	CDN 801-M5-25	EMCE GmbH	
	037	Coupling device network	CDN 801-T1	EMCE GmbH	
	038	Helmholtz coil	1x1m	EMCE GmbH	
	039	Helmholtz coil	1x1m	EMCE GmbH	
	040	Current transformer		EMCE GmbH	
	041	HZ-10	Shielded coil	Rohde & Schwarz	849788/020
☒	042	AC-Source / Analyzer / Normimpedance	EMV D5000/PAS	Spitzenberger + Spies	A274700/0 0501
	xx	Susceptibility test equipment according DIN EN 61000-4-3	Full anechoic chamber 3m test site	Siemens	xx

Contents:

1	Report.....	6
1.1	EMI Report FCC part 15 limit class B	6
1.1.1	Conducted Emissions.....	6
1.1.1.1	Test Configuration.....	6
1.1.1.2	Test Procedure	8
1.1.2	Radiated Emissions	22
1.1.2.1	Test Configuration.....	22
1.1.2.2	Test Procedure	24
2	Results.....	30


1 Report

1.1 EMI Report FCC part 15 limit class B

1.1.1 Conducted Emissions

1.1.1.1 Test Configuration

ANSI C63.4-1992
T2255 serial RS232 I/F



Test set up



1.1.1.2 Test Procedure

Regulations:

FCC part 15 limit class B
0.45 - 30MHz

Test Operation:

During the tests, the system was exercised using a Microsoft Word for Windows document which provided for complete system operation. Data were displayed on the monitor and then transferred to the printers on the parallel port (HP Deskjet 850C) and the serial port (T2255), where it was printed. These tests represented a continuous display-transfer-print program operation which is a worst case mode and provided for a worst case emanated profile. The printed characters were “HHHHH...”, 80 character per line, LQ print quality and the printer was configured with its default parameters.

PC:	SCENIC 5T90/PCI
Monitor	MCM 1702
T2255	2532125
Additional printer	HP Deskjet 850C
Parallel I/F cable:	Shielded cable
Serial I/F cable:	Shielded cable
Fanfold paper for the	T2255
Single sheet for the	HP Deskjet 850C
Supply voltage:	120VAC/60Hz

Test results:

Measurements are made with a CISPR receiver with the detector in peak mode. If the emanation is closer than 6dB to the limit or more, the receiver will stop and measure the exact value with quasipeak. The frequency, the maximum quasipeak value and the limit will be printed out.

Summary:

Limits for continuous disturbances:	☒	kept
	☐	not kept

| Remarks:

Protocol scope:

- ☒ Readings
- ☒ Diagram continuous emanations

Conducted emission of the T2255 serial I/F on L1- and N-Phase

Conducted emission of the PC + Monitor on L1- and N-Phase (the monitor was supplied via the PC)

Conducted emission of the HP Deskjet 850C parallel I/F on L1- and N-Phase

EMCE GmbH Ing_buero fuer EMV_Pruefungen

02. Jul 01 15:33

Conducted emission

EUT: Needle printer T2255, SN 2532125
Manuf: Tally GmbH Computerdrucker
Op Cond: "HHHH...", 10cpi, fanfold paper
Operator: Mr. Vogelmann
Test Spec: FCC Part 15 class B
Comment: Test ID PR127_01
TA127_11, Phase L - T2255


Scan Settings (1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
450k	30M	5k	10k	PK	20ms	AUTO	LN OFF	60dB

Final Measurement: x QP

Meas Time: 1 s
Subranges: 50
Acc Margin: 6dB

Transducer No.	Start	Stop	Name
2	1Hz	1000M	Kabel_6m



EMCE GmbH Ing_buero fuer EMV_Pruefungen

02. Jul 01 15:33

Conducted emission

EUT: Needle printer T2255, SN 2532125
Manuf: Tally GmbH Computerdrucker
Op Cond: "HHHH...", 10cpi, fanfold paper
Operator: Mr. Vogelmann
Test Spec: FCC Part 15 class B
Comment: Test ID PR127_01
TA127_11, Phase L - T2255

Scan Settings (1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
450k	30M	5k	10k	PK	20ms	AUTO	LN	OFF 60dB

Final Measurement Results:

Frequency MHz	QP Level dBuV	QP Limit dBuV
0.46500	38.3	46.0
0.62000	38.2	46.0
0.69500	40.3	46.0
0.92500	38.4	46.0
1.00500	40.1	46.0
1.16000	37.1	46.0
1.23500	39.6	46.0
1.54500	39.9	46.0
1.62000	37.2	46.0
1.85500	39.6	46.0
2.08500	39.0	46.0
2.32000	36.6	46.0
2.62500	37.1	46.0
2.70500	38.8	46.0
3.01000	37.5	46.0
3.24500	37.7	46.0
9.11500	34.3	46.0
9.70500	31.4	46.0
10.19500	38.9	46.0
10.97000	32.3	46.0
20.85000	34.4	46.0
21.46500	33.6	46.0
28.96000	20.9	46.0

*v1S * limit exceeded*v0S

EMCE GmbH Ing_buero fuer EMV_Pruefungen

02. Jul 01 15:45

Conducted emission

EUT: Needle printer T2255, SN 2532125
Manuf: Tally GmbH Computerdrucker
Op Cond: "HHHH...", 10cpi, fanfold paper
Operator: Mr. Vogelmann
Test Spec: FCC Part 15 class B
Comment: Test ID PR127_01
TA127_12, Phase N - T2255


Scan Settings (1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
450k	30M	5k	10k	PK	20ms	AUTO	LN	OFF 60dB

Final Measurement: x QP

Meas Time: 1 s
Subranges: 50
Acc Margin: 6dB

Transducer No.	Start	Stop	Name
2	1Hz	1000M	Kabel_6m



EMCE GmbH Ing_buero fuer EMV_Pruefungen

02. Jul 01 15:45

Conducted emission

EUT: Needle printer T2255, SN 2532125
Manuf: Tally GmbH Computerdrucker
Op Cond: "HHHH...", 10cpi, fanfold paper
Operator: Mr. Vogelmann
Test Spec: FCC Part 15 class B
Comment: Test ID PR127_01
TA127_12, Phase N - T2255

Scan Settings (1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
450k	30M	5k	10k	PK	20ms	AUTO	LN	OFF 60dB

Final Measurement Results:

Frequency MHz	QP Level dBuV	QP Limit dBuV
0.46500	38.7	46.0
0.69500	38.4	46.0
1.47000	36.8	46.0
2.39500	38.3	46.0
2.62500	37.1	46.0
2.70500	38.3	46.0
3.01500	38.0	46.0
3.24500	38.8	46.0
3.55500	38.9	46.0
3.86500	38.3	46.0
4.17000	36.2	46.0
9.20000	35.6	46.0
10.00500	39.2	46.0
10.43500	43.1	46.0
11.05500	36.4	46.0
15.22000	33.5	46.0
15.37500	33.7	46.0
19.62000	33.3	46.0
20.08000	35.3	46.0
21.55000	34.3	46.0

*v1S * limit exceeded*v0S

EMCE GmbH Ing_buero fuer EMV_Pruefungen

02. Jul 01 15:18

Conducted emission

EUT: Needle printer T2255, SN 2532125
Manuf: Tally GmbH Computerdrucker
Op Cond: "HHHH...", 10cpi, fanfold paper
Operator: Mr. Vogelmann
Test Spec: FCC Part 15 class B
Comment: Test ID PR127_01
TA127_13, Phase L - PC/Monitor


Scan Settings (1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
450k	30M	5k	10k	PK	20ms	AUTO	LN OFF	60dB

Final Measurement: x QP

Meas Time: 1 s
Subranges: 50
Acc Margin: 6dB

Transducer No.	Start	Stop	Name
2	1Hz	1000M	Kabel_6m



EMCE GmbH Ing_buero fuer EMV_Pruefungen

02. Jul 01 15:18

Conducted emission

EUT: Needle printer T2255, SN 2532125
 Manuf: Tally GmbH Computerdrucker
 Op Cond: "HHHH...", 10cpi, fanfold paper
 Operator: Mr. Vogelmann
 Test Spec: FCC Part 15 class B
 Comment: Test ID PR127_01
 TA127_13, Phase L - PC/Monitor

Scan Settings (1 Range)

Frequencies				Receiver Settings			
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp OpRge
450k	30M	5k	10k	PK	20ms	AUTO LN OFF	60dB

Final Measurement Results:

Frequency MHz	QP Level dBuV	QP Limit dBuV
2.39500	38.5	46.0
2.47000	37.1	46.0
2.70500	39.2	46.0
3.01000	39.1	46.0
3.24500	40.5	46.0
3.63000	39.8	46.0
3.86000	40.2	46.0
4.09000	38.1	46.0
4.40500	38.1	46.0
9.73500	36.0	46.0
15.06000	34.4	46.0
15.91000	35.3	46.0

*v1S * limit exceeded*v0S

EMCE GmbH Ing_buero fuer EMV_Pruefungen

02. Jul 01 15:24

Conducted emission

EUT: Needle printer T2255, SN 2532125
Manuf: Tally GmbH Computerdrucker
Op Cond: "HHHH...", 10cpi, fanfold paper
Operator: Mr. Vogelmann
Test Spec: FCC Part 15 class B
Comment: Test ID PR127_01
TA127_14, Phase N - PC/Monitor


Scan Settings (1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
450k	30M	5k	10k	PK	20ms	AUTO	LN OFF	60dB

Final Measurement: x QP

Meas Time: 1 s
Subranges: 50
Acc Margin: 6dB

Transducer No.	Start	Stop	Name
2	1Hz	1000M	Kabel_6m



EMCE GmbH Ing_buero fuer EMV_Pruefungen

02. Jul 01 15:24

Conducted emission

EUT: Needle printer T2255, SN 2532125
Manuf: Tally GmbH Computerdrucker
Op Cond: "HHHH...", 10cpi, fanfold paper
Operator: Mr. Vogelmann
Test Spec: FCC Part 15 class B
Comment: Test ID PR127_01
TA127_14, Phase N - PC/Monitor

Scan Settings (1 Range)

Frequencies				Receiver Settings			
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp OpRge
450k	30M	5k	10k	PK	20ms	AUTO LN OFF	60dB

Final Measurement Results:

Frequency MHz	QP Level dBuV	QP Limit dBuV
2.39500	38.5	46.0
2.62500	37.9	46.0
2.85500	36.6	46.0
3.01000	39.4	46.0
3.24500	40.4	46.0
3.55000	40.1	46.0
3.86000	40.1	46.0
4.09500	39.8	46.0
4.48000	37.5	46.0
9.73000	36.2	46.0
15.29000	33.6	46.0

*v1S * limit exceeded*v0S

EMCE GmbH Ing_buero fuer EMV_Pruefungen

02. Jul 01 16:08

Conducted emission

EUT: Needle printer T2255, SN 2532125
Manuf: Tally GmbH Computerdrucker
Op Cond: "HHHH...", 10cpi, fanfold paper
Operator: Mr. Vogelmann
Test Spec: FCC Part 15 class B
Comment: Test ID PR127_01
TA127_15, Phase L - HP Deskjet 850C


Scan Settings (1 Range)

Frequencies			Receiver Settings				
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp OpRge
450k	30M	5k	10k	PK	20ms	AUTO	LN OFF 60dB

Final Measurement: x QP

Meas Time: 1 s
Subranges: 50
Acc Margin: 6dB

Transducer No.	Start	Stop	Name
2	1Hz	1000M	Kabel_6m



EMCE GmbH Ing_buero fuer EMV_Pruefungen

02. Jul 01 16:08

Conducted emission

EUT: Needle printer T2255, SN 2532125
Manuf: Tally GmbH Computerdrucker
Op Cond: "HHHH...", 10cpi, fanfold paper
Operator: Mr. Vogelmann
Test Spec: FCC Part 15 class B
Comment: Test ID PR127_01
TA127_15, Phase L - HP Deskjet 850C

Scan Settings (1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
450k	30M	5k	10k	PK	20ms	AUTO	LN OFF	60dB

Final Measurement Results:

no Results

EMCE GmbH Ing_buero fuer EMV_Pruefungen

02. Jul 01 16:12

Conducted emission

EUT: Needle printer T2255, SN 2532125
Manuf: Tally GmbH Computerdrucker
Op Cond: "HHHH...", 10cpi, fanfold paper
Operator: Mr. Vogelmann
Test Spec: FCC Part 15 class B
Comment: Test ID PR127_01
TA127_16, Phase N - HP Deskjet 850C


Scan Settings (1 Range)

Frequencies			Receiver Settings				
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp OpRge
450k	30M	5k	10k	PK	20ms	AUTO	LN OFF 60dB

Final Measurement: x QP

Meas Time: 1 s
Subranges: 50
Acc Margin: 6dB

Transducer No.	Start	Stop	Name
2	1Hz	1000M	Kabel_6m



EMCE GmbH Ing_buero fuer EMV_Pruefungen

02. Jul 01 16:12

Conducted emission

EUT: Needle printer T2255, SN 2532125
Manuf: Tally GmbH Computerdrucker
Op Cond: "HHHH...", 10cpi, fanfold paper
Operator: Mr. Vogelmann
Test Spec: FCC Part 15 class B
Comment: Test ID PR127_01
TA127_16, Phase N - HP Deskjet 850C

Scan Settings (1 Range)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
450k	30M	5k	10k	PK	20ms	AUTO	LN OFF	60dB


Final Measurement Results:

no Results


1.1.2 Radiated Emissions

1.1.2.1 Test Configuration

ANSI C63.4-1992
T2255 serial RS232 I/F



Open field test configuration



1.1.2.2 Test Procedure

Regulations:

FCC part 15 limit class B
30 - 1000MHz

Test Operation:

During the tests, the system was exercised using a Microsoft Word for Windows document which provided for complete system operation. Data were displayed on the monitor and then transferred to the printers on the parallel port (HP Deskjet 850C) and the serial port (T2255), where it was printed. These tests represented a continuous display-transfer-print program operation which is a worst case mode and provided for a worst case emanated profile. The printed characters were “HHHHH...”, 80 character per line, LQ print quality and the printer was configured with its default parameters.

PC:	SCENIC 5T90/PCI
Monitor	MCM 1702
T2255	2532125
Additional printer	HP Deskjet 850C
Parallel I/F cable:	Shielded cable
Serial I/F cable:	Shielded cable
Fanfold paper for the	T2255
Single sheet for the	HP Deskjet 850C
Supply voltage:	120VAC/60Hz

Summary:

Limits for continuous disturbances:	☒	kept
	☐	not kept

| Remarks:

Protocol scope:

- ☒ Readings - Antenna horizontal polarised (margin to the limits <10dB).
- ☒ Diagram - Antenna horizontal polarised.
- ☒ Readings - Antenna vertical polarised (margin to the limits <10dB)
- ☒ Diagram - Antenna vertical polarised.
- ☐ Precompliance measurement(s).


Readings - Antenna horizontal polarised

Frequency	Measured	+ AF	+ KF	Emission	Limit	Difference	Ant.-	Ant.-
MHz	value	dB/m	dB		dBµV/m	dBµV	Height	Polar.
	dBµV	Antenna	Cable	dBµV/m			meter	H/V
103.845	22.0	10.2	2.1	34.3	43.5	9.2	2.2	H
119.821	23.0	10.9	2.3	36.2	43.5	7.3	2.2	H
125.180	20.0	11.2	2.3	33.5	43.5	10.0	2.4	H
127.809	25.0	11.3	2.3	38.7	43.5	4.8	2.2	H
156.040	20.0	12.8	2.6	35.4	43.5	8.1	2.4	H
167.751	18.0	13.4	2.7	34.1	43.5	9.4	1.9	H
168.040	26.0	13.4	2.7	42.1	43.5	1.4	2.4	H
175.739	17.0	13.8	2.8	33.6	43.5	9.9	1.9	H
264.067	14.0	17.6	3.5	35.1	46.0	10.9	1.6	H
600.154	12.5	19.0	5.1	36.6	46.0	9.4	1.3	H
624.160	13.0	19.3	5.2	37.4	46.0	8.6	1.3	H

Diagram - Antenna horizontal polarised

Limits according FCC rules part 15

□ Class A
⊗ Class B




Readings - Antenna vertical polarised

Frequency	Measured	+ AF	+ KF	Emission	Limit	Difference	Ant.-	Ant.-
MHz	value	dB/m	dB		dB μ V/m	dB μ V	Height	Polar.
	dB μ V	Antenna	Cable	dB μ V/m			meter	H/V
127.810	25.0	11.3	2.3	38.7	43.5	4.8	1.0	V
125.180	22.0	11.2	2.3	35.5	43.5	8.0	1.0	V
123.826	22.0	11.1	2.3	35.4	43.5	8.1	1.0	V
119.822	22.0	10.9	2.3	35.2	43.5	8.3	1.0	V

Diagram - Antenna vertical polarised

Limits according FCC rules part 15

□ Class A
⊗ Class B



2 Results

EMI:

Regulation	Class	Result	Remarks
FCC part 15 limit class B			
Conducted Emission 0.45 - 30MHz	B	kept	
Radiated Emission 30 -1000MHz	B	kept	

Burgrieden, 07/14/2001



Dipl.Ing.(FH) Christian Vogelmann