SAR Test Report

Report No.: AGC05041151002FH01

FCC ID	:	EW780-0242-00
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	DECT 6.0 Cordless Telephone Handset
BRAND NAME	:	at&t
MODEL NAME	:	CLP99286, CLP99386, CLP99486, CLP99456, CLP99586, CLP99546 CLP99556, CLP99006, CLP99XY6, CLP990Y6
CLIENT	:	VTech Telecommunications Ltd.
DATE OF ISSUE	:	Dec. 28,2015
STANDARD(S)	:	IEEE Std. 1528:2013; FCC 47CFR § 2.1093; IEEE/ANSI C95.1:1992
REPORT VERSION	:	V1.0

Attestation of Global Compliance(Shenzhen) Co., Ltd.

CAUTION:
This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Dec. 28,2015	Valid	Original Report

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Report Certification

Applicant Name :	VTech Telecommunications Ltd.
Applicant Address :	23/F, Tai Ping Industrial Centre, Block 1, 57 Ting Kok Road, Tai Po, Hong Kong
Manufacturer Name :	VTech (Dongguan) Telecommunications Limited.
Manufacturer Address :	VTech Science Park, Xia Ling Bei Management Zone, Liaobu, Dongguan Guangdong, China.
Product Designation :	DECT 6.0 Cordless Telephone Handset
Brand Name :	at&t
Model Name :	CLP99286, CLP99386, CLP99486, CLP99456, CLP99586, CLP99546 CLP99556, CLP99006, CLP99XY6, CLP990Y6
Different Description	See Page 7, The test model is CLP99286
EUT Voltage :	DC2.4V by battery
Applicable Standard :	IEEE Std. 1528:2013; FCC 47CFR § 2.1093; IEEE/ANSI C95.1:1992
Test Date :	Dec. 21,2015
Performed Location	Attestation of Global Compliance(Shenzhen) Co., Ltd.
	2 F, Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang Street, Bao'an District, Shenzhen, China
Report Template	AGCRT-US-2.4G/SAR (2015-05-01)

Tested By

Summer Li(Li Jian'e) Dec. 28,2015

Checked By

Angela Li(Li Jiao) Dec. 28,2015

Authorized By

Solger Zhang(Zhang Hongyi)
Authorized Officer
Dec. 28,2015

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

TABLE OF CONTENTS

1. SUMMARY OF MAXIMUM SAR VALUE 5

2. GENERAL INFORMATION 6

2.1. EUT DESCRIPTION 6
2.3. TEST ENVIRONMENT 10

3. SAR MEASUREMENT SYSTEM 11

3.1. SATIMO SYSTEM DESCRIPTION 11
3.2. COMOSAR E-FIELD PROBE 12
3.3. ROBOT 12
3.4. VIDEO POSITIONING SYSTEM 13
3.5. DEVICE HOLDER 13
3.6. SAM TWIN PHANTOM 14

4. SAR MEASUREMENT PROCEDURE 15

4.1. SPECIFIC ABSORPTION RATE (SAR) 15
4.2. SAR MEASUREMENT PROCEDURE 16
4.3. RF EXPOSURE CONDITIONS 18
5.1. THE COMPOSITION OF THE TISSUE SIMULATING LIQUID(% WEIGHT) 19
5.2. TISSUE DIELECTRIC PARAMETERS FOR HEAD AND BODY PHANTOMS 19
5.3. TISSUE CALIBRATION RESULT 20

6. SAR SYSTEM CHECK&VALIDATION PROCEDURE 21

6.1. SAR SYSTEM CHECK PROCEDURES 21
6.2. SAR SYSTEM CHECK 22
6.3. SAR SYSTEM VALIDATION 23

7. EUT TEST POSITION 24

7.1. BODY PART POSITION 24

8. SAR EXPOSURE LIMITS 25

9. TEST EQUIPMENT LIST 26

10. MEASUREMENT UNCERTAINTY 27

11. CONDUCTED POWER MEASUREMENT 29

12. TEST RESULTS 30

12.1. SAR TEST RESULTS SUMMARY 30

APPENDIX A. SAR SYSTEM CHECK DATA 32

APPENDIX B. SAR MEASUREMENT DATA 36

APPENDIX C. TEST SETUP PHOTOGRAPHS &EUT PHOTOGRAPHS 78

APPENDIX D. CALIBRATION DATA 79

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

1. SUMMARY OF MAXIMUM SAR VALUE

The maximum results of Specific Absorption Rate (SAR) found during testing for EUT are as follows:

Highest Reported SAR ：

Battery Model	Exposure Position	Frequency Band(MHz)	Highest Reported 1g-SAR(W/Kg)
CR1530	Head	1924.992	0.062
	Body	1924.992	0.054
GP1249	Head	1924.992	0.067
	Body	1924.992	0.059
GY1516	Head	1924.992	0.062
	Body	1924.992	0.058

This device is compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6W/Kg) specified in IEEE Std. 1528:2013; FCC47CFR § 2.1093; IEEE/ANSI C95.1 and the following specific FCC Test Procedures:

- KDB 447498 D01 General RF Exposure Guidance v06
- KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

2. GENERAL INFORMATION

2.1. EUT Description

General Information	
Product Designation	DECT 6.0 Cordless Telephone Handset
Test Model	CLP99286
Hardware Version	CN_KB_KB-6160
Software Version	N/A
Device Category	Portable
RF Exposure Environment	Uncontrolled
Antenna Type	Internal
Duty Cycle	4.3%
DECT Band	
TX Frequency Range	1900: 1921.536-1928.448MHz
RX Frequency Range	1900: 1922.400-1929.312MHz
Type of modulation	GFSK
Antenna Gain	0dBi
Max. Peak Power	19.6dBm
Accessories	
Battery One	Brand name: Corun Model No. : CR1530 Voltage and Capacitance:2.4V 400mAh
Battery Two	Brand name: GPI Model No. : GP1249 Voltage and Capacitance:2.4V 400mAh
Battery Three	Brand name: Coslight Model No. : GY1516 Voltage and Capacitance:2.4V 400mAh
Adapter	Brand name. : N/A Model No:RJ-AS060400U001 Input: AC 100-120V, 60Hz, 150mA Output: DC 6.0V, 400mA

Product	Type	
	☒ Production unit	☐ Identical Prototype

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

vtech

VTech Telecommunications Ltd

Oct 26, 2015

To whom it may concern,

FCC-Multiple Models Confirmation Letter

I, the undersigned, hereby confirm that the family models are listed in the following table.

These models are identical as follows:

☒ Electrical designs, including software & firmware
☒ PCB layout ☒ Construction design/Physical design/Enclosure
☐ Others, please specify _____

The only differences between these models are the follows for marketing purpose:

☒ Color ☐ Cosmetic details
☐ Trade name ☒ Model number
☒ Others, please specify package type(material), no. of Handset and Charger

☒ Suffix (" Y ") represents
☐ Color code ☐ Packing configuration
☒ Others, please specify Y= Any alphanumeric character is presenting different package type (material) or color of enclosure.

,but models with suffix (" Y ") are identical in:
☒ Electrical designs, including software & firmware
☒ PCB layout
☒ Construction design/Physical design/Enclosure
☐ Others, please specify _____

For the product subject to authorization under FCC Declaration of Conformity:
In addition, it is to confirm that all the below information
1) The U.S. responsible party,
2) FCC label artworks and location,
3) FCC required statement in the user manual
Are the same but different in the following model numbers only:

Item #	New Model	Model Number	Trade Name	Remarks
1	☒ YES	CLP99006	at&t	1HS+1Charger
2	☒ YES	CLP990Y6	at&t	1HS+1Charger

The sample(s) being submitted to Intertek Testing Services for conformity assessment is CLP99006 of the above list.

Regards,

Michael Tsui
Approbation Supervisor

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

vtech

VTech Telecommunications Ltd

Oct 26, 2015

To whom it may concern,

FCC-Multiple Models Confirmation Letter

I, the undersigned, hereby confirm that the family models are listed in the following table.

These models are identical as follows:

☒ Electrical designs, including software & firmware
☒ PCB layout ☒ Construction design/Physical design/Enclosure
☐ Others, please specify _____

The only differences between these models are the follows for marketing purpose:

☒ Color ☐ Cosmetic details
☐ Trade name ☒ Model number
☒ Others, please specify package type(material), no. of Handset and Charger

☒ Suffix (" X, Y ") represents
☐ Color code ☐ Packing configuration
☒ Others, please specify X= Any alphanumeric character is presenting no. of Handset and Charger
Y=Number (0, 4, 5, 8, 9) is presenting different package type (material) or color of enclosure.

,but models with suffix (" X, Y ") are identical in:
☒ Electrical designs, including software & firmware
☒ PCB layout
☒ Construction design/Physical design/Enclosure
☐ Others, please specify _____

For the product subject to authorization under FCC Declaration of Conformity:
In addition, it is to confirm that all the below information
1) The U.S. responsible party,
2) FCC label artworks and location,
3) FCC required statement in the user manual
Are the same but different in the following model numbers only:

Item #	New Model	Model Number	Trade Name	Remarks
1	☒ YES	CLP99286	at&t	2HS+1BS(W/ ITAD)+1Charger
2	☒ YES	CLP99386	at&t	3HS+1BS(W/ ITAD)+2Chargers
3	☒ YES	CLP99486	at&t	4HS+1BS(W/ ITAD)+3Chargers
4	☒ YES	CLP99456	at&t	4HS+1BS(W/ ITAD)+3Chargers
5	☒ YES	CLP99586	at&t	5HS+1BS(W/ ITAD)+4Chargers
6	☒ YES	CLP99556	at&t	5HS+1BS(W/ ITAD)+4Chargers
7	☒ YES	CLP99546	at&t	5HS+1BS(W/ ITAD)+4Chargers
8	☒ YES	CLP99XY6	at&t	XHS+1BS(W/ITAD)+(X-1)Charger(s)

The sample(s) being submitted to Intertek Testing Services for conformity assessment is CLP99286 of the above list.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

vtech

VTech Telecommunications Ltd

Regards,

Michael Tsui
Approbation Supervisor

2.2. Test Procedure

1	Turn on the power of all equipment.
2	EUT Communicate with RTX2012, and test them respectively at DECT bands

2.3. Test Environment

Ambient conditions in the laboratory:

Items	Required	Actual
Temperature (°C)	18-25	21± 2
Humidity (%RH)	30-70	55±2

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

3. SAR MEASUREMENT SYSTEM

3.1. SATIMO System Description



The COMOSAR system for performing compliance tests consists of the following items:

- The PC. It controls most of the bench devices and stores measurement data. A computer running WinXP and the Opensar software
- The E-Field probe. The probe is a 3-axis system made of 3 distinct dipoles. Each dipole returns a voltage in function of the ambient electric field.
- The Keithley multimeter measures each probe dipole voltages.
- The SAM phantom simulates a human head. The measurement of the electric field is made inside the phantom.
- The liquids simulate the dielectric properties of the human head tissues.
- The network emulator controls the mobile phone under test.
- The validation dipoles are used to measure a reference SAR. They are used to periodically check the bench to make sure that there is no drift of the system characteristics over time.
- The phantom, the device holder and other accessories according to the targeted measurement.
- The lower SAR detection threshoid of the system is 0.0015 W/Kg.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

3.2. COMOSAR E-Field Probe

The SAR measurement is conducted with the dissymmetric probe manufactured by SATIMO. The probe is specially designed and calibrated for use in liquid with high permittivity. The dissymmetric probe has special calibration in liquid at different frequency. SATIMO conducts the probe calibration in compliance with international and national standards (e.g. IEEE 1528-2013 and relevant KDB files) Under ISO17025. The calibration data are in Appendix D.

Isotropic E-Field Probe Specification

Model	SSE5	
Manufacture	MVG	
Frequency	0.3GHz-3GHz Linearity:±0.12dB(300MHz-3GHz)	
Dynamic Range	0.01W/Kg-100W/Kg Linearity:±0.12dB	
Dimensions	Overall length:330mm Length of individual dipoles:4.5mm Maximum external diameter:8mm Probe Tip external diameter:5mm Distance between dipoles/ probe extremity:2.7mm	
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 3 GHz with precision of better 30%.	

3.3. Robot

The COMOSAR system uses the KUKA robot from SATIMO SA (France).For the 6-axis controller COMOSAR system, the KUKA robot controller version from SATIMO is used. The XL robot series have many features that are important for our application: High precision (repeatability 0.02 mm) High reliability (industrial design) Jerk-free straight movements Low ELF interference (the closed metallic construction shields against motor control fields) 6-axis controller	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

3.4. Video Positioning System

The video positioning system is used in OpenSAR to check the probe. Which is composed of a camera, LED, mirror and mechanical parts.The camera is piloted by the main computer with firewire link. During the process, the actual position of the probe tip with respect to the robot arm is measured, as well as the probe length and the horizontal probe offset. The software then corrects all movements, such that the robot coordinates are valid for the probe tip. The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned probe, the same position will be reached with another aligned probe within 0.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position.	

3.5. Device Holder

The COMOSAR device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR). Thus the device needs no repositioning when changing the angles. The COMOSAR device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity εr =3 and loss tangent δ = 0.02. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

3.6. SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region where shell thickness increases to 6mm). It has three measurement areas: Left head Right head Flat phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

4. SAR MEASUREMENT PROCEDURE

4.1. Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and occupational/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element(dv) of given mass density (ρ). The equation description is as below:

$$\mathrm{SAR} = \frac{\mathrm{d}}{\mathrm{d}t}\left(\frac{\mathrm{d}W}{\mathrm{d}m}\right) = \frac{\mathrm{d}}{\mathrm{d}t}\left(\frac{\mathrm{d}W}{\rho \mathrm{d}V}\right)$$

SAR is expressed in units of Watts per kilogram (W/Kg)
SAR can be obtained using either of the following equations:

$$\mathrm{SAR} = \frac{\sigma E^2}{\rho}$$

$$\mathrm{SAR} = c_h \left.\frac{\mathrm{d}T}{\mathrm{d}t}\right|_{t=0}$$

Where

SAR	is the specific absorption rate in watts per kilogram;
E	is the r.m.s. value of the electric field strength in the tissue in volts per meter;
σ	is the conductivity of the tissue in siemens per metre;
ρ	is the density of the tissue in kilograms per cubic metre;
c_h	is the heat capacity of the tissue in joules per kilogram and Kelvin;
$\frac{\mathrm{dT}}{\mathrm{dt}} \mid \mathrm{t} = 0$	is the initial time derivative of temperature in the tissue in kelvins per second

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

4.2. SAR Measurement Procedure

Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurement are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface is 2.7mm This distance cannot be smaller than the distance os sensor calibration points to probe tip as `defined in the probe properties,

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in SATIMO software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in db) is specified in the standards for compliance testing. For example, a 2db range is required in IEEE Standard 1528 and IEC62209 standards, whereby 3db is a requirement when compliance is assessed in accordance with the ARIB standard (Japan) If one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximum are detected, the number of Zoom Scan has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100MHz to 6GHz

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	½·δ·ln(2) ± 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: Δx_{Area}, Δy_{Area}	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

Step 3: Zoom Scan

Zoom Scan are used to assess the peak spatial SAR value within a cubic average volume containing 1g abd 10g of simulated tissue. The Zoom Scan measures points(refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1g and 10g and displays these values next to the job's label.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Zoom Scan Parameters extracted from KDB865664 d01 SAR Measurement 100MHz to 6GHz

Maximum zoom scan spatial resolution: Δx_{Zoom}, Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

Step 4: Power Drift Measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the same settings. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

4.3. RF Exposure Conditions

Test Configuration and setting:

The EUT is a model of DECT. For DECT SAR testing, the device was controlled through software to set fixed frequency, and then connected with RTX2012.

The distance between the EUT and the antenna is larger than 50cm, and the output power radiated from the antenna is at least 30db smaller than the output power of EUT.

Antenna Location: (back view)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

5. TISSUE SIMULATING LIQUID

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15cm. For head SAR testing the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15cm For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15cm.The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in 4.2

5.1. The composition of the tissue simulating liquid(% Weight)

Ingredient	1900MHz	1900MHz
(% Weight)	Head	Body
Water	54.9	40.4
Salt	0.18	0.5
Sugar	0.0	58.0
HEC	0.0	1.0
Bactericide	0.0	0.1
DGBE	44.92	0.0

5.2. Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE 1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in IEEE 1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in IEEE 1528.

Target Frequency (MHz)	**head**		**body**	
	εr	**σ (S/m)**	**εr**	**σ (S/m)**
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	1.01	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800–2000	**40.0**	**1.40**	**53.3**	**1.52**
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

(εr = relative permittivity, σ = conductivity and ρ = 1000 kg/m3)

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

5.3. Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using SATIMO Dielectric Probe Kit and R&S Network Analyzer ZVL6.

Tissue Stimulant Measurement for 1900MHz					
Head	Fr. (MHz)	Dielectric Parameters (±5%)		Tissue Temp [°C]	Test time
		εr40.00(38.00-42.00)	δ[s/m]1.40(1.33-1.47)		
	1900	40.81	1.38	21.3	Dec. 21,2015
	1925	39.62	1.43		Dec. 21,2015

Tissue Stimulant Measurement for 1900MHz					
Body	Fr. (MHz)	Dielectric Parameters (±5%)		Tissue Temp [°C]	Test time
		εr 53.30 50.635-55.965	δ[s/m] 1.52 1.444-1.596		
	1900	53.90	1.48	21.2	Dec. 21,2015
	1925	53.02	1.50		Dec. 21,2015

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

6. SAR SYSTEM CHECK&VALIDATION PROCEDURE

6.1. SAR System Check Procedures

SAR system check is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are remeasured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

Each SATIMO system is equipped with one or more system check kits. These units, together with the predefined measurement procedures within the SATIMO software, enable the user to conduct the system check and system validation. System kit includes a dipole, and dipole device holder.

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system check setup is shown as below.





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

6.2. SAR System Check

6.2.1. Dipoles



The dipoles used is based on the IEEE-1528 standard, and is complied with mechanical and electrical specifications in line with the requirements of IEEE. the table below provides details for the mechanical and electrical
Specifications for the dipoles.

Frequency	L (mm)	h (mm)	d (mm)
1900MHz	68	39.5	3.6

6.2.2. System Check Result

System Performance Check at 1900MHz											
Validation Kit: SN 46/11DIP 1G900-187											
Freq. [MHz]	Target Value(W/Kg)		Reference Result (± 10%)		Tested SAR Value(W/Kg) Input Power=18dBm		Normalized to 1W (W/Kg)		Tissue Temp. [°C]	Test time
	1g	10g	1g	10g	1g	10g	1g	10g		
1900 Head	39.65	20.24	35.685-43.615	18.216-22.264	2.485	1.290	39.38	20.45	21.3	Dec. 21,2015
1900 Body	40.74	21.43	36.666-44.814	19.287-23.573	2.574	1.335	40.79	21.16	21.2	Dec. 21,2015

Note:

(1) We use a CW signal of 18dBm for system check, and then all SAR value are normalized to 1W forward power. The result must be within ±10% of target value.

(2) Tested normalized SAR (W/kg) = Tested SAR (W/kg) ×[1000/ 10^1.8]

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

6.3. SAR System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01.
SAR probe and tissue dielectric parameters are as shown bellow.

Test Data	Probe S/N	Tested Freq. (MHz)	Tissue Type	Cond.	Perm	CW validation			Mod. validation		
						Sensitivity	Probe Linearity	Probe Isotropy	Mod. Type	Duty Factor	Peak to average power ratio
20/11/2015	SN 19/15 EP254	1900	head	40.08	1.43	PASS	PASS	PASS	GFSK	PASS	N/A
21/11/2015	SN 19/15 EP254	1900	body	54.37	1.55	PASS	PASS	PASS	GFSK	PASS	N/A

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

7. EUT TEST POSITION

This EUT was tested in **Right Cheek, Right Titled, Left Cheek, Left Titled, Body back, Body front and Face up.**

7.1. Body Part Position

(1) To position the EUT parallel to the phantom surface.

(2) To adjust the EUT parallel to the flat phantom.

(3) To adjust the distance between the EUT surface and the flat phantom to **0mm for body back touch and body front, Face up with 25mm.**





The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

8. SAR EXPOSURE LIMITS

SAR assessments have been made in line with the requirements of IEEE-1528, and comply with ANSI/IEEE C95.1-1992 “Uncontrolled Environments” limits. These limits apply to a location which is deemed as “Uncontrolled Environment” which can be described as a situation where the general public may be exposed to an RF source with no prior knowledge or control over their exposure.

Limits for General Population/Uncontrolled Exposure (W/kg)

Type Exposure	Uncontrolled Environment Limit (W/kg)
Spatial Peak SAR (1g cube tissue for brain or body)	1.60
Spatial Average SAR (Whole body)	0.08
Spatial Peak SAR (Limbs)	4.0

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

9. TEST EQUIPMENT LIST

Equipment description	Manufacturer/ Model	Identification No.	Current calibration date	Next calibration date
SAR Probe	MVG	SN 19/15 EP254	07/10/2015	07/09/2016
TISSUE Probe	SATIMO	SN 45/11 OCPG45	12/02/2015	12/01/2016
Phantom	SATIMO	SN_4511_SAM90	Validated. No cal required.	Validated. No cal required.
Liquid	SATIMO	-	Validated. No cal required.	Validated. No cal required.
Multimeter	Keithley 2000	1188656	03/06/2015	03/05/2016
Comm Tester	RTX 2012HS-RF	1239-6203	10/20/2015	10/19/2016
Dipole	SATIMO SID1900	SN46/11 DIP 1G900-187	11/14/2013	11/13/2016
Signal Generator	Agilent-E4438C	MY44260051	03/06/2015	03/05/2016
Spectrum Analyzer E4440	Agilent	US41421290	07/23/2015	07/22/2016
Network Analyzer	Rhode & Schwarz ZVL6	SN100132	03/06/2015	03/05/2016
Attenuator	Warison /WATT-6SR1211	N/A	N/A	N/A
Attenuator	Mini-circuits / VAT-10+	N/A	N/A	N/A
Amplifier	EM30180	SN060552	03/06/2015	03/05/2016
Directional Couple	Werlatone/ C6026-10	SN99482	07/29/2015	07/28/2016
Power Sensor	NRP-Z21	1137.6000.02	10/20/2015	10/19/2016
Power Sensor	NRP-Z23	US38261498	03/06/2015	03/05/2016
Power Viewer	R&S	V2.3.1.0	N/A	N/A

Note: Per KDB 865664 Dipole SAR Validation, AGC Lab has adopted 3 years calibration intervals. On annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:
1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss is within 20% of calibrated measurement;
4. Impedance is within 5Ω of calibrated measurement.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

10. MEASUREMENT UNCERTAINTY

SATIMO Uncertainty Measurement uncertainty for 300 MHz to 3 GHz averaged over 1 gram / 10 gram.									
Uncertainty Component	Sec.	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System									
Probe calibration	E.2.1	5.831	N	1	1	1	5.83	5.83	∞
Axial Isotropy	E.2.2	2.5	R	$\sqrt{3}$	1	1	1.44	1.44	∞
Hemispherical Isotropy	E.2.2	4.0	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	E.2.4	2.81	R	$\sqrt{3}$	1	1	1.62	1.62	∞
System detection limits	E.2.5	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Readout Electronics	E.2.6	0.02	N	1	1	1	0.02	0.02	∞
Response Time	E.2.7	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Integration Time	E.2.8	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
RF ambient Conditions	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Probe positioning with respect to Phantom Shell	E.6.3	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Extrapolation, interpolation and integration Algoritms for Max. SAR Evaluation	E.5.2	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Test sample Related									
Test sample positioning	E.4.2.1	0.03	N	1	1	1	0.03	0.03	N-1
Device Holder Uncertainty	E.4.1.1	5.00	N	1	1	1	5.00	5.00	∞
Output power Variation - SAR drift measurement	6.6.2	0.65	R	$\sqrt{3}$	1	1	0.38	0.38	∞
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Liquid conductivity deviation from target value	E.3.2	5.00	R	$\sqrt{3}$	0.64	0.43	1.85	1.24	∞
Liquid conductivity - measurement uncertainty	E.3.3	5.00	N	1	0.64	0.43	3.20	2.15	∞
Liquid permittivity - deviation from target value	E.3.2	0.03	R	$\sqrt{3}$	0.6	0.49	0.01	0.01	∞
Liquid permittivity - measurement uncertainty	E.3.3	10.00	N	1	0.6	0.49	6.00	4.90	M
Combined Standard Uncertainty			RSS				10.27	9.68	∞
Expanded Uncertainty (95% Confidence interval)			k				20.53	19.37	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

SATIMO Uncertainty

System uncertainty for 300 MHz to 3 GHz averaged over 1 gram / 10 gram.

Uncertainty Component	Sec.	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System									
Probe calibration	E.2.1	5.831	N	1	1	1	5.83	5.83	∞
Axial Isotropy	E.2.2	2.5	R	$\sqrt{3}$	1	1	1.44	1.44	∞
Hemispherical Isotropy	E.2.2	4.0	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Boundary Effects	E.2.3	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	E.2.4	2.81	R	$\sqrt{3}$	1	1	1.62	1.62	∞
System detection limits	E.2.5	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Readout Electronics	E.2.6	0.02	N	1	1	1	0.02	0.02	∞
Response Time	E.2.7	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Integration Time	E.2.8	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
RF ambient Conditions	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Probe positioning with respect to Phantom Shell	E.6.3	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Extrapolation, interpolation and integration Algoritms for Max. SAR Evaluation	E.5.2	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Dipole									
Dipole axis to liquid Distance	8,E.4.2	1.00	N	$\sqrt{3}$	1	1	0.58	0.58	N-1
Input power and SAR drift measurement	8,6.6.2	0.65	R	$\sqrt{3}$	1	1	0.38	0.38	∞
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Liquid conductivity - deviation from target value	E.3.2	5.00	R	$\sqrt{3}$	0.64	0.43	1.85	1.24	∞
Liquid conductivity - measurement uncertainty	E.3.3	5.00	N	1	0.64	0.43	3.20	2.15	∞
Liquid permittivity - deviation from target value	E.3.2	0.03	R	$\sqrt{3}$	0.6	0.49	0.01	0.01	∞
Liquid permittivity - measurement uncertainty	E.3.3	10.00	N	1	0.6	0.49	6.00	4.90	M
Combined Standard Uncertainty			RSS				8.99	8.31	
Expanded Uncertainty (95% Confidence interval)			k				17.97	16.62	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

11. CONDUCTED POWER MEASUREMENT

DECT BAND

Battery Model- CR1530

Mode	Frequency (MHz)	Maximum Peak Conducted Power (dBm)
DECT	1928.448	19.5
	1926.720	19.5
	1924.992	19.5
	1923.264	19.6
	1921.536	**19.6**

Battery Model- GP1249

Mode	Frequency (MHz)	Maximum Peak Conducted Power (dBm)
DECT	1928.448	19.4
	1926.720	19.4
	1924.992	19.3
	1923.264	19.5
	1921.536	**19.5**

Battery Model- GY1516

Mode	Frequency (MHz)	Maximum Peak Conducted Power (dBm)
DECT	1928.448	19.4
	1926.720	19.3
	1924.992	19.3
	1923.264	19.5
	1921.536	**19.5**

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

12. TEST RESULTS

12.1. SAR Test Results Summary

12.1.1. Test position and configuration

Head SAR was performed with the device configured in the positions according to IEEE 1528-2013

12.1.2. Operation Mode

1. Per KDB 447498 D01 v06, for each exposure position, if the highest 1-g SAR is ≤ 0.8 W/kg, testing for low and high channel is optional.
2. Per KDB 865664 D01 v01r04,for each frequency band, if the measured SAR is ≥0.8W/Kg, testing for repeated SAR measurement is required , that the highest measured SAR is only to be tested. When the SAR results are near the limit, the following procedures are required for each device to verify these types of SAR measurement related variation concerns by repeating the highest measured SAR configuration in each frequency band.
   (1) When the original highest measured SAR is ≥0.8W/Kg, repeat that measurement once.
   (2) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is ＞1.20 or when the original or repeated measurement is ≥1.45 W/Kg.
   (3) Perform a third repeated measurement only if the original, first and second repeated measurement is ≥1.5 W/Kg and ratio of largest to smallest SAR for the original, first and second measurement is ≥ 1.20.
3. Maximum Scaling SAR in order to calculate the Maximum SAR values to test under the standard Peak Power, Calculation method is as follows:
   Maximum Scaling SAR =tested SAR (Max.) ×[maximum turn-up power (mw)/ maximum measurement output power(mw)]
4. DECT has a TDD/TDMA frame structure with a complete frame of 10ms duration with 24 time slots. And under these 24 time slots, the first 12 slots are allocated for the transmission from base station to handsets, and the other 12 slots are for the transmission from handsets to base station. During a call, this product will use one of 24 time slots to transmit under worst case, which gives a duty cycle of 1/24 (= 4.2%).

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

12.1.3. Test Result

SAR MEASUREMENT									
Depth of Liquid (cm):>15				Relative Humidity (%): 52.4					
Product: DECT 6.0 Cordless Telephone Handset									
Test Model: CLP99286									
Position	**Mode**	**Ch.**	**Fr. (MHz)**	**Power Drift (<±5%)**	**SAR (1g) (W/kg)**	**Max. Turn-up Power (dBm)**	**Meas. output Power (dBm)**	**Scaled SAR (W/Kg)**	**Limit W/kg**
Battery Model-CR1530									
Left Cheek	voice	2	1924.992	-0.22	0.042	21	19.5	0.059	1.6
Left Tilt	voice	2	1924.992	1.02	0.034	21	19.5	0.048	1.6
Right Cheek	voice	2	1924.992	-0.32	**0.044**	21	19.5	**0.062**	1.6
Right Tilt	voice	2	1924.992	0.02	0.030	21	19.5	0.042	1.6
Body Back With 0mm	voice	2	1924.992	0.12	0.014	21	19.5	0.020	1.6
Body Front With 0mm	voice	2	1924.992	-1.30	**0.038**	21	19.5	**0.054**	1.6
Face up With 25mm	voice	2	1924.992	-0.02	0.016	21	19.5	0.023	1.6
Battery Model-GP1249									
Left Cheek	voice	2	1924.992	-0.12	**0.045**	21	19.3	**0.067**	1.6
Left Tilt	voice	2	1924.992	-1.02	0.032	21	19.3	0.047	1.6
Right Cheek	voice	2	1924.992	0.32	0.041	21	19.3	0.061	1.6
Right Tilt	voice	2	1924.992	0.05	0.031	21	19.3	0.046	1.6
Body Back With 0mm	voice	2	1924.992	-1.02	0.017	21	19.3	0.025	1.6
Body Front With 0mm	voice	2	1924.992	0.02	**0.040**	21	19.3	**0.059**	1.6
Face up With 25mm	voice	2	1924.992	0.32	0.018	21	19.3	0.027	1.6
Battery Model-GY1516									
Left Cheek	1voice	2	1924.992	-0.02	0.037	21	19.3	0.055	1.6
Left Tilt	voice	2	1924.992	0.32	0.031	21	19.3	0.046	1.6
Right Cheek	voice	2	1924.992	1.02	**0.042**	21	19.3	**0.062**	1.6
Right Tilt	voice	2	1924.992	-0.02	0.030	21	19.3	0.044	1.6
Body Back With 0mm	voice	2	1924.992	-0.32	0.017	21	19.3	0.025	1.6
Body Front With 0mm	voice	2	1924.992	0.15	**0.039**	21	19.3	**0.058**	1.6
Face up With 25mm	voice	2	1924.992	-1.02	0.022	21	19.3	0.033	1.6

Note:
(1).When the 1-g Reported SAR is ≤ 0.8 W/kg, testing for low and high channel is optional. Refer to KDB 447498.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

APPENDIX A. SAR SYSTEM CHECK DATA

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
System Check Head 1900MHz
DUT: Dipole 1900 MHz; Type: SID 1900
Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Duty Cycle:1:1; Conv.F=5.40;
Frequency: 1900 MHz; Medium parameters used: f = 1900 MHz; σ=1.38 mho/m; εr =40.81; ρ= 1000 kg/m³ ;
Phantom section: Flat Section; Input Power=18dBm
Ambient temperature (℃)21.4, Liquid temperature (℃):21.3

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration/System Check 1900 Head/Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/System Check 1900 Head/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm

SURFACE SAR	VOLUME SAR
	

Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	1.290289
SAR 1g (W/Kg)	2.485482

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	2.6338	1.4216	0.7924	0.4471	0.2545	0.1464



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
System Check Body 1900MHz
DUT: Dipole 1900 MHz; Type: SID 1900
Communication System: CW; Communication System Band: D1900 (1900.0 MHz); Duty Cycle:1:1; Conv.F=5.61
Frequency: 1900 MHz; Medium parameters used: f = 1900 MHz; σ=1.48 mho/m; εr =53.90; ρ= 1000 kg/m³ ;
Phantom section: Flat Section; Input Power=18dBm
Ambient temperature (℃):21.4, Liquid temperature (℃):21.2

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration/System Check 1900 Body/Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/System Check 1900 Body/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm

SURFACE SAR	VOLUME SAR
	

Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	1.334719
SAR 1g (W/Kg)	2.573859

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	2.7277	1.4690	0.8195	0.4617	0.2637	0.1515



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

APPENDIX B. SAR MEASUREMENT DATA

Battery Model- CR1530
Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid-Touch- Left
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.40;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.43 mho/m; εr =39.62; ρ= 1000 kg/m³ ;
Phantom section: Left Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.3

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration/1900 Mid-Touch- Left /Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid-Touch- Left t/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Left head
Device Position	Cheek
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-11.00, Y=0.00

SAR 10g (W/Kg)	0.024039
SAR 1g (W/Kg)	0.042086

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0452	0.0270	0.0160	0.0102	0.0102	0.0102



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid- Tilt-Left
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.40;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.43 mho/m; εr =39.62; ρ= 1000 kg/m³ ;
Phantom section: Left Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.3

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration/1900 Mid- Tilt-Left /Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid- Tilt-Left /Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Left head
Device Position	Tilt
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-10.00, Y=0.00

SAR 10g (W/Kg)	0.019464
SAR 1g (W/Kg)	0.033813

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0361	0.0211	0.0123	0.0102	0.0102	0.0102



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid-Touch-Right
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.40;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.43 mho/m; εr =39.62; ρ= 1000 kg/m³ ;
Phantom section: Right Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.3

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration/1900 Mid-Touch-Right/Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid-Touch-Right/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-9.00, Y=-1.00

SAR 10g (W/Kg)	0.023029
SAR 1g (W/Kg)	0.043940

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0453	0.0223	0.0102	0.0102	0.0102	0.0102



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid- Tilt -Right
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.40;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.43 mho/m; εr =39.62; ρ= 1000 kg/m³ ;
Phantom section: Right Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.3

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration/1900 Mid- Tilt -Right/Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid- Tilt -Right/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Tilt
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-10.00, Y=1.00

SAR 10g (W/Kg)	0.016277
SAR 1g (W/Kg)	0.029673

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0290	0.0136	0.0102	0.0102	0.0102	0.0102



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid-Body-Back
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.61;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.50 mho/m; εr =53.02; ρ= 1000 kg/m³ ;
Phantom section: Flat Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.2

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration1900 Mid-Body-Back/Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid-Body-Back/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	surf_sam_plan.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body Back
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=7.00, Y=-11.00

SAR 10g (W/Kg)	0.011742
SAR 1g (W/Kg)	0.014136

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0144	0.0111	0.0111	0.0111	0.0111	0.0111



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid-Body- Front
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.61;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.50 mho/m; εr =53.02; ρ= 1000 kg/m³ ;
Phantom section: Flat Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.2

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration1900 Mid-Body- Front /Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid-Body- Front /Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	surf_sam_plan.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body Front
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=1.00, Y=-17.00

SAR 10g (W/Kg)	0.019389
SAR 1g (W/Kg)	0.037812

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0385	0.0204	0.0113	0.0111	0.0111	0.0111



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid-Face up
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.40;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.43 mho/m; εr =39.62; ρ= 1000 kg/m³ ;
Phantom section: Flat Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.3

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration1900 Mid -Face up /Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid- Face up /Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	surf_sam_plan.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Face up
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-2.00, Y=6.00

SAR 10g (W/Kg)	0.011891
SAR 1g (W/Kg)	0.016445

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0161	0.0102	0.0102	0.0102	0.0102	0.0102



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Battery Model- GP1249
Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid-Touch- Left
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.40;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.43 mho/m; εr =39.62; ρ= 1000 kg/m³ ;
Phantom section: Left Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.3

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration/1900 Mid-Touch- Left /Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid-Touch- Left t/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Left head
Device Position	Cheek
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-15.00, Y=0.00

SAR 10g (W/Kg)	0.024576
SAR 1g (W/Kg)	0.044633

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0476	0.0279	0.0165	0.0102	0.0102	0.0102



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid- Tilt-Left
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.40;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.43 mho/m; εr =39.62; ρ= 1000 kg/m³ ;
Phantom section: Left Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.3

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration/1900 Mid- Tilt-Left /Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid- Tilt-Left /Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Left head
Device Position	Tilt
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-14.00, Y=0.00

SAR 10g (W/Kg)	0.018272
SAR 1g (W/Kg)	0.031510

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0334	0.0200	0.0116	0.0102	0.0102	0.0102



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid-Touch-Right
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.40;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.43 mho/m; εr =39.62; ρ= 1000 kg/m³ ;
Phantom section: Right Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.3

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration/1900 Mid-Touch-Right/Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid-Touch-Right/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-8.00, Y=-2.00

SAR 10g (W/Kg)	0.021892
SAR 1g (W/Kg)	0.041438

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0431	0.0219	0.0105	0.0102	0.0102	0.0102



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid- Tilt -Right
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.40;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.43 mho/m; εr =39.62; ρ= 1000 kg/m³ ;
Phantom section: Right Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.3

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration/1900 Mid- Tilt -Right/Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid- Tilt -Right/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Tilt
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-7.00, Y=1.00

SAR 10g (W/Kg)	0.016727
SAR 1g (W/Kg)	0.030774

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0306	0.0134	0.0102	0.0102	0.0102	0.0102



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid-Body-Back
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.61;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.50 mho/m; εr =53.02; ρ= 1000 kg/m³ ;
Phantom section: Flat Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.2

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration1900 Mid-Body-Back/Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid-Body-Back/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	surf_sam_plan.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body Back
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=7.00, Y=-6.00

SAR 10g (W/Kg)	0.012502
SAR 1g (W/Kg)	0.016761

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0168	0.0111	0.0111	0.0111	0.0111	0.0111



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid-Body- Front
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.61;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.50 mho/m; εr =53.02; ρ= 1000 kg/m³ ;
Phantom section: Flat Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.2

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration1900 Mid-Body- Front /Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid-Body- Front /Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	surf_sam_plan.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body Front
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=1.00, Y=-15.00

SAR 10g (W/Kg)	0.020574
SAR 1g (W/Kg)	0.040096

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0421	0.0221	0.0111	0.0111	0.0111	0.0111



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid-Face up
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.40;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.43 mho/m; εr =39.62; ρ= 1000 kg/m³ ;
Phantom section: Flat Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.3

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration1900 Mid -Face up /Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid- Face up /Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	surf_sam_plan.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Face up
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=0.00, Y=8.00

SAR 10g (W/Kg)	0.012587
SAR 1g (W/Kg)	0.018429

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0178	0.0102	0.0102	0.0102	0.0102	0.0102



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Battery Model- GY1516
Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid-Touch- Left
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.40;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.43 mho/m; εr =39.62; ρ= 1000 kg/m³ ;
Phantom section: Left Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.3

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration/1900 Mid-Touch- Left /Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid-Touch- Left t/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Left head
Device Position	Cheek
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-7.00, Y=1.00

SAR 10g (W/Kg)	0.021347
SAR 1g (W/Kg)	0.036850

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0393	0.0243	0.0145	0.0102	0.0102	0.0102



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid- Tilt-Left
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.40;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.43 mho/m; εr =39.62; ρ= 1000 kg/m³ ;
Phantom section: Left Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.3

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration/1900 Mid- Tilt-Left /Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid- Tilt-Left /Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Left head
Device Position	Tilt
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-7.00, Y=1.00

SAR 10g (W/Kg)	0.018276
SAR 1g (W/Kg)	0.031242

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0333	0.0200	0.0116	0.0102	0.0102	0.0102



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid-Touch-Right
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.40;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.43 mho/m; εr =39.62; ρ= 1000 kg/m³ ;
Phantom section: Right Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.3

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration/1900 Mid-Touch-Right/Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid-Touch-Right/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-9.00, Y=-2.00

SAR 10g (W/Kg)	0.021981
SAR 1g (W/Kg)	0.041972

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0433	0.0214	0.0102	0.0102	0.0102	0.0102



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid- Tilt -Right
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.40;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.43 mho/m; εr =39.62; ρ= 1000 kg/m³ ;
Phantom section: Right Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.3

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration/1900 Mid- Tilt -Right/Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid- Tilt -Right/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	sam_direct_droit2_surf8mm.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Tilt
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-8.00, Y=0.00

SAR 10g (W/Kg)	0.016222
SAR 1g (W/Kg)	0.029722

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0294	0.0128	0.0102	0.0102	0.0102	0.0102



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid-Body-Back
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.61;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.50 mho/m; εr =53.02; ρ= 1000 kg/m³ ;
Phantom section: Flat Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.2

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration1900 Mid-Body-Back/Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid-Body-Back/Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	surf_sam_plan.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body Back
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=7.00, Y=-13.00

SAR 10g (W/Kg)	0.012458
SAR 1g (W/Kg)	0.016583

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0166	0.0111	0.0111	0.0111	0.0111	0.0111



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid-Body- Front
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.61;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.50 mho/m; εr =53.02; ρ= 1000 kg/m³ ;
Phantom section: Flat Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.2

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration1900 Mid-Body- Front /Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid-Body- Front /Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	surf_sam_plan.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body Front
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=0.00, Y=-14.00

SAR 10g (W/Kg)	0.020186
SAR 1g (W/Kg)	0.038993

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0407	0.0212	0.0111	0.0111	0.0111	0.0111



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Test Laboratory: AGC Lab **Date: Dec. 21,2015**
DECT 1900 Mid-Face up
DUT: DECT 6.0 CORDLESS PHONE HANDSET; Type: CLP99286

Communication System: DECT; Communication System Band: 1900; Duty Cycle: 4.3%; Conv.F=5.40;
Frequency: 1924.992 MHz; Medium parameters used: f = 1900 MHz; σ= 1.43 mho/m; εr =39.62; ρ= 1000 kg/m³ ;
Phantom section: Flat Section
Ambient temperature (℃): 21.4, Liquid temperature (℃): 21.3

SATIMO Configuration:
Probe: SSE5; Calibrated: 07/10/2015; Serial No.: SN 19/15 EP254
Sensor-Surface: 4mm (Mechanical Surface Detection)
Phantom: SAM twin phantom
Measurement SW: OpenSAR V4_02_01

Configuration1900 Mid -Face up /Area Scan: Measurement grid: dx=8mm, dy=8mm
Configuration/1900 Mid- Face up /Zoom Scan: Measurement grid: dx=8mm,dy=8mm, dz=5mm;

Area Scan	surf_sam_plan.txt
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Face up
Band	DECT
Channels	Middle
Signal	Crest factor: 23

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-1.00, Y=0.00

SAR 10g (W/Kg)	0.013757
SAR 1g (W/Kg)	0.021805

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	0.0216	0.0127	0.0102	0.0102	0.0102	0.0102



3D screen shot	Hot spot position
	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

APPENDIX C. TEST SETUP PHOTOGRAPHS &EUT PHOTOGRAPHS

Refer to Attached files.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com

APPENDIX D. CALIBRATION DATA

Refer to Attached files.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at http://www.agc-cert.com