


OVERVIEW - BABY UNIT



SOUND SENSITIVITY AND SOUND ACTIVATION

Adjust sound detection sensitivity

With sound sensitivity setting, you can choose to hear sounds from the baby unit all the time, or to hear sounds that exceed a certain level.

Sound level	Sound level	Sound level	Sound level
Low	Medium	High	Very High

The default setting is **Low**. To adjust the sound sensitivity, press the **Sound** button on the baby unit.

Sound activated screen

When the sound sensitivity is set to **High** or **Very High**, the screen will turn on automatically when the baby unit detects sound. Once the baby unit detects sound, the screen will turn on automatically. If it is not busy, the screen will turn on automatically. If it is busy, the screen will turn on automatically after 10 seconds of no sound detection.

NIGHT VISION

The baby unit has infrared LEDs that allow you to see your baby clearly at night in a dark room. When the baby unit is powered on, the infrared LEDs are activated automatically. The image from the baby unit is visible on the screen.

DIM MODE

With dim mode preset to **on**, your screen on display will dim its screen energy after 10 minutes of inactivity, in which time a control key presentation about received from the baby unit.

Note: If you do not want LEDs to turn on automatically, turn off the Dim Mode.

MOUNT THE BABY UNIT ON DRY WALL (OPTIONAL)

Items to purchase

You will need to purchase the following items according to mount your baby unit:

- 2 screws
- 2 anchors

Note: The type of screw and anchor you need depends on the material of the wall.

Step 1: Drill two holes in the wall. If you drill the holes into a stud, go to step 2.

Step 2: Press all the holes into an object other than a stud. Insert the wall anchors into the holes. Tap gently on the ends with a hammer until the wall anchors are flush with the surface of the wall. Use the baby unit down until it fits into place.

Step 3: Depending on your preference, choose the appropriate level of the screen to mount your unit. Align the wall mount holes of the bottom of the baby unit with the anchors on the wall. Use the baby unit down until it fits into place.

Step 4: Tighten the screws to adjust camera angle.

For VM5251-2 ONLY

Status check = Two baby units

If you are viewing baby unit **1**, the **POWER** LED light of baby unit **2** turns on. Actually, unit **2** is not being viewed, its **POWER** LED light flashes.

Change different views = Single-CAM

In **Single-CAM** or **Patrol** mode, press **VIEW** to switch between the image of baby unit **1** and **2**.

Change different views = Patrol

Select **Patrol** your monitoring mode to alternately view the image from baby unit **1** and **2** every 10 seconds.

Change different views = Split

Select **Split** as your monitoring mode to view the image from both baby unit at once.

Note: If you connect an LED light to the unit, you may see light when the screen is off. The light is not a problem. It is a normal function of the unit. If you want to turn off the light, press **VIEW** in **Single-CAM** or **Patrol** mode to turn it off.