


© 2011 Intel Corporation. Intel, the Intel logo, and other marks contained herein are trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

TECHNICAL SPECIFICATIONS

Press and hold **TALK** and speak to your parent unit. Your voice is transmitted to the baby unit. Release **TALK** when finish talking and hear your baby again.

For more support information:


[illegible]

The diagram consists of two line drawings of a walkie-talkie. The left drawing shows the front view, and the right drawing shows the back view. Numbered callouts (1-14) point to specific features on both views.

- Front View (Left):**
 - 1: LED lights (top left)
 - 2: LCD display (center)
 - 3: Microphone (top right)
 - 4: POWER button (bottom left)
 - 5: TALK button (bottom left)
 - 6: MENU/SELECT button (center)
 - 7: Arrow keys (center)
 - 8: Volume knob (center)
 - 9: VIEW / LCD ON/OFF button (bottom right)
- Back View (Right):**
 - 10: @/EXIT button (top right)
 - 11: Antenna (top)
 - 12: RESET button (center)
 - 13: Stand (bottom)
 - 14: Power Jack (bottom right)

NOTES

- The rechargeable battery in the parent unit is built-in.
- Use only the power adapters supplied with this product.
- Make sure the baby monitor is *not* connected to a switch-controlled electric outlet.
- Connect the power adapters in a vertical or floor mount position only. The adapters' prongs are not designed to hold the weight of baby monitor, so do not connect them to any ceiling, under-the-table, or cabinet outlets. Otherwise, the adapters may not properly connect to the outlets.
- Make sure the parent unit, the baby units and the power adapter cords are out of reach of children.



The diagram illustrates the components of the baby unit. It includes three views: a front view of the unit with the top cover open, a side view, and a top-down view of the internal components. The numbered callouts are as follows:

- 1: Light sensor (pointing to the sensor on the top cover)
- 2: Camera lens (pointing to the lens on the top cover)
- 3: Microphone (pointing to the mic on the top cover)
- 4: Night light (pointing to the light on the top cover)
- 5: On/Off switch (pointing to the switch on the side of the unit)
- 6: On/Off LED light (pointing to the LED light on the side of the unit)
- 7: Speaker (pointing to the speaker grille on the side of the unit)
- 8: Night light on/off key (pointing to the key on the top cover)
- 9: Power jack (pointing to the jack on the side of the unit)
- 10: Slots for wall mounting (pointing to the mounting slots on the back of the unit)

For operators and guides to help you using your video monitor, and for latest information and support, go and check the online help topics and online FAQs.

Use your smartphone or mobile device to access our online help.

Go to <https://help.vtechphones.com/VM5263> or <https://help.vtechphones.com/VM5263-2>

Scan the QR code on the right. Launch the camera app or QR code scanner app on your smartphone or tablet. Hold the device's camera up to the QR code and frame it. Tap the notification to trigger the redirection of the online help.

If the QR code is not clearly displayed, adjust your camera's focus by moving your device closer or further away until the QR code is clear.

You can also call our Customer Support at 1 (800) 995-9512 [in US] or 1 (800) 267-3777 [in Canada].

VM5263

VM5263-2

1 Slide the switch to power on or off your baby unit.

The diagram illustrates the power switch on the baby unit. The unit is a white dome-shaped camera on a base. A callout shows the switch being slid to the 'Power on' position (indicated by a left arrow). Another callout shows the switch being slid to the 'Power off' position (indicated by a right arrow).

1. The default volume of your parent unit is level 4, and the maximum volume is level 7. If you experience high-pitched screeching noise from your baby monitor while positioning:

- Make sure your baby unit and parent unit are more than 3 feet (2 meter) apart, OR
- Lower the volume of your parent unit.

2. The parent unit should be placed at least 3 feet (1 meter) away from the baby unit.

3. The parent unit should be placed at least 3 feet (1 meter) away from the baby unit.

4. The parent unit should be placed at least 3 feet (1 meter) away from the baby unit.

NOTE

- To avoid interference from other electronic devices, place your baby monitor at least 3 feet (2 meter) away from devices such as wireless routers, microwaves, cell phones and computers.

Once you power on both your baby unit and parent unit, your parent unit displays image from the baby unit, and the **LINK** LED light turns on.

The **ON** LED light of baby unit turns on.

The diagram illustrates the connection between the baby unit and the parent unit. On the left, the baby unit is shown with a green 'LINK' LED light illuminated. A wireless signal is represented by a curved line connecting it to the parent unit on the right. The parent unit's screen displays the video feed from the baby unit, showing a baby's face. The parent unit also has a green 'LINK' LED light illuminated.

Main menu icons			
Main menu	Sub-menu	Main menu	Sub-menu
Brightness Adjust the parent unit's LCD brightness.		Night light ON/OFF Turn on/off night light - Select one of the night light colors. - Change to all seven colors in cycles. - Set timer to turn the night light off. OFF - Select to set the night light to always on. AUTO - Set to auto turn on the night light when baby unit detects sound. It will turn off after 15 minutes of no sound detection. You can set VOX sensitivity level to detect sounds that exceed certain levels. See Sound sensitivity and sound activation section.	
Camera settings Baby unit speaker volume - Adjust the baby unit's speaker volume. Monitoring mode (For VMS263-2 only) Single mode Split mode Patrol mode		Alert tones - Set the parent unit to beep when the battery is low. - Set the parent unit to beep when the link between the parent unit and the baby unit is lost. - Set the confirmation tone on or off when selecting an option in the menus. - Set the parent unit to beep when the baby unit detects sounds while in Split mode (For VMS263-2 only).	
Library Play/Stop library - Select one of the soothing sounds, or white noise. - Select one of the five melodies. - Play all melodies. 60min 45min 30min 15min - Set timer to stop playing the selected melody or soothing sound.		Sound activation - screen and audio ON/OFF Turn on/off sound activation - Set sound activation on or off. - When it is on, and the baby unit detects no sound, the parent unit screen stays off to save power. Once a sound is detected, the parent unit screen and speaker turn on automatically, and you can see and hear your baby. The parent unit will then turn off again after 50 seconds of no sound detection. NOTE - When the parent unit screen is off and it receives alerts, for example, link lost between parent unit and baby unit, or battery is low, the parent unit screen and speaker will turn on for 10 seconds.	
Temperature ON/OFF - Turn on/off temperature alert tone. - Set the parent unit to beep whenever the room temperature detected by the baby unit falls outside of the set temperature range. - Set the minimum temperature. - Set the maximum temperature. - Set temperature display in Fahrenheit (°F) or Celsius (°C).		VOX (Voice Activated Alert) Sensitivity Also set VOX sensitivity level to activate parent unit screen and sound when baby unit detects sounds that exceed certain levels. See Sound sensitivity and sound activation section.	

Status icons	Status icons	Alert icons
Connection status - Strong signal strength. - Moderate signal strength. - Low signal strength. - Weak signal strength.	F or °C Real-time temperature - Real-time temperature detected by the baby unit in Fahrenheit (°F) or Celsius (°C) (e.g. 57°F or 14°C). Temperature alert tone - On 9-level sound indicator - indicates low sound level detected by the baby unit. - indicates moderate sound level detected by the baby unit. - indicates high sound level detected by the baby unit. Mute alert - Displays when the parent unit speaker volume is set to off. - Displays when the parent unit is talking to the baby unit. Battery status - animates when the battery is charging. - battery is fully charged. - battery is low and needs charging.	- Displays when parent unit's battery is low and needs charging. - Displays when connection between parent unit and baby unit is lost. - Displays when sound is detected at a baby unit when in Split view. (*For VMS263-2 only) - Baby unit detects temperature reaches or exceeds the set maximum. - Baby unit detects temperature is at or is lower than the set minimum.
Split mode (*For VMS263-2 only) Patrol mode (*For VMS263-2 only) Current view status - The baby unit number that is being viewed when in: Single CAM mode. Patrol mode (*For VMS263-2 only) Split mode (*For VMS263-2 only) Night vision - On Zoom - On Lullaby - On Night light - On Night light - Auto-on - Color icon indicates the night light is set to auto-on, and is currently turned on by sound activation. - Gray icon indicates the night light is currently off but is set to auto-on. Night light will turn on when sound is detected by the baby unit.		

Adjust sound detection sensitivity

You can turn on **Sound activation** and adjust the **VOX sensitivity** to detect sounds and the **VOX sensitivity** to turn the parent unit while its screen is switched off or dimmed.

When the baby unit detects sounds that exceed certain levels, the parent unit screen will turn on and the baby unit starts transmitting the sounds to the parent unit, and you can see and hear your baby. If you have turned on the **Night Light Auto-on** feature, it will turn on automatically to soothe your baby.

If you turn off **Sound activation**, you will hear sounds from the baby unit all the time, even when the parent unit screen is switched off.

If you have turned on sound alert, the parent unit beeps when the baby unit detect sounds while in **Split mode** (*For VM323-2 only).

VOX SENSITIVITY LEVEL	Default setting	The parent unit screen and speaker turn on for very small sounds, including background noises from your baby's room.	The parent unit screen and speaker turn on for soft babbling and louder sounds from your baby. The parent unit remains quiet when your baby sleeps soundly.	The parent unit screen and speaker turns loud and is sound when your parent remains when baby softly
Level 5 (Highest)				
Level 4 (High)				
Level 3 (Medium)				

NIGHT VISION

The baby unit has infrared LEDs that allow you to see your baby clearly at night or in a dark room. When the baby unit being viewed detects low light levels, the infrared LEDs are switched on automatically. The images from the baby unit are in black and white, and appears on the screen.

NOTES

- It is normal if you see a short white glare on your parent unit screen as the baby unit is adapting to the dark environment.
- When the infrared LEDs are on, the images are in black and white. This is normal.

TIP

- Depending on the surroundings and other interfering factors, like lightings, objects, colors and background, the video quality may vary. Adjust the baby unit's angle or place the baby unit at a higher level to prevent glare and blurry display.

Notes

- Check for reception strength and camera angle before drilling the holes.
- The types of screws and anchors you need depend on the composition of the wall. You may need to purchase the screws and anchors separately to mount your camera units.

1. Place the wall mount bracket on a wall and then use a pencil to mark two holes in parallel. Remove the wall mount bracket and drill two holes in the wall (7/32 inch drill bit).

3. Align the wall mount bracket and screws with the holes in the wall as shown. Tighten the screw in the middle hole first, so that the wall mount bracket position is fixed. You can tighten the other screw in the top hole.

3. Insert the screws into the holes and tighten the screws until only 1/4 inch of the screws are exposed.

4. Place the camera unit on the wall mount bracket, and then slide it forward until it locks into place. Connect the power adapter to the camera unit and a power supply not controlled by a wall switch.

4. Place the camera unit on the wall mount bracket, and then slide it forward until it locks into place. Align the holes on the wall mount bracket with the screws on the wall, and slide the wall mount bracket down until it locks into place.

5. You can maximize your camera unit's viewing angles by tilting the wall mount bracket. Hold the camera unit, and then rotate the knob in anticlockwise direction. This will loosen the joint of the wall mount bracket. Tilt your camera unit up or down to adjust to your preferred angle. Then, rotate the knob in clockwise direction to tighten the joint and secure the angle.

participate in an industry program to recycle lithium-ion batteries at the end or once their useful lives, when taken from service in the United States and Canada.

The program provides a convenient alternative to placing used lithium-ion batteries into the trash or other chemical wastes which may be illegal in your area.

Vic's participation in this program is voluntary. Vic's involvement in this program at retail locations participating in the program at or after the date of this document is not intended to constitute a particular representation or warranty by Vic's regarding disposal bans/restrictions in your area. Vic's involvement in this program is part of its commitment to protecting the environment and its commitment to its customers.

The **BBRC** and **LBIC** (BATTERY) are registered trademarks of Call2Recycle, Inc.

FCC and IC Regulations

FCC Part 15

This equipment has been tested and found to comply with the requirements for a Class B digital device under Part 15 of the Federal Communications Commission (FCC) rules. These requirements are intended to provide reasonable protection against the interference of this equipment with other radio communications. Please see **15000 A BATTERY** for information on lithium-ion battery recycling and, if installed and used in accordance with the instructions, may cause harmful interference to radio communications. This equipment may cause, receive, or be disturbed by radio frequency interference. This equipment does not cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, and observing the effect. The device must be used in accordance with one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

WARNING: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference, including interference that may cause undesired operation.

For example, if the FCC has established criteria for the amount of radio frequency energy that can be safely absorbed by a user or bystander according to the intended usage of the product, this product has been tested and found to comply with those criteria. The device must be used in accordance with the instructions and must be maintained at a distance of approximately 8 in (20 cm) or more. The transmitter and antenna of the parent unit shall be held at least 1 in (2.5 cm) from your mouth.

This Class B digital apparatus complies with Canadian requirement.

Can ICES-3 (B) /NMB-330

Industry Canada

This device complies with Industry Canada's (IC) license-exempt (receiving) that comply with Innovation, Science and Economic Development Canada's license-exempt (R5000). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

The terms "IC" before the certification/registration number only signifies that the Industry Canada technical specifications were met.

RF Radiation Exposure Statement

This product meets the applicable Innovation, Science and Economic Development Canada technical specifications.

The baby unit complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The baby unit should be installed and operated with a minimum distance of 8 in (20 cm) between the baby unit and all persons' body. Use of other accessories, such as a car seat, stroller, or crib, may increase the distance between the baby unit and the person's body. To avoid body contact in conjunction with any other antenna or transmitter, this equipment complies also with Industry Canada RSS-2010 with respect to the Canada's health code for exposure of humans to RF fields.

CALIFORNIA ENERGY COMMISSION (CEC) REGULATIONS FOR ENERGY CONSUMPTION

CHARGING TESTING MODE

This baby monitor meets the California Energy Commission (CEC) regulations for energy consumption. Your baby monitor is designed to be used in the "Charging Testing Mode" by pressing the "TEST" button on the box. Follow the instructions to install and charge the battery. The CEC battery charging testing mode is activated while charging. Even if the parent unit is paired to baby unit, the baby unit will not be able to connect to the parent unit while in the "Charging Testing Mode".

[illegible]

The manufacturer of the Vtech Product warrants to the consumer that the Product is free from defects in materials and workmanship, pursuant to the following terms and conditions:

1. **Warranty Period.** Under the terms of this warranty, the limited warranty period for the Consumer for Products and Services is 90 days from the date of purchase, in accordance with the Product's operating instructions. This limited warranty period only for the Consumer for Products and Services.

2. **What will Vtech do if the Product is not free from defects in materials and workmanship?** If the Product is found to be defective, Vtech will, at its sole discretion, repair or replace the Vtech's option, without charge, a **Materiaily Defective Product**. If you repair the Product, you will be responsible for the cost of the repair. If we choose to replace the Product, we may replace the Product with a new or refurbished Product, without charge. In some cases, we may replace the Product with a similar design. We will retain defective parts, may replace them with parts of similar design, and may use them in the manufacture of other Products. We will not be responsible for Vtech's option, its exclusive remedy. Vtech will return the Product to you, at no charge, within 30 days of the date of purchase. You should expect the repair or replacement to take approximately 30 days.

3. **What is the limited warranty period?** The limited warranty period for the Product extends for 90 days from the date of purchase. If Vtech repairs or replaces the Product, the limited warranty period for the Product is extended for 90 days from the date of the repair or replacement. Product is not covered by the limited warranty if the Product is damaged, used, altered, or modified by anyone other than the consumer representative of Vtech;

4. **What is not covered by this limited warranty?** This limited warranty does not cover:

- 1. Products that are damaged, used, altered, or modified by anyone other than the consumer representative of Vtech;
- 2. Products that are damaged due to misuse, abuse, shipping or other physical damage, improper installation, abnormal operation or handling, neglect, inundation, or other causes not covered by the limited warranty;
- 3. Products that have been damaged due to use, alteration or modification by anyone other than the consumer representative of Vtech;
- 4. Products to the extent that the problem experienced is caused by a third party, or by a third party's use of cables or antenna or system;
- 5. Products for which the problem is caused by use of non-Vtech accessories;
- 6. Products for which the problem is caused by product serial numbers or serial numbers have been removed, altered or rendered illegible; or
- 7. Products for which the problem is caused by repair from outside the United States of America or Canada, or for which the problem is caused by a third party (but not limited to Products used for rental purposes); and
- 8. Products returned without a valid proof of purchase (see below).

5. **Charges for installation or set up, adjustment of customer controls, and installation or repair of systems outside the home.**

To obtain warranty service in the USA, please visit www.vtech.com or call 1-800-875-8288. Outside the USA, please visit www.vtechcanada.com or call 1-800-387-9288.

NOTE: Before calling for service, please review the user's manual - a check of the Product's controls and features may resolve the problem.

Except as provided by applicable law, you assume the risk of loss or damage during transit and transportation and are responsible for delivery or shipping charges (including transportation of the Product) to the service location. Vtech is not responsible for shipping or delivery charges for the Product. Vtech's responsibility, transportation, delivery or handling charges are limited to the cost of shipping or delivery charges for the Product in transit. If the Product failed is not covered by the limited warranty, Vtech will not be responsible for the terms of this limited warranty. Vtech will notify you and will request that you authorize the cost of repair or that you authorize the cost of shipping or delivery charges and return shipping charges for the repair of the Products that are not covered by the limited warranty.

What must you return with the Product to get warranty service?

1. The original, unopened package and contents including the Product to the Vtech service location along with a valid proof of purchase (sales receipt).

2. Include a "valid proof of purchase" (sales receipt) identifying the Product purchased (Product model and serial number) and the date of purchase or receipt.

3. Provide your name, complete and correct mailing address and telephone number.

This warranty is the complete and exclusive agreement between you and Vtech. It supersedes all other written or oral communications relating to the Product, except for no warranties for this Product. The warranty exclusively covers the Product's original retail price and does not include the Product. There are no other express warranties. No one is authorized to make modifications to the limited warranty and no one is authorized to alter any modification. This warranty is provided in English. This warranty gives you specific legal rights, and you may have other rights that vary by jurisdiction or country of purchase.

Limitations on remedies, including those of fitness for a particular purpose and merchantability (an implied warranty that the Product is fit for ordinary use) are limited by the terms of this limited warranty. Vtech and its service providers do not allow limitations on how long an implied warranty may last or how much of the Product's value it covers. In no event shall Vtech be liable for any indirect, special, consequential or punitive damages, or for lost profits, but not limited to lost profits or revenues, inability to use the Product, or any other damages, including those for substitute equipment, and claims by third parties) resulting from the use of this Product. Some states/provinces prohibit the exclusion or limitation of consequential damages, so the above limitation or exclusion may not apply to you.

Please retain your original sales receipt as proof of purchase.