

TEST REPORT

Application No.: HKEM2010001103AT

Applicant: VTECH TELECOMMUNICATIONS LTD

Address of Applicant: 23/F., BLOCK 1, TAI PING INDUSTRIAL CENTRE, NO. 57 TING KOK ROAD, TAI PO, N.T., Hong Kong

Equipment Under Test (EUT):

EUT Name: 2.4G WIFI Baby Monitor (BU)

Model No.: RM5764 BU, RM5764HD BU, RM5764-2HD BU, RM5764-aHD BU, RM5864 BU, RM5864HD BU, RM5864-aHD BU, VM906HD BU, VM906-1bHD BU, VM906-abHD BU, RM7764 BU, RM7764HD BU, RM7764-2HD BU, RM7764-aHD BU, RM7864 BU, RM7864HD BU, RM7864-2HD BU, RM7864-aHD BU, VM907HD BU, VM907-1bHD BU, VM907-abHD BU

Additional Model: Please refer to section 2 of this report which indicates which item was actually tested and which were electrically identical.

FCC ID: EW780-1922-00A

IC: 1135B-80192200A

HVIN: 35-400341BU

Standard(s) : 47 CFR Part 1.1307; 47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06
RSS102 Issue 5 March 2015

Date of Receipt: 2020-10-31

Date of Test: 2020-11-01 to 2020-11-10

Date of Issue: 2020-11-11

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Law Man Kit
EMC Manager

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request and accessible at <http://www.sgs.com/en/Terms-and-conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-conditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. The document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2020-11-11		Original

Authorized for issue by:			
			
		Leo Xu /Project Engineer	Date: 2020-11-11
			
		Law Man Kit /Reviewer	Date: 2020-11-11

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
RF Exposure	47 CFR Part 1.1307, 47 CFR Part 2.1093, KDB 447498 D01	KDB447498D01	KDB447498D01	PASS
RF Exposure	RSS102 Issue 5	RSS-102 Section 2.5.1	RSS102 Issue 5	PASS

Declaration of EUT Family Grouping:

Item no.: RM5764 BU, RM5764HD BU, RM5764-2HD BU, RM5764-aHD BU, RM5864 BU, RM5864HD BU, RM5864-aHD BU, VM906HD BU, VM906-1bHD BU, VM906-abHD BU, RM7764 BU, RM7764HD BU, RM7764-2HD BU, RM7764-aHD BU, RM7864 BU, RM7864HD BU, RM7864-2HD BU, RM7864-aHD BU, VM907HD BU, VM907-1bHD BU, VM907-abHD BU

a=any alphanumeric character or blank is presenting number of baby unit.

b= any alphanumeric character or blank is presenting color option

According to the confirmation from the applicant, the above models are identical in all electrical aspects in relating to the circuit design, PCB layout, electrical components used, internal wiring and functions. The differences are only the model/item No, color and decorations.

Therefore only the model RM5764HD BU was tested in this report.

Abbreviation:

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radiated Frequency.

CH: In this whole report CH means channel.

Volt: In this whole report Volt means Voltage.

Temp: In this whole report Temp means Temperature.

Humid: In this whole report Humid means humidity.

Press: In this whole report Press means Pressure.

N/A: In this whole report not application.



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 DETAILS OF E.U.T.	5
4.2 DESCRIPTION OF SUPPORT UNITS	6
4.3 TEST LOCATION	7
4.4 TEST FACILITY	7
4.5 DEVIATION FROM STANDARDS	7
4.6 ABNORMALITIES FROM STANDARD CONDITIONS	7
5 RADIO SPECTRUM TECHNICAL REQUIREMENT	8
5.1 RF EXPOSURE	8
5.1.1 <i>Test Requirement:</i>	8
5.1.1 <i>IC Radiofrequency radiation</i>	9
5.1.2 <i>EUT RF Exposure Evaluation</i>	10
6 PHOTOGRAPHS	12

4 General Information

4.1 Details of E.U.T.

Power supply:	Adaptor Model : VT05EUS05100 Input: AC 100 V - 240 V, 50/60, 0.15 A Output: DC 5.0 V, 1 A
Test voltage:	AC 120 V
Cable:	272.5 cm unshielded 2-wire DC cable
Antenna Gain:	2 dBi
Antenna Type:	PCB Antenna
Channel Spacing:	5MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Data rate:	802.11b: 1Mbps, 2Mbps, 5.5Mbps, 11 Mbps 802.11g: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54 802.11n: 6.5Mbps, 13Mbps, 19.5Mbps, 26Mbps, 39Mbps, 52Mbps, 58.5Mbps, 65Mbps
Number of Channels:	802.11b/g/n(HT20):11
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz
Tested Channels:	2412MHz, 2442MHz, 2462MHz
Version code:	T21N
Series number:	A1
Hardware Version:	V002
Software Version:	V0.2.0.1
	Remark: Power level setting was not adjustable and fixed default through SW Version.

Frequency List

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Remark: 1. Testing Channels are highlighted in **bold**.

4.2 Description of Support Units

The EUT has been tested with corresponding accessories as below:

Supplied by client

Description	Manufacturer	Model No.	SN/Certificate NO
UART Test board	N/A	MX3232	N/A
Test Software	MicroRidge System	Version 3.0.0.108	N/A

Supplied by SGS:

Description	Manufacturer	Model No.	SN/Certificate NO
NoteBook (EMC4)	Dell	P75F	N/A

4.3 Test Location

All tests were performed at:

SGS Hong Kong Limited

Unit 2 and 3, G/F, Block A, Po Lung Centre,

11 Wang Chiu Road, Kowloon Bay, Kowloon, Hong Kong

Tel: +852 2305 2570 Fax: +852 2756 4480

No tests were sub-contracted.

4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **HOKLAS (Lab Code: 009)**

SGS Hong Kong Limited has been accepted by HKAS Executive, on the recommendation of the Accreditation Advisory Board, as a HOKLAS Accredited Laboratory, this laboratory meets the requirements of ISO/IEC 17025:2017 and it has been accredited for performing specific test as listed in the scope of accreditation within the test category of Electrical and Electronic Products.

• **IAS Accreditation (Lab Code: TL-187)**

SGS Hong Kong Limited has met the requirements of AC89, IAS Accreditation Criteria for Testing Laboratories, and has demonstrated compliance with ISO/IEC Standard 17025:2017, General requirements for the competence of testing and calibration laboratories. This organization is accredited to provide the services specified in the scope of accreditation maintained on the IAS website (www.iasonline.org).

The report must not be used by the client to claim product certification, approval, or endorsement by IAS, NIST, or any agency of the Federal Government.

• **FCC Recognized Accredited Test Firm (CAB Registration No.: 514599)**

SGS Hong Kong Limited has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: HK0015, Test Firm Registration Number: 514599.

• **Industry Canada (Site Registration No.: 26103; CAB Identifier No.: HK0015)**

SGS Hong Kong Limited has been recognized by Department of Innovation, Science and Economic Development (ISED) Canada as a wireless testing laboratory. The acceptance letter from the ISED is maintained in our files. CAB Identifier No: HK0015, Site Registration Number: 26103.

4.5 Deviation from Standards

None

4.6 Abnormalities from Standard Conditions

None

5 Radio Spectrum Technical Requirement

5.1 RF Exposure

5.1.1 Test Requirement:

CFR 47 Part 1.1310

Limit:

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in Part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

According to IEEE C95.3:2002 section 5.5.1.1, The power density S at a point on the axis at a distance d from a transmitting antenna is given by the Friis free-space transmission formula

$$S = \frac{PG}{4\pi d^2}$$

S = power density (mW/cm²)
P = the net power delivered to the antenna (mW)
G = gain of the antenna in linear scale
d = distance between observation point and center of the radiator (cm)

5.1.1 IC Radiofrequency radiation

According to RSS-102 Issue 5, section 2.5.2 Exemption.

RF exposure evaluation is required if the separation distance between the user and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $22.48/f^{0.5} \text{ W}$ (adjusted for tune-up tolerance), where f is in MHz;

- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);

- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834} \text{ W}$ (adjusted for tune-up tolerance), where f is in MHz;

- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

5.1.2 EUT RF Exposure Evaluation

Antenna Gain:

The maximum Gain measured in fully anechoic chamber is 1.585 () in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

For FCC;

WiFi:

Operation mode	Channel	Frequency (MHz)	Conduct power (including Tune-up tolerance) (dBm)	Conduct power (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	MPE Ratios	Result
802.11b	Low	2412	10.3	10.715	0.00338	1	0.00338	PASS
802.11b	Middle	2442	9.5	8.913	0.00281	1	0.00281	PASS
802.11b	High	2462	8.6	7.244	0.00228	1	0.00228	PASS
802.11g	Low	2412	9.0	7.943	0.00250	1	0.00250	PASS
802.11g	Middle	2442	8.5	7.079	0.00223	1	0.00223	PASS
802.11g	High	2462	7.6	5.754	0.00181	1	0.00181	PASS
802.11n20	Low	2412	8.3	6.761	0.00213	1	0.00213	PASS
802.11n20	Middle	2442	8.5	7.079	0.00223	1	0.00223	PASS
802.11n20	High	2462	6.9	4.898	0.00154	1	0.00154	PASS

For IC:

WiFi:

Operation mode	Channel	Frequency (MHz)	Conduct power (including Tune-up tolerance) (dBm)	E.I.R.P (dBm)	E.I.R.P (W)	Limit (W)	Result
802.11b	Low	2412	10.3	12.3	0.016982	2.7	PASS
802.11b	Middle	2442	9.5	11.5	0.014125	2.7	PASS
802.11b	High	2462	8.6	10.6	0.011482	2.7	PASS
802.11g	Low	2412	9.0	11.0	0.012589	2.7	PASS
802.11g	Middle	2442	8.5	10.5	0.01122	2.7	PASS
802.11g	High	2462	7.6	9.6	0.00912	2.7	PASS
802.11n20	Low	2412	8.3	10.3	0.010715	2.7	PASS
802.11n20	Middle	2442	8.5	10.5	0.01122	2.7	PASS
802.11n20	High	2462	6.9	8.9	0.007762	2.7	PASS

Note: 1. Refer to report No. HKEM201000110302 for EUT test conducted power value. requirement.



Report No.: HKEM201000110303
Page: 12 of 12

6 Photographs

Remark: Photos refer to Appendix A, Appendix B and Appendix C of HKEM2007000716AT.

- End of the Report -
