

TEST REPORT

Applicant Name: FCC: VTech Telecommunications Ltd
IC: VTECH TELECOMMUNICATIONS LIMITED
Address: FCC: 23/F Tai Ping Ind Center Block 1 57 Ting Kok Rd Tai Po NT, Hong Kong
IC: BL.1 23/F Tai Ping Industr Ctr. 57 Ting Kok Road Tai Po, NT Hongkong
Report Number: 2501W00691E-RFA
FCC ID: EW780-2365-00B
IC: 1135B-80236500B

Test Standard (s)

FCC PART 15.247; RSS-GEN ISSUE 5, FEBRUARY 2021 AMENDMENT 2; RSS-247 ISSUE 3, AUGUST 2023

Sample Description

Product Type: Video Baby Monitor
Model No.: VM819
Multiple Model(s) No.: VM819-2, 819 Max, 819 Max Twin
Trade Mark: VTech
Date Received: 2025/08/11
Issue Date: 2025/10/24

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Bruce Lin

Bruce Lin
RF Engineer

Approved By:

Nancy Wang

Nancy Wang
RF Supervisor

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, Futian Free Trade Zone, Shenzhen, China

Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE	7
SPECIAL ACCESSORIES	7
EQUIPMENT MODIFICATIONS	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	10
TEST EQUIPMENT LIST	11
RSS-102 § 6.6 - FIELD REFERENCE LEVEL EXPOSURE EXEMPTION LIMITS.....	15
APPLICABLE STANDARD	15
TEST RESULT:	15
FCC §15.203 & RSS-GEN §6.8 - ANTENNA REQUIREMENT	16
APPLICABLE STANDARD	16
ANTENNA CONNECTOR CONSTRUCTION	16
FCC §15.207 (A) & RSS-GEN §8.8 - AC LINE CONDUCTED EMISSIONS.....	17
APPLICABLE STANDARD	17
EUT SETUP	18
EMI TEST RECEIVER SETUP.....	18
TEST PROCEDURE	18
FACTOR & OVER LIMIT CALCULATION.....	19
TEST DATA	19
FCC §15.205, §15.209 & §15.247(D) & RSS-247§ 5.5 - RADIATED EMISSIONS.....	24
APPLICABLE STANDARD	24
EUT SETUP	24
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	25
TEST PROCEDURE	26
FACTOR & OVER LIMIT/MARGIN CALCULATION	26
TEST DATA	26
FCC §15.247(A) (1) & RSS-247 § 5.1 (B) - CHANNEL SEPARATION TEST	52
APPLICABLE STANDARD	52
TEST PROCEDURE	52
TEST DATA	53

FCC §15.247(A) (1) & RSS-GEN § 6.7 & RSS-247 § 5.1 (A) - 99% OCCUPIED BANDWIDTH & 20 DB EMISSION BANDWIDTH.....	54
APPLICABLE STANDARD	54
TEST PROCEDURE	54
TEST DATA	55
FCC §15.247(A) (1) (III) & RSS-247 § 5.1 (D) - QUANTITY OF HOPPING CHANNEL TEST.....	58
APPLICABLE STANDARD	58
TEST PROCEDURE	58
TEST DATA	59
FCC §15.247(A) (1) (III) & RSS-247 § 5.1 (D) - TIME OF OCCUPANCY (DWELL TIME)	60
APPLICABLE STANDARD	60
TEST PROCEDURE	60
TEST DATA	61
FCC §15.247(B) (1) & RSS-247§ 5.1(B) &§ 5.4(B) - PEAK OUTPUT POWER MEASUREMENT	63
APPLICABLE STANDARD	63
TEST PROCEDURE	63
TEST DATA	64
FCC §15.247(D) & RSS-247 § 5.5 - BAND EDGES TESTING	66
APPLICABLE STANDARD	66
TEST PROCEDURE	66
TEST DATA	67
FCC §15.247(D) & RSS-247 § 5.5 - CONDUCTED SPURIOUS EMISSION	70
APPLICABLE STANDARD	70
TEST PROCEDURE	70
TEST DATA	71
EUT PHOTOGRAPHS	73
TEST SETUP PHOTOGRAPHS	74

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2501W00691E-RFA	Original Report	2025/10/24

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

HVIN	35-201931BUA
FVIN	N/A
Product	Video Baby Monitor
Tested Model	VM819
Multiple Model(s)	VM819-2, 819 Max, 819 Max Twin
Frequency Range	2405-2475MHz
Maximum conducted Peak output power	18.55dBm
Modulation Technique	GFSK
Antenna Specification [#]	0dBi(It is provided by the applicant)
Voltage Range	DC 6V by adapter
Sample number	386P-5 for RF Conducted Test 386P-1 for Radiated Emissions (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	Adapter 1 Model: VT05EUS06040 Input: AC 100-240V, 50/60Hz, 0.15A Output: DC 6.0V, 0.4A, 2.4W Adapter 2 Model: GQ06-060040-ZU Input: AC 100-240V, 50/60Hz, 0.3A Output: DC 6.0V, 0.4A
Note: The Multiple models are electrically identical with the test model except for model number and configuration. Please refer to the declaration letter [#] for more detail, which was provided by manufacturer.	

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules and RSS-247 Issue 3, August 2023, RSS-GEN Issue 5, Feb. 2021 Amendment 2 of the Innovation, Science and Economic Development Canada rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020 + Cor.1-2023▼, RSS-Gen and RSS-247.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		109.2kHz(k=2, 95% level of confidence)
RF Frequency		56.6Hz(k=2, 95% level of confidence)
RF output power, conducted		0.86dB(k=2, 95% level of confidence)
Unwanted Emission, conducted		1.60dB(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9 kHz~150 KHz	3.63dB(k=2, 95% level of confidence)
	150 kHz ~30MHz	3.66dB(k=2, 95% level of confidence)
Radiated Emissions	9kHz - 30MHz	3.60dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	5.32dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	5.43dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	5.77dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.73dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.34dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.40dB(k=2, 95% level of confidence)
	18GHz - 40GHz	5.64dB(k=2, 95% level of confidence)
Temperature		±1°C
Humidity		±1%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0023.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

Channel list

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2405	9	2422	17	2439	25	2458
2	2407	10	2424	18	2441	26	2460
3	2409	11	2426	19	2444	27	2462
4	2411	12	2428	20	2446	28	2467
5	2413	13	2430	21	2450	29	2469
6	2415	14	2433	22	2452	30	2471
7	2418	15	2435	23	2454	31	2473
8	2420	16	2437	24	2456	32	2475

EUT was test in channel 1,18, 32.

EUT Exercise Software

“SecureCRT.exe[#]” exercise software was used and the power level is default[#]. The software and power level was provided by the manufacturer.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
OUPU	Receptacle	Unknown	6971041358020

External I/O Cable


Cable Description	Length (m)	From Port	To
Unshielded detachable AC cable	1.2	AC mains/LISN	Receptacle
Unshielded detachable DC cable	1.2	EUT	Adapter

Block Diagram of Test Setup


For Conducted Emission



For Radiated Emission for Below 1GHz



For Radiated Emission for Above 1GHz



SUMMARY OF TEST RESULTS

FCC Rules	ISED Rules	Description of Test	Result
§1.1307§2.1091	-	MPE-BASED EXEMPTION	Compliant
-	RSS-102 § 6.6	Field reference level exposure exemption limits	Compliant
§15.203	RSS-Gen §6.8	Antenna Requirement	Compliant
§15.207(a)	RSS-Gen §8.8	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	RSS-247 § 5.5	Radiated Emissions	Compliant
§15.247(a)(1)	RSS- Gen§6.7, RSS-247 § 5.1 (a)	99% Occupied Bandwidth & 20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	RSS-247 § 5.1 (b)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	RSS-247 § 5.1 (d)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	RSS-247 § 5.1 (d)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	RSS-247 § 5.1(b) & § 5.4(b)	Peak Output Power Measurement	Compliant
§15.247(d)	RSS-247 § 5.5	Band edges	Compliant
§15.247(d)	RSS-247 § 5.5	Conducted Spurious Emission	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2024/12/04	2025/12/03
Rohde & Schwarz	LISN	ENV216	101613	2024/12/04	2025/12/03
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2025/04/29	2026/04/28
Unknown	CE Cable	Unknown	UF A210B-1-0720-504504	2025/04/29	2026/04/28
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
Radiated Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2024/12/04	2025/12/03
Sonoma instrument	Pre-amplifier	310 N	186238	2025/04/29	2026/04/28
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Cable	Chamber A Cable 1	N/A	2025/04/29	2026/04/28
Unknown	Cable	XH500C	J-10M-A	2025/04/29	2026/04/28
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Unknown	Cable	2Y194	0735	2024/12/04	2025/12/03
Unknown	Cable	PNG214	1354	2024/12/04	2025/12/03
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40	101605	2025/09/01	2026/08/31
A.H.System	Preamplifier	PAM-0118P	489	2024/11/15	2025/11/14
Schwarzbeck	Horn Antenna	BBHA9120D(1201)	1143	2023/07/26	2026/07/25
Unknown	RF Cable	KMSE	735	2024/12/06	2025/12/05
Unknown	RF Cable	UFA147	219661	2024/12/06	2025/12/05
Unknown	RF Cable	XH750A-N	J-10M	2024/12/06	2025/12/05
JD	Filter Switch Unit	DT7220FSU	DS79906	2025/08/12	2026/08/11
JD	Multiplex Switch Test Control Set	DT7220SCU	DS79903	2025/08/12	2026/08/11
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
A.H.System	Pre-amplifier	PAM-1840VH	190	2025/04/29	2026/04/28
Electro-Mechanics Co	Horn Antenna	3116	9510-2270	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2024/12/18	2025/12/17

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSU26	200120	2024/12/04	2025/12/03
Unknown	10dB Attenuator	Unknown	F-03-EM190	2025/06/26	2026/06/25

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC 1.1307 (B) & §2.1091- MPE-BASED EXEMPTION

Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 v01 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Result

Frequency (MHz)	Tune up conducted power [#]	Antenna Gain [#]		ERP		Evaluation Distance (m)	ERP Limit (W)
	(dBm)	(dBi)	(dBd)	(dBm)	(W)		
2405-2475	19	0	-2.15	16.85	0.048	0.2	0.768

Note: The tune up conducted power and antenna gain was declared by the applicant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant

RSS-102 § 6.6 - FIELD REFERENCE LEVEL EXPOSURE EXEMPTION LIMITS

Applicable Standard

According to RSS-102 Issue 6§6.6:

Field reference level (FRL) exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm (i.e. mobile devices), except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 1 W (adjusted for tune-up tolerance)
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance)
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz
- at or above 6 GHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 5 W (adjusted for tune-up tolerance) In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the EIRP was derived.

Test Result:

For worst case:

Mode	Frequency (MHz)	Gain# (dBi)	Max tune-up conducted power# (dBm)	Max tune-up EIRP# (dBm)	Max tune-up EIRP# (mW)	Distance (mm)	Exemption Limit (mW)	SAR Evaluation Exemption
FHSS	2405-2475	0	19	19	79.433	200	2679	Yes

Note 1: The antenna gain and Conducted output power including Tune-up Tolerance was declared and provided by the manufacturer

Result: Compliant

FCC §15.203 & RSS-GEN §6.8 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer. The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

Antenna Connector Construction

The EUT has one internal antenna arrangements which were permanently attached and the gain is 0dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Type	Antenna Gain [#]	Impedance
Monopole	0dBi	50Ω

Result: Compliant

FCC §15.207 (a) & RSS-GEN §8.8 - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a) & RSS-Gen §8.8

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50 μ H / 50 Ω line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT.

For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.


Table 4 - AC Power Lines Conducted Emission Limits		
Frequency range (MHz)	Conducted limit (dBμV)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56 ¹	56 to 46 ¹
0.5 – 5	56	46
5 – 30	60	50

Note 1: The level decreases linearly with the logarithm of the frequency.

For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

- (a) Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.
- (b) Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2020. The related limit was specified in FCC Part 15.207 and RSS-Gen limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).

Test Data

Environmental Conditions


Temperature:	24.7 °C
Relative Humidity:	60 %
ATM Pressure:	100.3 kPa

The testing was performed by Alex Yan on 2025-08-27.

EUT operation mode: Transmitting (worst case is low channel)

For Adapter 1

AC 120V/60 Hz, Line



Condition: Line


Project : 2501W00691E-RF

tester : Alex Yan Note:Transmitting

Setting : RBW:9kHz

	Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.165	3.70	24.38	10.50	10.18	55.21	-30.83	Average
2	0.165	18.99	39.67	10.50	10.18	65.21	-25.54	QP
3	0.202	1.80	22.69	10.70	10.19	53.54	-30.85	Average
4	0.202	15.31	36.20	10.70	10.19	63.54	-27.34	QP
5	0.373	11.40	32.16	10.56	10.20	48.43	-16.27	Average
6	0.373	19.88	40.64	10.56	10.20	58.43	-17.79	QP
7	1.928	9.74	31.04	11.07	10.23	46.00	-14.96	Average
8	1.928	17.49	38.79	11.07	10.23	56.00	-17.21	QP
9	3.041	10.16	31.41	10.98	10.27	46.00	-14.59	Average
10	3.041	19.02	40.27	10.98	10.27	56.00	-15.73	QP
11	6.733	5.05	25.91	10.62	10.24	50.00	-24.09	Average
12	6.733	15.24	36.10	10.62	10.24	60.00	-23.90	QP

AC 120V/60 Hz, Neutral



Condition: Neutral

Project : 2501W00691E-RF


tester : Alex Yan Note:Transmitting

Setting : RBW:9kHz

	Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.162	2.79	23.47	10.50	10.18	55.38	-31.91	Average
2	0.162	16.66	37.34	10.50	10.18	65.38	-28.04	QP
3	0.200	1.50	22.49	10.80	10.19	53.62	-31.13	Average
4	0.200	15.09	36.08	10.80	10.19	63.62	-27.54	QP
5	0.373	7.60	28.40	10.60	10.20	48.43	-20.03	Average
6	0.373	13.95	34.75	10.60	10.20	58.43	-23.68	QP
7	1.908	4.23	25.17	10.71	10.23	46.00	-20.83	Average
8	1.908	9.93	30.87	10.71	10.23	56.00	-25.13	QP
9	3.922	4.33	25.56	10.99	10.24	46.00	-20.44	Average
10	3.922	12.21	33.44	10.99	10.24	56.00	-22.56	QP
11	6.252	0.78	21.71	10.68	10.25	50.00	-28.29	Average
12	6.252	9.28	30.21	10.68	10.25	60.00	-29.79	QP

For Adapter 2

AC 120V/60 Hz, Line



Condition: Line


Project : 2501W00691E-RF

tester : Alex Yan Note:Transmitting

Setting : RBW:9kHz

	Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.170	5.52	26.24	10.53	10.19	54.94	-28.70	Average
2	0.170	16.07	36.79	10.53	10.19	64.94	-28.15	QP
3	0.242	4.74	25.60	10.66	10.20	52.04	-26.44	Average
4	0.242	11.61	32.47	10.66	10.20	62.04	-29.57	QP
5	0.389	20.56	41.32	10.55	10.21	48.08	-6.76	Average
6	0.389	24.51	45.27	10.55	10.21	58.08	-12.81	QP
7	1.172	9.45	30.33	10.71	10.17	46.00	-15.67	Average
8	1.172	17.60	38.48	10.71	10.17	56.00	-17.52	QP
9	2.309	2.66	23.96	11.06	10.24	46.00	-22.04	Average
10	2.309	12.40	33.70	11.06	10.24	56.00	-22.30	QP
11	18.232	7.31	28.34	10.77	10.26	50.00	-21.66	Average
12	18.232	16.37	37.40	10.77	10.26	60.00	-22.60	QP

AC 120V/60 Hz, Neutral



Condition: Neutral

Project : 2501W00691E-RF

tester : Alex Yan Note:Transmitting

Setting : RBW:9kHz

	Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.169	2.13	22.88	10.56	10.19	55.03	-32.15	Average
2	0.169	13.38	34.13	10.56	10.19	65.03	-30.90	QP
3	0.208	-0.02	20.96	10.79	10.19	53.27	-32.31	Average
4	0.208	9.98	30.96	10.79	10.19	63.27	-32.31	QP
5	0.389	14.11	34.90	10.58	10.21	48.08	-13.18	Average
6	0.389	21.09	41.88	10.58	10.21	58.08	-16.20	QP
7	0.880	2.58	23.53	10.73	10.22	46.00	-22.47	Average
8	0.880	10.80	31.75	10.73	10.22	56.00	-24.25	QP
9	2.167	-1.53	19.44	10.73	10.24	46.00	-26.56	Average
10	2.167	5.97	26.94	10.73	10.24	56.00	-29.06	QP
11	18.232	3.54	24.64	10.84	10.26	50.00	-25.36	Average
12	18.232	11.15	32.25	10.84	10.26	60.00	-27.75	QP


FCC §15.205, §15.209 & §15.247(d) & RSS-247§ 5.5 - RADIATED EMISSIONS

Applicable Standard


FCC §15.205; §15.209; §15.247(d) and RSS-247§ 5.5; RSS-GEN § 8.10


EUT Setup

9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209, FCC 15.247 limits and RSS-247/RSS-Gen limits.

EMI Test Receiver & Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement	Detector
9 kHz – 150 kHz	/	/	200 Hz	QP	QP
	300 Hz	1 kHz	/	PK	Peak
150 kHz – 30 MHz	/	/	9 kHz	QP	QP
	10 kHz	30 kHz	/	PK	Peak
30 MHz – 1000 MHz	/	/	120 kHz	QP	QP
	100 kHz	300 kHz	/	PK	Peak
Above 1 GHz	Harmonics				
	1MHz	3 MHz	/	PK	Peak
	Average Emission Level=Peak Emission Level+20*log(Duty cycle)				
	Band Edge & Other Emissions				
	1MHz	3 MHz	/	PK	Peak
	1MHz	≥10 Hz	/	Average	Peak

For Duty cycle measurement:

Use the duty cycle factor correction factor method per 15.35(c).

Duty cycle=On time/100milliseconds, On time= $N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$,

Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulse, etc.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit/Margin} &= \text{Level/Corrected Amplitude} - \text{Limit} \\ \text{Level / Corrected Amplitude} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Test Data

Environmental Conditions

Temperature:	22.1~25.2 °C
Relative Humidity:	51~54 %
ATM Pressure:	100.2~101.5 kPa

The testing was performed by Anson Su on 2025-08-29 for below 1GHz and Leon Guo on 2025-09-18 for above 1GHz.

EUT operation mode: Transmitting

Note: Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.


The spurious emission from 9 kHz-30MHz of IC RSS-Gen standard, the unit of final result on the test plots are dBμV/m, so the limit should be added by 51,5 dB from dBμA/m to dBμV/m.

For Adapter 1

9 kHz-30MHz:


Note: When the test result of peak was less than the limit of QP/Average more than 6dB, just peak value were recorded.

Parallel (worst case)



Site : Chamber A
Condition : 3m
Project Number : 2501W00691E-RF
Test Mode : Transmitting
Note : BU
Detector: Peak RBW/VBW: 0.3/1kHz
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.011	32.18	23.90	56.08	127.08	-71.00	Peak
2	0.017	30.95	21.20	52.15	122.94	-70.79	Peak
3	0.027	28.98	22.07	51.05	118.83	-67.78	Peak
4	0.045	26.97	21.35	48.32	114.62	-66.30	Peak
5	0.084	23.09	21.62	44.71	109.07	-64.36	Peak
6	0.128	20.37	19.53	39.90	105.48	-65.58	Peak




Site : Chamber A
 Condition : 3m
 Project Number : 2501W00691E-RF
 Test Mode : Transmitting
 Note : BU
 Detector: Peak RBW/VBW: 10/30kHz
 Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.484	6.70	34.94	41.64	93.91	-52.27	Peak
2	0.583	5.37	34.27	39.64	72.25	-32.61	Peak
3	0.737	3.48	35.53	39.01	70.18	-31.17	Peak
4	1.040	1.09	34.16	35.25	67.13	-31.88	Peak
5	1.363	0.18	32.14	32.32	64.73	-32.41	Peak
6	1.980	-1.54	31.24	29.70	69.54	-39.84	Peak

30MHz-1GHz: (Maximum output power mode, low channel)


Horizontal



Site : Chamber A
 Condition : 3m Horizontal
 Project Number : 2501W00691E-RF
 Test Mode : Transmitting
 Note : BU
 Detector: Peak RBW/VBW: 100/300kHz
 Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	215.93	-14.20	50.00	35.80	43.50	-7.70	QP
2	228.09	-13.94	42.68	28.74	46.00	-17.26	Peak
3	384.10	-9.04	41.69	32.65	46.00	-13.35	Peak
4	408.05	-8.20	44.30	36.10	46.00	-9.90	Peak
5	671.96	-3.84	34.62	30.78	46.00	-15.22	Peak
6	768.07	-2.57	34.32	31.75	46.00	-14.25	Peak

Vertical



Site : Chamber A
Condition : 3m Vertical
Project Number : 2501W00691E-RF
Test Mode : Transmitting
Note : BU
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	34.25	-8.43	29.62	21.19	40.00	-18.81	Peak
2	56.42	-18.32	34.26	15.94	40.00	-24.06	Peak
3	216.02	-14.20	44.78	30.58	46.00	-15.42	Peak
4	408.05	-8.20	39.03	30.83	46.00	-15.17	Peak
5	431.98	-7.78	40.24	32.46	46.00	-13.54	Peak
6	480.11	-6.34	37.78	31.44	46.00	-14.56	Peak

For Adapter 2

9 kHz-30MHz:


Note: When the test result of peak was less than the limit of QP/Average more than 6dB, just peak value were recorded.

Parallel (worst case)



Site : Chamber A
Condition : 3m
Project Number : 2501W00691E-RF
Test Mode : Transmitting
Note : BU
Detector: Peak RBW/VBW: 0.3/1kHz
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.011	32.18	24.33	56.51	127.09	-70.58	Peak
2	0.020	30.34	21.59	51.93	121.45	-69.52	Peak
3	0.035	27.96	20.99	48.95	116.70	-67.75	Peak
4	0.060	25.37	22.33	47.70	111.99	-64.29	Peak
5	0.097	22.19	21.16	43.35	107.85	-64.50	Peak
6	0.137	19.80	19.85	39.65	104.86	-65.21	Peak




Site : Chamber A
 Condition : 3m
 Project Number : 2501W00691E-RF
 Test Mode : Transmitting
 Note : BU
 Detector: Peak RBW/VBW: 10/30kHz
 Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.512	6.25	33.94	40.19	73.41	-33.22	Peak
2	0.611	5.03	34.06	39.09	71.84	-32.75	Peak
3	0.763	3.15	34.41	37.56	69.87	-32.31	Peak
4	1.017	1.15	33.90	35.05	67.32	-32.27	Peak
5	1.387	0.12	31.10	31.22	64.57	-33.35	Peak
6	2.000	-1.60	31.97	30.37	69.54	-39.17	Peak

30MHz-1GHz: (Maximum output power mode, low channel)


Horizontal



Site : Chamber A
 Condition : 3m Horizontal
 Project Number : 2501W00691E-RF
 Test Mode : Transmitting
 Note : BU
 Detector: Peak RBW/VBW: 100/300kHz
 Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	203.97	-13.36	48.03	34.67	43.50	-8.83	Peak
2	216.02	-14.20	50.41	36.21	46.00	-9.79	Peak
3	384.10	-9.04	41.57	32.53	46.00	-13.47	Peak
4	408.05	-8.20	42.08	33.88	46.00	-12.12	Peak
5	624.26	-4.69	39.14	34.45	46.00	-11.55	Peak
6	717.31	-3.26	36.44	33.18	46.00	-12.82	Peak

Vertical



Site : Chamber A
Condition : 3m Vertical
Project Number : 2501W00691E-RF
Test Mode : Transmitting
Note : BU
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	56.64	-18.32	35.33	17.01	40.00	-22.99	Peak
2	216.02	-14.20	42.53	28.33	46.00	-17.67	Peak
3	408.05	-8.20	43.92	35.72	46.00	-10.28	Peak
4	432.17	-7.78	43.46	35.68	46.00	-10.32	Peak
5	528.01	-5.80	39.38	33.58	46.00	-12.42	Peak
6	575.89	-5.25	39.05	33.80	46.00	-12.20	Peak

Above 1GHz:

Frequency (MHz)	Reading (dBμV)	PK/AV	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low Channel 2405MHz							
The maximum value of the main wave on the X-axis:100.28dBμV							
The maximum value of the main wave on the Y-axis:101.64dBμV							
The maximum value of the main wave on the Z-axis:102.37dBμV *(worst case position)							
4810.00	52.76	PK	H	-7.78	44.98	74	-29.02
4810.00	51.61	PK	V	-7.78	43.83	74	-30.17
Middle Channel 2441MHz							
4882.00	52.23	PK	H	-7.59	44.64	74	-29.36
4882.00	52.37	PK	V	-7.59	44.78	74	-29.22
High Channel 2475MHz							
4950.00	52.65	PK	H	-7.63	45.02	74	-28.98
4950.00	51.94	PK	V	-7.63	44.31	74	-29.69

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude = Corrected Factor + Reading


Margin = Corrected. Amplitude - Limit

Other emissions which were more than 20dB below limit or on noise floor level was not recorded.

The test result of peak was less than the limit of average, so just peak values were recorded.

Test plots for Band Edge Measurements (Radiated):






Test Channel:

2405MHz

Ant. Polar. :

Vertical_Peak



Condition : Vertical

Project No. : 2501W00691E-RF

Tester : Leon Guo

Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak

Note : 2.4G_2405


		Read		Limit	Over	Remark
Freq Factor		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2382.897	-10.98	78.31	67.33	74.00	-6.67 Peak
2	2390.000	-10.98	66.15	55.17	74.00	-18.83 Peak

Test Channel:

2405MHz

Ant. Polar. :

Vertical_Average



Condition : Vertical

Project No. : 2501W00691E-RF

Tester : Leon Guo

Spectrum setting: Average reading: RBW:1MHz VBW:1kHz Detector:Peak

Note : 2.4G_2405


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2389.040	-10.98	59.19	48.21	54.00	-5.79	Average
2	2390.000	-10.98	54.34	43.36	54.00	-10.64	Average

Test Channel:

2475MHz

Ant. Polar. :

Horizontal_Peak



Condition : Horizontal

Project No. : 2501W00691E-RF


Tester : Leon Guo

Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak

Note : 2.4G_2475


	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	61.38	50.41	74.00	-23.59	Peak
2	2490.948	-10.98	65.32	54.34	74.00	-19.66	Peak


Test Channel: 2475MHz Ant. Polar. : Horizontal_Average




Condition : Horizontal
 Project No. : 2501W00691E-RF
 Tester : Leon Guo
 Spectrum setting: Average reading: RBW:1MHz VBW:1kHz Detector:Peak
 Note : 2.4G_2475

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	48.60	37.63	54.00	-16.37	Average
2	2490.873	-10.98	53.28	42.30	54.00	-11.70	Average






Listed with the worst margin test plot:




Vertical





1-4GHz


Condition : Vertical
Project No. : 2501W00691E-RF
Tester : Leon Guo
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : 2.4G_2475


	Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3583.750	-10.03	56.57	46.54	74.00	-27.46	Peak














FCC §15.247(a) (1) & RSS-247 § 5.1 (b) - CHANNEL SEPARATION TEST

Applicable Standard

According to FCC §15.247(a) (1):

Frequency hopping systems (FHSs) shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

According to RSS-247 § 5.1 (b):

Frequency hopping systems (FHSs) shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the -20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, FHSs operating in the band 2400-2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz or two thirds of the -20 dB bandwidth of the hopping channel, whichever is greater, provided that the systems operate with an output power no greater than 0.125 W. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.


Test Procedure

Test Method: ANSI C63.10-2020 Clause 7.8.2

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) $\geq$ RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined.



Test Data

Environmental Conditions

Temperature:	25.9 °C
Relative Humidity:	51 %
ATM Pressure:	100.5 kPa

The testing was performed by Cheeb Huang on 2025-08-29.

EUT operation mode: Transmitting


Test Result: Compliant

Note: According to frequency table in page 7 and investigating the hopping channel test in page 59, the minimum channel separation is the worst case which were recorded as below:

Test Frequency (MHz)	Test Frequency (MHz)	Channel Separation (MHz)	Limits (MHz)
2405-2475	Hop_2405MHz	2.026	1.433
Note: Limit= Two-thirds of the 20 dB bandwidth			

Please refer to the below plots:

Hop_2405MHz



ProjectNo.:2501W00691E-RF Tester:Cheeb Huang
Date: 29.AUG.2025 13:38:17

FCC §15.247(a) (1) & RSS-GEN § 6.7 & RSS-247 § 5.1 (a) - 99% OCCUPIED BANDWIDTH & 20 dB EMISSION BANDWIDTH

Applicable Standard

According to FCC §15.247(a) (1):

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

According to RSS-247 § 5.1 (a), RSS-GEN § 6.7:

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “20 dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated 20 dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

Test Procedure

Test Method: ANSI C63.10-2020 Clause 7.8.7 & Clause 6.9.2


- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max hold.
- g) Determine the reference value: Set the EUT to transmit an un-modulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.

i) If the reference value is determined by an un-modulated carrier, then turn the EUT modulation on, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).

j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “- xx dB down

amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “- xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



Test Data

Environmental Conditions

Temperature:	25.9 °C
Relative Humidity:	51 %
ATM Pressure:	100.5 kPa

The testing was performed by Cheeb Huang on 2025-08-29.


EUT operation mode: Transmitting

Test Result: Compliant

Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)	OBW (MHz)
Lowest	2405	2.150	1.811
Middle	2441	2.127	1.799
Highest	2475	2.146	1.805

Please refer to the below plots:

Low Channel



ProjectNo.:2501W00691E-RF Tester:Cheeb Huang
Date: 29.AUG.2025 11:28:40

ProjectNo.:2501W00691E-RF Tester:Cheeb Huang
Date: 29.AUG.2025 11:23:59

Low Channel	99% Emission Bandwidth Ref 40.5 dBm Att 30 dB RBW 30 kHz VBW 100 kHz SWT 30 ms Marker 1 [T1] 13.62 dBm 2.405000000 GHz Offset 10.15 dB OSW 1.810810811 MHz Temp 1 [T1 OSW] -3.08 dBm 2.404108108 GHz Temp 2 [T1 OSW] -3.18 dBm 2.40591919 GHz LVL Center 2.405 GHz 600 kHz/ Span 6 MHz ProjectNo.:2501W00691E-RF Tester:Cheeb Huang Date: 29.AUG.2025 11:42:20
--	--

FCC §15.247(a) (1) (iii) & RSS-247 § 5.1 (d) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

According to FCC §15.247(a) (1) (iii):

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

According to RSS-247 § 5.1 (d):


Frequency hopping systems (FHSS) operating in the band 2400-2483.5 MHz shall use at least 15 hopping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed. Transmissions on particular hopping frequencies may be avoided or suppressed provided that at least 15 hopping channels are used.

Test Procedure

Test Method: ANSI C63.10-2020 Clause 7.8.3

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW $\geq$ RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.

It might prove necessary to break the span up into sub ranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels.



Test Data

Environmental Conditions


Temperature:	25.9 °C
Relative Humidity:	51 %
ATM Pressure:	100.5 kPa

The testing was performed by Cheeb Huang on 2025-08-29.

EUT operation mode: Transmitting

Test Result: Compliant

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
GFSK	2400-2483.5	16	≥15



Note: The EUT has 32 channels available, but only 16 channels will be activated randomly each time..

FCC §15.247(a) (1) (iii) & RSS-247 § 5.1 (d) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

According to FCC §15.247(a) (1) (iii):

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.


According to RSS-247 § 5.1 (d):

Frequency hopping systems (FHSs) operating in the band 2400-2483.5 MHz shall use at least 15 hopping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed. Transmissions on particular hopping frequencies may be avoided or suppressed provided that at least 15 hopping channels are used.

Test Procedure

According to ANSI C63.10-2020 section 7.8.4

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses



Test Data**Environmental Conditions**


Temperature:	25.9 °C
Relative Humidity:	51 %
ATM Pressure:	100.5 kPa

The testing was performed by Cheeb Huang on 2025-08-29.


EUT operation mode: Transmitting

Test Result: Compliant

Test Frequency (MHz)	Pulse Width (ms)	Observation time (s)	Hopping Numbers in Observation time	Dwell Time (s)	Limit (s)
Hop_2405	7.505	6.4	30	0.225	0.400
Observation time= Hopping Channel Number× 0.4= 16× 0.4= 6.4 (s)					
Dwell Time = Pulse Width × Hopping Numbers in Observation time					



ProjectNo.:2501W00691E-RF Tester:Cheeb Huang
Date: 29.AUG.2025 13:50:28



ProjectNo.:2501W00691E-RF Tester:Cheeb Huang
Date: 29.AUG.2025 13:47:58

FCC §15.247(b) (1) & RSS-247§ 5.1(b) &§ 5.4(b) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

According to § RSS-247§ 5.4(b), For frequency hopping systems (FHSs) operating in the band 2400–2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels. The e.i.r.p. shall not exceed 4 W (see Section 5.4(e) for exceptions).

According to § RSS-247§ 5.1(b), Frequency hopping systems (FHSs) shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, FHSs operating in the band 2400–2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz or two thirds of the -20 dB bandwidth of the hopping channel, whichever is greater, provided that the systems operate with an output power no greater than 0.125 W.

Test Procedure

Test Method: ANSI C63.10-2020 Clause 7.8.5

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:


a) Use the following spectrum analyzer settings:

- 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- 2) RBW > 20 dB bandwidth of the emission being measured.
- 3) VBW ≥ RBW.
- 4) Sweep: Auto.
- 5) Detector function: Peak.
- 6) Trace: Max hold.

b) Allow trace to stabilize.

c) Use the marker-to-peak function to set the marker to the peak of the emission.

d) The indicated level is the peak output power, after any corrections for external attenuators and cables.



Note: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was add with offset into test equipment, the total offset consists of attenuator and/or RF cable loss

Test Data**Environmental Conditions**

Temperature:	25.9 °C
Relative Humidity:	51 %
ATM Pressure:	100.5 kPa


The testing was performed by Cheeb Huang on 2025-08-29.

EUT operation mode: Transmitting

Test Result: Compliant


Mode	Test Channel	Test Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)	Limits (dBm)
GFSK	Lowest	2405	18.55	21
	Middle	2441	18.02	21
	Highest	2475	16.72	21
Note: the antenna gain=0dBi, the maximum EIRP=18.55dBm<36dBm(ISED limit)				

Low Channel




ProjectNo.:2501W00691E-RF Tester:Cheeb Huang
Date: 29.AUG.2025 09:54:05

Middle Channel



ProjectNo.:2501W00691E-RF Tester:Cheeb Huang
Date: 29.AUG.2025 09:55:55

High Channel



ProjectNo.:2501W00691E-RF Tester:Cheeb Huang
Date: 29.AUG.2025 09:57:20

FCC §15.247(d) & RSS-247 § 5.5 - BAND EDGES TESTING

Applicable Standard

According to FCC §15.247(d).

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


According to RSS-247 § 5.5.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(e), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Test Procedure

According to ANSI C63.10-2020 section 6.10

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data**Environmental Conditions**

Temperature:	25.9 °C
Relative Humidity:	51 %
ATM Pressure:	100.5 kPa


The testing was performed by Cheeb Huang on 2025-08-29.

EUT operation mode: Transmitting

Test Result: Compliant


Conducted Band Edge Result:

GFSK_Low Channel




ProjectNo.:2501W00691E-RF Tester:Cheeb Huang
Date: 29.AUG.2025 10:09:34

GFSK_Hop_Low Channel




ProjectNo.:2501W00691E-RF Tester:Cheeb Huang
Date: 29.AUG.2025 13:53:15

GFSK_High Channel



ProjectNo.:2501W00691E-RF Tester:Cheeb Huang
Date: 29.AUG.2025 10:06:59

GFSK_Hop_High Channel



ProjectNo.:2501W00691E-RF Tester:Cheeb Huang
Date: 29.AUG.2025 14:15:18

FCC §15.247(d) & RSS-247 § 5.5 - CONDUCTED SPURIOUS EMISSION**Applicable Standard**

According to FCC §15.247(d).

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to RSS-247 § 5.5.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(e), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Test Procedure

Test Method: ANSI C63.10-2020 Clause 11.11.3

Establish an emission level by using the following procedure:

a) Set the center frequency and span to encompass frequency range to be measured. Note that the frequency range might need to be divided into multiple frequency ranges to retain frequency resolution.

NOTE—the number of points can also be increased for large spans to retain frequency resolution

b) Set the RBW = 100 kHz.

c) Set the VBW $\geq [3 \times \text{RBW}]$.

d) Detector = peak.


e) Sweep time = No faster than coupled (auto) time.

f) Trace mode = max-hold.

g) Allow trace to fully stabilize.

h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit



Note: Worst case: Offset (10.5dB) = Attenuator (10dB) + Cable loss (0.5dB)

Test Data**Environmental Conditions**


Temperature:	25.9 °C
Relative Humidity:	51 %
ATM Pressure:	100.5 kPa

The testing was performed by Cheeb Huang on 2025-08-29.

EUT operation mode: Transmitting


Test Result: Compliant

Low Channel




ProjectNo.:2501W00691E-RF Tester:Cheeb Huang
Date: 29.AUG.2025 10:39:12

Middle Channel



ProjectNo.:2501W00691E-RF Tester:Cheeb Huang
Date: 29.AUG.2025 11:54:56

High Channel



ProjectNo.:2501W00691E-RF Tester:Cheeb Huang
Date: 29.AUG.2025 13:13:47

EUT PHOTOGRAPHS

Please refer to the attachment 2501W00691E-RF-EXPA External photo and 2501W00691E-RF-INPA Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2501W00691E-RFA-TSP Test Setup photo.

******* END OF REPORT *******