

TEST REPORT

Report No.: 25090305HKG-001

VTech Telecommunications Ltd.

Application For Original Grant of 47 CFR Part 15 Certification

New Family of RSS-247 Issue 4 Certification

Video Baby Monitor

FCC ID: EW780-3688-00

IC: 1135B-80368800

This report contains the data of 2.4GHz Wi-Fi portion only

Prepared and Checked by:

Approved by:

Signed on File

Leung Chun Ning, Peter
Engineer

 Digitally signed by
Herbert Wong
Location: Intertek
Testing Services
Hong Kong Limited

Wong Cheuk Ho, Herbert
Assistant Manager
Date: February 05, 2026

Intertek's standard Terms and Conditions can be obtained at our website <http://www.intertek.com/terms/>.

The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

© 2017 Intertek

TEST REPORT

GENERAL INFORMATION

Grantee:	VTech Telecommunications Ltd.
Grantee Address:	23/F., Tai Ping Industrial Centre, Block 1, 57 Ting Kok Road, Tai Po, Hong Kong.
Manufacturer Name:	VTech (Dongguan) Telecommunications Limited
Manufacturer Address:	VTech Science Park, Xia Ling Bei Management Zone, Liaobu, Dongguan, Guangdong, China.
FCC Specification Standard:	FCC Part 15, October 1, 2024 Edition
FCC ID:	EW780-3688-00
FCC Model(s):	RM7968HQ BU, RM7968-2HQ BU
IC Specification Standard:	RSS-247 Issue 4, July 2025 RSS-Gen Issue 5 Amendment 2, February 2021
IC:	1135B-80368800
HVIN:	35-400644BU
PMN:	RM7968HQ BU, RM7968-2HQ BU
Type of EUT:	Spread Spectrum Transmitter
Description of EUT:	Video Baby Monitor
Brand Name:	Vtech
Sample Receipt Date:	October 08, 2025
Date of Test:	October 08, 2025 to December 12, 2025
Report Date:	February 05, 2026
Environmental Conditions:	Temperature: +10 to 40°C Relative Humidity: 10 to 90%
Conclusion:	Test was conducted by client submitted sample. The submitted sample as received complied with the 47 CFR Part 15 / RSS-247 Issue 4 Certification.

This report contains the data of 2.4GHz Wi-Fi portion only

TEST REPORT

SUMMARY OF TEST RESULT

Test Items	FCC Part 15 Section	RSS-247 / RSS-Gen [#] Section	Results
Antenna Requirement	15.203	6.8 [#]	Complied
Max. Conducted Output Power (Peak)	15.247(b)(3)&(4)	5.4(d)	Complied
Min. 6dB RF Bandwidth	15.247(a)(2)	5.2(a)	Complied
Max. Power Density (Average)	15.247(e)	5.2(b)	Complied
Out of Band Antenna Conducted Emission	15.247(d)	5.5	Complied
Radiated Emission in Restricted Bands and Spurious Emissions	15.247(d), 15.209 & 15.109	5.5	Complied
AC Power Line Conducted Emission	15.207 & 15.107	7.2 [#]	Complied

Note: Pursuant to FCC Part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

For all technical data, which can be referred to Annex B – Report cover sheet.

For electronic filing, the Annex B – Report cover sheet is saved with filename: Annex B.pdf.

The equipment under test is found to be complying with the following standards:

FCC Part 15, October 1, 2024 Edition

RSS-247 Issue 4, July 2025

RSS-Gen Issue 5 Amendment 2, February 2021

TEST REPORT

TABLE OF CONTENTS

EXHIBIT 1	GENERAL DESCRIPTION	5
1.1	Product Description.....	5
1.2	Test Methodology	5
1.3	Test Facility.....	6
1.4	Related Submittal(s) Grants	6
EXHIBIT 2	SYSTEM TEST CONFIGURATION	7
2.1	Justification	7
2.2	EUT Exercising Software	8
2.3	Details of EUT and Description of Accessories	9
2.4	Measurement Uncertainty	9
EXHIBIT 3	TEST RESULTS	10
3.1	Maximum Conducted (Peak) Output Power at Antenna Terminals	10
3.2	Minimum 6dB RF Bandwidth.....	12
3.3	Minimum Power Spectral Density	13
3.4	Out of Band Conducted Emissions	14
3.5	Field Strength Calculation	16
3.6	Transmitter Radiated Emissions in Restricted Bands and Spurious Emissions	17
3.7	Transmitter Duty Cycle Calculation	40
3.8	AC Power Line Conducted Emission	40
EXHIBIT 4	EQUIPMENT LIST	44

TEST REPORT

EXHIBIT 1 GENERAL DESCRIPTION

1.1 Product Description

The RM7968HQ BU (35-400644BU) is a Video Baby Monitor - Baby Unit.

The Equipment Under Test (EUT) operates at frequency range of 2412 MHz to 2462 MHz with 11 channels.

For IEEE 802.11b mode, it operates at frequency range of 2412.000 MHz to 2462.000 MHz with 11 channels. It transmits via Direct-sequence spread spectrum (DSSS) modulation. Maximum bit rate can be up to 11Mbps.

For IEEE 802.11g mode, it operates at frequency range of 2412.000 MHz to 2462.000 MHz with 11 channels. It transmits via Orthogonal Frequency Division Multiplexing (OFDM) modulation. Maximum bit rate can be up to 54Mbps.

For IEEE 802.11n (with 20 MHz bandwidth) mode, it operates at frequency range of 2412.000 MHz to 2462.000 MHz with 11 channels. It transmits via Orthogonal Frequency Division Multiplexing (OFDM) modulation. Maximum bit rate can support up to 72.2Mbps.

For IEEE 802.11ax (with 20 MHz bandwidth) mode, it operates at frequency range of 2412.000 MHz to 2462.000 MHz with 11 channels. It transmits via Orthogonal Frequency Division Multiplexing (OFDM) modulation. Maximum bit rate can support up to 143.4Mbps.

The EUT is powered by 100-240VAC 50/60Hz 0.35A adaptor.

The antenna(s) used in the EUT is integral, and the test sample is a prototype.
Peak Antenna Gain: 0dBi

For FCC, the Model(s): RM7968-2HQ BU is the same as the Model: RM7968HQ BU in electronics/electrical designs including software & firmware, PCB layout and construction design/physical design/enclosure. The only differences between these models are model number to be sold for marketing purpose as declared by client.

The circuit description is saved with filename: descri.pdf.

1.2 Test Methodology

Both AC power line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024. Preliminary radiated scans and all radiated measurements were performed in radiated emission test sites. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

Antenna port conducted measurements were performed according to ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024 and KDB Publication No. 558074 D01 v05r02 (April 02, 2019) All other measurements were made in accordance with the procedures in 47 CFR Part 2 and RSS-Gen Issue 5 Amendment 2, February 2021.

TEST REPORT

1.3 Test Facility

The radiated emission test site and antenna port conducted measurement facility used to collect the radiated data and conductive data are at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong SAR, China. This test facility and site measurement data have been fully placed on file with the FCC and Industry Canada No.: 2042H, CABID is "HKAP01".

1.4 Related Submittal(s) Grants

This is a single application for certification of a transceiver (2.4GHz Wi-Fi Portion).

TEST REPORT

EXHIBIT 2 SYSTEM TEST CONFIGURATION

2.1 Justification

For radiated emissions testing, the equipment under test (EUT) was setup to transmit / receive continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables (if any) were manipulated to produce worst case emissions.

The EUT was powered by 120VAC during test.

For the measurements, the EUT was attached to a plastic stand if necessary and placed on the wooden turntable at 0.8m height from the ground plane for emission testing at or below 1GHz and 1.5m for emission measurements above 1GHz. If the baby unit attached to peripherals, they were connected and operational (as typical as possible). The parent unit was remotely located as far from the antenna and the baby as possible to ensure full power transmission from the parent unit. Else, the base was wired to transmit full power with modulation.

For maximizing emissions below 30MHz, the EUT was rotated through 360°, the centre of the loop antenna was placed 1 meter above the ground, and the antenna polarization was changed.

The signal was maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization were varied during the search for maximum signal level. The antenna height was varied from 1 to 4 meters. Radiated emissions were taken at three meters unless the signal level was too low for measurement at that distance. If necessary, a pre-amplifier was used and/or the test was conducted at a closer distance.

For any intentional radiator powered by AC power line, measurements of the radiated signal level of the fundamental frequency component of the emission was performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

Radiated emission measurement for transmitter were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

Emission that are directly caused by digital circuits in the transmit path and transmitter portion were measured, and the limit are according to FCC Part 15 Section 15.209 / RSS-247 2.5. Digital circuitries used to control additional functions other than the operation of the transmitter are subject to FCC Part 15 Section 15.109 / RSS-247 Section 5.5 Limits.

TEST REPORT

2.1 Justification (Cont'd)

Detector function for radiated emissions was in peak mode. Average readings, when required, were taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in section 4.8.3.

Determination of pulse desensitization was made according to *Hewlett Packard Application Note 150-2, Spectrum Analysis... Pulsed RF*. The effective period (Teff) was referred to Exhibit 4.8.3. With the resolution bandwidth 1MHz and spectrum analyzer IF bandwidth 3dB, the pulse desensitization factor was 0dB.

For AC power line-conducted emission test, the EUT along with its peripherals were placed on a 1.0m(W)x1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN), which provided 50ohm coupling impedance for measuring instrument. The LISN housing, measuring instrument case, reference ground plane, and vertical ground plane were bounded together. The excess power cable between the EUT and the LISN was bundled.

All connecting cables of EUT and peripherals were manipulated to find the maximum emission.

All relevant operation modes have been tested, and the worst-case data is included in this report.

All data rates were tested under normal mode of Wi-Fi. Only the worst-case data is shown in the report for DSSS and OFDM.

For simultaneous transmission, both Wi-Fi, BLE and FHSS portions are also switched on when taking radiated emission for determining worst-case spurious emission.

2.2 EUT Exercising Software

The EUT exercise program (Tera Terms Version 4.106) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

TEST REPORT

2.3 Details of EUT and Description of Accessories

Details of EUT:

An AC/DC Adaptor (provided with the unit) was used to power the device.
Their descriptions are listed below.

- (1) An AC/DC adaptor (Model: A938-050150W-US1; Brand Name: Aohai; Input: 100-240VAC 50/60Hz 0.35A; Output: 5.0VDC 1.5A) (Provided by Applicant)
- (2) An AC/DC adaptor (Model: VT07EUS05150; Brand Name: VTPL; Input: 100-240VAC 50/60Hz 0.5A; Output: 5.0VDC 1.5A 7.5W) (Provided by Applicant)

Description of Accessories:

- (1) Parent Unit (Provided by Applicant)

2.4 Measurement Uncertainty

Decision Rule for compliance: For FCC/IC standard, the measured value must be within the limits of applicable standard without accounting for the measurement uncertainty. For EN/IEC/HKTA/HKTC standard, conformity rules will be used as per standard directly excepted EN/IEC 61000-3-2, EN/IEC 61000-3-3, HKTA1004, HKCA1008, HKTA1019, HKTA1020, HKTA1041 and HKTA1044.


TEST REPORT

EXHIBIT 3 TEST RESULTS

3.1 Maximum Conducted (Peak) Output Power at Antenna Terminals

RF Conduct Measurement Test Setup

The figure below shows the test setup, which is utilized to make these measurements.



The antenna port of the EUT was connected to the input of a spectrum analyzer.

- ☒ The antenna power of the EUT was connected to the input of a power meter. Power was read directly and cable loss correction was added to the reading to obtain power at the EUT antenna terminals. The measurement procedure 8.3.2.3 was used.
- ☐ The EUT should be configured to transmit continuously (at a minimum duty cycle of 98%) at full power over the measurement duration. The measurement procedure AVG1 was used.

IEEE 802.11b (DSSS, 1 Mbps) Peak Antenna Gain = 0 dBi (Refer to Test Data1.pdf)

Frequency (MHz)	Output in dBm	Output in mW
Low Channel: 2412 (P.6)	20.98	125.31
Middle Channel: 2437 (P.18)	21.88	154.17
High Channel: 2462 (P.27)	21.52	141.91

IEEE 802.11g (OFDM, 6 Mbps) Peak Antenna Gain = 0 dBi (Refer to Test Data2.pdf)

Frequency (MHz)	Output in dBm	Output in mW
Low Channel: 2412 (P.6)	18.19	65.92
Middle Channel: 2437 (P.18)	18.96	78.70
High Channel: 2462 (P.27)	18.68	73.79

IEEE 802.11n (20MHz) (OFDM, MCS0) Peak Antenna Gain = 0 dBi (Refer to Test Data3.pdf)

Frequency (MHz)	Output in dBm	Output in mW
Low Channel: 2412 (P.6)	18.19	65.92
Middle Channel: 2437 (P.18)	18.84	76.56
High Channel: 2462 (P.27)	18.52	71.12

IEEE 802.11ax (20MHz) (OFDM, MCS0) Peak Antenna Gain = 0 dBi (Refer to Test Data4.pdf)

Frequency (MHz)	Output in dBm	Output in mW
Low Channel: 2412 (P.6)	17.24	52.97
Middle Channel: 2437 (P.18)	17.90	61.66
High Channel: 2462 (P.27)	17.59	57.41

TEST REPORT

3.1 Maximum Conducted (Peak) Output Power at Antenna Terminals (Cont'd)

Cable loss: 0.5 dB External Attenuation: 0 dB

Cable loss, external attenuation: ☒ included in OFFSET function
☐ added to SA raw reading

IEEE 802.11b (DSSS, 1 Mbps)

Max. Conducted (Peak) Output Level = 21.88 dBm

IEEE 802.11g (OFDM, 6 Mbps)

Max. Conducted (Peak) Output Level = 18.96 dBm

IEEE 802.11n (20MHz) (OFDM, MCS0)

Max. Conducted (Peak) Output Level = 18.84 dBm

IEEE 802.11ax (20MHz) (OFDM, MCS0)

Max. Conducted (Peak) Output Level = 17.90 dBm


Limits:

1W (30dBm) for antennas with gains of 6dBi or less.

TEST REPORT

3.2 Minimum 6dB RF Bandwidth

The figure below shows the test setup, which is utilized to make these measurements.



The antenna port of the EUT was connected to the input of a spectrum analyzer. The EBW measurement procedure was used. A PEAK output reading was taken, a DISPLAY line was drawn 6dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

IEEE 802.11b (DSSS, 1 Mbps) (Refer to Test Data1.pdf)

Frequency (MHz)	6dB Bandwidth (MHz)
Low Channel: 2412 (P.3)	10.45
Middle Channel: 2437 (P.17)	11.50
High Channel: 2462 (P.26)	9.75

IEEE 802.11g (OFDM, 6 Mbps) (Refer to Test Data2.pdf)

Frequency (MHz)	6dB Bandwidth (MHz)
Low Channel: 2412 (P.3)	15.65
Middle Channel: 2437 (P.17)	14.20
High Channel: 2462 (P.26)	15.80

IEEE 802.11n (20MHz) (OFDM, MCS0) (Refer to Test Data3.pdf)

Frequency (MHz)	6dB Bandwidth (MHz)
Low Channel: 2412 (P.3)	16.80
Middle Channel: 2437 (P.17)	16.65
High Channel: 2462 (P.26)	17.80

IEEE 802.11ax (20MHz) (OFDM, MCS0) (Refer to Test Data4.pdf)

Frequency (MHz)	6dB Bandwidth (MHz)
Low Channel: 2412 (P.3)	17.65
Middle Channel: 2437 (P.17)	16.40
High Channel: 2462 (P.26)	17.35


Limits:

6dB bandwidth shall be at least 500kHz.

TEST REPORT

3.3 Minimum Power Spectral Density

The figure below shows the test setup, which is utilized to make these measurements.



Antenna output of the EUT was coupled directly to spectrum analyzer. The measurement procedure 10.2 PKPSD was used. If an external attenuator and/or cable was used, these losses are compensated for using the OFFSET function of the analyser.

IEEE 802.11b (DSSS, 1 Mbps) (Refer to Test Data1.pdf)

Frequency (MHz)	PSD in 100kHz (dBm)
Low Channel: 2412 (P.7)	5.345
Middle Channel: 2437 (P.19)	6.702
High Channel: 2462 (P.28)	5.445

IEEE 802.11g (OFDM, 6 Mbps) (Refer to Test Data2.pdf)

Frequency (MHz)	PSD in 100kHz (dBm)
Low Channel: 2412 (P.7)	-0.037
Middle Channel: 2437 (P.19)	2.001
High Channel: 2462 (P.28)	-1.928

IEEE 802.11n (20MHz) (OFDM, MCS0) (Refer to Test Data3.pdf)

Frequency (MHz)	PSD in 100kHz (dBm)
Low Channel: 2412 (P.7)	0.912
Middle Channel: 2437 (P.19)	2.884
High Channel: 2462 (P.28)	0.907

IEEE 802.11ax (20MHz) (OFDM, MCS0) (Refer to Test Data4.pdf)

Frequency (MHz)	PSD in 100kHz (dBm)
Low Channel: 2412 (P.7)	0.005
Middle Channel: 2437 (P.19)	1.776
High Channel: 2462 (P.28)	0.877


Cable Loss: 0.5dB

Limit: 8dBm in 3kHz

TEST REPORT

3.4 Out of Band Conducted Emissions

The figure below shows the test setup, which is utilized to make these measurements.



For IEEE 802.11b/g/n20MHz/ax20MHz, the maximum conducted (peak) output power was used to demonstrate compliance as described in 9.1. Then the display line (in red) shown in the following plots denotes the limit at 20dB below maximum measured in-band peak PSD level in 100 KHz bandwidth for IEEE 802.11b/g/n20MHz/ax20MHz.

The measurement procedures under sections 11 of KDB558074 D01 v05r02 (April 2, 2019) were used.

Furthermore, delta measurement technique for measuring bandedge emissions was incorporated in the test of the edge at 2483.5MHz.

Limits:

All spurious emission and up to the tenth harmonic was measured and they were found to be at least 20dB below the maximum measured in-band peak PSD level for IEEE 802.11b/g/n20MHz/ax20MHz.

IEEE 802.11b (DSSS, 1 Mbps) (Refer to Test Data1.pdf)

Frequency (MHz)	Out of Band Conducted Emissions	Band Edge
Low Channel: 2412	P.12	P.8
Middle Channel: 2437	P.21	N/A
High Channel: 2462	P.33	P.29

IEEE 802.11g (OFDM, 6 Mbps) (Refer to Test Data2.pdf)

Frequency (MHz)	Out of Band Conducted Emissions	Band Edge
Low Channel: 2412	P.12	P.8
Middle Channel: 2437	P.23	N/A
High Channel: 2462	P.33	P.29

IEEE 802.11n (20MHz) (OFDM, MCS0) (Refer to Test Data3.pdf)

Frequency (MHz)	Out of Band Conducted Emissions	Band Edge
Low Channel: 2412	P.12	P.8
Middle Channel: 2437	P.21	N/A
High Channel: 2462	P.33	P.29

TEST REPORT

IEEE 802.11ax (20MHz) (OFDM, MCS0) (Refer to Test Data4.pdf)

Frequency (MHz)	Out of Band Conducted Emissions	Band Edge
Low Channel: 2412	P.12	P.8
Middle Channel: 2437	P.21	N/A
High Channel: 2462	P.33	P.29

TEST REPORT

3.5 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

Where	FS	=	Field Strength in dB μ V/m
	RA	=	Receiver Amplitude (including preamplifier) in dB μ V
	CF	=	Cable Attenuation Factor in dB
	AF	=	Antenna Factor in dB
	AG	=	Amplifier Gain in dB
	PD	=	Pulse Desensitization in dB
	AV	=	Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Example:

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29.0 dB is subtracted. The pulse desensitization factor of the spectrum analyzer is 0.0 dB, and the resultant average factor is -10.0 dB. The net field strength for comparison to the appropriate emission limit is 32.0 dB μ V/m. This value in dB μ V/m is converted to its corresponding level in μ V/m.

$$\begin{aligned}
 RA &= 62.0 \text{ dB}\mu\text{V} \\
 AF &= 7.4 \text{ dB} \\
 CF &= 1.6 \text{ dB} \\
 AG &= 29.0 \text{ dB} \\
 PD &= 0.0 \text{ dB} \\
 AV &= -10.0 \text{ dB} \\
 FS &= 62.0 + 7.4 + 1.6 - 29.0 + 0.0 + (-10.0) = 32.0 \text{ dB}\mu\text{V/m}
 \end{aligned}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(32.0 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

TEST REPORT

3.6 Transmitter Radiated Emissions in Restricted Bands and Spurious Emissions

Data is included of the worst-case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

3.6.1 Radiated Emission Configuration Photograph

Worst Case Restricted Band Radiated Emission at 4874 MHz.

The worst case radiated emission configuration photographs are saved with filename:
Setup Photos.pdf

3.6.2 Radiated Emission Data


The data in tables 1-16 list the significant emission frequencies, the limit and the margin of compliance.

Judgement – Passed by 6.3 dB margin


TEST REPORT

3.6.3 Radiated Emission Test Setup

The figure below shows the test setup, which is utilized to make these measurements.




Test setup of radiated emissions 9kHz to 30MHz



Test setup of radiated emissions up to 1GHz

TEST REPORT



Test setup of radiated emissions above 1GHz

TEST REPORT

RADIATED EMISSION DATA

Mode: TX-Channel 01

Table 1, IEEE 802.11b DSSS 1Mbps

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (average) (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
H	2390.000	49.1	33	29.4	45.5	54.0	-8.5
V	4824.000	41.4	33	34.9	43.3	54.0	-10.7
V	7236.000	31.8	33	37.9	36.7	54.0	-17.3
H	9648.000	34.0	33	40.4	41.4	54.0	-12.6
V	12060.000	37.8	33	40.5	45.3	54.0	-8.7
V	14472.000	38.7	33	40.0	45.7	54.0	-8.3

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
H	2390.000	62.7	33	29.4	59.1	74.0	-14.9
V	4824.000	57.0	33	34.9	58.9	74.0	-15.1
V	7236.000	46.0	33	37.9	50.9	74.0	-23.1
H	9648.000	47.7	33	40.4	55.1	74.0	-18.9
V	12060.000	51.1	33	40.5	58.6	74.0	-15.4
V	14472.000	52.2	33	40.0	59.2	74.0	-14.8

- Notes:
1. Peak detector is used for the emission measurement.
 2. Average detector is used for the average data of emission measurement.
 3. All measurements were made at 3 meters.
 4. Negative value in the margin column shows emission below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
 7. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.
 8. For the measurement of radiated emission, summation method was used which numerical integrating (in terms of linear power) over the transmitter occupied bandwidth.
 9. For the linear power measurement, data in 1MHz spacing was collected by spectrum analyzer with 1MHz resolution bandwidth.

TEST REPORT

RADIATED EMISSION DATA

Mode: TX-Channel 06

Table 2, IEEE 802.11b DSSS 1Mbps

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (average) (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	4874.000	45.8	33	34.9	47.7	54.0	-6.3
V	7311.000	30.9	33	37.9	35.8	54.0	-18.2
V	9748.000	32.5	33	40.4	39.9	54.0	-14.1
V	12185.000	38.5	33	40.5	46.0	54.0	-8.0
V	14622.000	38.7	33	38.4	44.1	54.0	-9.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	4874.000	61.8	33	34.9	63.7	74.0	-10.3
V	7311.000	43.9	33	37.9	48.8	74.0	-25.2
V	9748.000	46.0	33	40.4	53.4	74.0	-20.6
V	12185.000	51.8	33	40.5	59.3	74.0	-14.7
V	14622.000	52.7	33	38.4	58.1	74.0	-15.9

- Notes:
1. Peak detector is used for the emission measurement.
 2. Average detector is used for the average data of emission measurement.
 3. All measurements were made at 3 meters.
 4. Negative value in the margin column shows emission below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
 7. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.
 8. For the measurement of radiated emission, summation method was used which numerical integrating (in terms of linear power) over the transmitter occupied bandwidth.
 9. For the linear power measurement, data in 1MHz spacing was collected by spectrum analyzer with 1MHz resolution bandwidth.

TEST REPORT

RADIATED EMISSION DATA

Mode: TX-Channel 11

Table 3, IEEE 802.11b DSSS 1Mbps

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (average) (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
H	2483.500	49.7	33	29.4	46.1	54.0	-7.9
V	4924.000	40.8	33	34.9	42.7	54.0	-11.3
V	7386.000	32.0	33	37.9	36.9	54.0	-17.1
V	9848.000	32.9	33	40.4	40.3	54.0	-13.7
H	12310.000	38.7	33	40.5	46.2	54.0	-7.8
H	14772.000	37.7	33	38.4	43.1	54.0	-10.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
H	2483.500	63.3	33	29.4	59.7	74.0	-14.3
V	4924.000	56.4	33	34.9	58.3	74.0	-15.7
V	7386.000	47.2	33	37.9	52.1	74.0	-21.9
V	9848.000	46.4	33	40.4	53.8	74.0	-20.2
H	12310.000	52.4	33	40.5	59.9	74.0	-14.1
H	14772.000	51.7	33	38.4	57.1	74.0	-16.9

- Notes:
1. Peak detector is used for the emission measurement.
 2. Average detector is used for the average data of emission measurement.
 3. All measurements were made at 3 meters.
 4. Negative value in the margin column shows emission below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
 7. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.
 8. For the measurement of radiated emission, summation method was used which numerical integrating (in terms of linear power) over the transmitter occupied bandwidth.
 9. For the linear power measurement, data in 1MHz spacing was collected by spectrum analyzer with 1MHz resolution bandwidth.

TEST REPORT

RADIATED EMISSION DATA

Mode: TX-Channel 01

Table 4, IEEE 802.11g OFDM, 6 Mbps

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (average) (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2390.000	49.3	33	29.4	45.7	54.0	-8.3
V	4824.000	37.4	33	34.9	39.3	54.0	-14.7
H	7236.000	30.7	33	37.9	35.6	54.0	-18.4
V	9648.000	32.8	33	40.4	40.2	54.0	-13.8
V	12060.000	37.3	33	40.5	44.8	54.0	-9.2
V	14472.000	38.5	33	40.0	45.5	54.0	-8.5

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2390.000	65.5	33	29.4	61.9	74.0	-12.1
V	4824.000	47.5	33	34.9	49.4	74.0	-24.6
H	7236.000	44.6	33	37.9	49.5	74.0	-24.5
V	9648.000	46.2	33	40.4	53.6	74.0	-20.4
V	12060.000	51.1	33	40.5	58.6	74.0	-15.4
V	14472.000	51.5	33	40.0	58.5	74.0	-15.5

- Notes:
1. Peak detector is used for the emission measurement.
 2. Average detector is used for the average data of emission measurement.
 3. All measurements were made at 3 meters.
 4. Negative value in the margin column shows emission below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
 7. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.
 8. For the measurement of radiated emission, summation method was used which numerical integrating (in terms of linear power) over the transmitter occupied bandwidth.
 9. For the linear power measurement, data in 1MHz spacing was collected by spectrum analyzer with 1MHz resolution bandwidth.

TEST REPORT

RADIATED EMISSION DATA

Mode: TX-Channel 06

Table 5, IEEE 802.11g OFDM, 6 Mbps

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (average) (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	4874.000	31.7	33	34.9	33.6	54.0	-20.4
H	7311.000	30.9	33	37.9	35.8	54.0	-18.2
V	9748.000	33.4	33	40.4	40.8	54.0	-13.2
H	12185.000	38.5	33	40.5	46.0	54.0	-8.0
V	14622.000	38.7	33	38.4	44.1	54.0	-9.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	4874.000	51.2	33	34.9	53.1	74.0	-20.9
H	7311.000	44.9	33	37.9	49.8	74.0	-24.2
V	9748.000	47.2	33	40.4	54.6	74.0	-19.4
H	12185.000	51.8	33	40.5	59.3	74.0	-14.7
V	14622.000	52.0	33	38.4	57.4	74.0	-16.6

- Notes:
1. Peak detector is used for the emission measurement.
 2. Average detector is used for the average data of emission measurement.
 3. All measurements were made at 3 meters.
 4. Negative value in the margin column shows emission below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
 7. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.
 8. For the measurement of radiated emission, summation method was used which numerical integrating (in terms of linear power) over the transmitter occupied bandwidth.
 9. For the linear power measurement, data in 1MHz spacing was collected by spectrum analyzer with 1MHz resolution bandwidth.

TEST REPORT

RADIATED EMISSION DATA

Mode: TX-Channel 11

Table 6, IEEE 802.11g OFDM, 6 Mbps

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (average) (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2483.500	50.0	33	29.4	46.4	54.0	-7.6
V	4924.000	31.0	33	34.9	32.9	54.0	-21.1
V	7386.000	31.5	33	37.9	36.4	54.0	-17.6
H	9848.000	32.7	33	40.4	40.1	54.0	-13.9
H	12310.000	38.6	33	40.5	46.1	54.0	-7.9
V	14772.000	37.7	33	38.4	43.1	54.0	-10.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2483.500	68.9	33	29.4	65.3	74.0	-8.7
V	4924.000	48.1	33	34.9	50.0	74.0	-24.0
V	7386.000	48.0	33	37.9	52.9	74.0	-21.1
H	9848.000	46.3	33	40.4	53.7	74.0	-20.3
H	12310.000	52.1	33	40.5	59.6	74.0	-14.4
V	14772.000	50.9	33	38.4	56.3	74.0	-17.7

- Notes:
1. Peak detector is used for the emission measurement.
 2. Average detector is used for the average data of emission measurement.
 3. All measurements were made at 3 meters.
 4. Negative value in the margin column shows emission below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
 7. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.
 8. For the measurement of radiated emission, summation method was used which numerical integrating (in terms of linear power) over the transmitter occupied bandwidth.
 9. For the linear power measurement, data in 1MHz spacing was collected by spectrum analyzer with 1MHz resolution bandwidth.

TEST REPORT

RADIATED EMISSION DATA

Mode: TX-Channel 01

Table 7, IEEE 802.11n (20MHz) OFDM, MCS0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (average) (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2390.000	49.2	33	29.4	45.6	54.0	-8.4
V	4824.000	31.8	33	34.9	33.7	54.0	-20.3
H	7236.000	30.7	33	37.9	35.6	54.0	-18.4
H	9648.000	32.8	33	40.4	40.2	54.0	-13.8
V	12060.000	37.3	33	40.5	44.8	54.0	-9.2
V	14472.000	38.5	33	40.0	45.5	54.0	-8.5

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2390.000	66.2	33	29.4	62.6	74.0	-11.4
V	4824.000	52.8	33	34.9	54.7	74.0	-19.3
H	7236.000	44.0	33	37.9	48.9	74.0	-25.1
H	9648.000	46.0	33	40.4	53.4	74.0	-20.6
V	12060.000	50.9	33	40.5	58.4	74.0	-15.6
V	14472.000	52.2	33	40.0	59.2	74.0	-14.8

- Notes:
1. Peak detector is used for the emission measurement.
 2. Average detector is used for the average data of emission measurement.
 3. All measurements were made at 3 meters.
 4. Negative value in the margin column shows emission below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
 7. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.
 8. For the measurement of radiated emission, summation method was used which numerical integrating (in terms of linear power) over the transmitter occupied bandwidth.
 9. For the linear power measurement, data in 1MHz spacing was collected by spectrum analyzer with 1MHz resolution bandwidth.

TEST REPORT

RADIATED EMISSION DATA

Mode: TX-Channel 06

Table 8, IEEE 802.11n (20MHz) OFDM, MCS0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (average) (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	4874.000	30.6	33	34.9	32.5	54.0	-21.5
V	7311.000	30.9	33	37.9	35.8	54.0	-18.2
H	9748.000	33.4	33	40.4	40.8	54.0	-13.2
H	12185.000	38.5	33	40.5	46.0	54.0	-8.0
H	14622.000	38.7	33	38.4	44.1	54.0	-9.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	4874.000	48.6	33	34.9	50.5	74.0	-23.5
V	7311.000	43.9	33	37.9	48.8	74.0	-25.2
H	9748.000	47.3	33	40.4	54.7	74.0	-19.3
H	12185.000	51.8	33	40.5	59.3	74.0	-14.7
H	14622.000	51.6	33	38.4	57.0	74.0	-17.0

- Notes:
1. Peak detector is used for the emission measurement.
 2. Average detector is used for the average data of emission measurement.
 3. All measurements were made at 3 meters.
 4. Negative value in the margin column shows emission below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
 7. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.
 8. For the measurement of radiated emission, summation method was used which numerical integrating (in terms of linear power) over the transmitter occupied bandwidth.
 9. For the linear power measurement, data in 1MHz spacing was collected by spectrum analyzer with 1MHz resolution bandwidth.

TEST REPORT

RADIATED EMISSION DATA

Mode: TX-Channel 11

Table 9, IEEE 802.11n (20MHz) OFDM, MCS0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (average) (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2483.500	49.9	33	29.4	46.3	54.0	-7.7
H	4924.000	30.2	33	34.9	32.1	54.0	-21.9
H	7386.000	31.2	33	37.9	36.1	54.0	-17.9
V	9848.000	32.7	33	40.4	40.1	54.0	-13.9
V	12310.000	38.7	33	40.5	46.2	54.0	-7.8
H	14772.000	37.7	33	38.4	43.1	54.0	-10.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2483.500	66.9	33	29.4	63.3	74.0	-10.7
H	4924.000	45.3	33	34.9	47.2	74.0	-26.8
H	7386.000	44.4	33	37.9	49.3	74.0	-24.7
V	9848.000	46.8	33	40.4	54.2	74.0	-19.8
V	12310.000	52.0	33	40.5	59.5	74.0	-14.5
H	14772.000	50.9	33	38.4	56.3	74.0	-17.7

- Notes:
1. Peak detector is used for the emission measurement.
 2. Average detector is used for the average data of emission measurement.
 3. All measurements were made at 3 meters.
 4. Negative value in the margin column shows emission below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
 7. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.
 8. For the measurement of radiated emission, summation method was used which numerical integrating (in terms of linear power) over the transmitter occupied bandwidth.
 9. For the linear power measurement, data in 1MHz spacing was collected by spectrum analyzer with 1MHz resolution bandwidth.

TEST REPORT

RADIATED EMISSION DATA

Mode: TX-Channel 01

Table 10, IEEE 802.11ax (20MHz) OFDM, MCS0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (average) (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2390.000	49.4	33	29.4	45.8	54.0	-8.2
V	4824.000	31.2	33	34.9	33.1	54.0	-20.9
V	7236.000	30.8	33	37.9	35.7	54.0	-18.3
V	9648.000	32.8	33	40.4	40.2	54.0	-13.8
H	12060.000	37.3	33	40.5	44.8	54.0	-9.2
V	14472.000	38.5	33	40.0	45.5	54.0	-8.5

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2390.000	66.4	33	29.4	62.8	74.0	-11.2
V	4824.000	51.0	33	34.9	52.9	74.0	-21.1
V	7236.000	46.0	33	37.9	50.9	74.0	-23.1
V	9648.000	46.0	33	40.4	53.4	74.0	-20.6
H	12060.000	50.9	33	40.5	58.4	74.0	-15.6
V	14472.000	52.4	33	40.0	59.4	74.0	-14.6

- Notes:
1. Peak detector is used for the emission measurement.
 2. Average detector is used for the average data of emission measurement.
 3. All measurements were made at 3 meters.
 4. Negative value in the margin column shows emission below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
 7. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.
 8. For the measurement of radiated emission, summation method was used which numerical integrating (in terms of linear power) over the transmitter occupied bandwidth.
 9. For the linear power measurement, data in 1MHz spacing was collected by spectrum analyzer with 1MHz resolution bandwidth.

TEST REPORT

RADIATED EMISSION DATA

Mode: TX-Channel 06

Table 11, IEEE 802.11ax (20MHz) OFDM, MCS0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (average) (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	4874.000	31.5	33	34.9	33.4	54.0	-20.6
V	7311.000	30.9	33	37.9	35.8	54.0	-18.2
V	9748.000	33.3	33	40.4	40.7	54.0	-13.3
H	12185.000	38.4	33	40.5	45.9	54.0	-8.1
H	14622.000	38.7	33	38.4	44.1	54.0	-9.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	4874.000	50.8	33	34.9	52.7	74.0	-21.3
V	7311.000	44.1	33	37.9	49.0	74.0	-25.0
V	9748.000	46.6	33	40.4	54.0	74.0	-20.0
H	12185.000	51.8	33	40.5	59.3	74.0	-14.7
H	14622.000	51.7	33	38.4	57.1	74.0	-16.9

- Notes:
1. Peak detector is used for the emission measurement.
 2. Average detector is used for the average data of emission measurement.
 3. All measurements were made at 3 meters.
 4. Negative value in the margin column shows emission below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
 7. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.
 8. For the measurement of radiated emission, summation method was used which numerical integrating (in terms of linear power) over the transmitter occupied bandwidth.
 9. For the linear power measurement, data in 1MHz spacing was collected by spectrum analyzer with 1MHz resolution bandwidth.

TEST REPORT

RADIATED EMISSION DATA

Mode: TX-Channel 11

Table 12, IEEE 802.11ax (20MHz) OFDM, MCS0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (average) (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
H	2483.500	49.8	33	29.4	46.2	54.0	-7.8
H	4924.000	29.8	33	34.9	31.7	54.0	-22.3
H	7386.000	31.2	33	37.9	36.1	54.0	-17.9
H	9848.000	32.7	33	40.4	40.1	54.0	-13.9
V	12310.000	38.6	33	40.5	46.1	54.0	-7.9
V	14772.000	37.7	33	38.4	43.1	54.0	-10.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
H	2483.500	63.4	33	29.4	59.8	74.0	-14.2
H	4924.000	43.3	33	34.9	45.2	74.0	-28.8
H	7386.000	44.2	33	37.9	49.1	74.0	-24.9
H	9848.000	46.1	33	40.4	53.5	74.0	-20.5
V	12310.000	52.6	33	40.5	60.1	74.0	-13.9
V	14772.000	52.1	33	38.4	57.5	74.0	-16.5

- Notes:
1. Peak detector is used for the emission measurement.
 2. Average detector is used for the average data of emission measurement.
 3. All measurements were made at 3 meters.
 4. Negative value in the margin column shows emission below limit.
 5. Horn antenna is used for the emission over 1000MHz.
 6. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
 7. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.
 8. For the measurement of radiated emission, summation method was used which numerical integrating (in terms of linear power) over the transmitter occupied bandwidth.
 9. For the linear power measurement, data in 1MHz spacing was collected by spectrum analyzer with 1MHz resolution bandwidth.

TEST REPORT

RADIATED EMISSION DATA

Mode: B Mode TX-Channel 06 Baseband

Table 13

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
V	30.121	24.1	16	10.0	18.1	40.0	-21.9
V	74.014	19.7	16	6.0	9.7	40.0	-30.3
V	123.484	24.1	16	14.0	22.1	43.5	-21.4
V	498.753	14.7	16	26.0	24.7	46.0	-21.3
V	708.636	15.9	16	30.0	29.9	46.0	-16.1
V	977.569	14.8	16	33.0	31.8	54.0	-22.2

- Notes:
1. Peak detector are used for the emission measurement.
 2. All measurements were made at 3 meters.
 3. Negative value in the margin column shows emission below limit.
 4. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
 5. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.

TEST REPORT

RADIATED EMISSION DATA

Mode: G Mode TX-Channel 11 Baseband

Table 14

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
V	30.121	24.0	16	10.0	18.0	40.0	-22.0
V	64.193	17.2	16	9.0	10.2	40.0	-29.8
V	123.484	24.5	16	14.0	22.5	43.5	-21.0
V	498.753	14.5	16	26.0	24.5	46.0	-21.5
V	686.448	17.6	16	29.0	30.6	46.0	-15.4
V	955.623	14.6	16	33.0	31.6	46.0	-14.4

- Notes:
1. Peak detector are used for the emission measurement.
 2. All measurements were made at 3 meters.
 3. Negative value in the margin column shows emission below limit.
 4. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
 5. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.

TEST REPORT

RADIATED EMISSION DATA

Mode: 2.4GHz Wi-Fi + BLE + FHSS Operating (Adaptor: A938-050150W-US1)

Table 15

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
V	35.941	34.1	16	10.0	28.1	40.0	-11.9
H	288.020	29.1	16	22.0	35.1	46.0	-10.9
H	466.621	26.6	16	26.0	36.6	46.0	-9.4
V	499.965	23.8	16	26.0	33.8	46.0	-12.2
V	768.049	18.1	16	31.0	33.1	46.0	-12.9
V	960.230	27.7	16	33.0	44.7	54.0	-9.3

- Notes:
1. Peak detector are used for the emission measurement.
 2. All measurements were made at 3 meters.
 3. Negative value in the margin column shows emission below limit.
 4. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
 5. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.

TEST REPORT

RADIATED EMISSION DATA

Mode: 2.4GHz Wi-Fi + BLE + FHSS Operating (Adaptor: VT07EUS05150)

Table 16

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
V	77.409	29.9	16	6.0	19.9	40.0	-20.1
V	121.301	27.0	16	14.0	25.0	43.5	-18.5
V	143.369	30.3	16	14.0	28.3	43.5	-15.2
V	288.020	27.7	16	22.0	33.7	46.0	-12.3
H	466.621	27.0	16	26.0	37.0	46.0	-9.0
V	559.984	18.7	16	28.0	30.7	46.0	-15.3

- Notes:
1. Peak detector are used for the emission measurement.
 2. All measurements were made at 3 meters.
 3. Negative value in the margin column shows emission below limit.
 4. Emissions within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-Gen Section 8.10.
 5. Measurement Uncertainty is ± 5.3 dB at a level of confidence of 95%.

TEST REPORT

RADIATED EMISSION PLOTS

Mode: B Mode TX-Channel 06




Figure 1. 9k-30MHz




Figure 2. 30M-1GHz




Figure 3. 1-18GHz Peak




Figure 4. 1-18GHz Average




Figure 5. 18-40GHz Peak




Figure 6. 18-40GHz Average

For Figure 3 and 4, Fundamental emission is filtered out by notch filter during measurement.

TEST REPORT

RADIATED EMISSION PLOTS

Mode: G Mode TX-Channel 11




Figure 7. 9k-30MHz




Figure 8. 30M-1GHz




Figure 9. Band Edge




Figure 10. 1-18GHz Peak




Figure 11. 1-18GHz Average

For Figure 10 and 11, Fundamental emission is filtered out by notch filter during measurement.

TEST REPORT




Figure 12. 18-40GHz Peak




Figure 13. 18-40GHz Average

TEST REPORT

RADIATED EMISSION PLOTS

Mode: 2.4GHz Wi-Fi + BLE + FHSS Operating (Adaptor: VT07EUS05150)




Figure 14. 9k-30MHz




Figure 15. 30M-1GHz

TEST REPORT

3.7 Transmitter Duty Cycle Calculation

Not Applicable – No average factor is required

3.8 AC Power Line Conducted Emission

- ☐ Not Applicable – EUT is only powered by battery for operation.
- ☒ EUT connects to AC power line. Emission Data is listed in following pages.
- ☐ Base Unit connects to AC power line and has transmission. Handset connects to AC power line but has no transmission. Emission Data of Base Unit is listed in following pages.

3.8.1 AC Power Line Conducted Emission Configuration Photograph

Worst Case Line-Conducted Configuration at 0.465 MHz.


The worst-case line conducted configuration photographs are attached in the Appendix and saved with filename: Setup Photos.pdf.

3.8.2 AC Power Line Conducted Emission Data

The plot(s) and data in the following pages list the significant emission frequencies, the limit and the margin of compliance.

Passed by 10.97 dB margin

3.8.3 Conducted Emission Test Setup



The EUT along with its peripherals were placed on a 1.0m(W)×1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN), which provided 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. The excess power cable between the EUT and the LISN was bundled.

All connecting cables of EUT and peripherals were moved to find the maximum emission.

TEST REPORT

AC POWER LINE CONDUCTED EMISSION


Worst Case: 2.4GHz Wi-Fi + BLE + FHSS Operating (Adaptor: A938-050150W-US1)



REW 9 kHz

MT 1 s

Att 10 dB AUTIC PREAMP OFF



EDIT PEAK LIST (Final Measurement Results)

Trace1: CF15MQP

Trace2: CF15MAV


Trace3: ---

TRACE	FREQUENCY	LEVEL dBμV	DELTA LIMIT dB
1 Quasi Peak	159 kHz	48.93 I1	-16.58
1 Quasi Peak	222 kHz	43.00 I1	-19.74

TEST REPORT

AC POWER LINE CONDUCTED EMISSION

Worst Case: 2.4GHz Wi-Fi + BLE + FHSS Operating (Adaptor: VT07EUS05150)



EDIT PEAK LIST (Final Measurement Results)

Trace1: CF15MQP

Trace2: CF15MAV


Trace3: ---

	TRACE	FREQUENCY	LEVEL dBμV		DELTA LIMIT dB
1	Quasi Peak	177 kHz	39.93	N	-24.69
2	CISPR Average	465 kHz	35.62	L1	-10.97
1	Quasi Peak	469.5 kHz	41.08	N	-15.43
1	Quasi Peak	928.5 kHz	30.82	N	-25.17
1	Quasi Peak	1.365 MHz	24.85	L1	-31.14

TEST REPORT

OCCUPIED BANDWIDTH

The figure below shows the test setup, which is utilized to make these measurements.



Occupied Bandwidth Results: (IEEE 802.11b) (Refer to Test Data1.pdf)

Frequency (MHz)	Occupied Bandwidth (MHz)
Low Channel: 2412 (P.4)	14.80
Middle Channel: 2437 (P.15)	15.10
High Channel: 2462 (P.24)	15.00

Occupied Bandwidth Results: (IEEE 802.11g) (Refer to Test Data2.pdf)

Frequency (MHz)	Occupied Bandwidth (MHz)
Low Channel: 2412 (P.4)	16.40
Middle Channel: 2437 (P.15)	16.40
High Channel: 2462 (P.20)	16.30

Occupied Bandwidth Results: (IEEE 802.11n (20MHz)) (Refer to Test Data3.pdf)

Frequency (MHz)	Occupied Bandwidth (MHz)
Low Channel: 2412 (P.4)	17.50
Middle Channel: 2437 (P.15)	17.70
High Channel: 2462 (P.24)	17.50

Occupied Bandwidth Results: (IEEE 802.11ax (20MHz)) (Refer to Test Data4.pdf)

Frequency (MHz)	Occupied Bandwidth (MHz)
Low Channel: 2412 (P.4)	17.50
Middle Channel: 2437 (P.15)	17.60
High Channel: 2462 (P.24)	17.60

TEST REPORT

EXHIBIT 4 EQUIPMENT LIST

1) Radiated Emissions Test

Equipment	EMI Test Receiver (9kHz to 26.5GHz)	Biconical Antenna (30MHz to 300MHz)	Log Periodic Antenna
Registration No.	EW-3156	EW-3242	EW-3243
Manufacturer	ROHDESCHWARZ	EMCO	EMCO
Model No.	ESR26	3110C	3148B
Calibration Date	May 02, 2025	July 30, 2024	July 30, 2024
Calibration Due Date	May 02, 2026	July 30, 2026	July 30, 2026

Equipment	Double Ridged Guide Antenna (1GHz - 18GHz)	Active Loop Antenna (H-field) (9kHz to 30MHz)	Solid State Low Noise Preamplifier Assembly (1 - 18)GHz
Registration No.	EW-0194	EW-3326	EW-3229
Manufacturer	EMCO	EMCO	BONN ELEKTRO
Model No.	3115	6502	BLMA 0118-5G
Calibration Date	January 23, 2025	January 05, 2024	October 14, 2024
Calibration Due Date	July 23, 2026	January 05, 2026	January 14, 2026

Equipment	2.4GHz Notch Filter	14m Double Shield RF Cable (9kHz - 6GHz)	RF Cable 14m (1GHz to 26.5GHz)
Registration No.	EW-3435	EW-2376	EW-2781
Manufacturer	MICROWAVE	RADIAL	GREATBILLION
Model No.	N0324413	n m/br56/bnc m 14m	SMA m/SHF5MPU /SMA m ra14m,26G
Calibration Date	October 09, 2024	November 06, 2025	February 18, 2025
Calibration Due Date	January 09, 2026	November 06, 2026	February 18, 2026

Equipment	12 metre RF Cable (1-40)GHz	Pyramidal Horn Antenna
Registration No.	EW-2774	EW-0905
Manufacturer	GREATBILLION	EMCO
Model No.	SMA m-m ra 12m 40G outdoor	3160-09
Calibration Date	February 18, 2025	November 06, 2025
Calibration Due Date	February 18, 2026	May 06, 2027

TEST REPORT

EXHIBIT 4 EQUIPMENT LIST (CONT'D)

2) Conducted Emissions Test

Equipment	RF Cable 240cm (RG142) (9kHz to 30MHz)	Artificial Mains Network	EMI Test Receiver (9kHz to 3GHz)
Registration No.	EW-2454	EW-3360	EW-3095
Manufacturer	RADIALL	ROHDESCHWARZ	ROHDESCHWARZ
Model No.	Bnc m st / 142 / bnc mra 240cm	ENV-216	ESCI
Calibration Date	June 12, 2025	June 23, 2025	June 19, 2025
Calibration Due Date	June 12, 2026	June 23, 2026	June 19, 2026

3) Conductive Measurement Test

Equipment	RF Power Meter with Power Sensor (N1921A)	Signal and Spectrum Analyzer (10Hz to 40GHz)
Registration No.	EW-3309	EW-3281
Manufacturer	ROHDESCHWARZ	ROHDESCHWARZ
Model No.	NRP-Z81	FSV40
Calibration Date	July 29, 2025	May 22, 2025
Calibration Due Date	July 29, 2026	May 22, 2026

4) Control Software for Radiated Emission

Software Information	
Software Name	EMC32
Manufacturer	ROHDESCHWARZ
Software version	10.50.40

END OF TEST REPORT