

TABLE OF CONTENTS

APPLICANT: VTECH TELECOMMUNICATIONS LTD.

FCC ID: EW789-5004-00

TEST REPORT CONTAINING:

PAGE 1.....TEST EQUIPMENT LIST AND TEST PROCEDURE
PAGE 2.....TEST PROCEDURE CONTD.
PAGE 3-4.....RADIATION INTERFERENCE TEST DATA
PAGE 5.....POWERLINE CONDUCTED
PAGE 6.....OCCUPIED BANDWIDTH

EXHIBIT ATTACHMENTS:

EXHIBIT 1.....FCC ID LABEL SAMPLE & SKETCH OF LOCATION
EXHIBIT 2.....BLOCK DIAGRAM
EXHIBIT 3A.....SCHEMATIC - BASE UNI
EXHIBIT 3B.....SCHEMATIC - RF BOARD - BASE
EXHIBIT 3C.....SCHEMATIC - RF BOARD - HANDSET
EXHIBIT 3D.....SCHEMATIC - KEYBORAD - HANDSET
EXHIBIT 4A.....FRONT VIEW EXTERNAL PHOTOGRAPHS
EXHIBIT 4B.....REAR VIEW EXTERNAL PHOTOGRAPHS
EXHIBIT 4C-4D.....COMPONENT VIEW INTERNAL PHOTOGRAPH
EXHIBIT 4E-4F.....COPPER VIEW INTERNAL PHOTOGRAPH
EXHIBIT 5A-5R.....INSTRUCTION MANUAL
EXHIBIT 6A-6C.....CIRCUIT DESCRIPTION
EXHIBIT 7A-7B.....POWERLINE CONDUCTED PLOTS
EXHIBIT 8A.....OCCUPIED BANDWIDTH PLOT - HIGH FREQUENCY - HD
EXHIBIT 8B.....OCCUPIED BANDWIDTH PLOT - 2500 Hz - BASE
EXHIBIT 8C.....OCCUPIED BANDWIDTH PLOT - LOW FREQUENCY - BASE
EXHIBIT 8D.....OCCUPIED BANDWIDTH PLOT - LOUD VOICE
EXHIBIT 9A.....BASE RADIATED TEST SET UP PHOTO
EXHIBIT 9B.....HANDSET RADIATED TEST SET UP PHOTO
EXHIBIT 10.....POWERLINE CONDUCTED TEST SET UP PHOTO

APPLICANT: VTECH TELECOMMUNICATIONS LTD.

FCC ID: EW789-5004-00

REPORT #: T:\CUS\V\VTECH\226AH0\226AH0.RPT

PAGE: TABLE OF CONTENTS LIST

APPLICANT: VTECH TELECOMMUNICATIONS LTD.
FCC ID: EW789-5004-00

TEST EQUIPMENT LIST

1. X Spectrum Analyzer: HP 8566B-Opt 462, S/N 3138A07786, w/
preselector HP 85685A, S/N 3221A01400, Quasi-Peak Adapter
HP 85650A, S/N 3303A01690 & Preamplifier HP 8449B-OPT H02,
S/N 3008A00372 Cal. 10/17/99
2. X Biconnical Antenna: Eaton Model 94455-1, S/N 1057
3. X Log-Periodic Antenna: Electro-Metrics Model EM-6950, S/N 632
4. X Double-Ridged Horn Antenna: Electro-Metrics Model RGA-180,
1-18 GHz, S/N 2319 Cal. 4/27/99
5. Horn 40-60GHz: ATM Part #19-443-6R
6. X Line Impedance Stabilization Network: Electro-Metrics Model
ANS-25/2, S/N 2604 Cal. 2/9/00
7. Temperature Chamber: Tenney Engineering Model TTRC, S/N 11717-7
8. Frequency Counter: HP Model 5385A, S/N 3242A07460 Cal 10/6/99
9. Peak Power Meter: HP Model 8900C, S/N 2131A00545 Cal 7/19/99
10. X Open Area Test Site #1-3meters Cal. 12/22/99
11. Signal Generator: HP 8640B, S/N 2308A21464 Cal. 9/23/99
12. Signal Generator: HP 8614A, S/N 2015A07428 Cal. 5/29/99
13. Passive Loop Antenna: EMC0 Model 6512, 9KHz to 30MHz, S/N
9706-1211 Cal. 6/23/97
14. Dipole Antenna Kit: Electro-Metrics Model TDA-30/1-4, S/N 153
Cal. 11/24/99
15. AC Voltmeter: HP Model 400FL, S/N 2213A14499 Cal. 9/21/99
16. Digital Multimeter: Fluke Model 8012A, S/N 4810047 Cal 9/21/99
17. Digital Multimeter: Fluke Model 77, S/N 43850817 Cal 9/21/99
18. Oscilloscope: Tektronix Model 2230, S/N 300572 Cal 9/23/99

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC. The UUT was transmitting a test signal during the testing.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz up to 1.0GHz and 1.0MHz with a video BW of 3.0MHz above 1.0GHz. The ambient temperature of the UUT was 74.3oF with a humidity of 69%.

APPLICANT: VTECH TELECOMMUNICATIONS LTD.
FCC ID: EW789-5004-00
REPORT #: T:\CUS\V\VTECH\226AH0\226AH0.RPT
PAGE #: 1

APPLICANT: VTECH TELECOMMUNICATIONS LTD.
FCC ID: EW789-5004-00

TEST PROCEDURES CONTINUED

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz)	METER READING + ACF = FS
33	20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-1992 using a 50uH LISN. Both lines were observed. The bandwidth of the spectrum analyzer was 10kHz with an appropriate sweep speed. The ambient temperature of the UUT was 74.30F with a humidity of 69%.

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The UUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The UUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSIC63.4-1992 with the EUT 40 cm from the vertical ground wall.

APPLICANT: VTECH TELECOMMUNICATIONS LTD.
FCC ID: EW789-5004-00
REPORT NO.: T:\CUS\V\VTECH\226AH0\226AH0.RPT
PAGE #: 2

APPLICANT: VTECH TELECOMMUNICATIONS LTD.

FCC ID: EW789-5004-00

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NUMBER: 15.249, 15.209

REQUIREMENTS:

FIELD STRENGTH	FIELD STRENGTH	S15.209
of Fundamental: 902-928 MHz 2.4-2.4835 GHz 94 dBuV/m @3m	of Harmonics 54 dBuV/m @3m	30 - 88 MHz 40 dBuV/m @3M 88 -216 MHz 43.5 216 -960 MHz 46 ABOVE 960 MHz 54dBuV/m

EMISSIONS RADIATED OUTSIDE OF THE SPECIFIED FREQUENCY BANDS, EXCEPT FOR HARMONICS, SHALL BE ATTENUATED BY AT LEAST 50 dB BELOW THE LEVEL OF THE FUNDAMENTAL OR TO THE GENERAL RADIATED EMISSION LIMITS IN 15.209, WHICHEVER IS THE LESSER ATTENUATION.

TEST RESULTS: This unit DOES meet the FCC requirements.

TEST DATA:

EMISSION FREQUENCY MHz	METER READING AT 3 METERS dBuV	COAX LOSS dB	ANTENNA CORRECTION FACTOR FACTOR	PEAK FIELD STRENGTH dB dBuV/m@3m	FCC LIMIT dB	ANT. POL.
BASE						
902.60	48.50	2.90	24.19	75.59	94.00	V
1805.20	4.50	1.00	27.22	32.72	54.00	V
903.90	50.75	2.90	24.18	77.83	94.00	V
1806.47	14.30	1.00	27.23	42.53	54.00	V
HANDSET						
926.50	48.60	2.90	24.11	75.61	94.00	V
1852.90	11.20	1.01	27.41	39.62	54.00	H
927.80	53.00	2.90	24.12	80.02	94.00	V
1855.50	3.30	1.01	27.42	31.73	54.00	V

APPLICANT: VTECH TELECOMMUNICATIONS LTD.

FCC ID: EW789-5004-00

REPORT #: T:\CUS\V\VTECH\226AH0\226AH0.RPT

PAGE #: 3

APPLICANT: VTECH TELECOMMUNICATIONS LTD.

FCC ID: EW789-5004-00

NAME OF TEST: RADIATION INTERFERENCE

TEST PROCEDURE: ANSI STANDARD C63.4-1992 using a Hewlett Packard Model 8566B spectrum analyzer, a Hewlett Packard Model 85685A Preselector, a Hewlett Packard Model 85650A Quasi-Peak adapter, and calibrated antenna appropriate for the frequencies measured. The bandwidth of spectrum analyzer was 100 kHz with an appropriate sweep speed. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The spectrum was searched to at least the tenth(10) harmonic of the fundamental.

PERFORMED BY: _____ DATE: 22 JUNE 2000

APPLICANT: VTECH TELECOMMUNICATIONS LTD.
FCC ID: EW789-5004-00
REPORT #: T:\CUS\V\VTECH\226AH0\226AH0.RPT
PAGE #: 4

APPLICANT: VTECH TELECOMMUNICATIONS LTD.
FCC ID: EW789-5004-00
NAME OF TEST: POWER LINE CONDUCTED INTERFERENCE
RULES PART NUMBER: 15.107
MINIMUM REQUIREMENTS: FREQUENCY LEVEL
 ___MHz___ __uV__
 0.450-30 250
TEST PROCEDURE: ANSI STANDARD C63.4-1992

THE HIGHEST EMISSION READ FOR LINE 1 WAS 75.0 uV @ 570 kHz.

THE HIGHEST EMISSION READ FOR LINE 2 WAS 35.5 uV @ 570 kHz.

THE PLOTS IN EXHIBIT 7A-7B REPRESENT THE EMISSIONS READ FOR
POWERLINE CONDUCTED FOR THIS DEVICE.

TEST RESULTS: Both lines were observed. The measurements indicate that the unit DOES appear to meet the FCC requirements for this class of equipment.

PERFORMED BY: _____ DATE: 22 JUNE 2000

APPLICANT: VTECH TELECOMMUNICATIONS LTD.
FCC ID: EW789-5004-00
REPORT #: T:\CUS\V\VTECH\226AH0\226AH0.RPT
PAGE #: 5

APPLICANT: VTECH TELECOMMUNICATIONS LTD.
FCC ID: EW789-5004-00
NAME OF TEST: Occupied Bandwidth
RULES PART NO.: 15.249
REQUIREMENTS: The field strength of any emissions appearing outside the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 50 dB below the level of the carrier or to the general limits of 15.249.

THE PLOTS IN EXHIBIT 8A-8D REPRESENTS THE EMISSIONS TAKEN FOR THIS DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was printed. The vertical scale is set to -10 dBm per division. The horizontal scale is set to 5 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: _____ 22 JUNE 2000

APPLICANT: VTECH TELECOMMUNICATIONS LTD.
FCC ID: EW789-5004-00
REPORT #: T:\CUS\V\VTECH\226AH0\226AH0.RPT
PAGE #: 6