Vtech Communications Limited

Class II Permissive Change

900MHz 30 Channels Analog Modulation Cordless Telephone

(FCC ID: EW79108)

WO# 0002416
WL/at
April 28, 2000

- The test results reported in this report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report shall not be reproduced except in full without prior authorization form Intertek Testing Services Limited

FCC ID: EW79108

Intertek Testing Services Hong Kong Ltd.

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2741 1693

LIST OF EXHIBITS

INTRODUCTION

EXHIBIT 1: General Description

EXHIBIT 2: System Test Configuration

EXHIBIT 3: Emission Results

EXHIBIT 4: Equipment Photographs

EXHIBIT 5: Product Labelling

EXHIBIT 6: Technical Specifications

EXHIBIT 7: Instruction Manual

EXHIBIT 8: Security Code Information

MEASUREMENT/TECHNICAL REPORT

Vtech Communications Limited - MODEL: 9111
FCC ID: EW79108

This report concerns (check one:) Original Grant_____ Class II Change __X__

Equipment Type : Cordless Telephone (example : computer, modem, transmitter, etc.)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes _____ No __X__

If yes, defer until : _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37 ? Yes _____ No __X__

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-1-98 Edition] Provision.

Report prepared by:

Wilson Loke
Intertek Testing Services.
2/F., Garment Centre,
576 Castle Peak Road,
Kowloon, Hong Kong.
Phone : 852-2173-8888
Fax: 852-2741-1693

Table of Contents

1.0 **General Description** 2
1.1 Product Description 2
1.2 Purpose of Application 2
1.3 Related Submittal(s) Grants 2
1.4 Test Methodology 3
1.5 Test Facility 2

2.0 **System Test Configuration** 5
2.1 Justification 5
2.2 EUT Exercising Software 5
2.3 Support Equipment List and Description 6
2.4 Equipment Modification 7

3.0 **Emission Results** 9
3.1 Field Strength Calculation 10
3.2 Radiated Emission Configuration Photograph - Base Unit 11
3.3 Radiated Emission Data - Base Unit 12
3.4 Radiated Emission Configuration Photograph - Handset 15
3.5 Radiated Emission Configuration Data - Handset 16
3.6 Radiated Emission on the bandedge 19
3.7 Line Conducted Configuration Photograph - Base Unit 21
3.8 Line Conducted Data - Base Unit 22

4.0 **Equipment Photographs** 25

5.0 **Product Labelling** 27

6.0 **Technical Specifications** 29

7.0 **Instruction Manual** 31

8.0 **Security Code Information** 33

List of attached file

Exhibit type	File Description	filename
Cover Letter	Letter of Agency	letter.pdf
Test Report	Test Report	report.doc
Operation Description	Technical Description	descri.pdf
Test Setup Photo	Radiated Emission for Base	base1.jpg, base2.jpg
Test Setup Photo	Radiated Emission for Handset	handset1.jpg, handset2.jpg
Test Report	Emission Plot	emission.pdf
Test Setup Photo	Conducted Emission	conduct1.jpg to conduct3.jpg
Test Report	Conducted Emission Test Result	conduct.pdf
External Photo	External Photo	ophoto1.jpg, ophoto2.jpg
Internal Photo	Internal Photo	iphoto1.jpg to iphoto7.jpg
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf

EXHIBIT 1
GENERAL DESCRIPTION

1.0 General Description

1.1 Product Description

The 9111 is a 900MHz 30 Channels Analog Modulation Cordless Telephone. The unit is capable of either tone or pulse dialing. The internal power supply's isolation is accomplished through a power transformer having an adequate dielectric rating. The circuit wiring is consistent under the requirement of part 68.

The handset unit consists of a keypad with twelve standard keys (0,...9,*,#), Four function keys (Off, Program, Memory, Redial), and one channel switch key. A Phone key is provided to control pick/release telephone line in a toggle base.

The base unit has a page key, which is used to page the handset unit.

The circuit description is saved with filename: descri.pdf

Connection between the device and the telephone network is accomplished through the use of USOC RJ11C in the 2-wire loop calling central office line.

1.2 Purpose of Application

The purpose of this application is to report changes in the basic model (FCC ID: EW79108) which include the addition of two LEDs namely Power LED and In Use LED and the addition of the headset feature.

1.3 Related Submittal(s) Grants

This is an Class II Permissive Change Application of a cordless telephone system. Two transmitters are included in this Application. This specific report details the emission characteristics of each transmitter. The receivers are subject to the verification authorization process, in accordance with 15.101(b). A verification report has been prepared for the receiver sections of each device. The device is also subject to Part 68 Registration.

1.4 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (1992). All measurements were performed in Open Area Test Sites. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

1.5 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC.

EXHIBIT 2
SYSTEM TEST CONFIGURATION

2.0 System Test Configuration

2.1 Justification

For emission testing, the equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). During testing, all cables were manipulated to produce worst case emissions. The handset was powered by a fully charged battery.

For the measurements, the EUT is attached to a cardboard box and placed on the wooden turntable. If the base unit attaches to peripherals, they are connected and operational (as typical as possible). The handset is remotely located as far from the antenna and the base as possible to ensure full power transmission from the base. Else, the base is wired to transmit full power without modulation.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Detector function is in peak mode. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater. All emissions greater than 20 dBµV/m are recorded.

Radiated emission measurement were performed from 30 MHz to tenth harmonics.

2.2 EUT Exercising Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

For emissions testing, the units were setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing.

2.3 Support Equipment List and Description

The FCC ID's for all equipment, plus descriptions of all cables used in the tested system (included inserted cards, which have grants) are:

HARDWARE:

The unit was operated standalone. An AC adapter (provided with the unit) was used to power the device. Its description is listed below.

(1) AC adapter with two meter unshielded power cord permanently affixed.

CABLES:

(1) Telecommunication cable with RJ11C connectors (1m, unshielded), terminated

OTHERS:

(1) A headset for telephone use with 1.2m unshielded cable permanently affixed.

2.4 Equipment Modification

Any modifications installed previous to testing by Vtech Communications Limited will be incorporated in each production model sold/leased in the United States.

No modifications were installed by ETL Division, Intertek Testing Services Hong Kong Ltd.

All the items listed under section 2.0 of this report are confirmed by:

Confirmed by:

Wilson Loke
Manager
Intertek Testing Services
Agent for Vtech Communications Limited

_____ Signature

April 28, 2000 Date

EXHIBIT 3
EMISSION RESULTS

3.0 **Emission Results**

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CF - AG

where FS = Field Strength in dBμV/m
RA = Receiver Amplitude (including preamplifier) in dBμV
CF = Cable Attenuation Factor in dB
AF = Antenna Factor in dB
AG = Amplifier Gain in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:-

FS = RR + LF

where FS = Field Strength in dBμV/m
RR = RA - AG in dBμV
LF = CF + AF in dB

Assume a receiver reading of 52.0 dBμV is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving a field strength of 32 dBμV/m. This value in dBμV/m was converted to its corresponding level in μV/m.

RA = 52.0 dBμV/m
AF = 7.4 dB
CF = 1.6 dB
AG = 29.0 dB
FS = RR + LF
FS = 23 + 9 = 32 dBμV/m

RR = 23.0 dBμV
LF = 9.0 dB

Level in μV/m = Common Antilogarithm [(32 dBμV/m)/20] = 39.8 μV/m

3.2 Radiated Emission Configuration Photograph - Base Unit

Worst Case Radiated Emission

at 902.300 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: base1.jpg and base2.jpg

3.3 Radiated Emission Data - Base Unit

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Judgement : Passed by 6.6 dB

****

TEST PERSONNEL:

_____
Tester Signature

H. Y. Vu, Engineer
Typed/Printed Name

April 27, 2000
Date

Company: Vtech Communications Limited Date of Test: April 11, 2000
Model: 9111
Mode : TX-Channel 1

Table 1, Base unit

Radiated Emissions

Polarity	Frequency (MHz)	Reading (dBµV)	Antenna Factor (dB)	Pre-Amp Gain (dB)	Net at 3m (dBµV/m)	Limit (dBµV/m)	Margin (dB)
V	902.300	71.4	32.0	16	87.4	94	-6.6
V	1804.600	44.9	26.5	34	37.4	54	-16.6
V	*2706.900	43.4	29.1	34	38.5	54	-15.5
V	*3609.200	36.2	32.8	34	35.0	54	-19.0
V	*4511.500	34.1	34.0	34	34.1	54	-19.9

NOTES: 1. Peak Detector data

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna and average detector are used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak detector data for frequencies below 1000 MHz and average detector data for frequencies over 1000 MHz.

Test Engineer: H. Y. Vu

Company: Vtech Communications Limited Date of Test: April 11, 2000
Model: 9111
Mode : TX-Channel 18

Table 2, Base unit

Radiated Emissions

Polarity	Frequency (MHz)	Reading (dBµV)	Antenna Factor (dB)	Pre-Amp Gain (dB)	Net at 3m (dBµV/m)	Limit (dBµV/m)	Margin (dB)
V	906.650	70.5	32.0	16	86.5	94	-7.5
V	1813.300	44.7	26.5	34	37.2	54	-16.8
V	*2719.950	43.1	29.1	34	38.2	54	-15.8
V	*3626.600	36.2	32.8	34	35.0	54	-19.0
V	*4533.250	34.0	34.0	34	34.0	54	-20.0

NOTES: 1. Peak Detector data

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna and average detector are used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak detector data for frequencies below 1000 MHz and average detector data for frequencies over 1000 MHz.

Test Engineer: H. Y. Vu

3.4 Radiated Emission Configuration Photograph - Handset

Worst Case Radiated Emission

at 923.100 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: handset1.jpg and handset2.jpg

3.5 Radiated Emission Data - Handset

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Judgement : Passed by 9.4 dB

****

TEST PERSONNEL:

Tester Signature

H. Y. Vu, Engineer
Typed/Printed Name

April 27, 2000
Date

Company: Vtech Communications Limited Date of Test: April 11, 2000
Model: 9111
Mode : TX-Channel 8

Table 3, Handset

Radiated Emissions

Polarity	Frequency (MHz)	Reading (dBµV)	Antenna Factor (dB)	Pre-Amp Gain (dB)	Net at 3m (dBµV/m)	Limit (dBµV/m)	Margin (dB)
V	923.100	67.6	33.0	16	84.6	94	-9.4
V	1846.200	45.2	26.5	34	37.7	54	-16.3
V	*2769.300	42.5	29.1	34	37.6	54	-16.4

NOTES: 1. Peak Detector data

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna and average detector are used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak detector data for frequencies below 1000 MHz and average detector data for frequencies over 1000 MHz.

Test Engineer: H. Y. Vu

Company: Vtech Communications Limited Date of Test: April 11, 2000
Model: 9111
Mode : TX-Channel 25

Table 4, Handset

Radiated Emissions

Polarity	Frequency (MHz)	Reading (dBµV)	Antenna Factor (dB)	Pre-Amp Gain (dB)	Net at 3m (dBµV/m)	Limit (dBµV/m)	Margin (dB)
V	927.750	66.9	33.0	16	83.9	94	-10.1
V	1855.500	46.2	26.5	34	38.7	54	-15.3
V	*2783.250	42.5	29.1	34	37.6	54	-16.4

NOTES: 1. Peak Detector data

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna and average detector are used for the emission over 1000MHz.

* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak detector data for frequencies below 1000 MHz and average detector data for frequencies over 1000 MHz.

Test Engineer: H. Y. Vu

3.6 Radiated Emission on the bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band and they are at least 50 dB below the carrier level at band edge (902 and 928 MHz). It meets the requirement of section 15.249(c).

Emission Plot

For electronic filing, the emission plots are saved with filename: emission.pdf

3.7 Line Conducted Configuration Photograph - Base Unit

Worst Case Line-Conducted Configuration

at 15.970 MHz

For electronic filing, the worst case line conducted configuration photographs are saved with filename: conduct1.jpg to conduct3.jpg

3.8 Line Conducted Emission Configuration Data

The data on the following pages list the significant emission frequencies, the limit, and the margin of compliance.

Judgement : Passed by 4.8 dB

TEST PERSONNEL:

Tester Signature

H. Y. Vu, Engineer
Typed/Printed Name

April 27, 2000
Date

Company: VTECH COMMUNICATIONS LIMITED Date of Test: April 11, 2000
Model: 9111

Conducted Emissions

For electronic filing, the conducted emission test result is saved with filename: conduct.pdf

EXHIBIT 4
EQUIPMENT PHOTOGRAPHS

4.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: ophoto1.jpg to ophoto2.jpg & iphoto1.jpg to iphoto7.jpg

EXHIBIT 5
PRODUCT LABELLING

5.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf

EXHIBIT 6
TECHNICAL SPECIFICATIONS

6.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

EXHIBIT 7
INSTRUCTION MANUAL

7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf

Please note that the required FCC Information to the User can be found on Page 4 of 4 of this manual.

This manual will be provided to the end-user with each unit sold/leased in the United States.

EXHIBIT 8
SECURITY CODE INFORMATION

8.0 Security code information

All data communication over the RF link will include a security code as required by FCC Part 15. When a data packet is received over the RF link, the security code contained in the packet will be verified before any data is processed. This prevents the handset from receiving commands form another base unit and view-versa.

The handset and base units will use an identical, 16-bit digital security codes. The security code is stored in the non-volatile memory in the base and handset unit and factory defaulted I production. During production, all units will be passed through a test jig in pair. The test jig will test some parameters of the unit pair and write the security code into the memory once all test parameters passed. The test jig will count on the security code (Totally 65536 - 16 bit buffer and reset after the buffer full) and write to the unit pair.