



















### Band Edge Plots, Configuration 3







































### Test Setup / Conditions / Data

Test Location: CKC Laboratories Inc. • 110 N. Olinda Pl. • Brea, CA 92823 • 714-993-6112  
 Customer: **Itron, Inc.**  
 Specification: **15.247(d) / 15.209 Radiated Spurious Emissions**  
 Work Order #: **104621** Date: 1/25/2021  
 Test Type: **Radiated Emissions** Time: 10:18:32  
 Tested By: Don Nguyen Sequence#: 11  
 Software: EMITest 5.03.19

#### Equipment Tested:

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 1 |              |         |     |

#### Support Equipment:

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 1 |              |         |     |

#### Test Conditions / Notes:

The EUT is placed on Styrofoam platform and powered from 3.6V fresh battery. The EUT is connected to a remote located laptop running CLI Tool ver.2.0.1.24.  
 EUT has fixed orientation per manufacture's specification.  
 Operating frequency range/ mode  
 902.4 - 927.6MHz, 400kHz steps, 64 channels, 300kbps GFSK LV2/LV3  
 Frequency of measurement: 614-960MHz  
 RBW=120kHz, VBW=360kHz (restricted band)  
 RBW=100kHz, VBW=300kHz (-20dBc)  
  
 Test Method: ANSI C63.10 (2013)  
 Temperature (°C): 24  
 Relative Humidity (%): 30  
 Modification 1 was in place during testing.

#### Test Equipment:

| ID | Asset #  | Description                          | Model    | Calibration Date | Cal Due Date |
|----|----------|--------------------------------------|----------|------------------|--------------|
| T1 | ANP05281 | Attenuator                           | 1B       | 4/7/2020         | 4/7/2022     |
| T2 | AN01993  | Biconilog Antenna                    | CBL6111C | 6/11/2019        | 6/11/2021    |
| T3 | AN02869  | Spectrum Analyzer                    | E4440A   | 8/3/2020         | 8/3/2021     |
| T4 | ANP05198 | Cable-Amplitude<br>+15C to +45C (dB) | 8268     | 12/21/2020       | 12/21/2022   |

**Measurement Data:**

Reading listed by margin.

Test Distance: 3 Meters

| # | Freq<br>MHz | Rdng<br>dBμV | T1<br>dB | T2<br>dB | T3<br>dB | T4<br>dB | Dist<br>Table | Corr<br>dBμV/m | Spec<br>dBμV/m  | Margin<br>dB | Polar<br>Ant |
|---|-------------|--------------|----------|----------|----------|----------|---------------|----------------|-----------------|--------------|--------------|
| 1 | 614.000M    | 11.5         | +5.9     | +19.8    | +0.0     | +4.6     | +0.0          | 41.8           | 46.0<br>hopping | -4.2         | Vert         |
| 2 | 960.000M    | 12.9         | +6.0     | +24.4    | +0.0     | +6.0     | +0.0          | 49.3           | 54.0            | -4.7         | Vert         |
| 3 | 614.000M    | 10.8         | +5.9     | +19.8    | +0.0     | +4.6     | +0.0          | 41.1           | 46.0            | -4.9         | Vert         |
| 4 | 960.000M    | 11.1         | +6.0     | +24.4    | +0.0     | +6.0     | +0.0          | 47.5           | 54.0<br>hopping | -6.5         | Vert         |
| 5 | 902.000M    | 32.5         | +6.0     | +23.5    | +0.0     | +5.8     | +0.0          | 67.8           | 88.5            | -20.7        | Vert         |
| 6 | 928.000M    | 31.0         | +6.0     | +23.9    | +0.0     | +5.9     | +0.0          | 66.8           | 88.5            | -21.7        | Vert         |
| 7 | 928.000M    | 30.5         | +6.0     | +23.9    | +0.0     | +5.9     | +0.0          | 66.3           | 88.5<br>hopping | -22.2        | Vert         |
| 8 | 902.000M    | 30.9         | +6.0     | +23.5    | +0.0     | +5.8     | +0.0          | 66.2           | 88.5<br>hopping | -22.3        | Vert         |

Test Location: CKC Laboratories Inc. • 110 N. Olinda Pl. • Brea, CA 92823 • 714-993-6112  
 Customer: **Itron, Inc.**  
 Specification: **15.247(d) / 15.209 Radiated Spurious Emissions**  
 Work Order #: **104621** Date: 12/22/2020  
 Test Type: **Radiated Emissions** Time: 10:51:22  
 Tested By: Don Nguyen Sequence#: 2  
 Software: EMITest 5.03.19

**Equipment Tested:**

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 1 |              |         |     |

**Support Equipment:**

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 1 |              |         |     |

**Test Conditions / Notes:**

The EUT is placed on Styrofoam platform and powered from 3.6V fresh battery. The EUT is connected to a remote located laptop running CLI Tool ver.2.0.1.24.  
 EUT has fixed orientation per manufacture's specification.  
 Operating frequency range/ mode  
 903 - 926.8MHz, 200kHz steps, 120 channels, 16384 OOK LV1  
 Frequency of measurement: 614-960MHz  
 RBW=120kHz, VBW=360kHz (restricted band)  
 RBW=100kHz, VBW=300kHz (-20dBc)  
  
 Test Method: ANSI C63.10 (2013)  
 Temperature (°C): 24  
 Relative Humidity (%): 30  
 Modification 1 was in place during testing.

**Test Equipment:**

| ID | Asset #  | Description                          | Model    | Calibration Date | Cal Due Date |
|----|----------|--------------------------------------|----------|------------------|--------------|
| T1 | AN03643  | Spectrum Analyzer                    | E4440A   | 5/20/2020        | 5/20/2022    |
| T2 | ANP01911 | Cable-Amplitude<br>+15C to +45C (dB) | RG214/U  | 1/2/2020         | 1/2/2022     |
| T3 | ANP05281 | Attenuator                           | 1B       | 4/7/2020         | 4/7/2022     |
| T4 | AN01993  | Biconilog Antenna                    | CBL6111C | 6/11/2019        | 6/11/2021    |

**Measurement Data:**

Reading listed by margin.

Test Distance: 3 Meters

| # | Freq<br>MHz | Rdng<br>dBμV | T1<br>dB | T2<br>dB | T3<br>dB | T4<br>dB | Dist<br>Table | Corr<br>dBμV/m | Spec<br>dBμV/m  | Margin<br>dB | Polar<br>Ant |
|---|-------------|--------------|----------|----------|----------|----------|---------------|----------------|-----------------|--------------|--------------|
| 1 | 614.000M    | 13.9         | +0.0     | +2.5     | +5.9     | +19.8    | +0.0          | 42.1           | 46.0            | -3.9         | Vert         |
| 2 | 960.000M    | 15.2         | +0.0     | +3.3     | +6.0     | +24.4    | +0.0          | 48.9           | 54.0            | -5.1         | Vert         |
| 3 | 614.000M    | 12.2         | +0.0     | +2.5     | +5.9     | +19.8    | +0.0          | 40.4           | 46.0<br>hopping | -5.6         | Vert         |
| 4 | 960.000M    | 13.2         | +0.0     | +3.3     | +6.0     | +24.4    | +0.0          | 46.9           | 54.0<br>hopping | -7.1         | Vert         |
| 5 | 928.000M    | 43.9         | +0.0     | +3.3     | +6.0     | +23.9    | +0.0          | 77.1           | 89.6            | -12.5        | Vert         |
| 6 | 902.000M    | 43.5         | +0.0     | +3.2     | +6.0     | +23.5    | +0.0          | 76.2           | 89.6            | -13.4        | Vert         |
| 7 | 928.000M    | 42.3         | +0.0     | +3.3     | +6.0     | +23.9    | +0.0          | 75.5           | 89.6<br>hopping | -14.1        | Vert         |
| 8 | 902.000M    | 41.7         | +0.0     | +3.2     | +6.0     | +23.5    | +0.0          | 74.4           | 89.6<br>hopping | -15.2        | Vert         |

Test Location: CKC Laboratories Inc. • 110 N. Olinda Pl. • Brea, CA 92823 • 714-993-6112  
 Customer: **Itron, Inc.**  
 Specification: **15.247(d) / 15.209 Radiated Spurious Emissions**  
 Work Order #: **104621** Date: 1/25/2021  
 Test Type: **Radiated Emissions** Time: 10:22:10  
 Tested By: Don Nguyen Sequence#: 3  
 Software: EMITest 5.03.19

**Equipment Tested:**

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 1 |              |         |     |

**Support Equipment:**

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 1 |              |         |     |

**Test Conditions / Notes:**

The EUT is placed on Styrofoam platform and powered from 3.6V fresh battery. The EUT is connected to a remote located laptop running CLI Tool ver.2.0.1.24.  
 EUT has fixed orientation per manufacture's specification.  
 Operating frequency range/ mode  
 903 - 926.8MHz, 200kHz steps, 120 channels, 16384 OOK LV3  
 Frequency of measurement: 614-960MHz  
 RBW=120kHz, VBW=360kHz (restricted band)  
 RBW=100kHz, VBW=300kHz (-20dBc)  
  
 Test Method: ANSI C63.10 (2013)  
 Temperature (°C): 24  
 Relative Humidity (%): 30  
 Modification 1 was in place during testing.

**Test Equipment:**

| ID | Asset #  | Description                          | Model    | Calibration Date | Cal Due Date |
|----|----------|--------------------------------------|----------|------------------|--------------|
| T1 | ANP05281 | Attenuator                           | 1B       | 4/7/2020         | 4/7/2022     |
| T2 | AN01993  | Biconilog Antenna                    | CBL6111C | 6/11/2019        | 6/11/2021    |
| T3 | AN02869  | Spectrum Analyzer                    | E4440A   | 8/3/2020         | 8/3/2021     |
| T4 | ANP05198 | Cable-Amplitude<br>+15C to +45C (dB) | 8268     | 12/21/2020       | 12/21/2022   |

**Measurement Data:**

Reading listed by margin.

Test Distance: 3 Meters

| # | Freq<br>MHz | Rdng<br>dBμV | T1<br>dB | T2<br>dB | T3<br>dB | T4<br>dB | Dist<br>Table | Corr<br>dBμV/m | Spec<br>dBμV/m  | Margin<br>dB | Polar<br>Ant |
|---|-------------|--------------|----------|----------|----------|----------|---------------|----------------|-----------------|--------------|--------------|
| 1 | 614.000M    | 10.9         | +5.9     | +19.8    | +0.0     | +4.6     | +0.0          | 41.2           | 46.0<br>hopping | -4.8         | Vert         |
| 2 | 614.000M    | 10.7         | +5.9     | +19.8    | +0.0     | +4.6     | +0.0          | 41.0           | 46.0            | -5.0         | Vert         |
| 3 | 960.000M    | 12.0         | +6.0     | +24.4    | +0.0     | +6.0     | +0.0          | 48.4           | 54.0<br>hopping | -5.6         | Vert         |
| 4 | 960.000M    | 11.1         | +6.0     | +24.4    | +0.0     | +6.0     | +0.0          | 47.5           | 54.0            | -6.5         | Vert         |
| 5 | 902.000M    | 45.9         | +6.0     | +23.5    | +0.0     | +5.8     | +0.0          | 81.2           | 93.9<br>hopping | -12.7        | Vert         |
| 6 | 902.000M    | 45.5         | +6.0     | +23.5    | +0.0     | +5.8     | +0.0          | 80.8           | 93.9            | -13.1        | Vert         |
| 7 | 928.000M    | 43.4         | +6.0     | +23.9    | +0.0     | +5.9     | +0.0          | 79.2           | 93.9<br>hopping | -14.7        | Vert         |
| 8 | 928.000M    | 43.2         | +6.0     | +23.9    | +0.0     | +5.9     | +0.0          | 79.0           | 93.9            | -14.9        | Vert         |

Test Location: CKC Laboratories Inc. • 110 N. Olinda Pl. • Brea, CA 92823 • 714-993-6112  
 Customer: **Itron, Inc.**  
 Specification: **15.247(d) / 15.209 Radiated Spurious Emissions**  
 Work Order #: **104621** Date: 1/25/2021  
 Test Type: **Radiated Emissions** Time: 09:55:52  
 Tested By: Don Nguyen Sequence#: 5  
 Software: EMITest 5.03.19

**Equipment Tested:**

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 2 |              |         |     |

**Support Equipment:**

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 2 |              |         |     |

**Test Conditions / Notes:**

The EUT is placed on Styrofoam platform and powered from 3.6V fresh battery. The EUT is connected to a remote located laptop running CLI Tool ver.2.0.1.24.  
 EUT has fixed orientation per manufacture's specification.  
 Operating frequency range/ mode  
 902.4 - 927.6MHz, 400kHz steps, 64 channels, 300k GFSK LV2/LV3  
 Frequency of measurement: 614-960MHz  
 RBW=120kHz, VBW=360kHz (restricted band)  
 RBW=100kHz, VBW=300kHz (-20dBc)  
  
 Test Method: ANSI C63.10 (2013)  
 Temperature (°C): 24  
 Relative Humidity (%): 30  
 Modification 1 was in place during testing.

**Test Equipment:**

| ID | Asset #  | Description                          | Model    | Calibration Date | Cal Due Date |
|----|----------|--------------------------------------|----------|------------------|--------------|
| T1 | ANP05281 | Attenuator                           | 1B       | 4/7/2020         | 4/7/2022     |
| T2 | AN01993  | Biconilog Antenna                    | CBL6111C | 6/11/2019        | 6/11/2021    |
| T3 | AN02869  | Spectrum Analyzer                    | E4440A   | 8/3/2020         | 8/3/2021     |
| T4 | ANP05198 | Cable-Amplitude<br>+15C to +45C (dB) | 8268     | 12/21/2020       | 12/21/2022   |

**Measurement Data:**

Reading listed by margin.

Test Distance: 3 Meters

| # | Freq<br>MHz | Rdng<br>dBμV | T1<br>dB | T2<br>dB | T3<br>dB | T4<br>dB | Dist<br>Table | Corr<br>dBμV/m | Spec<br>dBμV/m  | Margin<br>dB | Polar<br>Ant |
|---|-------------|--------------|----------|----------|----------|----------|---------------|----------------|-----------------|--------------|--------------|
| 1 | 614.000M    | 12.9         | +5.9     | +19.8    | +0.0     | +4.6     | +0.0          | 43.2           | 46.0            | -2.8         | Vert         |
| 2 | 614.000M    | 12.9         | +5.9     | +19.8    | +0.0     | +4.6     | +0.0          | 43.2           | 46.0<br>hopping | -2.8         | Vert         |
| 3 | 960.000M    | 11.7         | +6.0     | +24.4    | +0.0     | +6.0     | +0.0          | 48.1           | 54.0            | -5.9         | Vert         |
| 4 | 960.000M    | 11.2         | +6.0     | +24.4    | +0.0     | +6.0     | +0.0          | 47.6           | 54.0<br>hopping | -6.4         | Vert         |
| 5 | 928.000M    | 34.0         | +6.0     | +23.9    | +0.0     | +5.9     | +0.0          | 69.8           | 87.6            | -17.8        | Vert         |
| 6 | 928.000M    | 33.8         | +6.0     | +23.9    | +0.0     | +5.9     | +0.0          | 69.6           | 87.6<br>hopping | -18.0        | Vert         |
| 7 | 902.000M    | 31.0         | +6.0     | +23.5    | +0.0     | +5.8     | +0.0          | 66.3           | 87.6            | -21.3        | Vert         |
| 8 | 902.000M    | 30.1         | +6.0     | +23.5    | +0.0     | +5.8     | +0.0          | 65.4           | 87.6<br>hopping | -22.2        | Vert         |

Test Location: CKC Laboratories Inc. • 110 N. Olinda Pl. • Brea, CA 92823 • 714-993-6112  
 Customer: **Itron, Inc.**  
 Specification: **15.247(d) / 15.209 Radiated Spurious Emissions**  
 Work Order #: **104621** Date: 12/22/2020  
 Test Type: **Radiated Emissions** Time: 13:57:49  
 Tested By: Don Nguyen Sequence#: 8  
 Software: EMITest 5.03.19

**Equipment Tested:**

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 2 |              |         |     |

**Support Equipment:**

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 2 |              |         |     |

**Test Conditions / Notes:**

The EUT is placed on Styrofoam platform and powered from 3.6V fresh battery. The EUT is connected to a remote located laptop running CLI Tool ver.2.0.1.24.  
 EUT has fixed orientation per manufacture's specification.  
 Operating frequency range/ mode  
 903 - 926.8MHz, 200kHz steps, 120 channels, 16384 OOK LV1  
 Frequency of measurement: 614-960MHz  
 RBW=120kHz, VBW=360kHz (restricted band)  
 RBW=100kHz, VBW=300kHz (-20dBc)  
  
 Test Method: ANSI C63.10 (2013)  
 Temperature (°C): 24  
 Relative Humidity (%): 30  
 Modification 1 was in place during testing.

**Test Equipment:**

| ID | Asset #  | Description                          | Model    | Calibration Date | Cal Due Date |
|----|----------|--------------------------------------|----------|------------------|--------------|
| T1 | AN03643  | Spectrum Analyzer                    | E4440A   | 5/20/2020        | 5/20/2022    |
| T2 | ANP01911 | Cable-Amplitude<br>+15C to +45C (dB) | RG214/U  | 1/2/2020         | 1/2/2022     |
| T3 | ANP05281 | Attenuator                           | 1B       | 4/7/2020         | 4/7/2022     |
| T4 | AN01993  | Biconilog Antenna                    | CBL6111C | 6/11/2019        | 6/11/2021    |

**Measurement Data:**

Reading listed by margin.

Test Distance: 3 Meters

| # | Freq<br>MHz | Rdng<br>dBμV | T1<br>dB | T2<br>dB | T3<br>dB | T4<br>dB | Dist<br>Table | Corr<br>dBμV/m | Spec<br>dBμV/m  | Margin<br>dB | Polar<br>Ant |
|---|-------------|--------------|----------|----------|----------|----------|---------------|----------------|-----------------|--------------|--------------|
| 1 | 614.000M    | 14.1         | +0.0     | +2.5     | +5.9     | +19.8    | +0.0          | 42.3           | 46.0<br>hopping | -3.7         | Vert         |
| 2 | 614.000M    | 12.5         | +0.0     | +2.5     | +5.9     | +19.8    | +0.0          | 40.7           | 46.0            | -5.3         | Vert         |
| 3 | 960.000M    | 12.2         | +0.0     | +3.3     | +6.0     | +24.4    | +0.0          | 45.9           | 54.0            | -8.1         | Vert         |
| 4 | 960.000M    | 12.0         | +0.0     | +3.3     | +6.0     | +24.4    | +0.0          | 45.7           | 54.0<br>hopping | -8.3         | Vert         |
| 5 | 902.000M    | 41.7         | +0.0     | +3.2     | +6.0     | +23.5    | +0.0          | 74.4           | 88.2<br>hopping | -13.8        | Vert         |
| 6 | 902.000M    | 41.5         | +0.0     | +3.2     | +6.0     | +23.5    | +0.0          | 74.2           | 88.2            | -14.0        | Vert         |
| 7 | 928.000M    | 40.9         | +0.0     | +3.3     | +6.0     | +23.9    | +0.0          | 74.1           | 88.2            | -14.1        | Vert         |
| 8 | 928.000M    | 40.8         | +0.0     | +3.3     | +6.0     | +23.9    | +0.0          | 74.0           | 88.2<br>hopping | -14.2        | Vert         |

Test Location: CKC Laboratories Inc. • 110 N. Olinda Pl. • Brea, CA 92823 • 714-993-6112  
 Customer: **Itron, Inc.**  
 Specification: **15.247(d) / 15.209 Radiated Spurious Emissions**  
 Work Order #: **104621** Date: 1/25/2021  
 Test Type: **Radiated Emissions** Time: 10:00:39  
 Tested By: Don Nguyen Sequence#: 4  
 Software: EMITest 5.03.19

**Equipment Tested:**

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 2 |              |         |     |

**Support Equipment:**

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 2 |              |         |     |

**Test Conditions / Notes:**

The EUT is placed on Styrofoam platform and powered from 3.6V fresh battery. The EUT is connected to a remote located laptop running CLI Tool ver.2.0.1.24.  
 EUT has fixed orientation per manufacture's specification.  
 Operating frequency range/ mode  
 903 - 926.8MHz, 200kHz steps, 120 channels, 16384 OOK LV3  
 Frequency of measurement: 614-960MHz  
 RBW=120kHz, VBW=360kHz (restricted band)  
 RBW=100kHz, VBW=300kHz (-20dBc)  
  
 Test Method: ANSI C63.10 (2013)  
 Temperature (°C): 24  
 Relative Humidity (%): 30  
 Modification 1 was in place during testing.

**Test Equipment:**

| ID | Asset #  | Description                          | Model    | Calibration Date | Cal Due Date |
|----|----------|--------------------------------------|----------|------------------|--------------|
| T1 | ANP05281 | Attenuator                           | 1B       | 4/7/2020         | 4/7/2022     |
| T2 | AN01993  | Biconilog Antenna                    | CBL6111C | 6/11/2019        | 6/11/2021    |
| T3 | AN02869  | Spectrum Analyzer                    | E4440A   | 8/3/2020         | 8/3/2021     |
| T4 | ANP05198 | Cable-Amplitude<br>+15C to +45C (dB) | 8268     | 12/21/2020       | 12/21/2022   |

**Measurement Data:**

Reading listed by margin.

Test Distance: 3 Meters

| # | Freq<br>MHz | Rdng<br>dB $\mu$ V | T1<br>dB | T2<br>dB | T3<br>dB | T4<br>dB | Dist<br>Table | Corr<br>dB $\mu$ V/m | Spec<br>dB $\mu$ V/m | Margin<br>dB | Polar<br>Ant |
|---|-------------|--------------------|----------|----------|----------|----------|---------------|----------------------|----------------------|--------------|--------------|
| 1 | 614.000M    | 11.3               | +5.9     | +19.8    | +0.0     | +4.6     | +0.0          | 41.6                 | 46.0<br>hopping      | -4.4         | Vert         |
| 2 | 960.000M    | 12.3               | +6.0     | +24.4    | +0.0     | +6.0     | +0.0          | 48.7                 | 54.0<br>hopping      | -5.3         | Vert         |
| 3 | 614.000M    | 10.1               | +5.9     | +19.8    | +0.0     | +4.6     | +0.0          | 40.4                 | 46.0                 | -5.6         | Vert         |
| 4 | 960.000M    | 12.0               | +6.0     | +24.4    | +0.0     | +6.0     | +0.0          | 48.4                 | 54.0                 | -5.6         | Vert         |
| 5 | 902.000M    | 46.4               | +6.0     | +23.5    | +0.0     | +5.8     | +0.0          | 81.7                 | 93.0                 | -11.3        | Vert         |
| 6 | 902.000M    | 46.2               | +6.0     | +23.5    | +0.0     | +5.8     | +0.0          | 81.5                 | 93.0<br>hopping      | -11.5        | Vert         |
| 7 | 928.000M    | 42.3               | +6.0     | +23.9    | +0.0     | +5.9     | +0.0          | 78.1                 | 93.0<br>hopping      | -14.9        | Vert         |
| 8 | 928.000M    | 42.1               | +6.0     | +23.9    | +0.0     | +5.9     | +0.0          | 77.9                 | 93.0                 | -15.1        | Vert         |

Test Location: CKC Laboratories Inc. • 110 N. Olinda Pl. • Brea, CA 92823 • 714-993-6112  
 Customer: **Itron, Inc.**  
 Specification: **15.247(d) / 15.209 Radiated Spurious Emissions**  
 Work Order #: **104621** Date: 1/25/2021  
 Test Type: **Radiated Emissions** Time: 10:04:36  
 Tested By: Don Nguyen Sequence#: 10  
 Software: EMITest 5.03.19

**Equipment Tested:**

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 3 |              |         |     |

**Support Equipment:**

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 3 |              |         |     |

**Test Conditions / Notes:**

The EUT is placed on Styrofoam platform and powered from 3.6V fresh battery. The EUT is connected to a remote located laptop running CLI Tool ver.2.0.1.24.  
 EUT has fixed orientation per manufacture's specification.  
 Operating frequency range/ mode  
 902.4 - 927.6MHz, 400kHz steps, 64 channels, 300kbps GFSK LV2/LV3  
 Frequency of measurement: 614-960MHz  
 RBW=120kHz, VBW=360kHz (restricted band)  
 RBW=100kHz, VBW=300kHz (-20dBc)  
  
 Test Method: ANSI C63.10 (2013)  
 Temperature (°C): 24  
 Relative Humidity (%): 30  
 Modification 1 was in place during testing.

**Test Equipment:**

| ID | Asset #  | Description                          | Model    | Calibration Date | Cal Due Date |
|----|----------|--------------------------------------|----------|------------------|--------------|
| T1 | ANP05281 | Attenuator                           | 1B       | 4/7/2020         | 4/7/2022     |
| T2 | AN01993  | Biconilog Antenna                    | CBL6111C | 6/11/2019        | 6/11/2021    |
| T3 | AN02869  | Spectrum Analyzer                    | E4440A   | 8/3/2020         | 8/3/2021     |
| T4 | ANP05198 | Cable-Amplitude<br>+15C to +45C (dB) | 8268     | 12/21/2020       | 12/21/2022   |

**Measurement Data:**

Reading listed by margin.

Test Distance: 3 Meters

| # | Freq<br>MHz | Rdng<br>dB $\mu$ V | T1<br>dB | T2<br>dB | T3<br>dB | T4<br>dB | Dist<br>Table | Corr<br>dB $\mu$ V/m | Spec<br>dB $\mu$ V/m | Margin<br>dB | Polar<br>Ant |
|---|-------------|--------------------|----------|----------|----------|----------|---------------|----------------------|----------------------|--------------|--------------|
| 1 | 614.000M    | 10.9               | +5.9     | +19.8    | +0.0     | +4.6     | +0.0          | 41.2                 | 46.0                 | -4.8         | Vert         |
| 2 | 614.000M    | 10.6               | +5.9     | +19.8    | +0.0     | +4.6     | +0.0          | 40.9                 | 46.0<br>hopping      | -5.1         | Vert         |
| 3 | 960.000M    | 11.9               | +6.0     | +24.4    | +0.0     | +6.0     | +0.0          | 48.3                 | 54.0                 | -5.7         | Vert         |
| 4 | 960.000M    | 10.8               | +6.0     | +24.4    | +0.0     | +6.0     | +0.0          | 47.2                 | 54.0<br>hopping      | -6.8         | Vert         |
| 5 | 928.000M    | 34.2               | +6.0     | +23.9    | +0.0     | +5.9     | +0.0          | 70.0                 | 90.5<br>hopping      | -20.5        | Vert         |
| 6 | 928.000M    | 33.9               | +6.0     | +23.9    | +0.0     | +5.9     | +0.0          | 69.7                 | 90.5                 | -20.8        | Vert         |
| 7 | 902.000M    | 33.4               | +6.0     | +23.5    | +0.0     | +5.8     | +0.0          | 68.7                 | 90.5                 | -21.8        | Vert         |
| 8 | 902.000M    | 32.8               | +6.0     | +23.5    | +0.0     | +5.8     | +0.0          | 68.1                 | 90.5<br>hopping      | -22.4        | Vert         |

Test Location: CKC Laboratories Inc. • 110 N. Olinda Pl. • Brea, CA 92823 • 714-993-6112  
 Customer: **Itron, Inc.**  
 Specification: **15.247(d) / 15.209 Radiated Spurious Emissions**  
 Work Order #: **104621** Date: 12/23/2020  
 Test Type: **Radiated Emissions** Time: 09:13:09  
 Tested By: Don Nguyen Sequence#: 9  
 Software: EMITest 5.03.19

**Equipment Tested:**

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 3 |              |         |     |

**Support Equipment:**

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 3 |              |         |     |

**Test Conditions / Notes:**

The EUT is placed on Styrofoam platform and powered from 3.6V fresh battery. The EUT is connected to a remote located laptop running CLI Tool ver.2.0.1.24.  
 EUT has fixed orientation per manufacture's specification.  
 Operating frequency range/ mode  
 903 - 926.8MHz, 200kHz steps, 120 channels, 16384 OOK LV1  
 Frequency of measurement: 614-960MHz  
 RBW=120kHz, VBW=360kHz (restricted band)  
 RBW=100kHz, VBW=300kHz (-20dBc)  
 Test Method: ANSI C63.10 (2013)  
 Temperature (°C): 24  
 Relative Humidity (%): 30  
 Modification 1 was in place during testing.

**Test Equipment:**

| ID | Asset #  | Description                          | Model    | Calibration Date | Cal Due Date |
|----|----------|--------------------------------------|----------|------------------|--------------|
| T1 | AN03643  | Spectrum Analyzer                    | E4440A   | 5/20/2020        | 5/20/2022    |
| T2 | ANP01911 | Cable-Amplitude<br>+15C to +45C (dB) | RG214/U  | 1/2/2020         | 1/2/2022     |
| T3 | ANP05281 | Attenuator                           | 1B       | 4/7/2020         | 4/7/2022     |
| T4 | AN01993  | Biconilog Antenna                    | CBL6111C | 6/11/2019        | 6/11/2021    |

**Measurement Data:** Reading listed by margin. Test Distance: 3 Meters

| # | Freq<br>MHz | Rdng<br>dBμV | T1<br>dB | T2<br>dB | T3<br>dB | T4<br>dB | Dist<br>Table | Corr<br>dBμV/m | Spec<br>dBμV/m  | Margin<br>dB | Polar<br>Ant |
|---|-------------|--------------|----------|----------|----------|----------|---------------|----------------|-----------------|--------------|--------------|
| 1 | 614.000M    | 14.9         | +0.0     | +2.5     | +5.9     | +19.8    | +0.0          | 43.1           | 46.0            | -2.9         | Vert         |
| 2 | 614.000M    | 13.0         | +0.0     | +2.5     | +5.9     | +19.8    | +0.0          | 41.2           | 46.0<br>hopping | -4.8         | Vert         |
| 3 | 960.000M    | 14.9         | +0.0     | +3.3     | +6.0     | +24.4    | +0.0          | 48.6           | 54.0            | -5.4         | Vert         |
| 4 | 960.000M    | 12.5         | +0.0     | +3.3     | +6.0     | +24.4    | +0.0          | 46.2           | 54.0<br>hopping | -7.8         | Vert         |
| 5 | 902.000M    | 44.0         | +0.0     | +3.2     | +6.0     | +23.5    | +0.0          | 76.7           | 89.4            | -12.7        | Vert         |
| 6 | 902.000M    | 44.0         | +0.0     | +3.2     | +6.0     | +23.5    | +0.0          | 76.7           | 89.4<br>hopping | -12.7        | Vert         |
| 7 | 928.000M    | 42.1         | +0.0     | +3.3     | +6.0     | +23.9    | +0.0          | 75.3           | 89.4<br>hopping | -14.1        | Vert         |
| 8 | 928.000M    | 42.1         | +0.0     | +3.3     | +6.0     | +23.9    | +0.0          | 75.3           | 89.4            | -14.1        | Vert         |

Test Location: CKC Laboratories Inc. • 110 N. Olinda Pl. • Brea, CA 92823 • 714-993-6112  
 Customer: **Itron, Inc.**  
 Specification: **15.247(d) / 15.209 Radiated Spurious Emissions**  
 Work Order #: **104621** Date: 1/25/2021  
 Test Type: **Radiated Emissions** Time: 10:11:40  
 Tested By: Don Nguyen Sequence#: 9  
 Software: EMITest 5.03.19

**Equipment Tested:**

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 3 |              |         |     |

**Support Equipment:**

| Device          | Manufacturer | Model # | S/N |
|-----------------|--------------|---------|-----|
| Configuration 3 |              |         |     |

**Test Conditions / Notes:**

The EUT is placed on Styrofoam platform and powered from 3.6V fresh battery. The EUT is connected to a remote located laptop running CLI Tool ver.2.0.1.24.  
 EUT has fixed orientation per manufacture's specification.  
 Operating frequency range/ mode  
 903 - 926.8MHz, 200kHz steps, 120 channels, 16384 OOK LV3  
 Frequency of measurement: 614-960MHz  
 RBW=120kHz, VBW=360kHz (restricted band)  
 RBW=100kHz, VBW=300kHz (-20dBc)  
 Test Method: ANSI C63.10 (2013)  
 Temperature (°C): 24  
 Relative Humidity (%): 30  
 Modification 1 was in place during testing.

**Test Equipment:**

| ID | Asset #/Serial # | Description                          | Model    | Calibration Date | Cal Due Date |
|----|------------------|--------------------------------------|----------|------------------|--------------|
| T1 | ANP05281         | Attenuator                           | 1B       | 4/7/2020         | 4/7/2022     |
| T2 | AN01993          | Biconilog Antenna                    | CBL6111C | 6/11/2019        | 6/11/2021    |
| T3 | AN02869          | Spectrum Analyzer                    | E4440A   | 8/3/2020         | 8/3/2021     |
| T4 | ANP05198         | Cable-Amplitude<br>+15C to +45C (dB) | 8268     | 12/21/2020       | 12/21/2022   |

**Measurement Data:**

Reading listed by margin.

Test Distance: 3 Meters

| # | Freq<br>MHz | Rdng<br>dBμV | T1<br>dB | T2<br>dB | T3<br>dB | T4<br>dB | Dist<br>Table | Corr<br>dBμV/m | Spec<br>dBμV/m  | Margin<br>dB | Polar<br>Ant |
|---|-------------|--------------|----------|----------|----------|----------|---------------|----------------|-----------------|--------------|--------------|
| 1 | 614.000M    | 12.6         | +5.9     | +19.8    | +0.0     | +4.6     | +0.0          | 42.9           | 46.0            | -3.1         | Vert         |
| 2 | 614.000M    | 12.3         | +5.9     | +19.8    | +0.0     | +4.6     | +0.0          | 42.6           | 46.0<br>hopping | -3.4         | Vert         |
| 3 | 960.000M    | 12.1         | +6.0     | +24.4    | +0.0     | +6.0     | +0.0          | 48.5           | 54.0<br>hopping | -5.5         | Vert         |
| 4 | 960.000M    | 11.5         | +6.0     | +24.4    | +0.0     | +6.0     | +0.0          | 47.9           | 54.0            | -6.1         | Vert         |
| 5 | 902.000M    | 45.5         | +6.0     | +23.5    | +0.0     | +5.8     | +0.0          | 80.8           | 94.6            | -13.8        | Vert         |
| 6 | 928.000M    | 44.0         | +6.0     | +23.9    | +0.0     | +5.9     | +0.0          | 79.8           | 94.6<br>hopping | -14.8        | Vert         |
| 7 | 928.000M    | 43.9         | +6.0     | +23.9    | +0.0     | +5.9     | +0.0          | 79.7           | 94.6            | -14.9        | Vert         |
| 8 | 902.000M    | 40.5         | +6.0     | +23.5    | +0.0     | +5.8     | +0.0          | 75.8           | 94.6<br>hopping | -18.8        | Vert         |

**Test Setup Photo(s)**



Configuration 1, Below 1GHz




Configuration 1, Below 1GHz



Configuration 1, Above 1GHz




Configuration 1, Above 1GHz



Configuration 2, Below 1GHz



Configuration 2, Below 1GHz



Configuration 2, Above 1GHz



Configuration 2, Above 1GHz




Configuration 3, Below 1GHz



Configuration 3, Below 1GHz



Configuration 3, Above 1GHz



Configuration 3, Above 1GHz

## SUPPLEMENTAL INFORMATION

### Measurement Uncertainty

| Uncertainty Value | Parameter                 |
|-------------------|---------------------------|
| 4.73 dB           | Radiated Emissions        |
| 3.34 dB           | Mains Conducted Emissions |
| 3.30 dB           | Disturbance Power         |

Uncertainties reported are worst case for all CKC Laboratories' sites and represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ . Compliance is deemed to occur provided measurements are below the specified limits.

### Emissions Test Details

#### TESTING PARAMETERS

Unless otherwise indicated, the following configuration parameters are used for equipment setup: The cables were routed consistent with the typical application by varying the configuration of the test sample. Interface cables were connected to the available ports of the test unit. The effect of varying the position of the cables was investigated to find the configuration that produced maximum emissions. Cables were of the type and length specified in the individual requirements. The length of cable that produced maximum emissions was selected.

The equipment under test (EUT) was set up in a manner that represented its normal use, as shown in the setup photographs. Any special conditions required for the EUT to operate normally are identified in the comments that accompany the emissions tables.

The emissions data was taken with a spectrum analyzer or receiver. Incorporating the applicable correction factors for distance, antenna, cable loss and amplifier gain, the data was reduced as shown in the table below. The corrected data was then compared to the applicable emission limits. Preliminary and final measurements were taken in order to ensure that all emissions from the EUT were found and maximized.

#### CORRECTION FACTORS

The basic spectrum analyzer reading was converted using correction factors as shown in the highest emissions readings in the tables. For radiated emissions in  $\text{dB}\mu\text{V}/\text{m}$ , the spectrum analyzer reading in  $\text{dB}\mu\text{V}$  was corrected by using the following formula. This reading was then compared to the applicable specification limit. Individual measurements were compared with the displayed limit value in the margin column. The margin was calculated based on subtracting the limit value from the corrected measurement value; a positive margin represents a measurement exceeding the limit, while a negative margin represents a measurement less than the limit.

| SAMPLE CALCULATIONS |                     |                                     |
|---------------------|---------------------|-------------------------------------|
|                     | Meter reading       | ( $\text{dB}\mu\text{V}$ )          |
| +                   | Antenna Factor      | ( $\text{dB}/\text{m}$ )            |
| +                   | Cable Loss          | ( $\text{dB}$ )                     |
| -                   | Distance Correction | ( $\text{dB}$ )                     |
| -                   | Preamplifier Gain   | ( $\text{dB}$ )                     |
| =                   | Corrected Reading   | ( $\text{dB}\mu\text{V}/\text{m}$ ) |

#### TEST INSTRUMENTATION AND ANALYZER SETTINGS

The test instrumentation and equipment listed were used to collect the emissions data. A spectrum analyzer or receiver was used for all measurements. Unless otherwise specified, the following table shows the measuring equipment bandwidth settings that were used in designated frequency bands. For testing emissions, an appropriate reference level and a vertical scale size of 10 dB per division were used.

| MEASURING EQUIPMENT BANDWIDTH SETTINGS PER FREQUENCY RANGE |                     |                  |                   |
|------------------------------------------------------------|---------------------|------------------|-------------------|
| TEST                                                       | BEGINNING FREQUENCY | ENDING FREQUENCY | BANDWIDTH SETTING |
| CONDUCTED EMISSIONS                                        | 150 kHz             | 30 MHz           | 9 kHz             |
| RADIATED EMISSIONS                                         | 9 kHz               | 150 kHz          | 200 Hz            |
| RADIATED EMISSIONS                                         | 150 kHz             | 30 MHz           | 9 kHz             |
| RADIATED EMISSIONS                                         | 30 MHz              | 1000 MHz         | 120 kHz           |
| RADIATED EMISSIONS                                         | 1000 MHz            | >1 GHz           | 1 MHz             |

#### SPECTRUM ANALYZER/RECEIVER DETECTOR FUNCTIONS

The notes that accompany the measurements contained in the emissions tables indicate the type of detector function used to obtain the given readings. Unless otherwise noted, all readings were made in the "positive peak" detector mode. Whenever a "quasi-peak" or "average" reading was recorded, the measurement was annotated with a "QP" or an "Ave" on the appropriate rows of the data sheets. In cases where quasi-peak or average limits were employed and data exists for multiple measurement types for the same frequency then the peak measurement was retained in the report for reference, however the numbering for the affected row was removed and an arrow or caret ("^") was placed in the far left-hand column indicating that the row above takes precedence for comparison to the limit. The following paragraphs describe in more detail the detector functions and when they were used to obtain the emissions data.

##### Peak

In this mode, the spectrum analyzer or receiver recorded all emissions at their peak value as the frequency band selected was scanned. By combining this function with another feature called "peak hold," the measurement device had the ability to measure intermittent or low duty cycle transient emission peak levels. In this mode the measuring device made a slow scan across the frequency band selected and measured the peak emission value found at each frequency across the band.

##### Quasi-Peak

Quasi-peak measurements were taken using the quasi-peak detector when the true peak values exceeded or were within 2 dB of a quasi-peak specification limit. Additional QP measurements may have been taken at the discretion of the operator.

##### Average

Average measurements were taken using the average detector when the true peak values exceeded or were within 2 dB of an average specification limit. Additional average measurements may have been taken at the discretion of the operator. If the specification or test procedure requires trace averaging, then the averaging was performed using 100 samples or as required by the specification. All other average measurements are performed using video bandwidth averaging. To make these measurements, the test engineer reduces the video bandwidth on the measuring device until the modulation of the signal is filtered out. At this point the measuring device is set into the linear mode and the scan time is reduced.