

Detector features

- PowerG wireless photoelectric beam detector
- Battery life for transmitter is approximately four years, battery life for receiver is approximately five years when using LSH20 (3.6V, 13Ah) batteries manufactured by SAFT
- Battery saving function
- Intermittent output function
- Quad high-power beams
- Smart design with slim body
- Vivid interior colour for optical alignment
- IP65 waterproof structure
- 4-channel beam frequency selector
- Viewfinder with 2X magnification
- Beam interruption adjustment function
- D.Q. circuit (environmental disqualification)
- Tamper function
- LED indicator for an easy alignment
- Outdoor detection range of 350 ft

Introduction

The PG9350SL is a PowerG wireless photoelectric beam detector that provides protection for outdoor perimeters.

Warning: Failure to follow the instructions provided with this device or improper handling may cause death or serious injury.

Caution: Failure to follow the instructions provided with this device or improper handling may cause injury and/or property damage.

Safety information

Warnings


- Do not use the product for purposes other than the detection of moving objects such as people and vehicles.
- Do not use the product to activate a shutter, etc., which may cause an accident.
- Do not touch the unit base or power terminals of the product with wet hands. It may cause electric shock.
- Do not touch when the product is wet. It may cause electric shock.
- Never attempt to disassemble or repair the product. It may cause fire or damage to the devices.
- Do not use batteries that have different levels of power remaining, that is, new and used batteries. Not observing these guidelines may result in an explosion, leakage of electrolyte, emission of toxic gases, or other outcomes that may be harmful to people and property.
- When handling batteries, do not recharge, short circuit, crush, disassemble, exceed heat above 100°C (212°F), incinerate, or expose contents to water. Do not solder directly to the cell. Not observing these guidelines may result in fire, explosion, or severe burn hazard.

Cautions

- Do not solder directly to the cell.
- Do not pour water over the product with a bucket, hose, or similar. The water may enter, which may cause damage to the devices.

- Clean and check the product periodically for safe use. If any problem is found, do not attempt to use the product as it is and have the product repaired by a professional engineer or electrician.

Installation advice




A	Do not install the unit on an unstable surface
B	Do not install the pole in location where it is not stable.
C	Do not install the unit near trees or other objects that may block the beam.
D	The pole size should be 34 - 48 mm (1.34" - 1.89").
E	Do not install the receiver in a location that is exposed to direct sunlight.
F	Install the unit at a height where an object can be detected without fail
G	Install the unit at least 1 m (3.3 ft.) away from a wall or fence that is parallel to the beam.
H	Do not install the unit where the infrared beam from a different model can reach the receiver

Caution Install the chassis, waterproof packing, and back box together. Not doing this may compromise IP rate of this product.

Box contents

Transmitter and receiver modules
Installation Manual
Hardware Pack


Parts identification



Accessories



4×20 self tapping for wall mounting
(with rubber washer): 12




Pole brackets
(with double-sided tape): 4




M4×30 screws for pole mounting
(with rubber washer): 8



U-brackets: 4



Banding bands: 2



Beam blocking plate: 2
(attached on the back of the cover)

Ordering detector batteries

Specified batteries: Four LSH20 batteries manufactured by SAFT, two for the transmitter and two for the transceiver.

For information about batteries, visit the following website and contact your local SAFT sales representative. See <http://www.saftbatteries.com/battery-search/lsh/>.

Enrolment


The device is compatible with the following panels:

- PowerSeries NEO (v1.37 and higher)
- PowerSeries Pro (v1.31 and higher)
- IQ2 (v2.6 and higher)
- IQ3 (v3.0 and higher)
- IQ4 (v4.0 and higher)
- PowerSeries NEO2 / Lucy Hybrid v1.0

The device transmitter and receiver enrol separately onto the control panel. The modules can enrol onto the panel in any order.

Enrolling the device

The device begins the enrolment process when the OPTEX RF module is powered on. The OPTEX RF module is a card in the detector.



1. Install batteries in the detector.
2. Turn the RF module power switch located on the interface board to the ON position.


Refer to the control panel installation manual for the complete set of enrolment instructions and testing procedures. The enrolment procedure should begin automatically if the panel is already in enrolment mode. If the automatic enrolment procedure fails, refer to the control panel instructions and attempt manual enrolment of the device.

Installation


Separating the unit

1. Loosen the cover lock screw with a screwdriver.
2. Place a coin in the recess and twist slightly to remove the cover.


3. Pull the cover from the back of the unit.



4. To remove the main unit from the chassis, turn the optical unit 90° and remove the screws from both sides.
5. Pull the upper part of the main unit forward and up to remove it.
Caution: Do not place the main unit where it is exposed to direct sunlight. Doing so may cause damage to the product.



6. Remove the chassis from the back box.
Note: The screws to secure the back box cannot be removed from the chassis.
Caution: When the waterproof packing is detached, attach it to the back of the chassis before mounting. Not doing so may compromise the IP rate of this product.




Notes:


Avoid installing the transmitter and receiver facing each other through the corner of the cover. While doing this installation, the maximum detection range must be half of the original detection range to compensate the attenuation of beam by the corner of the cover.

Mounting on a wall


1. Using a screwdriver or similar tool, break the six knockouts in the back box.
Note: The knockout positions are marked **WALL**.




2. Mount the back box to the wall. If two detectors are installed, the distance between the upper and lower detector should be at least 20 mm. If mounting in a corner location, ensure the distance from the side wall is at least 1 m. Use a pitch of 83.5 mm when connecting to a gang electric box.
3. Insert the batteries into the back box.
Note: Use of batteries other than recommended may shorten the battery life.
Caution: Remove all batteries prior to replacing with new ones. If this is not followed, the low battery indicator LED will not reset and continue to blink.
4. Pull the cable through the chassis and tighten the screws.
Caution: Tighten the screws completely by torque of 1.0 - 1.5 N·m. Not doing so may cause malfunction of the wall tamper.
 Avoid cables from being caught between chassis. When the waterproof packing is detached, be sure to attach it on the back of the chassis before mounting. Not doing so may compromise IP rate of this product.




5. To fix the main unit onto the chassis, insert the lower part, and then push the upper part onto the chassis.



6. Turn the optical unit 90 degrees and tighten the screws on both sides.




7. Connect the cables and complete the setting and alignment



8. To close the cover, hook on the upper part of the chassis and push the lower part of the cover until it clicks into position. **Caution:** Do not contact with the optical unit when mounting the

cover. Otherwise malfunction may occur due to the shift of the optical axis, resulting in the need of readjustment.

9. Fasten the cover lock screw.




Notes: Ensure the cables do not get caught between the main unit and the cover. Push the middle part of the cover to hide the orange label completely when in operation.

Mounting on a pole


1. Using a screwdriver or similar tool, break the four knockouts marked **POLE** on the back box.

Note: When mounting the single set of detectors to the pole, use a pair of the inside knockouts. The knockout positions are marked **POLE(1)**.

Caution: If you accidentally open an unnecessary knockout, be sure to fill the knockout. Not doing so may result in waterproof failure and malfunction of the product.




2. Fix the back box on the pole. If two detectors are installed, the distance between the upper and lower detector should be at least 20 mm. If mounting in a corner location, ensure the distance from the side wall is at least 1m.
3. Temporarily attach the pole mounting bracket to the back of the back box with double-sided tape. This makes it easier to mount the unit with the combinations of the brackets.




4. Insert the batteries into the back box.
Note: Use of batteries other than recommended may shorten the battery life.
Caution: Remove all batteries prior to replacing with new ones. If this is not followed, the low battery indicator LED will not reset and continue to blink.
5. Run the cables so that they are not pinched between the chassis and back box.
6. Pass the cables through the wiring hole of the chassis and mount the chassis to the back box.
7. Tighten the screws.
Caution: Tighten the screws completely by torque of 1.0 - 1.5 N·m. Not doing so may cause malfunction of the wall tamper.
 Avoid cables from being caught between chassis. When the waterproof packing is detached, be sure to attach it on the back of the chassis before mounting. Not doing so may compromise IP rate of this product.
8. To fix the main unit onto the chassis, insert the lower part, and then push the upper part onto the chassis.
9. Turn the optical unit 90 degrees and tighten the screws on both sides.
10. Connect the cables and complete setting and alignment ([see Wiring](#)).
11. To close the cover, hook on the upper part of the chassis and push the lower part of the cover until it clicks into position. **Caution:** Do not contact with the optical unit when mounting the cover. Otherwise malfunction may occur due to the shift of the optical axis, resulting in the need of readjustment.
12. Fasten the cover lock screw.
Notes: Ensure the cables do not get caught between the main unit and the cover.
 Push the middle part of the cover to hide the orange label completely when in operation.

Installing two detectors in opposing directions

1. Using a screwdriver or similar tool, break the four knockouts on the back box.
Note: Choose a different pair of knockouts. Pairs of the knockout positions are marked **POLE(1)** and **POLE(2)**.









2. Fix the back box on the pole. Double-sided tapes attached to the pole mounting brackets make it easier to mount the unit with the combinations of the brackets.



3. Perform the wall mounting procedure steps 4 to 9.


Mounting the detector in the beam tower

1. Select a mounting pattern from the following options:

Mounting pattern	Main unit	Main unit plus chassis	Main unit plus chassis plus back box
			
Tamper position			

Caution: When using the tamper output, install the detector with the tamper shown above being pressed. Not doing so may cause malfunction of wall tamper.

2. When installing the detector without the cover, lock the tamper button with the tamper lock plate.
 - a. Loosen the screw and rotate the tamper lock plate.
 - b. Fasten the screw to lock the tamper button.




Caution:

- The switch selection is not recognized when locking the tamper button. Release the tamper button before selecting a function using the switch.
- After completing the settings, be sure to lock the tamper button to check that all LEDs are OFF. If the tamper button is not locked, the LEDs are kept ON, which consumes more battery power.
- The monitor jack output is disabled when the tamper button is locked.
- When locking the tamper button, the beam alignment test point will be disabled. Complete the alignment procedure before locking the tamper button.

Mounting the detector separate from the back box in the beam tower

1. To remove the waterproof packing, remove the two screws fixing the waterproof packing.
2. Open the wiring guide on the back of the chassis using pliers.





3. Fix the back box and main unit.

Wiring

This product is provided with wiring based on the assumption that N.C. wireless transmitters are used. Connect the cables from the back box (Yellow/Yellow-white, Green/Green-white, and Black/Black white) to the respective terminals on the wireless transmitters.

Functional settings



Receiver DIP switch

4 Channel beam frequency selector switch

Battery saving timer switch

Intermittent output function switch

Beam interruption adjustment switch 1

Beam interruption adjustment switch 2

Transmitter DIP switch

4 Channel beam frequency selector switch

Battery saving timer switch

Intermittent output function switch

4 channel beam frequency selector


The 4 channel beam frequency selector can be used to avoid unwanted crosstalk that can occur when using multiple photoelectric detectors for long distance or beam stacking applications.

- To select between 4 separate beam frequencies, use the switch provided.
- Make sure the receiver and transmitter that are facing each other are set to the same channel.
- More than double stacked application is not possible


Always switch the frequencies two channels apart when stacking units on top of one another. The upper unit is set on channel 1 while the lower is on channel 3, channels 2 and 4 could have also been used.

Examples:


- Double stacked protection. Since Receiver B may receive the infrared beam from Transmitter A, select the frequencies as shown in the figure above. (In the figure, each number in the square indicate a channel numbers.)




- Long distance protection. Since Receiver C may receive the infrared beam from Transmitter A, select their frequencies as shown in the figure below.




- c. Double stacked long distance protection. More than double stacked application is not possible.



- d. Perimeter protection.



- e. Perimeter protection in a two-stack configuration.




Warning:

- Do not attempt to install this product with any other photoelectric detector. It may cause the detector to fail or not respond to movements. If the receiver of this product receives the beam from the wired photoelectric detector, it may cause false alarms.
- If you install the battery-operated photoelectric detector with Optex hard-wired photoelectric detector at the same site, ensure that the hard-wired transmitter cannot affect any other battery-operated receivers for avoiding cross talk between photoelectric detector.

Optical alignment

Optical alignment is an important procedure to increase reliability.


Be sure to take alignment step 1 through 5 described below to attain the maximum level of the output through the monitor jack.



1. Perform rough alignment of the horizontal angle.


Notes:

- Mount a beam blocking plate to the lower unit and then start optical alignment from the upper unit.
 - Beam blocking plate is attached on the back of the cover.
 - Return the beam blocking plate to the cover after use.
2. Look into the viewfinder and perform fine alignment of the horizontal and vertical angles using the alignment dial.



Note: Check the diagram below and perform fine alignment for both horizontal alignment and vertical alignment. Turn the small dial for horizontal alignment. Turn the large dial for vertical alignment.

- Clockwise: Upward
- Counterclockwise: Downward



Warning: Do not look at strong light sources such as sunlight through the viewfinder.

Caution: Do not touch the lens during optical adjustment.

- After the alignment using the viewfinder, make adjustment with the voltmeter for more accurate optical alignment.

Set the voltmeter range to 5 to 10 VDC.

After checking the receiving level of optical axis by using the Level indicator LED, make sure to make fine alignment for both transmitter and receiver with voltmeter to achieve a monitor output level of "Excellent". Insert the voltmeter's positive pin into the positive terminal of the monitor jack, and the negative pin into the negative terminal.

- Adjust the horizontal and vertical angles while checking the light receiving status by Alarm indicator LED on the pairing receiver.

Level indicator LED	Light interrupted	Light received				
	ON (red)	Fast blink	Slow blink	OFF		
Adjustment level	Re-adjust angle			Fair	Good	Excellent
Monitor jack output	0 V > 1.0 V > 2.4 V > 2.8 V					


Caution: The Alarm indicator LED is a supporting tool for easy alignment. Be sure to perform fine alignment to ensure the maximum output level through the monitor jack.

The Level indicator LED should only be used for rough alignment, for fine alignment always use the monitor jack output level.

- Complete steps 1 to 4 for the lower transmitter.

Optional: Adjusting the beam interruption

Initial setting is at 50 ms for normal work. According to the speed of a supposed target you select one specific setting out of 4 steps. Set the beam interruption adjustment switches of the Receiver according to the speed of the human object to detect.



Optional: Setting the battery saving timer

Alarm output activation is limited to 2 minutes by a timer. Even if there are continuous alarm events, the alarm output operates only once in the timer period.

Caution: Remove **all** batteries prior to replacing with new ones. If this is not followed, the low battery indicator LED will not reset and continue to blink.

Optional: Setting the intermittent output function

When wireless configuration is being used, which is unable to determine whether the alarm output continues, setting the intermittent output function to the “ON” position, turns on the intermittent alarm output. This configures the wireless transmitter to send alarms at a specific time intervals.

	Receiver						Transmitter				
ON OFF	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	• Alarm output: 1 output/ 1 minute
SL-350QFR	1	2	3	4	5	6	1	2	3	4	• D.Q. output: 1 output/ 1 minute
SL-350QNR	-	-	1	2	3	4	-	-	1	2	• Low battery output: 1 output/ 5 minutes


Optional: D.Q. output (environmental disqualification)

The D.Q. output features detects when the beam strength is below acceptable levels due to environmental factors such as heavy rain, snow, or fog. If the beam strength is low for more than 20 seconds due to these conditions, a D.C. output signal sends from the receiver. The signal will return to normal when the beam strength is at acceptable levels for more than 2 seconds.

The D.C. output signal can be configured for one of the following uses:

- **Separate Output:** Alerts the user that the detector is not working effectively due to weather conditions
- **Bypass:** This bypasses the alarm when the D.Q. output is triggered by adverse weather conditions.

You can configure either option with the following jumper pin settings on interface board of the Receiver:



D.Q. and Alarm Separate Output

Bypass Alarm Setting


Checking the LED operation

	Detection (beam interruption)	Normal	Low battery power
Alarm (receiver)	ON	OFF	—
Power (transmitter)	ON	ON	—
Low battery (receiver and transmitter)	—	—	Blink

Checking the transmitter operation

After installation is complete to check the operation.

1. Turn off the battery saving mode.
2. Make sure that the alarm indicator is off. If it is illuminated even when the beams are not blocked, make optical alignment again.
3. Check that the low battery indicator LEDs on both transmitter and receiver are OFF. If the indicator LED is blinking, the battery power is low. Replace with the new batteries.
4. Conduct a walk test to check that Alarm indicator LED on the receiver turns ON as the walker interrupts the beams. Be sure to conduct a walk test at the following three points:
 - A. In front of the transmitter
 - B. In front of the receiver
 - C. At the mid point between the transmitter and receiver



The detector is installed properly when Alarm indicator LED turns ON in the tests at all the three points.

Caution:

For battery power savings, perform the operation check before checking the following items.


- (1) When installing on a wall or pole, make sure the cover is properly attached to main unit.
- (2) When installing in a beam tower, make sure the tamper bushing is properly attached to main unit.

Troubleshooting

Problem	Possible cause	Corrective action
LEDs are not Illuminated (transmitter or receiver)	Reversed battery polarity	Check battery polarity
Low battery indicator blinks even though the battery has been inserted (transmitter or receiver)	Reversed battery polarity	Check battery polarity
Alarm is not output	Reflection from the floor or wall.	Align beams away from the floor or wall.
	Beam has not been blocked.	Block all four beams.
Alarm is kept output	Channels of transmitter and receiver are different.	Set the same channel to both transmitter and receiver
	Multiple photoelectric detector for long distance or beam stacking applications.	Set channels 1-3 or 2-4 or 1-4.
	Optical alignment was not performed properly.	See <u>Optical alignment</u> .
Batteries are going flat too quickly	Tamper button has not performed properly.	Set the cover of the tamper lock plate properly.
Frost, snow or heavy rain causes false alarm.	Optical alignment not optimized.	See <u>Optical alignment</u> and make realignment.
Improper output	The wiring is incorrect.	Correct the wiring.
Wall tamper does	Screws between the	Tighten screws completely.

not activate.	chassis and the back box are loose.	
	The waterproof packing on back box is misplaced.	Remove chassis from the back box and align the waterproof packing onto the chassis.

Dimensions



Specifications

GENERAL

Maximum detection range 100 m/350 ft.

Maximum arrival distance 1000 m/3500 ft.

Detection method Quad infrared beam interruption detection

Selectable beam frequency 4 channels

Interruption time Variable between 50/100/250/500 ms (4 steps)

Power source Recommend: 3.6 V, 13.0 Ah LSH20 lithium batteries manufactured by SAFT.

Current draw 745 μ A Transmitter: 420 μ A + Receiver: 325 μ A (at 25°C, 3.6 VDC)

Battery life Transmitter: Approximately 4 years. Receiver: Approximately 5 years

Operating temperature -20°C - +60°C (-4°F - 140°F)

Operating humidity 95 % (max.)

Alignment angle $\pm 90^\circ$ Horizontal, $\pm 10^\circ$ Vertical

Dimension H x W x D mm (inch): 452 (17.9) x 83 (3.3) x 138 (5.4)

Weight 3300 g (Total weight of Transmitter + Receiver, excluding accessories)

International protection IP65

Frequency 915 MHz

Supervisory transmission frequency: 433 MHz / 868 MHz/915 MHz 128/256 second intervals

Maximum Tx power: 433.22 MHz - 434.64 MHz: 10 mW/10 dBm, 868.0 MHz - 868.6 MHz:

25mW/14dBm, 868.7 MHz - 869.2 MHz: 25mW/14dBm

OUTPUT

Alarm output Form C-Solid State Switch: 3.6 VDC, 0.01 A

Alarm period 2 sec (± 1) (Nominal)

D.Q output Form C-Solid State Switch: 3.6 VDC, 0.01 A (Receiver only)

Low battery output N.C. (Solid State Switch): 3.6 VDC, 0.01 A

Tamper output (cover, back box, main unit) N.C. (Mechanical Switch): 3.6 VDC, 0.01 A. Opens when cover, main unit or back box is removed.

INDICATOR

Alarm indicator (Receiver) Alarm: ON Light receiving: OFF

Level indicator (Receiver) Not Light receiving: OFF Light receiving: Blinking or OFF

Power indicator (Transmitter) Power ON: ON Power OFF: OFF

Low battery indicator Voltage reduction: Blinking

Specifications and design are subject to change without prior notice.

* The value is based on the condition that it is used within the ambient temperature range of 20 to 25°C. (LSH-20 x2 pcs)

** Using batteries other than those recommended may shorten the battery life.

Note: These units are designed to detect an intruder and activate an alarm control panel; they are part of a complete system, therefore the manufacturer cannot accept responsibility for any damages or other consequences resulting from an intrusion.

Compliance with standards

USA: FCC- CFR 47 Part 15
UL639, UL1023



Canada: IC RSS – 247
ULC-S306, ULC-S304
ISED Canada RSS247 Certification
CISPR32 Class B

This device complies with Part 15 of the FCC Rules and with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes : (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

To comply with FCC Section 1.1310 for human exposure to radio frequency electromagnetic fields and IC requirements, implement the following instruction: A distance of at least 20cm. between the equipment and all persons should be maintained during the operation of the equipment. Le dispositif doit être placé à une distance d'au moins 20 cm à partir de toutes les personnes au cours de son fonctionnement normal. Les antennes utilisées pour ce produit ne doivent pas être situées ou exploitées conjointement avec une autre antenne ou transmetteur.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures: Reorient or relocate the receiving antenna. Increase the separation between the equipment and receiver. Connect the equipment into an outlet on a circuit different

from that to which the receiver is connected. Consult the dealer or an experienced radio/TV technician for help.

- This Class B digital apparatus complies with Canadian ICES-003.
- Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada.

WARNING! Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

UL/ULC Notes

Only model PG9350SL operating in the frequency band 912-919MHz is UL/ULC listed. The PG9350SL has been listed by UL for commercial and residential burglary applications and by ULC for residential burglary applications

in accordance with the requirements in the Standards UL 639 and ULC-S306 for Intrusion Detection Units.

For UL/ULC installations use these devices only in conjunction with compatible DSC wireless receivers: HSM2HOST9, HS2LCDRF(P)9, HS2ICNRF(P) 9, PG9920, WS900-19, WS900-29, PowerSeries NEO (v1.37 and higher), PowerSeries Pro (v1.31 and higher), IQ2 (v2.6 and higher), IQ3 (v3.0 and higher), IQ4 (v4.0 and higher), IQ NEO and IQ PRO. After installation verify the product functionality in conjunction with the compatible receiver used.

FCC COMPLIANCE STATEMENT

WARNING! Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in residential installations. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio and television reception. However, there is no guarantee that interference will not occur in a particular installation. If this device does cause such interference, which can be verified by turning the device off and on, the user is encouraged to eliminate the interference by one or more of the following measures:

- Re-orient or re-locate the receiving antenna.
- Increase the distance between the device and the receiver.
- Connect the device to an outlet on a circuit different from the one that supplies power to the receiver.
- Consult the dealer or an experienced radio/TV technician.

FCC ID: F5321PG9350SL

Innovation Science and Economic Development Canada (ISED) Statement

This equipment complies with FCC and ISED Canada RF radiation exposure limits set forth for an uncontrolled environment.

This device complies with FCC Rules Part 15 and with ISED Canada license exempt RSS standard(s). Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference that may be received or that may cause undesired operation.

Le présent appareil est conforme aux CNR d'ISED Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes : (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

To comply with FCC Section 1.1310 for human exposure to radio frequency electromagnetic fields

and IC requirements, implement the following instruction: A distance of at least 20cm. between the

equipment and all persons should be maintained during the operation of the equipment.

Le dispositif doit être placé à une distance d'au moins 20 cm à partir de toutes les personnes au cours de son fonctionnement normal. Les antennes utilisées pour ce produit ne doivent pas être situées ou exploitées conjointement avec une autre antenne ou transmetteur.

IC: 160A-PG9350SL

The term IC before the radio certification number signifies that the Industry Canada technical specifications were met. This Class B digital apparatus complies with Canadian ICES-003. This device complies with RSS-247 of Industry Canada. Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device. Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada. Ce dispositif satisfait aux exigences d'Industrie Canada, prescrites dans le document CNR-247. son utilisation est autorisée seulement aux conditions suivantes: (1) il ne doit pas produire de brouillage et (2) l'utilisateur du dispositif doit être prêt à accepter tout brouillage radioélectrique reçu, même si ce brouillage est susceptible de compromettre le fonctionnement du dispositif.

Limited Warranty

Digital Security Controls warrants that for a period of 12 months from the date of purchase, the product shall be free of defects in materials and workmanship under normal use and that in fulfilment of any breach of such warranty, Digital Security Controls shall, at its option, repair or replace the defective equipment upon return of the equipment to its repair depot. This warranty applies only to defects in parts and workmanship and not to damage incurred in shipping or handling, or damage due to causes beyond the control of Digital Security Controls such as lightning, excessive voltage, mechanical shock, water damage, or damage arising out of abuse, alteration or improper application of the equipment.

The foregoing warranty shall apply only to the original buyer, and is and shall be in lieu of any and all other warranties, whether expressed or implied and of all other obligations or liabilities on the part of Digital Security Controls. Digital Security Controls neither assumes responsibility for, nor authorizes any other person purporting to act on its behalf to modify or to change this warranty, nor to assume for it any other warranty or liability concerning this product.

In no event shall Digital Security Controls be liable for any direct, indirect or consequential damages, loss of anticipated profits, loss of time or any other losses incurred by the buyer in connection with the purchase, installation or operation or failure of this product.

Warning: *Digital Security Controls recommends that the entire system be completely tested on a regular basis. However, despite frequent testing, and due to, but not limited to, criminal tampering or electrical disruption, it is possible for this product to fail to perform as expected.*

Important Information: *Changes or modifications not expressly approved by Digital Security Controls could void the user's authority to operate this equipment.*

IMPORTANT - READ CAREFULLY: DSC Software purchased with or without Products and Components is copyrighted and is purchased under the following license terms:

- This End-User License Agreement ("EULA") is a legal agreement between You (the company, individual or entity who acquired the Software and any related Hardware) and Digital Security Controls, a division of Tyco Safety Products Canada Ltd. ("DSC"), the manufacturer of the integrated security systems and the developer of the software and any related products or components ("HARDWARE") which You acquired.
- If the DSC software product ("SOFTWARE PRODUCT" or "SOFTWARE") is intended to be accompanied by HARDWARE, and is NOT accompanied by new HARDWARE, You may not use, copy or install the SOFTWARE PRODUCT. The SOFTWARE PRODUCT includes computer software, and may include associated media, printed materials, and "online" or electronic documentation.
- Any software provided along with the SOFTWARE PRODUCT that is associated with a separate end-user license agreement is licensed to You under the terms of that license agreement. • By installing, copying, downloading, storing, accessing or otherwise using the SOFTWARE PRODUCT, You agree unconditionally to be bound by the terms of this EULA, even if this EULA is deemed to be

a modification of any previous arrangement or contract. If You do not agree to the terms of this EULA, DSC is unwilling to license the SOFTWARE PRODUCT to You, and You have no right to use it.

LICENSE

The SOFTWARE PRODUCT is protected by copyright laws and international copyright treaties, as well as other intellectual property laws and treaties. The SOFTWARE PRODUCT is licensed, not sold.

1. GRANT OF LICENSE This EULA grants You the following rights:

(a) Software Installation and Use - For each license You acquire, You may have only one copy of the SOFTWARE PRODUCT installed.

(b) Storage/Network Use - The SOFTWARE PRODUCT may not be installed, accessed, displayed, run, shared or used concurrently on or from different computers, including a workstation, terminal or other digital electronic device ("Device"). In other words, if You have several workstations, You will have to acquire a license for each workstation where the SOFTWARE will be used.

(c) Backup Copy - You may make back-up copies of the SOFTWARE PRODUCT, but You may only have one copy per license installed at any given time. You may use the back-up copy solely for archival purposes. Except as expressly provided in this EULA, You may not otherwise make copies of the SOFTWARE PRODUCT, including the printed materials accompanying the SOFTWARE.

2. DESCRIPTION OF OTHER RIGHTS AND LIMITATIONS

(a) Limitations on Reverse Engineering, Decompilation and Disassembly - You may not reverse engineer, decompile, or disassemble the SOFTWARE PRODUCT, except and only to the extent that such activity is expressly permitted by applicable law notwithstanding this limitation. You may not make any changes or modifications to the Software, without the written permission of an officer of DSC. You may not remove any proprietary notices, marks or labels from the Software Product. You shall institute reasonable measures to ensure compliance with the terms and conditions of this EULA.

(b) Separation of Components - The SOFTWARE PRODUCT is licensed as a single product. Its component parts may not be separated for use on more than one HARDWARE unit.

(c) Single INTEGRATED PRODUCT - If You acquired this SOFTWARE with HARDWARE, then the SOFTWARE PRODUCT is licensed with the HARDWARE as a single integrated product. In this case, the SOFTWARE PRODUCT may only be used with the HARDWARE as set forth in this EULA.

(d) Rental - You may not rent, lease or lend the SOFTWARE PRODUCT. You may not make it available to others or post it on a server or web site.

(e) Software Product Transfer - You may transfer all of Your rights under this EULA only as part of a permanent sale or transfer of the HARDWARE, provided You retain no copies, You transfer all of the SOFTWARE PRODUCT (including all component parts, the media and printed materials, any upgrades and this EULA), and provided the recipient agrees to the terms of this EULA. If the SOFTWARE PRODUCT is an upgrade, any transfer must also include all prior versions of the SOFTWARE PRODUCT.

(f) Termination - Without prejudice to any other rights, DSC may terminate this EULA if You fail to comply with the terms and conditions of this EULA. In such event, You must destroy all copies of the SOFTWARE PRODUCT and all of its component parts.

(g) Trademarks - This EULA does not grant You any rights in connection with any trademarks or service marks of DSC or its suppliers.

3. COPYRIGHT

All title and intellectual property rights in and to the SOFTWARE PRODUCT (including but not limited to any images, photographs, and text incorporated into the SOFTWARE PRODUCT), the accompanying printed materials, and any copies of the SOFTWARE PRODUCT, are owned by DSC or its suppliers. You may not copy the printed materials accompanying the SOFTWARE PRODUCT. All title and intellectual property rights in and to the content which may be accessed through use of the SOFTWARE PRODUCT are the property of the respective content owner and may be protected by applicable copyright or other intellectual property laws and treaties. This EULA grants You no rights to use such content. All rights not expressly granted under this EULA are reserved by DSC and its suppliers.

4. EXPORT RESTRICTIONS

You agree that You will not export or re-export the SOFTWARE PRODUCT to any country, person, or entity subject to Canadian export restrictions.

5. CHOICE OF LAW

This Software License Agreement is governed by the laws of the Province of Ontario, Canada.

6. ARBITRATION

All disputes arising in connection with this Agreement shall be determined by final and binding arbitration in accordance with the Arbitration Act, and the parties agree to be bound by the arbitrator's decision. The place of arbitration shall be Toronto, Canada, and the language of the arbitration shall be English.

7. LIMITED WARRANTY

(a) NO WARRANTY - DSC PROVIDES THE SOFTWARE "AS IS" WITHOUT WARRANTY. DSC DOES NOT WARRANT THAT THE SOFTWARE WILL MEET YOUR REQUIREMENTS OR THAT OPERATION OF THE SOFTWARE WILL BE UNINTERRUPTED OR ERROR-FREE.

(b) CHANGES IN OPERATING ENVIRONMENT - DSC shall not be responsible for problems caused by changes in the operating characteristics of the HARDWARE, or for problems in the interaction of the SOFTWARE PRODUCT with non-DSC-SOFTWARE or HARDWARE PRODUCTS.

(c) LIMITATION OF LIABILITY; WARRANTY REFLECTS ALLOCATION OF RISK - IN ANY EVENT, IF ANY STATUTE IMPLIES WARRANTIES OR CONDITIONS NOT STATED IN THIS LICENSE AGREEMENT, DSC'S ENTIRE LIABILITY UNDER ANY PROVISION OF THIS LICENSE AGREEMENT SHALL BE LIMITED TO THE GREATER OF THE AMOUNT ACTUALLY PAID BY YOU TO LICENSE THE SOFTWARE PRODUCT AND FIVE CANADIAN DOLLARS (CAD\$5.00). BECAUSE SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OR LIMITATION OF LIABILITY FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES, THE ABOVE LIMITATION MAY NOT APPLY TO YOU.

(d) DISCLAIMER OF WARRANTIES - THIS WARRANTY CONTAINS THE ENTIRE WARRANTY AND SHALL BE IN LIEU OF ANY AND ALL OTHER WARRANTIES, WHETHER EXPRESSED OR IMPLIED (INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE) AND OF ALL OTHER OBLIGATIONS OR LIABILITIES ON THE PART OF DSC. DSC MAKES NO OTHER WARRANTIES. DSC NEITHER ASSUMES NOR AUTHORIZES ANY OTHER PERSON PURPORTING TO ACT ON ITS BEHALF TO MODIFY OR TO CHANGE THIS WARRANTY, NOR TO ASSUME FOR IT ANY OTHER WARRANTY OR LIABILITY CONCERNING THIS SOFTWARE PRODUCT.

(e) EXCLUSIVE REMEDY AND LIMITATION OF WARRANTY - UNDER NO CIRCUMSTANCES SHALL DSC BE LIABLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL OR INDIRECT DAMAGES BASED UPON BREACH OF WARRANTY, BREACH OF CONTRACT, NEGLIGENCE, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY. SUCH DAMAGES INCLUDE, BUT ARE

NOT LIMITED TO, LOSS OF PROFITS, LOSS OF THE SOFTWARE PRODUCT OR ANY ASSOCIATED EQUIPMENT, COST OF CAPITAL, COST OF SUBSTITUTE OR REPLACEMENT EQUIPMENT, FACILITIES OR SERVICES, DOWN TIME, PURCHASERS TIME, THE CLAIMS OF THIRD PARTIES, INCLUDING CUSTOMERS, AND INJURY TO PROPERTY.

WARNING: DSC recommends that the entire system be completely tested on a regular basis. However, despite frequent testing, and due to, but not limited to, criminal tampering or electrical disruption, it is possible for this SOFTWARE PRODUCT to fail to perform as expected.

Always ensure you obtain the latest version of the User Guide. Updated versions of this User Guide are available by contacting your distributor.

© 2021 Johnson Controls. All rights reserved. JOHNSON CONTROLS, and DSC are trademarks and/or registered trademarks. Unauthorized use is strictly prohibited.

This Class B digital apparatus complies with Canadian ICES-003. This device complies with RSS-247 of Industry Canada. Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device. Cet appareil numérique de la classe B est conforme à la norme NMB- 003 du Canada. Ce dispositif satisfait aux exigences d'Industrie Canada, prescrites dans le document CNR-247. son utilisation est autorisée seulement aux conditions suivantes: (1) il ne doit pas produire de brouillage et (2) l'utilisateur du dispositif doit être prêt à accepter tout brouillage radioélectrique reçu, même si ce brouillage est susceptible de compromettre le fonctionnement du dispositif.

www.dsc.com

Tech. Support: 1-800-387-3630 (Canada) 905-760-3000 (US)

PG9350SL user manual D-308404 29011055R001 Rev 0 (05/21)

29011055R001