

RADIO TEST REPORT

Report ID:

REP138332

Project number:

PRJ0090598

Type of assessment:

Limited Modular approval

Type of radio equipment:

Spread Spectrum/Digital Device (902–928 MHz)

Equipment class:

FHSS - frequency hopping spread spectrum

Applicant:

Tyco Safety Products Canada Ltd.

Model / HVIN:

PGPDC9

FCC identifier:

FCC ID: F5325PGPDC9

ISED certification number:

IC: 160A-PGPDC9

Specifications:

- ◆ FCC 47 CFR Part 15 Subpart C, §15.247
- ◆ RSS-247, Issue 4, July 2024, Section 6

Date of issue: March 4, 2026

Dishant Champaneri, EMC/RF Specialist


Tested by



Signature

Alvin Liu, EMC/RF Specialist

Tested by



Signature

Andrey Adelberg, Senior EMC/RF Specialist

Reviewed by



Signature

Nemko Canada Inc., a testing laboratory, is accredited by ANSI National Accreditation Board (ANAB).

The tests included in this report are within the scope of this accreditation.

The ANAB symbol is an official symbol of the ANSI National Accreditation Board, used under licence.

ANAB File Number: AT-3195 (Ottawa); AT-3193 (Pointe-Claire); AT-3194 (Cambridge)

Lab locations

Company name	Nemko Canada Inc.
Facilities	Ottawa site: 303 River Road, Ottawa, ON, Canada, K1V 1H2 Tel: +1 613 737 9680 Test site registration number: CA2040 Montréal site: 292 Labrosse Avenue, Pointe-Claire, QC, Canada, H9R 5L8 Tel: +1 514 694 2684 Test site registration number: CA2041 Cambridge site: 1-130 Saltsman Drive, Cambridge, ON, Canada, N3E 0B2 Tel: +1 519 650 4811 Test site registration number: CA0101
Website	www.nemko.com

Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Copyright notification

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

© Nemko Canada Inc.

Table of Contents

Table of Contents	3
Section 1 Report summary	4
1.1 Test specifications	4
1.2 Test methods	4
1.3 Exclusions	4
1.4 Statement of compliance	4
1.5 Test report revision history	4
Section 2 Engineering considerations	5
2.1 Modifications incorporated in the EUT for compliance	5
2.2 Technical judgment	5
2.3 Model variant declaration	5
2.4 Deviations from laboratory tests procedures	5
Section 3 Test conditions	6
3.1 Atmospheric conditions	6
3.2 Power supply range	6
Section 4 Information provided by the applicant	7
4.1 Disclaimer	7
4.2 Applicant / Manufacturer	7
4.3 EUT information	7
4.4 Radio technical information	8
4.5 EUT setup details	8
Section 5 Summary of test results	9
5.1 Testing period	9
5.2 Sample information	9
5.3 FCC test results	9
5.4 ISED test results	9
Section 6 Test equipment	10
6.1 Test equipment list	10
Section 7 Testing data	11
7.1 Variation of power source	11
7.2 Number of frequencies	12
7.3 Antenna requirement	14
7.4 AC power line conducted emissions limits	15
7.5 Frequency Hopping Systems requirements, 900 MHz operation	18
7.6 Transmitter output power and e.i.r.p. requirements for FHSS 900 MHz	25
7.7 Spurious (out-of-band) unwanted emissions	27
Section 8 Test setup diagrams	32
8.1 Radiated emissions set-up for frequencies below 1 GHz	32
8.2 Radiated emissions set-up for frequencies above 1 GHz	32
8.3 AC mains conducted emissions set-up	33

Section 1 Report summary

1.1 Test specifications

FCC 47 CFR Part 15, Subpart C, Clause 15.247	Operation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz
RSS-247, Issue 4, July 2025, Section 6	Requirements for frequency hopping systems, digital transmission systems and hybrid systems operating in the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz

1.2 Test methods

558074 D01 15.247 Meas Guidance v05r02 (April 2, 2019)	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules.
RSS-Gen, Issue 5, February 2021	General Requirements for Compliance of Radio Apparatus
ANSI C63.10:2020/Cor.1:2023+C63.10a-2024	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

1.3 Exclusions

None

1.4 Statement of compliance

Statement of Conformity:

The reported results have been evaluated against the specified limits of the standard(s) listed in **Section 1.1** of this report.

Conformity with the specified requirements is determined by comparing the measured results directly to the applicable limits. Measurement uncertainty is not applied to adjust or attribute to the measured value for the purpose of compliance determination.

In the configuration tested, the **Equipment Under Test (EUT)** was found to be compliant. Unless otherwise noted in **Section 1.3**, all testing was performed against the relevant requirements of the applicable test standard(s).

The results obtained indicate that the product under test complies in full with the requirements tested, and the test results relate only to the items tested.

Refer to the **Summary of Test Results** section for full details.

1.5 Test report revision history

Table 1.5-1: Test report revision history

Revision #	Date of issue	Details of changes made to test report
REP138332	March 4, 2026	Original report issued

Section 2 Engineering considerations

2.1 Modifications incorporated in the EUT for compliance

There were no modifications performed to the EUT during this assessment.

2.2 Technical judgment

EUT (PGPDC9) board has two separate antennas for each polarization. ANT0 was transmitted using Horizontal polarization and ANT1 using Vertical polarization. All tests were performed using both antennas in turn

2.3 Model variant declaration

There were no model variants declared by the applicant.

2.4 Deviations from laboratory tests procedures

No deviations were made from laboratory procedures.

Section 3 Test conditions

3.1 Atmospheric conditions

Temperature	15 °C – 35 °C
Relative humidity	20 % – 75 %
Air pressure	86 kPa (860 mbar) – 106 kPa (1060 mbar)

When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.

3.2 Power supply range

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages $\pm 5\%$, for which the equipment was designed.

Section 4 Information provided by the applicant

4.1 Disclaimer

This section contains information provided by the applicant and has been utilized to support the test plan. Inaccurate information provided by the applicant can affect the validity of the results contained within this test report. Nemko accepts no responsibility for the information contained within this section and the impact it may have on the test plan and resulting measurements.

4.2 Applicant / Manufacturer

Applicant name	Tyco Safety Products Canada Ltd.
Applicant address	3301 Langstaff Rd., Concord, ON L4K 4L2 Canada
Manufacturer name	Same as applicant
Manufacturer address	Same as applicant

4.3 EUT information

Product description	Wireless Alarm Transceiver
Model / HVIN	PGPDC9
Part number	PGPDC9
Power supply requirements	Host system 12 V(DC)
Hardware revision	UA778 Rev. 01
Software details	SW Ver. 2.10/PowerG 3.10
Product description and theory of operation	The PGPDC9 is a PowerG wireless transceiver module that connects to the communication bus of the NEO R panels (CORBUS) and allows wireless fire and intrusion initiating devices to send alarms to the main control panel. It is mounted in the host alarm panel plastic enclosure HSC202x and it works with models HS2128R, HS2064R, HS2032R and HS2016R. It operates in the band 912.75 – 919.106MHz. To be certified as a limited modular type approval

4.4 Radio technical information

Category of Wideband Data Transmission equipment	Frequency Hopping Spread Spectrum (FHSS) equipment	
Frequency band	902–928 MHz	
Frequency Min	912.75 MHz	
Frequency Max	919.106 MHz	
Measured BW, 99% OBW	ANT0: 75.5 kHz ANT1: 69.8 kHz	
Type of modulation	FSK/GFSK	
Transmitter spurious	ANT0: 56.6 (Peak), 2738.50 MHz ANT1: 55.9 (Peak), 2757.50 MHz	
Antenna information	ANT0	ANT1
	<i>Manufacturer:</i>	Ocean Spring
	<i>Model number:</i>	20-9154-10008
	<i>Type:</i>	Helical
	<i>Connector type:</i>	Soldering
	<i>Peak/Max Gain:</i>	0.8 dBi

4.5 EUT setup details

4.5.1 Radio exercise details

Operating conditions	The EUT was powered by compatible host using CORBUS and was preloaded with the test script to transmit continuously at low and high channel with max power.
Transmitter state	Transmitter set into continuous mode.

4.5.2 EUT setup configuration




Figure 4.5-1: Radiated testing block diagram

Section 5 Summary of test results

5.1 Testing period

Test start date	November 26, 2025	Test end date	November 28, 2025
-----------------	-------------------	---------------	-------------------

5.2 Sample information

Receipt date	October 30, 2025	Nemko sample ID number(s)	PRJ00905980001
--------------	------------------	---------------------------	----------------

5.3 FCC test results

Table 5.3-1: FCC requirements results

Part	Test description	Verdict
Generic requirements		
§15.207(a)	Conducted limits	Pass
§15.31(e)	Variation of power source	Pass
§15.31(m)	Number of tested frequencies	Pass
§15.203	Antenna requirement	Pass
§15.247(c)(1)	Fixed point-to-point operation with directional antenna gains greater than 6 dBi	Not applicable
§15.247(d)	Spurious emissions	Pass
§15.247(f)	Time of occupancy for hybrid systems	Not applicable
FHSS specific requirements		
§15.247(a)(1)(i)	Requirements for operation in the 902–928 MHz band	Pass
§15.247(b)(2)	Maximum peak output power in the 902–928 MHz band	Pass

Notes: None

5.4 ISED test results

Table 5.4-1: ISED requirements results

Part	Test description	Verdict
Generic requirements		
RSS-Gen, 7.3	Receiver radiated emission limits	Not applicable ¹
RSS-Gen, 7.4	Receiver conducted emission limits	Not applicable ¹
RSS-Gen, 6.9	Operating bands and selection of test frequencies	Pass
RSS-Gen, 8.8	AC powerline conducted emissions limits	Pass
RSS-247, 6.6	Unwanted emissions	Pass
FHSS specific requirements		
RSS-247, 6.2.1 (b)	Hopping channel carrier frequency separation	Pass
RSS-247, 6.2.2.1	Number of hopping channels, dwell time and occupied channel bandwidth in the 902–928 MHz band	Pass
RSS-247, 6.2.2.2	Transmitter output power and e.i.r.p. requirements in the 902–928 MHz band	Pass

Notes: ¹According to sections 5.2 and 5.3 of RSS-Gen, Issue 5 the EUT does not have a stand-alone receiver neither scanner receiver, therefore exempt from receiver requirements.

Section 6 Test equipment

6.1 Test equipment list

Table 6.1-1: Equipment list

Equipment	Manufacturer	Model no.	Asset no.	Cal./Ver. cycle	Next cal./ver.
3 m EMI test chamber	TDK	SAC-3	FA003012	1 year	March 9, 2026
Flush mount turntable	SUNAR	FM2022	FA003006	—	NCR
Controller	SUNAR	SC110V	FA002976	—	NCR
Antenna mast	SUNAR	TLT2	FA003007	—	NCR
Receiver/spectrum analyzer	Rohde & Schwarz	ESR26	101833	2 years	December 19, 2025
Bilog antenna (30–2000 MHz)	Sunol	JB3	FA002108	1 year	April 8, 2026
Horn antenna (1–18 GHz)	EMCO	3115	FA000649	1 year	April 16, 2026
Preamplifier (1–18 GHz)	ETS Lindgren	124334	FA002956	1 year	April 11, 2026
High pass filter (1.2–12 GHz)	Microwave circuits	H1G212G1	FA003031	—	NCR
50 Ω coax cable	Huber + Suhner	None	FA003047	1 year	Aug 06, 2026
50 Ω coax cable	Huber + Suhner	None	FA003402	1 year	Aug 06, 2026
50 Ω SMA coax cable	Huber + Suhner	None	FA003056	1 year	Aug 06, 2026
Spectrum analyzer	Rohde & Schwarz	FSW43	FA002971	1 year	November 30, 2025

Note: NCR - no calibration required

All equipment related to the contribution of measurement has been included in this list. Such items include, but are not limited to, cables, attenuators, directional couplers, and pre-amplifiers.

Table 6.1-2: Automation software details

Test description	Manufacturer of Software	Details
EMC/Radio test software	Rohde & Schwarz	EMC32, Software for EMC Measurements, Version 10.60.00

Table 6.1-3: Measurement uncertainty calculations based on equipment list

Measurement	Measurement uncertainty, ±dB
AC power line conducted emissions	2.4
Radiated spurious emissions (30 MHz to 1 GHz)	5.4
Radiated spurious emissions (1 GHz to 6 GHz)	5.1
Radiated spurious emissions (6 GHz to 18 GHz)	5.3
Occupied bandwidth	1.5%
Signal path calibration (Insertion loss)	1.38
Notes:	UKAS Lab 34, TIA-603 and ETSI TR 100 028-1&2 have been used as guidance for measurement uncertainty reasonable estimations with regards to previous experience and validation of data. Nemko Canada Inc. follows these test methods in order to satisfy ISO/IEC 17025 requirements for estimation of uncertainty of measurement for wireless products. Measurement uncertainty calculations assume a coverage factor of K = 2 with 95% certainty.

Section 7 Testing data

7.1 Variation of power source

7.1.1 References, definitions and limits

FCC §15.31 (e):

For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

7.1.2 Test summary

Verdict	Pass
Test date	November 27, 2025
Tested by	Alvin Liu
Test location	Cambridge

7.1.3 Observations, settings and special notes

The testing was performed as per ANSI C63.10 Section 5.13.

- Where the device is intended to be powered from an external power adapter, the voltage variations shall be applied to the input of the adapter provided with the device at the time of sale. If the device is not marketed or sold with a specific adapter, then a typical power adapter shall be used.
- For devices, where operating at a supply voltage deviating $\pm 15\%$ from the nominal rated value may cause damages or loss of intended function, test to minimum and maximum allowable voltage per manufacturer's specification and document in the report.
- For devices with wide range of rated supply voltage, test at 15% below the lowest and 15% above the highest declared nominal rated supply voltage.
- For devices obtaining power from an input/output (I/O) port (USB, firewire, etc.), a test jig is necessary to apply voltage variation to the device from a support power supply, while maintaining the functionalities of the device.
- For battery-operated equipment, the equipment tests shall be performed using a variable power supply.

7.1.4 Test data

- EUT Power Source Type: AC Mains Powered (including external AC/DC adapter)
- No noticeable output power variation observed

7.2 Number of frequencies

7.2.1 References, definitions and limits

FCC §15.31:

- (m) Measurements on intentional radiators or receivers shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table.

RSS-Gen, Clause 6.9:

Except where otherwise specified, measurements shall be performed for each frequency band of operation for which the radio apparatus is to be certified, with the device operating at the frequencies in each band of operation shown in table below. The frequencies selected for measurements shall be reported in the test report.

Table 7.2-1: Frequency Range of Operation

Frequency range over which the device operates (in each band)	Number of test frequencies required	Location of measurement frequency inside the operating frequency range
1 MHz or less	1	Center (middle of the band)
1–10 MHz	2	1 near high end, 1 near low end
Greater than 10 MHz	3	1 near high end, 1 near center and 1 near low end

Notes: “near” means as close as possible to or at the centre / low end / high end of the frequency range over which the device operates.

7.2.2 Test summary

Verdict	Pass
Test date	November 27, 2025
Tested by	Alvin Liu
Test location	Cambridge

7.2.3 Observations, settings and special notes

ANSI C63.10, Clause 5.6.2.1:

The number of channels tested can be reduced by measuring the center channel bandwidth first and then applying the following relaxations as appropriate:

- For each operating mode, if the measured channel bandwidth on the middle channel is at least 150% of the minimum permitted bandwidth, then it is not necessary to measure the bandwidth on the high and low channels.
- For multiple-input multiple-output (MIMO) systems, if the measured channel bandwidth on testing the middle channel exceeds the minimum permitted bandwidth by more than 50% on one transmit chain, then it is not necessary to repeat testing on the other chains.
- If the measured channel bandwidth on the middle channel is less than 50% of the maximum permitted bandwidth, then it is not necessary to measure the bandwidth on the high and low channels.

ANSI C63.10, Clause 5.6.2.2:

For devices with multiple operating modes, measurements on the middle channel can be used to determine the worst-case mode(s). The worst-case modes are as follows:

- Band edge requirements—Measurements on the mode with the widest bandwidth can be used to cover the same channel (center frequency) on modes with narrower bandwidth that have the same or lower output power for each modulation family (e.g., OFDM and direct sequence spread spectrum).
- Spurious emissions—Measure the mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum).
- In-band PSD—Measurements on the mode with the narrowest bandwidth can be used to cover all modes within the same modulation family of an equal or lower output power provided the result is less than 50% of the limit.

7.2.4 Test data

Table 7.2-2: *Test channels selection*

Start of Frequency range, MHz	End of Frequency range, MHz	Frequency range bandwidth, MHz	Low channel, MHz	High channel, MHz
912.750	919.106	6.606	912.750	919.106

7.3 Antenna requirement

7.3.1 References, definitions and limits

FCC §15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

FCC §15.247:

- (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:
- (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

RSS-Gen, Clause 6.8:

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report.

7.3.2 Test summary

Verdict	Pass
Test date	November 27, 2025
Tested by	Alvin Liu
Test location	Cambridge

7.3.3 Observations, settings and special notes

None

7.3.4 Test data

Does the EUT have detachable antenna(s)? ☒ NO ☐ YES

Table 7.3-1: Antenna information

Antenna	Antenna type	Manufacturer	Model number	Maximum gain	Connector type
ANT0 (Horizontal)	Helical	Ocean spring	20-9154-10008	0.80 dBi	PCB soldered
ANT1 (Vertical)	Helical	Ocean spring	20-9154-10008	2.89 dBi	PCB soldered

7.4 AC power line conducted emissions limits

7.4.1 References, definitions and limits

FCC §15.207:

- (a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

ANSI C63.10, Clause 6.2:

If the EUT normally receives power from another device that in turn connects to the public utility ac power lines, measurements shall be made on that device with the EUT in operation to demonstrate that the device continues to comply with the appropriate limits while providing the EUT with power. If the EUT is operated only from internal or dedicated batteries, with no provisions for connection to the public utility ac power lines (600 VAC or less) to operate the EUT (such as an adapter), then ac power-line conducted measurements are not required.

For direct current (dc) powered devices where the ac power adapter is not supplied with the device, an “off-the-shelf” unmodified ac power adapter shall be used. If the device is supposed to be installed in a host (e.g., the device is a module or PC card), then it is tested in a typical compliant host.

RSS-Gen, Clause 8.8:

A radio apparatus that is designed to be connected to the public utility (AC) power line shall ensure that the radio frequency voltage, which is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz, shall not exceed the limits in table below.

Unless the requirements applicable to a given device state otherwise, for any radio apparatus equipped to operate from the public utility AC power supply either directly or indirectly (such as with a battery charger), the radio frequency voltage of emissions conducted back onto the AC power lines in the frequency range of 0.15 MHz to 30 MHz shall not exceed the limits shown in table below. The more stringent limit applies at the frequency range boundaries.

Table 7.4-1: Conducted emissions limit

Frequency of emission, MHz	Conducted emissions limit, dB μ V	
	Quasi-peak	Average**
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

Notes: * - The level decreases linearly with the logarithm of the frequency.
 ** - A linear average detector is required.

7.4.2 Test summary

Verdict	Pass		
Test date	October 29, 2025	Temperature	23 °C
Tested by	Dishant Champaneri	Air pressure	980 mbar
Test location	Cambridge	Relative humidity	33 %


7.4.3 Observations, settings and special notes

Port under test – Coupling device	AC mains power port of AC/DC adapter – Artificial Mains Network (AMN)
EUT power input during test	120 V _{AC} , 60 Hz
EUT setup configuration	Table top
Measurement details	A preview measurement was generated with the receiver in continuous scan mode. Emissions detected within 10 dB or above the limit were re-measured with the appropriate detector against the correlating limit and recorded as the final measurement.
Additional notes:	– The EUT was set up as tabletop configuration per ANSI C63.10:2020/Cor.1:2023 measurement procedure. – The spectral scan has been corrected with transducer factors (i.e. cable loss, LISN factors, and attenuators) for determination of compliance. Correction factor (dB) = LISN factor IL (dB) + cable loss (dB) + attenuator (dB) – Emissions that were continuously present for a minimum of 1 second and occurred more than once for every 15 seconds observation period were considered valid emissions. The maximum value of valid emissions has been recorded.


Receiver settings:

Resolution bandwidth	9 kHz
Video bandwidth	30 kHz
Detector mode	Peak and Average (Preview), Quasi-peak and CAverage (Final)
Trace mode	Max Hold
Measurement time	100 ms (Preview), 160 ms (Final)

7.4.4 Test data



Plot 7.4-1: *Conducted emissions on phase line*



Plot 7.4-2: *Conducted emissions on neutral line*

7.5 Frequency Hopping Systems requirements, 900 MHz operation

7.5.1 References, definitions and limits

FCC §15.247:

- (a) Operation under the provisions of this Section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:
- (1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.
- (i) For frequency hopping systems operating in the 902–928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- (f) For the purposes of this section, hybrid systems are those that employ a combination of both frequency hopping and digital modulation techniques. The frequency hopping operation of the hybrid system, with the direct sequence or digital modulation operation turned-off, shall have an average time of occupancy on any frequency not to exceed 0.4 seconds within a time period in seconds equal to the number of hopping frequencies employed multiplied by 0.4. The power spectral density conducted from the intentional radiator to the antenna due to the digital modulation operation of the hybrid system, with the frequency hopping operation turned off, shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

RSS-247, Clause 6.2.1:

- a. The bandwidth of a frequency hopping channel is the 20 dB emission bandwidth, measured with the hopping stopped. The system's RF bandwidth is equal to the channel bandwidth multiplied by the number of channels in the hopset. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.
 - b. The hopping channel carrier frequencies shall be separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
- 6.2.2.1 The following bandwidth and hopping channel requirements shall apply:
- a. the maximum 20 dB bandwidth of the hopping channel shall be 500 kHz.
 - b. if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping channels and the average time of occupancy on any channel shall not be greater than 0.4 s within a 20 s period.
 - c. if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping channels and the average time of occupancy on any channel shall not be greater than 0.4 s within a 10 s period.

RSS-247, Clause 6.4:

Hybrid systems employ a combination of both frequency hopping and digital transmission techniques and shall comply with the following:

- b. With the digital transmission operation of the hybrid system turned off, the frequency hopping operation shall have an average time of occupancy on any frequency not exceeding 0.4 seconds within a duration in seconds equal to the number of hopping frequencies multiplied by 0.4.
- c. hybrid systems shall have a true frequency hopping system, as set out in sections 6.2.1 a) and 6.2.1 b). The hybrid systems shall comply with:
 - i. the minimum channel separation,
 - ii. the pseudo-random hop sequence, andthe receiver matching bandwidth and synchronization.

7.5.2 Test summary

Verdict	Pass		
Test date	November 27, 2025	Temperature	23 °C
Tested by	Alvin Liu	Air pressure	975 mbar
Test location	Cambridge	Relative humidity	26 %

7.5.3 Observations, settings and special notes

Carrier frequency separation was tested per ANSI C63.10 subclause 7.8.2. Spectrum analyser settings:

Resolution bandwidth	Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
Video bandwidth	≥ RBW
Frequency span	Wide enough to capture the peaks of two adjacent channels
Detector mode	Peak
Trace mode	Max Hold

Number of hopping frequencies was tested per ANSI C63.10 subclause 7.8.3. Spectrum analyser settings:

Resolution bandwidth	To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
Video bandwidth	≥ RBW
Frequency span	The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
Detector mode	Peak
Trace mode	Max Hold

Time of occupancy (dwell time) was tested per ANSI C63.10 subclause 7.8.4. Spectrum analyser settings:

Resolution bandwidth	shall be ≤ channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected dwell time per channel.
Video bandwidth	≥ RBW
Frequency span	Zero span, centered on a hopping channel.
Detector mode	Peak
Trace mode	Max Hold

20 dB bandwidth was tested per ANSI C63.10 subclause 6.9.2. Spectrum analyser settings:

Resolution bandwidth	≥ 1–5% of the 20 dB bandwidth
Video bandwidth	≥ RBW
Frequency span	approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel
Detector mode	Peak
Trace mode	Max Hold

7.5.4 Test data

Table 7.5-1: 20 dB bandwidth results

Antenna	Frequency, MHz	20 dB bandwidth, kHz	Maximum limit, kHz	Margin, kHz
ANT0 (Horizontal)	912.7	96.8	500.0	403.2
ANT0 (Horizontal)	919.1	83.4	500.0	416.6
ANT1 (Vertical)	912.7	95.8	500.0	404.2
ANT1 (Vertical)	919.1	82.4	500.0	417.6

Table 7.5-2: 99% occupied bandwidth results

Antenna	Frequency, MHz	99% occupied bandwidth, kHz
ANT0 (Horizontal)	912.7	75.5
ANT0 (Horizontal)	919.1	70.9
ANT1 (Vertical)	912.7	68.7
ANT1 (Vertical)	919.1	69.8

Notes: There is no 99% occupied bandwidth limit in the standard's requirements the measurement results provided for information purposes only.

Table 7.5-3: Carrier frequency separation results

Antenna	Carrier frequency separation, kHz	Minimum limit, kHz	Margin, kHz
ANT0 (Horizontal)	129.7	96.8	32.9
ANT1 (Vertical)	130.1	95.8	34.3

Table 7.5-4: Number of hopping frequencies results

Antenna	Number of hopping frequencies	Minimum limit	Margin
ANT0 (Horizontal)	50	50	0
ANT1 (Vertical)	50	50	0

Table 7.5-5: Average time of occupancy results

Dwell time of each pulse, ms	Number of pulses within period	Total dwell time within period, ms	Limit, ms	Margin, ms
99.3	4	397.2	400	2.8

Notes: Measurement Period is 20 s

Test data, continued




Figure 7.5-1: 20 dB bandwidth on low channel ANTO (H)




Figure 7.5-2: 20 dB bandwidth on high channel ANTO (H)




Figure 7.5-3: 20 dB bandwidth on low channel ANT1 (V)






Figure 7.5-4: 20 dB bandwidth on high channel ANT1 (V)

Test data, continued




Date: 28 NOV 2025 11:00:07

Figure 7.5-5: 99% occupied bandwidth on low channel ANTO (H)




Date: 28 NOV 2025 10:53:33

Figure 7.5-6: 99% occupied bandwidth on high channel ANTO (H)



Date: 28 NOV 2025 10:22:58


Figure 7.5-7: 99% occupied bandwidth on low channel ANT1 (V)



Date: 28 NOV 2025 10:42:21

Figure 7.5-8: 99% occupied bandwidth on high channel ANT1 (V)

Test data, continued




Date: 27.NOV.2025 17:21:45

Figure 7.5-9: Carrier frequency separation ANT0 (H)




Date: 27.NOV.2025 17:26:54

Figure 7.5-10: Carrier frequency separation ANT1 (V)



Date: 5.JAN.2026 12:39:16


Figure 7.5-11: Number of hopping channels ANT0 (H)



Date: 5.JAN.2026 12:50:40


Figure 7.5-12: Number of hopping channels ANT1 (V)

Test data, continued



Date: 5 JAN 2026 14:49:08

Figure 7.5-13: Dwell time (pulse width)



Date: 5 JAN 2026 14:51:53

Figure 7.5-14: Dwell time (number of pulses)

7.6 Transmitter output power and e.i.r.p. requirements for FHSS 900 MHz

7.6.1 References, definitions and limits

FCC §15.247:

- (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:
- (2) For frequency hopping systems operating in the 902–928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.
- (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

RSS-247, Clause 6.2.2.2:

The following transmitter output power and e.i.r.p. requirements shall apply:

- a. if the hopset uses 50 or more hopping channels, the maximum peak conducted output power shall not exceed 1.0 W, and the e.i.r.p. shall not exceed 4 W.
- b. if the hopset uses less than 50 hopping channels, the maximum peak conducted output power shall not exceed 0.25 W and the e.i.r.p. shall not exceed 1 W

7.6.2 Test summary

Verdict	Pass		
Test date	November 28, 2025	Temperature	23 °C
Tested by	Alvin Liu	Air pressure	975 mbar
Test location	Cambridge	Relative humidity	26 %

7.6.3 Observations, settings and special notes

Radiated testing was performed at a distance of 3 meters. Both antennas were evaluated in the vertical and horizontal planes, with only the worst-case values reported. Frequency hopping was disabled during this test. Spectrum analyser settings:

Resolution bandwidth	> 20 dB bandwidth of the emission being measured
Video bandwidth	≥ RBW
Frequency span	approximately 5 times the 20 dB bandwidth, centered on a hopping channel
Detector mode	Peak
Trace mode	Max Hold

7.6.4 Test data

Table 7.6-1: Output power and EIRP results

Antenna	Frequency, MHz	Measured field strength, dBμV/m	Converted EIRP, dBm	EIRP limit, dBm	Margin, dB	Antenna gain, dBi	Output power, dBm	Output power limit, dBm	EIRP margin, dB
ANT0 (H)	912.7	108.81	13.58	36.00	22.42	0.80	12.78	30.00	19.31
ANT0 (H)	919.1	110.66	15.43	36.00	20.57	0.80	14.63	30.00	17.46
ANT1 (V)	912.7	110.35	15.12	36.00	20.88	2.89	12.23	30.00	15.68
ANT1 (V)	919.1	110.14	14.91	36.00	21.09	2.89	12.02	30.00	15.89

Notes: EIRP = Measured field strength (at 3 m) – 95.23 dB. Output power = EIRP - Antenna gain.

Test data, continued




Figure 7.6-1: Output power on low channel ANTO (H)




Figure 7.6-2: Output power on high channel ANTO (H)




Figure 7.6-3: Output power on low channel ANT1 (V)




Figure 7.6-4: Output power on high channel ANT1 (V)

7.7 Spurious (out-of-band) unwanted emissions

7.7.1 References, definitions and limits

FCC §15.247:

- (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

RSS-247, Clause 6.6:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum device, digitally modulated device, or hybrid system is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power – based on either an RF conducted or a radiated measurement – provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 6.3.2, the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

RSS-Gen:

- 8.9 Except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table below.
- 8.10 Restricted frequency bands are designated primarily for safety-of-life services (distress calling and certain aeronautical activities), certain satellite downlinks, radio astronomy and some government uses. The following conditions related to the restricted frequency bands apply:
- a The transmit frequency, including fundamental components of modulation, of licence-exempt radio apparatus shall not fall within the restricted frequency bands.
 - b Unwanted emissions that fall into restricted frequency bands listed in table 7 shall comply with the limits specified in table below.
 - c Unwanted emissions that do not fall within the restricted frequency bands shall comply either with the limits specified in the applicable RSS or with those specified in table below.

Table 7.7-1: FCC §15.209 and RSS-Gen – Radiated emission limits

Frequency, MHz	Field strength of emissions		Measurement distance, m
	µV/m	dBµV/m	
0.009–0.490	2400/F	$67.6 - 20 \times \log_{10}(F)$	300
0.490–1.705	24000/F	$87.6 - 20 \times \log_{10}(F)$	30
1.705–30.0	30	29.5	30
30–88	100	40.0	3
88–216	150	43.5	3
216–960	200	46.0	3
above 960	500	54.0	3

Notes: In the emission table above, the tighter limit applies at the band edges.
 For frequencies above 1 GHz the limit on peak RF emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

References, definitions and limits, continued

Table 7.7-2: ISED restricted frequency bands

MHz	MHz	MHz	GHz
0.090–0.110	12.57675–12.57725	399.9–410	7.25–7.75
0.495–0.505	13.36–13.41	608–614	8.025–8.5
2.1735–2.1905	16.42–16.423	960–1427	9.0–9.2
3.020–3.026	16.69475–16.69525	1435–1626.5	9.3–9.5
4.125–4.128	16.80425–16.80475	1645.5–1646.5	10.6–12.7
4.17725–4.17775	25.5–25.67	1660–1710	13.25–13.4
4.20725–4.20775	37.5–38.25	1718.8–1722.2	14.47–14.5
5.677–5.683	73–74.6	2200–2300	15.35–16.2
6.215–6.218	74.8–75.2	2310–2390	17.7–21.4
6.26775–6.26825	108–138	2483.5–2500	22.01–23.12
6.31175–6.31225	149.9–150.05	2655–2900	23.6–24.0
8.291–8.294	156.52475–156.52525	3260–3267	31.2–31.8
8.362–8.366	156.7–156.9	3332–3339	36.43–36.5
8.37625–8.38675	162.0125–167.17	3345.8–3358	Above 38.6
8.41425–8.41475	167.72–173.2	3500–4400	
12.29–12.293	240–285	4500–5150	
12.51975–12.52025	322–335.4	5350–5460	

Note: Certain frequency bands listed in Table 7.7-2 and above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

Table 7.7-3: FCC restricted frequency bands

MHz	MHz	MHz	GHz
0.090–0.110	16.42–16.423	399.9–410	4.5–5.15
0.495–0.505	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225	123–138	2200–2300	14.47–14.5
8.291–8.294	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675	156.7–156.9	2690–2900	22.01–23.12
8.41425–8.41475	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025	240–285	3345.8–3358	36.43–36.5
12.57675–12.57725	322–335.4	3600–4400	Above 38.6
13.36–13.41			

7.7.2 Test summary

Verdict	Pass		
Test date	November 27, 2025	Temperature	23 °C
Tested by	Dishant Champaneri	Air pressure	975 mbar
Test location	Cambridge	Relative humidity	25 %

7.7.3 Observations, settings and special notes

- As part of the current assessment, the test range of 9 kHz to 10th harmonic has been fully considered and compared to the actual frequencies utilized within the EUT. Since the EUT contains a transmitter in the GHz range, the EUT has been deemed compliant without formal testing in the 9 kHz to 30 MHz test range, therefore formal test results (tabular data and/or plots) are not provided within this test report.
- Radiated measurements were performed at a distance of 3 m.
- DTS emissions in non-restricted frequency bands test was performed as per KDB 558074, section 8.5 with reference to ANSI C63.10 subclause 11.11.
- Since fundamental power was tested using the maximum peak conducted output power procedure to demonstrate compliance, the spurious emissions limit is –20 dBc/100 kHz.
- DTS emissions in restricted frequency bands test was performed as per KDB 558074, section 8.6 with reference to ANSI C63.10 subclause 11.12.
- FHSS emissions in restricted frequency bands test was performed with reference to ANSI C63.10 subclause 6.10.5.

Spectrum analyser settings for radiated measurements within restricted bands below 1 GHz:

Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Detector mode:	Peak
Trace mode:	Max Hold

Spectrum analyser settings for average radiated measurements within restricted bands above 1 GHz:

Method: 11.12.2.5.1 Trace average with continuous EUT transmission at full power

Resolution bandwidth:	1 MHz
Video bandwidth:	10 Hz
Detector mode:	RMS
Trace mode:	Average

7.7.4 Test data

Table 7.7-4: Radiated field strength measurement results

Channel	Frequency, MHz	Peak Field strength, dBμV/m		Margin, dB	Average Field strength, dBμV/m		Margin, dB
		Measured	Limit		Measured	Limit	
Low (ANT0)	2738.50	56.5	74.0	17.5	53.7	54.0	0.3
High (ANT0)	2757.50	56.0	74.0	18.0	53.8	54.0	0.2
Low (ANT1)	2738.50	55.4	74.0	18.6	53.9	54.0	0.1
High (ANT1)	2757.50	55.9	74.0	18.1	53.9	54.0	0.1

Notes: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.

Test Data, continued




Figure 7.7-1: Radiated spurious emissions on low channel ANT0 (H) 30 – 1000 MHz




Figure 7.7-2: Radiated spurious emissions on Low channel ANT0 (H) 1 – 10 GHz




Figure 7.7-3: Radiated spurious emissions on high channel ANT0 (H) 30 – 1000 MHz




Figure 7.7-4: Radiated spurious emissions on high channel ANT0 (H) 1 – 10 GHz

Test Data, continued




Figure 7.7-5: Radiated spurious emissions on low channel ANT1 (V) 30 – 1000 MHz




Figure 7.7-6: Radiated spurious emissions on low channel ANT1 (V) 1 – 10 GHz




Figure 7.7-7: Radiated spurious emissions on high channel ANT1 (V) 30 – 1000 MHz






Figure 7.7-8: Radiated spurious emissions on high channel ANT1 (V) 1 – 10 GHz

Section 8 Test setup diagrams


8.1 Radiated emissions set-up for frequencies below 1 GHz



8.2 Radiated emissions set-up for frequencies above 1 GHz



8.3 AC mains conducted emissions set-up



End of the test report