

TDK EMC CENTER CHIKUMAGAWA OPEN SITE

543 OTAI SAKU-CITY NAGANO JAPAN

REPORT OF MEASUREMENTS ON DIGITAL DEVICE

Date : June 13 ,2002


Issued in : Saku-city , JAPAN

TDK APPLICATION No.: TDC-02-0606(1)

1. Applicant : FUJI PHOTO FILM CO. , LTD.
13-45 , SENZUI 3 - CHOME , ASAKA - SHI , SAITAMA
351 - 8585 JAPAN
2. Factory : FUJIFILM PHOTONIX CO. , LTD.
1 - 6 , MATSUZAKADAIRA TAIWA - CHO ,
KUROKAWA - GUN , MIYAGI - KEN , 981 - 3492 JAPAN
FUJIFILM IMAGING SYSTEMS(SUZHOU) CO. , LTD.
138 Chang Jiang Road , New District , Jiangsu
16 Lingyan Road , New District , Jiangsu
3. Description of Equipment Under Test (EUT)
- 3-1. EUT : DIGITAL CAMERA
- 3-2. Category : FCC Class B Digital Device
- 3-3. FCC ID No. : F5GFP - 3800
- 3-4. Trade Name : FUJIFILM
- 3-5. Model No. : Fine Pix 3800
- 3-6. Serial No. : RUR00373
- 3-7. Date of Manufacture : June ,2002
- 3-8. Power Supply : 120 V AC , 60Hz
4. Regulation Applied : FCC Part 15 Subpart B CLASS B 3m
5. Measurement Procedure Used : FCC Part 15 Subpart B CLASS B 3m
6. Place of Measurement : TDK EMC CENTER CHIKUMAGAWA OPEN SITE
7. Date of Measurement : June 11 ,2002
8. Measurement Results : The test results show that EUT conform to regulations
applied as shown in the attached sheets.

Note : (1) The test results relate only to items tested.

(2) This report shall not be reproduced except in full without the written approval of testing laboratory.


Nobuyuki Ono

Chief of TDK CHIKUMAGAWA OPEN SITE

Phone : 047-378-9470

FAX : 047-378-9780

TDK Application No. : TDC-02-0606(1)

MEASUREMENT RESULTS OF RADIATED RADIO NOISE at 3m

Date : June 11, 2002

Temp. : 20 °C ; Humi. : 50 %

Test Receiver :	Rohde & Schwarz ESCS 30	
Operation Mode :	Detector function : CISPR Quasi-Peak	
	6dB Band width : 120kHz	External Attenuator : none

Description of Equipment DIGITAL CAMERA

Model No. : Fine Pix 3800

Test Condition of Equipment Under Test (EUT)


1) Configuration of EUT : Refer to sheet No.5, 6 and 7.

2) EUT Grounding : None.

3) Operating Condition : PC CAMERA Mode .


Frequency (MHz)	Correction Factor (dB)	Meter Reading (dB μ V/m)		Limit (dB μ V/m)	Emission Level (dB μ V/m)		Margin (dB)
		Hor.	Ver.		Hor.	Ver.	
42.800	14.9	---	26.4	40.0	---	26.4	13.6
70.000	7.8	22.5	31.9	40.0	22.5	31.9	8.1
75.500	7.7	---	36.4	40.0	---	36.4	3.6
137.710	16.3	29.5	---	43.5	29.5	---	14.0
186.130	18.8	---	32.8	43.5	---	32.8	10.7
220.900	20.3	30.9	---	46.0	30.9	---	15.1
269.990	21.4	36.9	---	46.0	36.9	---	9.1
336.020	20.3	34.1	25.3	46.0	34.1	25.3	11.9
415.230	21.8	---	26.7	46.0	---	26.7	19.3
498.800	23.6	---	32.8	46.0	---	32.8	13.2
540.080	24.4	36.7	---	46.0	36.7	---	9.3
558.410	24.8	35.8	---	46.0	35.8	---	10.2
587.040	25.7	38.3	---	46.0	38.3	---	7.7
598.800	26.0	---	34.3	46.0	---	34.3	11.7
615.680	26.3	36.6	---	46.0	36.6	---	9.4
736.340	28.0	37.9	38.7	46.0	37.9	38.7	7.3

Note : 1) Meter Readings include Correction Factor (Antenna factor , Cable loss).
 2) Margin = Limit - Emission Level.

Tested by : 
 Kunihiko Ooi

Engineer of TDK Chikumagawa Open Site

FCC 15B CLASS B RADIATED 3m
EUT : Fine Pix 3800 120V/60Hz
MODE : PC CAMERA Mode
Frequency : 30 ~ 1000 MHz



TDK Application No. : TDC-02-0606(1)

MEASUREMENT RESULTS OF RADIATED RADIO NOISE at 3m

Date : June 11, 2002

Temp. : 20 °C ; Humi. : 50 %

Test Receiver : Rohde & Schwarz ESCS 30
 Operation Mode : Detector function : CISPR Quasi-Peak
 6dB Band width : 120kHz External Attenuator : none

Description of Equipment DIGITAL CAMERA

Model No. : Fine Pix 3800

Test Condition of Equipment Under Test (EUT)


1) Configuration of EUT : Refer to sheet No.5, 6 and 7.

2) EUT Grounding : None.

3) Operating Condition : PLAY Mode .


Frequency (MHz)	Correction Factor (dB)	Meter Reading (dB μ V/m)		Limit (dB μ V/m)	Emission Level (dB μ V/m)		Margin (dB)
		Hor.	Ver.		Hor.	Ver.	
59.100	9.6	---	27.0	40.0	---	27.0	13.0
70.000	7.8	22.5	34.6	40.0	22.5	34.6	5.4
75.500	7.7	---	36.0	40.0	---	36.0	4.0
137.730	16.3	29.5	27.0	43.5	29.5	27.0	14.0
186.130	18.8	---	32.8	43.5	---	32.8	10.7
208.630	20.0	31.5	---	43.5	31.5	---	12.0
257.720	20.9	33.3	---	46.0	33.3	---	12.7
300.680	19.6	30.7	---	46.0	30.7	---	15.3
329.320	20.2	31.3	---	46.0	31.3	---	14.7
466.350	22.9	30.3	32.6	46.0	30.3	32.6	13.4
472.490	23.0	31.9	32.4	46.0	31.9	32.4	13.6
501.130	23.6	34.2	---	46.0	34.2	---	11.8
515.440	23.9	---	35.7	46.0	---	35.7	10.3
539.990	24.4	37.2	34.2	46.0	37.2	34.2	8.8
587.040	25.7	38.9	---	46.0	38.9	---	7.1
736.340	28.0	37.9	34.2	46.0	37.9	34.2	8.1


Note : 1) Meter Readings include Correction Factor (Antenna factor , Cable loss).
 2) Margin = Limit — Emission Level.

Tested by : 
 Kunihiro Ooi

Engineer of TDK Chikumagawa Open Site

FCC 15B CLASS B RADIATED 3m
EUT : Fine Pix 3800 120V/60Hz
MODE : PLAY Mode
Frequency : 30 ~ 1000 MHz





Test Configuration

No.	Device	MODEL No.	FCC ID	S/N	Manufacturer
EUT	DIGITAL CAMERA	Fine Pix 3800	F5GFP-3800	RUR00373	FUJI PHOTO FILM CO. , LTD.
A	PC NOTE BOOK COMPUTER	12XL212	DOC	1V08FHNJE1N5	COMPAQ COMPUTER COR.
B	MOUSE	M-BB48	DOC	LZE01271677	Logitech
C	PC MONITOR	M2978	BEJCA500	CY5430HF3CV	LG ELECTRONICS
D	SCANNER	AS1	F5GAS-1	0009	FUJI PHOTO FILM CO. , LTD.
E	AC ADAPTER	LE-9702B-01	----	177625-001	COMPAQ COMPUTER COR.
F	AC ADAPTER	AC-5VS	----	0106	FUJI PHOTO FILM CO. , LTD.

TDK Application No : TDC-02-0606(1)

Connection Cables

No.	I/F & Power Cable	Model No.	Cable Length	Feraite Core	Manufacturer
1	USB CABLE	-----	1.20 m	YES	SHIELD YES
2	AC ADAPTOR CABLE	-----	1.90 m	YES	
3	SCSI CABLE	-----	1.50 m	YES	SHIELD YES
4	PC MONITOR CABLE	-----	1.65 m	YES	SHIELD YES
5	MOUSE CABLE	-----	1.90 m		SHIELD YES
6	AC ADAPTOR CABLE(PC)	-----	1.55 m	YES	
7	AC CABLE(SCANNER)	-----	1.80 m		
8	PC MONITOR POWER CABLE	-----	1.70 m		

RADIATION MEASUREMENT


EUT : DIGITAL CAMERA

MODEL No. Fine Pix 3800

CONFIGURATION FRONT VIEW



CONFIGURATION REAR VIEW



EUT's Test Arrangement of Radiation

Fig 1

Non metallic (F. R. P.) Dome (W 8.0m × D 6.3m × H 5.5m)

