

TDK EMC CENTER CHIKUMAGAWA OPEN SITE

543 OTAI SAKU-CITY NAGANO JAPAN

REPORT OF MEASUREMENTS ON DIGITAL DEVICE

Date : June 28, 2000


Issued in : Saku-city, JAPAN

TDK APPLICATION No.: TDC-00-0607

1. Applicant : FUJI PHOTO FILM CO., LTD
13-45, SENZUI 3 - CHOME, ASAKA - SHI, SAITAMA
351 - 8585 JAPAN
2. Factory : FUJIX CO., LTD
1 - 6, MATSUZAKADAIRA TAIWA - CHO,
KUROKAWA - GUN, MIYAGI - KEN, 981 - 3492 JAPAN
3. Description of Equipment Under Test (EUT)
- 3-1. EUT : DIGITAL CAMERA
3-2. Category : FCC Class B Digital Device
3-3. FCC ID No. : F5GFP - 4900
3-4. Trade Name : FUJIFILM
3-5. Model No. : Fine Pix 4900 ZOOM
3-6. Serial No. : S00137
3-7. Date of Manufacture : May, 2000
3-8. Power Supply : 120 V AC, 60Hz
4. Regulation Applied : FCC Part 15 Subpart B CLASS B 3m
5. Measurement Procedure Used : ANSI C63.4 - 1992
6. Place of Measurement : TDK EMC CENTER CHIKUMAGAWA OPEN SITE
7. Date of Measurement : June 27, 2000
8. Measurement Results : The test results show that EUT conform to regulations
applied as shown in the attached sheets.

Note : (1) The test results relate only to items tested.

(2) This report shall not be reproduced except in full without the written approval of testing
laboratory.


Fumio Suga

Chief of TDK CHIKUMAGAWA OPEN SITE

MEASUREMENT RESULTS OF RADIATED RADIO NOISE at 3m

Date : June 27, 2000

Temp. : 15 °C ; Humi. : 85 %

Test Receiver : Rohde & Schwarz ESVP
 Operation Mode : Detector function : CISPR Quasi-Peak
 6dB Band width : 120kHz External Attenuator : none

Description of Equipment : DIGITAL CAMERA

Model No. : Fine Pix 4900 ZOOM

Test Condition of Equipment Under Test (EUT)

1) Configuration of EUT : Refer to sheet No.5, 6 and .7

2) EUT Grounding : None.

3) Operating Condition : CAMERA Mode .


Frequency (MHz)	Correction Factor (dB)	Meter Reading (dB μ V/m)		Limit (dB μ V/m)	Emission Level (dB μ V/m)		Margin (dB)
		Hor.	Ver.		Hor.	Ver.	
55.700	10.8	---	15.5	40.0	---	15.5	24.5
89.800	10.1	---	15.5	43.5	---	15.5	28.0
126.700	15.9	29.5	33.9	43.5	29.5	33.9	9.6
157.300	17.6	29.3	30.0	43.5	29.3	30.0	13.5
180.000	18.7	38.7	31.5	43.5	38.7	31.5	4.8
196.360	19.4	36.5	---	43.5	36.5	---	7.0
229.090	20.9	40.5	34.7	46.0	40.5	34.7	5.5
240.000	21.1	31.6	25.4	46.0	31.6	25.4	14.4
261.820	21.4	40.5	36.9	46.0	40.5	36.9	5.5
311.420	20.1	31.1	24.6	46.0	31.1	24.6	14.9
360.000	21.1	35.6	38.2	46.0	35.6	38.2	7.8
392.730	21.8	34.7	---	46.0	34.7	---	11.3
409.090	22.1	35.3	---	46.0	35.3	---	10.7
425.450	22.5	37.0	37.6	46.0	37.0	37.6	8.4
458.180	23.3	36.6	34.1	46.0	36.6	34.1	9.4
491.510	23.8	---	35.5	46.0	---	35.5	10.5
526.190	24.6	35.4	---	46.0	35.4	---	10.6
528.080	24.7	---	35.6	46.0	---	35.6	10.4
529.770	24.7	36.0	---	46.0	36.0	---	10.0
644.310	27.4	37.5	---	46.0	37.5	---	8.5
701.580	28.3	37.0	---	46.0	37.0	---	9.0

Note : 1) Meter Readings include Correction Factor (Antenna factor , Cable loss).

2) Margin = Limit - Emission Level.

Tested by : *Junichiro Ooi*
 Engineer of TDK Chikumagawa Open Site

FCC 15B CLASS B RADIATED 3m
EUT : Fine Pix 4900 ZOOM 120V/60Hz
MODE : CAMERA Mode
Frequency : 30 ~ 1000 MHz



TDK Application No. : TDC-00-0607

MEASUREMENT RESULTS OF RADIATED RADIO NOISE at 3m

Date : June 27, 2000

Temp. : 15 °C ; Humi. : 85 %

Test Receiver : Rohde & Schwarz ESVP
 Operation Mode : Detector function : CISPR Quasi-Peak
 6dB Band width : 120kHz External Attenuator : none

Description of Equipment : DIGITAL CAMERA

Model No. : Fine Pix 4900 ZOOM

Test Condition of Equipment Under Test (EUT)

1) Configuration of EUT : Refer to sheet No.5, 6 and .7

2) EUT Grounding : None.

3) Operating Condition : USB Mode .


Frequency (MHz)	Correction Factor (dB)	Meter Reading (dB μ V/m)		Limit (dB μ V/m)	Emission Level (dB μ V/m)		Margin (dB)
		Hor.	Ver.		Hor.	Ver.	
34.050	18.3	---	30.3	40.0	---	30.3	9.7
52.000	12.0	---	28.1	40.0	---	28.1	11.9
90.500	10.2	19.8	28.1	43.5	19.8	28.1	15.4
126.000	15.8	---	23.3	43.5	---	23.3	20.2
153.000	17.4	---	21.5	43.5	---	21.5	22.0
166.000	17.9	26.7	---	43.5	26.7	---	16.8
180.000	18.7	36.6	33.5	43.5	36.6	33.5	6.9
192.000	19.3	31.9	30.0	43.5	31.9	30.0	11.6
240.040	21.1	34.3	---	46.0	34.3	---	11.7
311.420	20.1	30.4	---	46.0	30.4	---	15.6
320.000	20.3	34.3	28.0	46.0	34.3	28.0	11.7
329.320	20.5	31.3	26.0	46.0	31.3	26.0	14.7
331.920	20.5	33.9	---	46.0	33.9	---	12.1
526.190	24.6	35.6	---	46.0	35.6	---	10.4
528.080	24.7	---	31.0	46.0	---	31.0	15.0
529.770	24.7	37.1	---	46.0	37.1	---	8.9
644.310	27.4	37.1	---	46.0	37.1	---	8.9

Note : 1) Meter Readings include Correction Factor (Antenna factor , Cable loss).

2) Margin = Limit - Emission Level.

Tested by : *Kumiko Ooi*
 Engineer of TDK Chikumagawa Open Site

FCC 15B CLASS B RADIATED 3m
EUT : Fine Pix 4900 ZOOM 120V/60Hz
MODE : USB Mode
Frequency : 30 ~ 1000 MHz



MEASUREMENT RESULTS OF CONDUCTED RADIO NOISE

Date : June 27, 2000

Temp. : 24 °C ; Humi. : 70 %

Test Receiver : Rohde & Schwarz ESH-3

Operation Mode : Detector function : CISPR Quasi-Peak

6dB Band width : 10kHz

External Attenuator : none

Description of Equipment : DIGITAL CAMERA

Model No. : Fine Pix 4900 ZOOM

; Type : Desk Top

Test Condition of Equipment Under Test (EUT)

1) Configuration of EUT : Refer to sheet No.13, 14 and 15.

2) EUT Grounding :	None.
--------------------	-------

3) Operating Condition : CAMERA Mode .

[illegible]

Note : 1) Correction Factor include LISN Factor and cable loss for 7 meters.

Meter Readings include Correction Factor.

2)VA : Between one end of the power cable and the grounded.


VB : Between the other end of the power cable and the grounded.

3) Margin = Limit - Emission Level.

Tested by :

Engineer of TDK Chikumagawa Open Site

FCC 15B CLASS B CONDUCTED
 EUT : Fine Pix 4900 ZOOM 120V/60Hz
 MODE : CAMERA Mode
 Frequency : 0.45 ~ 30 MHz



MEASUREMENT RESULTS OF CONDUCTED RADIO NOISE

Date : June 27, 2000

Temp. : 24 °C ; Humi. : 70 %

Test Receiver : Rohde & Schwarz ESH-3

Operation Mode : Detector function : CISPR Quasi-Peak

6dB Band width : 10kHz

External Attenuator : none

Description of Equipment : DIGITAL CAMERA

Model No. : Fine Pix 4900 ZOOM

; Type : Desk Top

Test Condition of Equipment Under Test (EUT)

1) Configuration of EUT : Refer to sheet No.13, 14 and 15.

2) EUT Grounding :	None.
--------------------	-------

3) Operating Condition : USB Mode .

[illegible]

Note : 1) Correction Factor include LISN Factor and cable loss for 7 meters.

Meter Readings include Correction Factor.

2)VA : Between one end of the power cable and the grounded.

VB : Between the other end of the power cable and the grounded.

3)Margin = Limit – Emission Level.

Tested by : Junichiko Ooi
Engineer of TDK Chikumagawa Open Site

FCC 15B CLASS B CONDUCTED
 EUT : Fine Pix 4900 ZOOM 120V/60Hz
 MODE : USB Mode
 Frequency : 0.45 ~ 30 MHz

