



January 12, 2006

Attn: Director of Certification

Dear Sir or Madam:

The following is the SAR calculation for the Digivance® CXD 1900 MHz EFC Band using the system's maximum RF emission. The calculation is based on FCC 47CFR Part 2 and OET 65.

Per OET 65:

Maximum Permissible Exposure is $\text{Freq. (MHz)}/1500 = \text{MPE mW/cm}^2$
 $1930 \text{ MHz}/1500 = 1.2867 \text{ mW/cm}^2$

The following equations determine the distance from the antenna that the power density is $\leq 1.2867 \text{ mW/cm}^2$.

+37.87 dBm Transmitter Power (Max)
22.13 dBi Antenna Gain (Max)
 $37.87 \text{ dBm} + 22.13 \text{ dBi} = +60 \text{ dBm EIRP}$
 $+60 \text{ dBm EIRP} = 1000 \text{ Watts EIRP}$
 $1000 \text{ Watts EIRP} = 1000 \times 10^3 \text{ mWatts EIRP}$
 $1.2867 \text{ mW/cm}^2 = 1000 \times 10^3 \text{ mW}/(4 \times \pi \times r^2)$
 $r = \text{SQR}(1000 \times 10^3 / 4 \times \pi \times 1.2867)$
 $r = 248.69 \text{ cm or } 2.48 \text{ Meters}$

In addition, the following statement will be added to our installation/operation manual:

To comply with Maximum Permissible Exposure (MPE) requirements, the maximum composite output from the antenna cannot exceed 1000 Watts EIRP and the antenna must be permanently installed in a fixed location that provides at least 6 meters (20 feet) of separation from all persons.

Sincerely,

A handwritten signature in cursive script that reads "Dave Conyers".

Dave Conyers
Vice President of Engineering
Tele: 952 403-8424
Fax: 952 403-8858
Email: dave.conyers@adc.com