Prüfbericht - Produkte
Test report - Products

Certificate #4301.01

Prüfbericht-Nr.: *Test Report No.:*	**CN24RVG1 001**	**Auftrags-Nr.:** *Order No.:*	**326049917**	**Seite 1 von 24** *Page 1 of 24*
Kunden-Referenz-Nr.: *Client Reference No.:*	**1288983**	**Auftragsdatum:** *Order date.:*	**2024-09-04**	
Auftraggeber: *Client:*	**IKEA of Sweden AB** Box 702, SE-343 81, Älmhult Sweden			
Prüfgegenstand: *Test item:*	**BLOMPRAKT**			
Bezeichnung / Typ-Nr.: *Identification / Type No.:*	**E2503**			
Auftrags-Inhalt: *Order content:*	**TÜV Rheinland EMC service**			
Prüfgrundlage: *Test specification:*	**FCC 47 CFR Part 15, Subpart B:2023 Class B** **ICES-003:2020 ICES-005:2018**			
Wareneingangsdatum: *Date of receipt:*	**2024-09-29**	Refer to the EUT photos file		
Prüfmuster-Nr.: *Test sample No.:*	**A003841290-001**			
Prüfzeitraum: *Testing period:*	**Refer to test report**			
Ort der Prüfung: *Place of testing:*	**Refer to clause 1.1**			
Prüflaboratorium: *Testing laboratory:*	**TÜV Rheinland (Shanghai) Co., Ltd.**			
Prüfergebnis*: *Test result*:*	**Pass**			

geprüft von: / *tested by:*

Datum: / *Date:* 2025-01-14 Xuelan zhang

Stellung: / *Position:* Project engineer

genehmigt von: / *authorized by:*

Datum: / *Date:* 2025-01-14 Jacky Chen

Stellung: / *Position:* Authorizer

Sonstiges / *Other:*	FCC ID: FHO-E2503 IC: 10912A-E2503 Test Firm Name: TUV Rheinland (Shanghai) Co., Ltd. Designation Number: CN1396 Test Firm Registration Number: 930979

Zustand des Prüfgegenstandes bei Anlieferung: *Condition of the test item at delivery:* **Prüfmuster vollständig und unbeschädigt** *Test item complete and undamaged*

* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet
Legend: P(ass) = passed a.m. test specifications(s) F(ail) = failed a.m. test specifications(s) N/A = not applicable N/T = not tested

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.

This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.

Prüfbericht - Nr.: **CN24RVG1 001**
Test Report No.:

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. *The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system.* *Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.*
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature *As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature*
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. *Test clauses with remark of * are subcontracted to qualified subcontractors and descripted under the respective test clause in the report.* *Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.*
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnisen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezueglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. *The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.*

Revision history of test report:

Report number	Issue date	Contents and reason for change if appropriate
CN24RVG1 001	2025-01-14	Initial release.

Contents

1 TEST SITES 5

1.1 TEST FACILITIES 5

2 GENERAL PRODUCT INFORMATION 6

2.1 PRODUCT FUNCTION AND INTENDED USE 6
2.2 RATINGS AND SYSTEM DETAILS 6
2.3 INDEPENDENT OPERATION MODESS 6
2.4 DESCRIPTION OF INTERCONNECTING CABLES 6
2.5 NOISE GENERATING AND NOISE SUPPRESSING PARTS 6
2.6 HIGHEST FREQUENCY GENERATED OR USED IN THE DEVICE OR ON WHICH THE DEVICE OPERATES OR TUNES 6
2.7 SUBMITTED DOCUMENTS 6

3 TEST SET-UP AND OPERATION MODES 7

3.1 PRINCIPLE OF CONFIGURATION SELECTION 7
3.2 EQUIPMENT AND CABLE ARRANGEMENT 7
3.3 TEST SOFTWARE 8
3.4 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT 8
3.5 COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE 8

4 CONFORMITY DECISION RULE 9

5 TEST RESULTS E M I S S I O N 10

5.1 EMISSION IN THE FREQUENCY RANGE UP TO 30 MHZ 10
5.1.1 Mains Terminal Continuous Disturbance Voltage 10
5.2 EMISSION IN THE FREQUENCY RANGE ABOVE 30 MHZ 14
5.2.1 Radiated emission （30 MHz - 1 GHz） 14
5.2.2 Radiated emission (Above 1 GHz) 18

6 PHOTOGRAPHS OF THE TEST SET-UP 22

7 LIST OF TEST AND MEASUREMENT INSTRUMENTS 23

8 LIST OF FIGURES 24

1 Test Sites

1.1 Test Facilities

Laboratory: TÜV Rheinland (Shanghai) Co., Ltd.
Address: Workshop14, North Half of Workshop 10 and Workshop 16, Pingqian (Taicang) Modern Industrial Park, No.525, Yuewang Lingang South Road, Shaxi, Taicang, Jiangsu, China

The used test equipment is in accordance with CISPR 16-1 series standards for measurement of radio interference.

Refer to Clause 6 for test and measurement instruments.

2 General Product Information

2.1 Product Function and Intended Use

The EUT (equipment under test) is a BLOMPRAKT. For the further information, refer to the user's manual.

2.2 Ratings and System Details

Rated input	:	AC 100-240 V, 50-60 Hz; 250-140 mA
Output	:	Audio 10 W, Lighting 1 W
Protection class	:	II

2.3 Independent Operation Modess

The basic operation mode is the below,

1. Continuous playing 1 kHz audio signal by Bluetooth.
2. Light on with dimming

2.4 Description of interconnecting cables

None.

2.5 Noise Generating and Noise Suppressing Parts

Refer to the circuit diagram for further information.

2.6 Highest frequency generated or used in the device or on which the device operates or tunes

The highest frequency used in the EUT is 2.4 GHz.

2.7 Submitted Documents

Circuit diagram, user's manual and rating label.

3 Test Set-up and Operation Modes

3.1 Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible emission level. The test conditions were adapted accordingly in reference to the instructions for use.

Refer to the related paragraph of this report.
The sequence of testing:
1. Radiated emission tests were performed on 2024-10-24~2024-10-30.
2. Conducted emission tests were performed on 2024-10-24.

3.2 Equipment and cable arrangement

Block diagram for both conducted emission and radiated emission tests is as follows:



(Conducted emission)



(Radiated emission)

3.3 Test Software

No special test software was used during the tests.

3.4 Special Accessories and Auxiliary Equipment

During the tests, the below equipment were used.

No.	Equipment	Model	Manufacturer
1	Cell phone	STF-AL10	Huawei

3.5 Countermeasures to achieve EMC Compliance

No other special measure is employed to achieve the requirement.

4 Conformity Decision Rule

For all EMI tests included in this report, as measurement uncertainties are less than the values U_{CISPR} given in CISPR 16-4-2, compliance with the limits is determined by comparing measurement results directly with corresponding limits without taking into consideration of measurement uncertainties.

5 Test Results E M I S S I O N

5.1 Emission in the Frequency Range up to 30 MHz

5.1.1 Mains Terminal Continuous Disturbance Voltage

Result:	**Passed**

Date of testing	:	2024-10-24
Test procedure	:	FCC 47 CFR Part 15, Subpart B:2023, ICES-003:2020, ICES-005:2018, ANSI C63.4-2014 and CISPR 16-2-1
Frequency range	:	0.15 – 30 MHz
Limits	:	Quasi-peak limit: 0.15 - 0.5 MHz, 66 to 56 dBµV (decrease with the logarithm of frequency); 0.5 - 5 MHz, 56 dBµV; 5 - 30 MHz, 60 dBµV Average limit: 0.15 - 0.5 MHz, 56 to 46 dBµV (decrease with the logarithm of frequency); 0.5 – 5 MHz, 46 dBµV; 5 – 30 MHz, 50 dBµV
Bandwidth of EMI receiver for final measurement	:	9 kHz
Measurement time for final measurement	:	1 s
Kind of test site	:	Shielded room
Input voltage	:	AC 120 V, 60 Hz
Operational mode	:	Modes 1+2 as defined in clause 2.3
Ambient condition	:	Temperature: 21.5 °C; Relative humidity: 48 %
Expanded measurement uncertainty (*k*=2)	:	2.33 dB The minimum margin to the limit is 13.86 dB at 0.350250 MHz. The margin is higher than expanded measurement uncertainty.

The measurement setup was made according to ANSI C63.4-2014 in a shielded room.

The measurement equipment like test rece1ivers, quasi-peak detector and artificial mains network (AMN) are in compliance with CISPR 16-1 series standards.
The tested object was set-up on a wooden support. The EUT was set 0.8 m away from the AMN. The cord longer than necessary to be connected to the AMN was folded forth and back parallel so as to form a bundle with a length between 0.3 m and 0.4 m.
The disturbance voltage test was performed on the neutral line and phase line of the power supply of the EUT respectively.

The following figures and tables were those measured by an automatic measuring system. Both quasi-peak and average measurements were performed. In the following spectral diagram, "◆" mean Quasi-Peak Value and "◆" mean Average Value results.

Notes on following tables of conducted emission results and conversions:

Level (dBµV): final measurement results by using quasi-peak detector and average detector
Transd (dB): transducer factor including cable loss, insertion loss of artificial mains network and gain of pre-amplifier (if used)
Margin: Limit (dBµV) - Level (dBµV)

Figure 1: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, L



Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.323250	36.78	59.62	22.84	1000.0	9.000	L1	10.3
0.350250	45.09	58.96	13.86	1000.0	9.000	L1	10.3
0.449250	32.17	56.89	24.72	1000.0	9.000	L1	10.3
0.474000	32.30	56.44	24.14	1000.0	9.000	L1	10.3
0.501000	31.58	56.00	24.42	1000.0	9.000	L1	10.3
1.027500	31.16	56.00	24.84	1000.0	9.000	L1	10.7

Final Average measurement result:

Frequency (MHz)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.325500	23.38	49.57	26.19	1000.0	9.000	L1	10.3
0.352500	33.93	48.90	14.98	1000.0	9.000	L1	10.3
0.372750	20.07	48.44	28.37	1000.0	9.000	L1	10.3
0.474000	17.56	46.44	28.88	1000.0	9.000	L1	10.3
0.705750	22.85	46.00	23.15	1000.0	9.000	L1	10.3
1.765500	22.48	46.00	23.52	1000.0	9.000	L1	10.2

Figure 2: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, N



Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.323250	30.51	59.62	29.11	1000.0	9.000	N	10.5
0.350250	37.47	58.96	21.48	1000.0	9.000	N	10.4
0.449250	25.30	56.89	31.59	1000.0	9.000	N	10.3
0.474000	25.33	56.44	31.12	1000.0	9.000	N	10.2
0.501000	24.45	56.00	31.55	1000.0	9.000	N	10.2
1.027500	24.15	56.00	31.85	1000.0	9.000	N	10.4

Final Average measurement result:

Frequency (MHz)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.325500	19.05	49.57	30.52	1000.0	9.000	N	10.5
0.352500	29.24	48.90	19.66	1000.0	9.000	N	10.4
0.372750	15.57	48.44	32.87	1000.0	9.000	N	10.4
0.705750	16.76	46.00	29.24	1000.0	9.000	N	10.4
1.765500	16.50	46.00	29.50	1000.0	9.000	N	10.5
4.762500	12.72	46.00	33.28	1000.0	9.000	N	10.7

5.2 Emission in the Frequency Range above 30 MHz

5.2.1 Radiated emission （30 MHz - 1 GHz）

Result:	**Passed**

Date of testing	:	2024-10-24~2024-10-30
Test procedure	:	FCC 47 CFR Part 15, Subpart B:2023, ICES-003:2020, ICES-005:2018, ANSI C63.4-2014 and CISPR 16-2-3
Frequency range	:	30 – 1000 MHz
Limits	:	Quasi-peak limits (3 m distance): 30 – 88 MHz, 40 dBμV/m; 88 – 216 MHz, 43.5 dBμV/m; 216 – 1000 MHz, 46 dBμV/m (see Note 1)
Bandwidth of EMI receiver for final measurement	:	120 kHz
Measurement time for final measurement	:	1 s
Kind of test site	:	Semi-anechoic chamber
Operational mode	:	Modes 1+2 as defined in clause 2.3
Input voltage	:	AC 120 V; 60 Hz
Ambient condition	:	Temperature: 20.5 °C; Relative humidity: 45 %
Expanded measurement uncertainty (*k*=2)	:	5.40 dB The minimum margin to the limit is 8.7 dB at 34.971250 MHz. The margin is higher than expanded measurement uncertainty.

The radiated disturbance test was carried out in a semi-anechoic chamber. The test distance from the receiving antenna to the EUT is 3 m. The normalized site attenuation of the semi-anechoic chamber is regularly calibrated to ensure the radiated disturbance test results are valid. During the test, the EUT was placed on a 0.8 m high wooden table above the reference ground plane. The wooden table was rotated 360° around and the height of the antenna was varied from 1 m to 4 m to find the maximum disturbance. The test was performed with the antenna both in its horizontal and vertical polarizations.

The following figures and tables were those measured by an automatic measurement system. A preview test was firstly performed with peak detector. The final test was performed with quasi-peak at those critical frequencies during the preview test. In the following spectral diagram, "×" means quasi-peak test results.

Note 1: The class B limits of ICES-005:2018 is stricter than those ICES-003:2020 and FCC 47 CFR Part 15, Subpart B:2023 for 3 m test distance. Therefore, the former limits are used in following figures and tables.

Notes on following tables of radiated emission results and conversions:

QuasiPeak (dBµV/m): final measurement results by using quasi-peak detector
Corr. (dB): correction factor including: antenna factor, cable loss, and gain of pre-amplifier (if used)
Margin: Limit (dBµV/m) - QuasiPeak (dBµV/m)

Figure 3: Spectral Diagrams and measurement results, horizontal polarization (30 MHz to 1 GHz)



Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBµV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
32.667500	27.8	120.000	200.0	H	165.0	23.6	12.2	40.0
37.153750	24.6	120.000	150.0	H	145.0	21.3	15.4	40.0
132.820000	21.5	120.000	200.0	H	112.0	18.5	22.0	43.5
313.482500	26.9	120.000	200.0	H	26.0	20.7	19.1	46.0
707.520000	32.4	120.000	120.0	H	179.0	26.9	13.6	46.0
932.100000	33.1	120.000	100.0	H	-14.0	28.9	12.9	46.0

Figure 4: Spectral Diagrams and measurement results, vertical polarization (30 MHz to 1 GHz)



Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBµV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
34.971250	31.3	120.000	130.0	V	115.0	22.5	8.7	40.0
42.246250	26.9	120.000	110.0	V	145.0	18.6	13.1	40.0
148.825000	24.5	120.000	150.0	V	89.0	17.6	19.0	43.5
321.121250	24.2	120.000	170.0	V	78.0	20.9	21.8	46.0
616.365000	30.3	120.000	200.0	V	-25.0	27.0	15.7	46.0
883.600000	33.2	120.000	200.0	V	-98.0	28.7	12.8	46.0

5.2.2 Radiated emission (Above 1 GHz)

Result:	**Passed**

Date of testing	:	2024-10-24~2024-10-30
Port	:	Enclosure
Test procedure	:	FCC 47 CFR Part 15, Subpart B:2023, ANSI C63.4-2014 and CISPR 16-2-3 ICES-003:2020
Limit	:	Above 1 GHz, Peak limit: 74 dBμV/m; Average limit: 54 dBμV/m
Frequency range	:	1-18 GHz Note: The highest frequency in the EUT is 2.4 GHz. According to FCC Part 15 subpart B §15.33 (b) (1), the upper frequency for radiated emission measurement is 12 GHz. The actual test frequency is up to 18 GHz.
Bandwidth of EMI receiver for final measurement	:	1000 kHz
Measurement time for final measurement	:	1 s
Test distance	:	3 m
Kind of test site	:	Semi-anechoic chamber
Operational mode	:	Mode 1 as defined in clause 2.3
Input voltage	:	AC 120 V; 60 Hz
Earthing	:	No earthing
Ambient condition	:	Temperature: 20.5 °C; Relative humidity: 45 %
Expanded measurement uncertainty (*k*=2)	:	5.08 dB The minimum margin to the limit is 7.3 dB at 17979.281250 MHz. The margin is higher than expanded measurement uncertainty.

The radiated disturbance test was carried out in a semi-anechoic chamber. The test distance from the receiving antenna to the EUT is 3 m. The normalized site attenuation of the semi-anechoic chamber is regularly calibrated to ensure the radiated disturbance test results are valid. During the test, the EUT was placed on a poly table, which is 0.8 m high. The wooden table was rotated 360° around and the antenna was varied from 1 m to 4 m to find the maximum disturbance. The test was performed with the antenna both in its horizontal and vertical polarizations.

The following figures and tables were those measured by an automatic measurement system. The final test was performed with peak detector and average detector at those critical frequencies during the preview test. In the following figure, “x(red)” means measurement results with peak detector and “+ (blue)” means measurement results with average detector.

Notes on following tables of radiated emission results and conversions:

Peak (dBμV/m): final measurement results by using peak detector
Average (dBμV/m): final measurement results by using average detector

Corr. (dB): correction factor including: antenna factor, cable loss, and gain of pre-amplifier (if used)
Margin: Limit PK (dBµV/m) - Peak (dBµV/m)
Limit CAV (dBµV/m) – Average (dBµV/m

Figure 5: Spectral Diagrams and measurement results, 1-18 GHz, horizontal polarization



Final Peak measurement results:

Frequency (MHz)	MaxPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/
2414.718750	49.0	1000.0	1000.000	100.0	H	-180.0	-15.7	25.0	74.0
2445.000000	41.4	1000.0	1000.000	100.0	H	-180.0	-15.8	32.6	74.0
2473.156250	39.7	1000.0	1000.000	100.0	H	-180.0	-15.8	34.3	74.0
7308.593750	46.6	1000.0	1000.000	100.0	H	-180.0	-6.0	27.4	74.0
14418.312500	51.2	1000.0	1000.000	100.0	H	-180.0	3.4	22.8	74.0
17979.281250	57.2	1000.0	1000.000	100.0	H	-180.0	13.0	16.8	74.0

Final Average measurement results:

Frequency (MHz)	Average (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/
2414.718750	30.6	1000.0	1000.000	100.0	H	-180.0	-15.7	23.4	54.0
2445.000000	22.7	1000.0	1000.000	100.0	H	-180.0	-15.8	31.3	54.0
2473.156250	23.2	1000.0	1000.000	100.0	H	-180.0	-15.8	30.8	54.0
7308.593750	32.7	1000.0	1000.000	100.0	H	-180.0	-6.0	21.3	54.0
14418.312500	39.2	1000.0	1000.000	100.0	H	-180.0	3.4	14.8	54.0
17979.281250	46.7	1000.0	1000.000	100.0	H	-180.0	13.0	7.3	54.0

Figure 6: Spectral Diagrams and measurement results, 1-18 GHz, vertical polarization



Final Peak measurement results:

Frequency (MHz)	MaxPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/
1497.781250	32.9	1000.0	1000.000	100.0	V	280.0	-18.4	41.1	74.0
2465.718750	35.5	1000.0	1000.000	100.0	V	280.0	-15.8	38.5	74.0
7202.343750	48.7	1000.0	1000.000	100.0	V	280.0	-5.4	25.3	74.0
7953.531250	48.5	1000.0	1000.000	100.0	V	280.0	-3.0	25.5	74.0
14201.562500	51.5	1000.0	1000.000	100.0	V	280.0	2.4	22.5	74.0
17956.437500	58.1	1000.0	1000.000	100.0	V	280.0	12.6	16.0	74.0

Final Average measurement results:

Frequency (MHz)	Average (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/
1497.781250	20.9	1000.0	1000.000	100.0	V	280.0	-18.4	33.1	54.0
2465.718750	22.6	1000.0	1000.000	100.0	V	280.0	-15.8	31.4	54.0
7202.343750	33.1	1000.0	1000.000	100.0	V	280.0	-5.4	20.9	54.0
7953.531250	35.5	1000.0	1000.000	100.0	V	280.0	-3.0	18.6	54.0
14201.562500	38.0	1000.0	1000.000	100.0	V	280.0	2.4	16.0	54.0
17956.437500	45.2	1000.0	1000.000	100.0	V	280.0	12.6	8.8	54.0

6 Photographs of the Test Set-Up

Refer to the test setup file.

7 List of Test and Measurement Instruments

Equip.	Description	Model	Manufacturer	Last Date DD.MM.YYYY	Due Date DD.MM.YYYY
9061503	Shielded enclosure	10.055x3.605x3.000	Frankonia	08.11.2023	08.11.2028
9023229	EMI test receiver	ESR3	Rohde&Schwarz	03.08.2024	03.08.2025
G1824248	Dual display multimeter	F45	Fluke	28.06.2024	28.06.2025
9062744	EMI measurement software	EMC32-E+(10.60.20)	Rohde&Schwarz	N/A	N/A
G1830003	Artificial mains network	ENV432	Rohde&Schwarz	11.10.2024	11.10.2025
G1811378	3m semi-anechoic chamber	SAC3	Frankonia	03.12.2023	03.12.2026
G1811391	EMI test receiver	ESCI	Rohde&Schwarz	17.10.2024	17.10.2025
G1811425	Bilog antenna	CBL 6112D	Teseq	20.04.2023	20.04.2026
9062745	EMI measurement software	EMC32-MEB (10.60.20)	Rohde&Schwarz	N/A	N/A
G1822695	Spectrum analyser	FSP30	Rohde&Schwarz	15.07.2024	15.07.2025
G1825371	Preamplifier	EMC051845SE	Taiwan EMCI	24.07.2024	24.07.2025
G1811417	Log periodic antenna	HL050	Rohde&Schwarz	19.04.2023	19.04.2026

8 List of Figures

Figure 1: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, L 12
Figure 2: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, N 13
Figure 3: Spectral Diagrams and measurement results, horizontal polarization (30 MHz to 1 GHz) 16
Figure 4: Spectral Diagrams and measurement results, vertical polarization (30 MHz to 1 GHz) 17
Figure 5: Spectral Diagrams and measurement results, 1-18 GHz, horizontal polarization 20
Figure 6: Spectral Diagrams and measurement results, 1-18 GHz, vertical polarization 21

End of test report