

Prüfbericht-Nr.: Test report no.:	CN26AIB9 001	Auftrags-Nr.: Order no.:	326173638	Seite 1 von 53 Page 1 of 53
Kunden-Referenz-Nr.: Client reference no.:	1288983	Auftragsdatum: Order date:	2026-02-24	
Auftraggeber: Client:	IKEA of Sweden AB Box 702, SE-343 81 Älmhult, Sweden			
Prüfgegenstand: Test item:	Remote Control (Scroll Wheel)			
Bezeichnung / Typ-Nr.: Identification / Type no.:	E2704			
Auftrags-Inhalt: Order content:	Test Report			
Prüfgrundlage: Test specification:	FCC CFR47 Part 15, Subpart C Section 15.247 RSS-Gen Issue 5, Amendment 2, February 2021 RSS-247 Issue 4, July 24, 2025			
Wareneingangsdatum: Date of sample receipt:	2026-03-26	Refer to photo document.		
Prüfmuster-Nr.: Test sample no.:	A004235068-004			
Prüfzeitraum: Testing period:	2026-05-13 ~ 2026-05-22			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:	X <u>Hongfei Wu</u> Signed by: Hongfei Wu		genehmigt von: authorized by:	X <u>Weidong Wang</u> Signed by: Weidong Wang
Datum: Date:	2026-06-11		Datum: Date:	2026-06-11
Stellung / Position:	Sachverständige(r)/Expert		Stellung / Position:	Sachverständige(r)/Expert
Sonstiges / Other:	FCC ID: FHO-E2704 IC: 10912A-E2704 HVIN: E2704 PMN: BILRESA This report is for BLE.			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
* Legend:	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.: CN26AIB9 001
Test report no.:

Seite 2 von 53
Page 2 of 53

Anmerkungen Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT*RESULT: Pass***5.1.2 6dB & 99% BANDWIDTH***RESULT: Pass***5.1.3 OUTPUT POWER***RESULT: Pass***5.1.4 POWER SPECTRAL DENSITY***RESULT: Pass***5.1.5 CONDUCTED BAND EDGE AND OUT-OF BAND EMISSIONS***RESULT: Pass***5.2.1 CONDUCTED EMISSION***RESULT: N/A***5.3.1 RADIATED BAND-EDGE***RESULT: Pass***5.3.2 RADIATED SPURIOUS EMISSION***RESULT: Pass*

Contents

1.	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS.....	5
2.	TEST SITES	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	7
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY	8
3.	GENERAL PRODUCT INFORMATION.....	9
3.1	PRODUCT FUNCTION AND INTENDED USE	9
3.2	RATINGS AND SYSTEM DETAILS.....	9
3.3	INDEPENDENT OPERATION MODES.....	10
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	10
4.	TEST SET-UP AND OPERATION MODES.....	11
4.1	PRINCIPLE OF CONFIGURATION SELECTION	11
4.2	TEST OPERATION AND TEST SOFTWARE.....	11
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	11
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	12
5.	TEST RESULTS	13
5.1	CONDUCTED TESTING AT ANTENNA PORT	13
5.1.1	<i>Antenna Requirement.....</i>	<i>13</i>
5.1.2	<i>6dB & 99% Bandwidth.....</i>	<i>15</i>
5.1.3	<i>Output Power</i>	<i>28</i>
5.1.4	<i>Power Spectral Density</i>	<i>29</i>
5.1.5	<i>Conducted Band Edge and out-of Band Emissions.....</i>	<i>36</i>
5.2	EMISSION IN THE FREQUENCY RANGE UP TO 30MHz.....	40
5.2.1	<i>Conducted Emission.....</i>	<i>40</i>
5.3	EMISSION IN THE FREQUENCY RANGE ABOVE 30MHz	41
5.3.1	<i>Radiated Band-Edge</i>	<i>41</i>
5.3.2	<i>Radiated Spurious Emission.....</i>	<i>46</i>
6.	LIST OF TABLES	53
7.	LIST OF FIGURES	53

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

2. Test Sites

2.1 Test Facilities

TÜV Rheinland (Shanghai) Co., Ltd.

Workshop 14, North Half of Workshop 10 and Workshop 16, Pingqian (Taicang) Modern Industrial Park, No.525, Yuewang Lingang South Road, Shaxi, Taicang, Jiangsu, China

The used test equipment is in accordance with CISPR 16 for measurement of radio interference.

The Federal Communications Commission has reviewed the technical characteristics of the radiated and conducted emission facility, and has found these test facilities to be in compliance with the requirements of section 2.948 of the FCC rules. The description of the test facility is listed under FCC registration number 930979.

The Innovation, Science and Economic Development Canada has reviewed the technical characteristics of the radiated and conducted emission facility, and has found these test facilities to be in compliance. The description of the test facility is listed under chambers filing number 33038.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Equip.	Description	Model	Manufacturer	Due Date
EMC-C-196	Wireless connectivity tester	CMW270	Rohde & Schwarz	2027-08-09
EMC-C-302	Signal generator	SMB100B (6 GHz)	Rohde & Schwarz	2026-11-27
EMC-C-303	Vector Signal generator	SMW200A	Rohde & Schwarz	2026-11-27
EMC-C-304	OSP	OSP-B157W8	Rohde & Schwarz	2026-12-17
EMC-C-161	Spectrum analyser	FSV40	Rohde&Schwarz	2026-07-11
EMC-C-019	Double ridged horn antenna	BBHA 9120 D	Schwarzbeck	2026-08-28
EMC-C-066	EMI test receiver	ESCI	Rohde&Schwarz	2026-09-28
EMC-C-068	Broadband horn antenna	BBHA 9170	Schwarzbeck	2028-06-18
EMC-C-155	BiLog antenna	CBL 6112D	Teseq	2026-09-24
EMC-C-175	Preamplifier	EMC051845SE	EMCI Taiwan	2026-07-11
EMC-C-176	Preamplifier	EMC184045SE	EMCI Taiwan	2026-07-11
EMC-C-001	3 m semi-anechoic chamber	SAC3	Frankonia	2026-12-03
software				
EMC-S-036	RF measurement software	WMS32-WB (11.40.00)	Rohde&Schwarz	NA
EMC-S-032	EMI measurement software	EMC32-E+ (10.60.20)	Rohde&Schwarz	NA

2.3 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

Table 2: Measurement Uncertainty

Measurement Type	Frequency	Uncertainty
Antenna Port Conducted Emission	< 1GHz	±0.39dB
	> 1GHz	±0.68dB
Conducted Emission	150kHz - 30MHz	±2.33dB
Radiated Emission	9kHz - 30MHz	±2.93dB
	30MHz - 1GHz	±5.34dB
	> 1GHz	±5.40dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT (Equipment Under Test) is a Remote control (Scroll Wheel) which support Bluetooth Low Energy, Zigbee and Thread.
The aim of this report is to evaluate RF character of Bluetooth Low Energy of the EUT.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Description of EUT	
Product Name:	Remote Control (Scroll Wheel)
Model No.:	E2704
Operation Voltage:	DC 2.4/3.0V (AAA*2)
RF Technical:	1) BLE 2) Zigbee 3) Thread
Technical Specification of BLE	
Frequency Range:	2402~2480MHz
Modulation Type:	GFSK
Data Rate:	1Mbps, 2Mbps
Antenna Type:	Metal Antenna
Antenna Gain:	-0.38 dBi (declared by client)

Note: After the pretest on the voltage of DC 2.4V and DC 3V, only the test result of the worst case is shown in the report.

Table 4: Operation Channel List

RF Channel	Frequency [MHz]	RF Channel	Frequency [MHz]	RF Channel	Frequency [MHz]	RF Channel	Frequency [MHz]
00	2402	10	2422	20	2442	30	2462
01	2404	11	2424	21	2444	31	2464
02	2406	12	2426	22	2446	32	2466
03	2408	13	2428	23	2448	33	2468
04	2410	14	2430	24	2450	34	2470
05	2412	15	2432	25	2452	35	2472
06	2414	16	2434	26	2454	36	2474
07	2416	17	2436	27	2456	37	2476
08	2418	18	2438	28	2458	38	2478
09	2420	19	2440	29	2460	39	2480

3.3 Independent Operation Modes

Test frequencies are lowest channel: 2402/2404 MHz, middle channel: 2440 MHz and highest channel: 2478/2480 MHz

The basic operation modes are:

- A. BLE transmitting mode

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10:2020 and ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024+Errata to C63.10a-2024.

Test Software: sscom 5.13.1

Table 5: Power parameter value

Mode	Power Parameter Setting Value
BLE	7

4.3 Special Accessories and Auxiliary Equipment

Table 6: Special Accessories

Accessories	Parameter
RF Cable between the antenna port and test system	Cable loss: 0.5dB

Note: The RF cable used in the test was provided by

- ☒ Client
☐ Test Lab

And the cable loss has been factored in the related test.

Table 7: Auxiliary Equipment

Equipment	Brand	Model
Laptop	Lenovo	21AJ-S57N0J

Prüfbericht - Nr.: CN26AIB9 001
Test Report No.

Seite 12 von 53
Page 12 of 53

4.4 Countermeasures to achieve EMC Compliance

Null.

5. Test Results

5.1 Conducted Testing at Antenna Port

5.1.1 Antenna Requirement

RESULT:**Pass**

According to the manufacturer declared, the EUT has one internal Metal antenna, the directional gain of antenna is -0.38 dBi and the antenna is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Table 8: Antenna Requirement

FCC 15.203 – Antenna Requirement 1		
Requirement:	No antenna other than that furnished by the responsible party shall be used with the device	
Results:	Antenna type:	Metal Antenna
Verdict:	Pass	

FCC 15.204 – Antenna Requirement 2		
Requirement:	An intentional radiator may be operated only with the antenna with which it is authorized. If an antenna is marketed with the intentional radiator, it shall be of a type which is authorized with the intentional radiator.	
Results:	Only one Metal antenna can be used	
Verdict:	Pass	

RSS-Gen 6.4 – External Control		
Requirement:	The device shall not have any external controls accessible to the user that enable it to be adjusted, selected or programmed to operate in violation of the regulatory requirements, including RSS-Gen and the applicable RSSs	
Results:	The device does not have any transmitter external controls accessible to the user that can be adjusted and operated in violation of the limits of this standard.	
Verdict:	PASS	

RSS-Gen 6.8 – Antenna Requirement

Requirement: When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

Results:

a) Antenna Type:	Metal Antenna
b) Manufacture:	N/A
c) Model No.:	N/A
d) Gain with reference to an isotropic radiator:	-0.38 dBi

Verdict: PASS

5.1.2 6dB & 99% Bandwidth**RESULT:****Pass**

Date of testing	:	2026-05-13
Ambient temperature	:	21.3°C
Relative humidity	:	49.5%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(a)(2) RSS-247 Issue 4, July 24, 2025, Clause 6.3.1(a) RSS-Gen Issue 5, Amendment 2, February 2021, Clause 6.7
Test procedure	:	ANSI C63.10:2020 ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024+Errata to C63.10a-2024
Test voltage	:	DC 3V
Test modes applied	:	A


6dB Bandwidth, 1Mbps, 2402MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	0.752476	0.500000	---	2401.643564	2402.396040

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2402.000000	6.4	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.40400 GHz	2.40400 GHz
Span	4.000 MHz	4.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 80
Sweptime	18.938 µs	AUTO
Reference Level	10.000 dBm	10.000 dBm
Attenuation	30.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	7 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.13 dB	0.50 dB


6dB Bandwidth, 1Mbps, 2440MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2440.000000	0.712872	0.500000	---	2439.643564	2440.356436

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2440.000000	6.7	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43800 GHz	2.43800 GHz
Stop Frequency	2.44200 GHz	2.44200 GHz
Span	4.000 MHz	4.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 80
SweepTime	18.938 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	11 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.26 dB	0.50 dB


6dB Bandwidth, 1Mbps, 2480MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	0.752476	0.500000	---	2479.643564	2480.396040

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2480.000000	5.8	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47800 GHz	2.47800 GHz
Stop Frequency	2.48200 GHz	2.48200 GHz
Span	4.000 MHz	4.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 80
Sweptime	18.938 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	12 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.08 dB	0.50 dB


6dB Bandwidth, 2Mbps, 2404MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2404.000000	1.435643	0.500000	---	2403.306931	2404.742574

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2404.000000	5.2	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40150 GHz	2.40150 GHz
Stop Frequency	2.40650 GHz	2.40650 GHz
Span	5.000 MHz	5.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 100
Sweptime	18.938 µs	AUTO
Reference Level	10.000 dBm	10.000 dBm
Attenuation	30.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	30 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.00 dB	0.50 dB


6dB Bandwidth, 2Mbps, 2440MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2440.000000	1.485148	0.500000	---	2439.306931	2440.792079

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2440.000000	5.1	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43750 GHz	2.43750 GHz
Stop Frequency	2.44250 GHz	2.44250 GHz
Span	5.000 MHz	5.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 100
Sweptime	18.938 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	11 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.02 dB	0.50 dB


6dB Bandwidth, 2Mbps, 2478MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2478.000000	1.435643	0.500000	---	2477.306931	2478.742574

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2478.000000	4.7	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47550 GHz	2.47550 GHz
Stop Frequency	2.48050 GHz	2.48050 GHz
Span	5.000 MHz	5.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	101	~ 100
Sweeptime	18.938 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	14 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.35 dB	0.50 dB


99% Occupied Channel Bandwidth, 1Mbps, 2402MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	1.020000	---	---	2401.495000	2402.515000

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2402.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.40400 GHz	2.40400 GHz
Span	4.000 MHz	4.000 MHz
RBW	20.000 kHz	>= 20.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	400	~ 400
SweepTime	94.824 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	37 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.26 dB	0.30 dB


99% Occupied Channel Bandwidth, 1Mbps, 2440MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2440.000000	1.010000	---	---	2439.505000	2440.515000

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2440.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43800 GHz	2.43800 GHz
Stop Frequency	2.44200 GHz	2.44200 GHz
Span	4.000 MHz	4.000 MHz
RBW	20.000 kHz	>= 20.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	400	~ 400
Sweptime	94.824 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	32 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.30 dB


99% Occupied Channel Bandwidth, 1Mbps, 2480MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	1.020000	---	---	2479.495000	2480.515000

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2480.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47800 GHz	2.47800 GHz
Stop Frequency	2.48200 GHz	2.48200 GHz
Span	4.000 MHz	4.000 MHz
RBW	20.000 kHz	>= 20.000 kHz
VBW	100.000 kHz	>= 60.000 kHz
SweepPoints	400	~ 400
Sweptime	94.824 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	43 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.30 dB

99% Occupied Channel Bandwidth, 2Mbps, 2404MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2404.000000	2.042042	---	---	2402.993994	2405.036036

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2404.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40150 GHz	2.40150 GHz
Stop Frequency	2.40650 GHz	2.40650 GHz
Span	5.000 MHz	5.000 MHz
RBW	30.000 kHz	>= 25.000 kHz
VBW	100.000 kHz	>= 90.000 kHz
SweepPoints	333	~ 333
Sweptime	63.218 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	43 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.30 dB


99% Occupied Channel Bandwidth, 2Mbps, 2440MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2440.000000	2.057057	---	---	2438.978979	2441.036036

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2440.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43750 GHz	2.43750 GHz
Stop Frequency	2.44250 GHz	2.44250 GHz
Span	5.000 MHz	5.000 MHz
RBW	30.000 kHz	>= 25.000 kHz
VBW	100.000 kHz	>= 90.000 kHz
SweepPoints	333	~ 333
Sweptime	63.218 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	52 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.30 dB


99% Occupied Channel Bandwidth, 2Mbps, 2478MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2478.000000	2.042042	---	---	2476.978979	2479.021021

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2478.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47550 GHz	2.47550 GHz
Stop Frequency	2.48050 GHz	2.48050 GHz
Span	5.000 MHz	5.000 MHz
RBW	30.000 kHz	>= 25.000 kHz
VBW	100.000 kHz	>= 90.000 kHz
SweepPoints	333	~ 333
Sweptime	63.218 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	31 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.30 dB

5.1.3 Output Power

RESULT:**Pass**

Date of testing : 2026-05-13
Ambient temperature : 21.3°C
Relative humidity : 49.5%
Atmospheric pressure : 101kPa
Test requirement : FCC Part 15.247(b)(3)
RSS-247 Issue 4, July 24, 2025, Clause 6.3.2
Test procedure : ANSI C63.10:2020
ANSI C63.10-2020+Cor. 1-2023+C63.10a-
2024+Errata to C63.10a-2024
Test voltage : DC 3V
Test modes applied : A

Table 9: Peak Output Power

Data Rate	Frequency [MHz]	Peak Conducted Output Power [dBm]	Limit [dBm]
1Mbps	2402	7.0	30
1Mbps	2440	7.1	30
1Mbps	2480	6.3	30
2Mbps	2404	7.1	30
2Mbps	2440	7.2	30
2Mbps	2478	6.5	30

Note:

EIRP=Conducted Output Power + Antenna Gain (-0.38dBi), which is far below the 4 W (36dBm).

5.1.4 Power Spectral Density

RESULT:


Pass

Date of testing	:	2026-05-13
Ambient temperature	:	21.3°C
Relative humidity	:	49.5%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(e) RSS-247 Issue 4, July 24, 2025, Clause 6.3.1(b)
Test procedure	:	ANSI C63.10:2020 ANSI C63.10-2020+Cor. 1-2023+C63.10a- 2024+Errata to C63.10a-2024
Test voltage	:	DC 3V
Test modes applied	:	A

Power Spectral Density, 1Mbps, 2402MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2402.000000	2402.072417	2.115	8.0	PASS

Peak Power Spectral Density



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40144 GHz	2.40144 GHz
Stop Frequency	2.40256 GHz	2.40256 GHz
Span	1.129 MHz	1.129 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	226	~ 226
Sweptime	1.130 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	34 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.38 dB	0.50 dB

Power Spectral Density, 1Mbps, 2440MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2440.000000	2439.937540	2.418	8.0	PASS

Peak Power Spectral Density



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43947 GHz	2.43947 GHz
Stop Frequency	2.44053 GHz	2.44053 GHz
Span	1.069 MHz	1.069 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	214	~ 214
SweepTime	1.070 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	25 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.27 dB	0.50 dB

Power Spectral Density, 1Mbps, 2480MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2480.000000	2479.907605	1.534	8.0	PASS

Peak Power Spectral Density



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47944 GHz	2.47944 GHz
Stop Frequency	2.48056 GHz	2.48056 GHz
Span	1.129 MHz	1.129 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	226	~ 226
Sweeptime	1.130 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	31 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.11 dB	0.50 dB

Power Spectral Density, 2Mbps, 2404MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2404.000000	2403.625267	-0.141	8.0	PASS

Peak Power Spectral Density



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40292 GHz	2.40292 GHz
Stop Frequency	2.40508 GHz	2.40508 GHz
Span	2.153 MHz	2.153 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	431	~ 431
SweepTime	2.160 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	46 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.26 dB	0.50 dB

Power Spectral Density, 2Mbps, 2440MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2440.000000	2439.627881	1.374	8.0	PASS

Peak Power Spectral Density



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.43889 GHz	2.43889 GHz
Stop Frequency	2.44111 GHz	2.44111 GHz
Span	2.228 MHz	2.228 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	446	~ 446
SweepTime	2.230 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	44 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.49 dB	0.50 dB

Power Spectral Density, 2Mbps, 2478MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2478.000000	2477.625267	0.431	8.0	PASS

Peak Power Spectral Density


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47692 GHz	2.47692 GHz
Stop Frequency	2.47908 GHz	2.47908 GHz
Span	2.153 MHz	2.153 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	431	~ 431
SweepTime	2.160 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	47 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.22 dB	0.50 dB

5.1.5 Conducted Band Edge and out-of Band Emissions

RESULT:**Pass**

Date of testing	:	2026-05-13
Ambient temperature	:	21.3°C
Relative humidity	:	49.5%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(d) RSS-247 Issue 4, July 24, 2025, Clause 6.6
Test procedure	:	ANSI C63.10:2020 ANSI C63.10-2020+Cor. 1-2023+C63.10a- 2024+Errata to C63.10a-2024
Test voltage	:	DC 3V
Test modes applied	:	A


Figure 1: Reference level




Figure 2: Conducted Spurious Emission


Figure 3: Conducted Band Edge


5.2 Emission in the Frequency Range up to 30MHz

5.2.1 Conducted Emission

RESULT:**N/A**

Date of testing	:	/
Ambient temperature	:	/
Relative humidity	:	/
Atmospheric pressure	:	/
Test requirement	:	FCC Part 15.207 (a) RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.8
Test procedure	:	ANSI C63.10:2020 ANSI C63.10-2020+Cor. 1-2023+C63.10a- 2024+Errata to C63.10a-2024
Test voltage	:	/
Test modes applied	:	/

Note: This product is power by battery, so it is not applicable for this test.

5.3 Emission in the Frequency Range above 30MHz


5.3.1 Radiated Band-Edge

RESULT:**Pass**

Date of testing	:	2026-05-22
Ambient temperature	:	20.5°C
Relative humidity	:	48.6%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(d) FCC Part 15.205(a) FCC Part 15.209(a) RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.9 RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.10 RSS-247 Issue 4, July 24, 2025, Clause 6.6
Test procedure	:	ANSI C63.10:2020 ANSI C63.10-2020+Cor. 1-2023+C63.10a- 2024+Errata to C63.10a-2024
Test voltage	:	DC 3V
Test modes applied	:	A

Figure 4: Radiated Band-Edge, 1Mbps, 2402MHz, H

XXY- 2310~ 2410 BE 1-18GHz_HL050_FSV40_Pre-10-YUNFANG


Figure 5: Radiated Band-Edge, 1Mbps, 2402MHz, V

XXY- 2310~ 2410 BE 1-18GHz_HL050_FSV40_Pre-10-YUNFANG





Figure 6: Radiated Band-Edge, 1Mbps, 2480MHz, H

XXY-2470° 2500 BE_1-18GHz_HL050_FSV40_Pre-10-YUNFANG


Figure 7: Radiated Band-Edge, 1Mbps, 2480MHz, V

XXY-2470° 2500 BE_1-18GHz_HL050_FSV40_Pre-10-YUNFANG





Figure 8: Radiated Band-Edge, 2Mbps, 2404MHz, H

XXY- 2310~ 2410 BE 1-18GHz_HL050_FSV40_Pre-10-YUNFANG


Figure 9: Radiated Band-Edge, 2Mbps, 2404MHz, V

XXY- 2310~ 2410 BE 1-18GHz_HL050_FSV40_Pre-10-YUNFANG






Figure 10: Radiated Band-Edge, 2Mbps, 2478MHz, H

XXY-2470° 2500 BE_1-18GHz_HL050_FSV40_Pre-10-YUNFANG


Figure 11: Radiated Band-Edge, 2Mbps, 2478MHz, V

XXY-2470° 2500 BE_1-18GHz_HL050_FSV40_Pre-10-YUNFANG




5.3.2 Radiated Spurious Emission**RESULT:****Pass**

Date of testing	:	2026-05-22
Ambient temperature	:	20.5°C
Relative humidity	:	48.6%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(d) FCC Part 15.209(a) RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.9 RSS-247 Issue 4, July 24, 2025, Clause 6.6
Test procedure	:	ANSI C63.10:2020 ANSI C63.10-2020+Cor. 1-2023+C63.10a- 2024+Errata to C63.10a-2024
Test voltage	:	DC 3V
Test modes applied	:	A

Note:

1. Only the worst case is shown in the report.
2. For the frequency range from 18GHz to 25GHz, no emission was found.

Figure 12: Radiated Spurious Emission, 2Mbps, 2404MHz


Limit and Margin
QP


Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
30.121250	21.3	H	25.3	18.7	40.0
33.758750	19.0	H	23.3	21.0	40.0
265.467500	22.3	H	21.2	23.7	46.0
305.601250	26.8	H	20.5	19.2	46.0
316.392500	27.6	H	20.5	18.4	46.0
325.365000	27.5	H	21.3	18.5	46.0
30.363750	21.2	V	25.2	18.8	40.0
108.327500	13.9	V	18.5	29.6	43.5
132.941250	21.1	V	18.4	22.4	43.5
531.611250	26.0	V	25.1	20.0	46.0
591.023750	26.6	V	26.4	19.4	46.0
666.562500	30.5	V	26.6	15.5	46.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1598.909091	35.5	H	-18.9	38.5	74.0
2166.454546	37.6	H	-16.0	36.4	74.0
4809.727273	48.6	H	-11.2	25.4	74.0
8032.281250	48.2	H	-3.4	25.8	74.0
10950.718750	49.9	H	-1.5	24.1	74.0
17984.187500	58.9	H	11.8	15.1	74.0
1864.545455	46.8	V	-18.5	27.2	74.0
2124.727273	46.4	V	-16.5	27.6	74.0
4807.818182	54.0	V	-11.2	20.0	74.0
8011.312500	47.8	V	-3.3	26.2	74.0
9615.593750	49.5	V	-4.4	24.5	74.0
17998.625000	59.7	V	12.1	14.3	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1598.909091	29.1	H	-18.9	24.9	54.0
2166.454546	28.5	H	-16.0	25.5	54.0
4809.727273	43.8	H	-11.2	10.2	54.0
8032.281250	37.7	H	-3.4	16.3	54.0
10950.718750	38.2	H	-1.5	15.8	54.0
17984.187500	47.9	H	11.8	6.1	54.0
1864.545455	36.2	V	-18.5	17.8	54.0
2124.727273	35.3	V	-16.5	18.7	54.0
4807.818182	50.0	V	-11.2	4.1	54.0
8011.312500	37.6	V	-3.3	16.4	54.0
9615.593750	42.4	V	-4.4	11.6	54.0
17998.625000	48.9	V	12.1	5.1	54.0

Figure 13: Radiated Spurious Emission, 2Mbps, 2440MHz


Prüfbericht - Nr.: CN26AIB9 001
Test Report No.
Seite 50 von 53
Page 50 of 53
Limit and Margin
QP


Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
30.485000	21.1	H	25.2	18.9	40.0
35.577500	18.0	H	22.3	22.0	40.0
265.710000	20.5	H	21.2	25.5	46.0
301.236250	25.6	H	20.9	20.4	46.0
316.392500	27.8	H	20.5	18.2	46.0
325.122500	27.4	H	21.3	18.6	46.0
30.485000	21.2	V	25.2	18.8	40.0
132.941250	21.4	V	18.4	22.1	43.5
148.340000	17.8	V	17.2	25.8	43.5
447.342500	19.8	V	23.8	26.2	46.0
530.883750	28.8	V	25.1	17.2	46.0
664.501250	25.6	V	26.6	20.5	46.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1462.818182	38.1	H	-18.6	35.9	74.0
1760.363636	39.9	H	-18.8	34.1	74.0
4879.818182	46.7	H	-11.1	27.3	74.0
8031.250000	47.6	H	-3.4	26.4	74.0
10565.718750	48.4	H	-1.4	25.6	74.0
17981.781250	57.1	H	11.8	16.9	74.0
1593.454546	38.8	V	-18.9	35.2	74.0
2189.636364	39.9	V	-15.8	34.1	74.0
4879.818182	52.3	V	-11.1	21.7	74.0
7319.343750	45.3	V	-6.3	28.7	74.0
11152.843750	48.3	V	-2.4	25.7	74.0
17983.500000	59.7	V	11.8	14.3	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1462.818182	29.4	H	-18.6	24.6	54.0
1760.363636	34.5	H	-18.8	19.6	54.0
4879.818182	41.1	H	-11.1	12.9	54.0
8031.250000	36.5	H	-3.4	17.5	54.0
10565.718750	37.2	H	-1.4	16.9	54.0
17981.781250	47.9	H	11.8	6.1	54.0
1593.454546	33.4	V	-18.9	20.6	54.0
2189.636364	30.9	V	-15.8	23.1	54.0
4879.818182	46.9	V	-11.1	7.1	54.0
7319.343750	37.2	V	-6.3	16.8	54.0
11152.843750	37.6	V	-2.4	16.5	54.0
17983.500000	48.6	V	11.8	5.4	54.0

Figure 14: Radiated Spurious Emission, 2Mbps, 2478MHz


Limit and Margin
QP

Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
30.485000	21.2	H	25.2	18.8	40.0
35.092500	18.2	H	22.6	21.8	40.0
283.291250	21.1	H	19.7	24.9	46.0
300.630000	23.8	H	20.8	22.2	46.0
311.906250	26.1	H	20.1	19.9	46.0
321.000000	27.0	H	21.1	19.0	46.0
31.091250	20.8	V	24.8	19.2	40.0
53.037500	9.5	V	13.8	30.5	40.0
132.335000	20.5	V	18.5	23.0	43.5
330.093750	17.3	V	21.4	28.7	46.0
532.096250	22.2	V	25.0	23.8	46.0
665.592500	24.3	V	26.6	21.7	46.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1803.727273	40.1	H	-18.7	33.9	74.0
2260.545455	43.1	H	-15.6	30.9	74.0
4958.090909	44.3	H	-11.0	29.7	74.0
8023.687500	47.4	H	-3.4	26.6	74.0
10576.718750	49.0	H	-1.2	25.0	74.0
17998.281250	60.3	H	12.1	13.7	74.0
1989.454546	41.3	V	-17.8	32.7	74.0
2188.818182	42.1	V	-15.8	31.9	74.0
4957.545455	47.1	V	-11.0	26.9	74.0
7434.156250	45.1	V	-5.8	28.9	74.0
10504.875000	48.5	V	-1.9	25.5	74.0
17993.812500	59.6	V	12.0	14.4	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1803.727273	31.0	H	-18.7	23.0	54.0
2260.545455	31.2	H	-15.6	22.8	54.0
4958.090909	40.0	H	-11.0	14.0	54.0
8023.687500	36.5	H	-3.4	17.5	54.0
10576.718750	37.2	H	-1.2	16.8	54.0
17998.281250	48.8	H	12.1	5.2	54.0
1989.454546	31.0	V	-17.8	23.0	54.0
2188.818182	31.0	V	-15.8	23.0	54.0
4957.545455	43.2	V	-11.0	10.8	54.0
7434.156250	36.1	V	-5.8	17.9	54.0
10504.875000	37.3	V	-1.9	16.7	54.0
17993.812500	48.9	V	12.0	5.1	54.0

6. List of Tables

Table 1: List of Test and Measurement Equipment	7
Table 2: Measurement Uncertainty	8
Table 3: Technical Specification of EUT	9
Table 4: Operation Channel List	10
Table 5: Power parameter value	11
Table 6: Special Accessories	11
Table 7: Auxiliary Equipment	11
Table 8: Antenna Requirement	13
Table 9: Peak Output Power	28

7. List of Figures

Figure 1: Reference level	37
Figure 2: Conducted Spurious Emission	38
Figure 3: Conducted Band Edge	39
Figure 4: Radiated Band-Edge, 1Mbps, 2402MHz, H	42
Figure 5: Radiated Band-Edge, 1Mbps, 2402MHz, V	42
Figure 6: Radiated Band-Edge, 1Mbps, 2480MHz, H	43
Figure 7: Radiated Band-Edge, 1Mbps, 2480MHz, V	43
Figure 8: Radiated Band-Edge, 2Mbps, 2404MHz, H	44
Figure 9: Radiated Band-Edge, 2Mbps, 2404MHz, V	44
Figure 10: Radiated Band-Edge, 2Mbps, 2478MHz, H	45
Figure 11: Radiated Band-Edge, 2Mbps, 2478MHz, V	45
Figure 12: Radiated Spurious Emission, 2Mbps, 2404MHz	47
Figure 13: Radiated Spurious Emission, 2Mbps, 2440MHz	49
Figure 14: Radiated Spurious Emission, 2Mbps, 2478MHz	51