


Prüfbericht-Nr.: Test Report No.:	CN26DAWC 001	Auftrags-Nr.: Order No.:	326173638	Seite 1 von 19 Page 1 of 19
Kunden-Referenz-Nr.: Client Reference No.:	1288983	Auftragsdatum: Order date.:	2026-02-24	
Auftraggeber: Client:	IKEA of Sweden AB Box 702, SE-343 81, Älmhult Sweden			
Prüfgegenstand: Test item:	Remote control (Scroll wheel)			
Bezeichnung / Typ-Nr.: Identification / Type No.:	E2704			
Auftrags-Inhalt: Order content:	TÜV Rheinland EMC service			
Prüfgrundlage: Test specification:	FCC 47 CFR Part 15, Subpart B:2024 Class B ICES-003:2020			
Wareneingangsdatum: Date of receipt:	2026-03-09	Refer to the EUT photos file		
Prüfmuster-Nr.: Test sample No.:	A004219861-008			
Prüfzeitraum: Testing period:	2026-04-17			
Ort der Prüfung: Place of testing:	Refer to clause 1.1			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: / tested by:  XueLan Zhang		genehmigt von: / authorized by:  JiaYi Zhou		
Datum: / Date: 2026-06-22		Ausstellungsdatum: / Issue date: 2026-06-22		
Stellung: / Position: Project engineer		Stellung: / Position: Authorizer		
Sonstiges / Other:	FCC ID: FHO-E704 IC: 10912A-E2704 Test Firm Name: TUV Rheinland (Shanghai) Co., Ltd. Designation Number: CN1396 Test Firm Registration Number: 930979			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:		Prüfmuster vollständig und unbeschädigt Test item complete and undamaged		
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: P(ass) = passed a.m. test specifications(s) F(ail) = failed a.m. test specifications(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht - Nr.: CN26DAWC 001

Seite 2 von 19

Test Report No.:

Page 2 of 19

Anmerkungen
Remarks

- | | |
|----------|--|
| 1 | <p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.
Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system.</i></p> <p><i>Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p> |
| 2 | <p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i></p> |
| 3 | <p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben.
Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i></p> <p><i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p> |
| 4 | <p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p> |

Prüfbericht - Nr.: CN26DAWC 001

Test Report No.:

Seite 3 von 19

Page 3 of 19

Revision history of test report:

Report number	Issue date	Contents and reason for change if appropriate
CN26DAWC 001	2026-06-22	Initial release.

Contents

1	TEST SITES	5
1.1	TEST FACILITIES	5
2	GENERAL PRODUCT INFORMATION	6
2.1	PRODUCT FUNCTION AND INTENDED USE	6
2.2	RATINGS AND SYSTEM DETAILS	6
2.3	INDEPENDENT OPERATION MODESS	6
2.4	DESCRIPTION OF INTERCONNECTING CABLES.....	6
2.5	NOISE GENERATING AND NOISE SUPPRESSING PARTS	6
2.6	HIGHEST FREQUENCY GENERATED OR USED IN THE DEVICE OR ON WHICH THE DEVICE OPERATES OR TUNES	6
2.7	SUBMITTED DOCUMENTS.....	6
3	TEST SET-UP AND OPERATION MODES	7
3.1	PRINCIPLE OF CONFIGURATION SELECTION	7
3.2	EQUIPMENT AND CABLE ARRANGEMENT.....	7
3.3	TEST SOFTWARE	7
3.4	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	7
3.5	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	7
4	CONFORMITY DECISION RULE	8
5	TEST RESULTS EMISSION	9
5.1	EMISSION IN THE FREQUENCY RANGE ABOVE 30 MHz.....	9
5.1.1	Radiated emission (30 MHz - 1 GHz)	9
5.1.2	Radiated emission (Above 1 GHz).....	13
6	PHOTOGRAPHS OF THE TEST SET-UP.....	17
7	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	18
8	LIST OF FIGURES.....	19

Prüfbericht - Nr.: CN26DAWC 001

Test Report No.:

Seite 5 von 19

Page 5 of 19

1 Test Sites

1.1 Test Facilities

Laboratory: TÜV Rheinland (Shanghai) Co., Ltd.

Address: Workshop14, North Half of Workshop 10 and Workshop 16, Pingqian (Taicang) Modern Industrial Park, No.525, Yuewang Lingang South Road, Shaxi, Taicang, Jiangsu, China

The used test equipment is in accordance with CISPR 16-1 series standards for measurement of radio interference.

Refer to Clause 6 for test and measurement instruments.

2 General Product Information

2.1 Product Function and Intended Use

The EUT (equipment under test) is a Remote control (Scroll wheel). For the further information, refer to the user's manual.

2.2 Ratings and System Details

Rated input : 2.4 V/3.0 V, 2*AAA

2.3 Independent Operation Modess

The basic operation mode is on by 2.4 GHz wireless connection.

2.4 Description of interconnecting cables

None.

2.5 Noise Generating and Noise Suppressing Parts

Refer to the circuit diagram for further information.

2.6 Highest frequency generated or used in the device or on which the device operates or tunes

The highest frequency used in the EUT is 2.4 GHz.

2.7 Submitted Documents

Circuit diagram, user's manual and rating label.

3 Test Set-up and Operation Modes

3.1 Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible emission level. The test conditions were adapted accordingly in reference to the instructions for use.


Refer to the related paragraph of this report.

The sequence of testing:

1. Radiated emission tests were performed on 2026-04-17.

3.2 Equipment and cable arrangement

Block diagram for radiated emission tests is as follows:



3.3 Test Software

No special test software was used during the tests.

3.4 Special Accessories and Auxiliary Equipment

During the tests, the below equipment were used.

No.	Equipment	Model	Manufacturer
1	Lamp	T2504	IKEA

3.5 Countermeasures to achieve EMC Compliance

No other special measure is employed to achieve the requirement.

4 Conformity Decision Rule

For all EMI tests included in this report, as measurement uncertainties are less than the values U_{CISPR} given in CISPR 16-4-2, compliance with the limits is determined by comparing measurement results directly with corresponding limits without taking into consideration of measurement uncertainties.

5 Test Results EMISSION

5.1 Emission in the Frequency Range above 30 MHz

5.1.1 Radiated emission (30 MHz - 1 GHz)

Result:		Passed
Date of testing	: 2026-04-17	
Test procedure	: FCC 47 CFR Part 15, Subpart B:2024, ICES-003:2020, ANSI C63.4-2014 and CISPR 16-2-3	
Frequency range	: 30 – 1000 MHz	
Limits	: Quasi-peak limits (3 m distance): 30 – 88 MHz, 40 dB μ V/m; 88 – 216 MHz, 43.5 dB μ V/m; 216 – 960 MHz, 46 dB μ V/m; Above 960 MHz, 54 dB μ V/m (see Note 1)	
Bandwidth of EMI receiver for final measurement	: 120 kHz	
Measurement time for final measurement	: 1 s	
Kind of test site	: Semi-anechoic chamber	
Operational mode	: Mode as defined in clause 2.3	
Input voltage	: 2*AAA (see Note 2)	
Ambient condition	: Temperature: 21.1 °C; Relative humidity: 48.4 %	
Expanded measurement uncertainty ($k=2$)	: 5.40 dB The minimum margin to the limit is 19.1 dB at 31.212500 MHz. The margin is higher than expanded measurement uncertainty.	
Test setup photo	: Photograph 2 of Attachment 1	

The radiated disturbance test was carried out in a semi-anechoic chamber. The test distance from the receiving antenna to the EUT is 3 m. The normalized site attenuation of the semi-anechoic chamber is regularly calibrated to ensure the radiated disturbance test results are valid. During the test, the EUT was placed on a 0.8 m high wooden table above the reference ground plane. The wooden table was rotated 360° around and the height of the antenna was varied from 1 m to 4 m to find the maximum disturbance. The test was performed with the antenna both in its horizontal and vertical polarizations.

The following figures and tables were those measured by an automatic measurement system.

Prüfbericht - Nr.: CN26DAWC 001

Test Report No.:

Seite 10 von 19

Page 10 of 19

A preview test was firstly performed with peak detector. The final test was performed with quasi-peak at those critical frequencies during the preview test. In the following spectral diagram, “x” means quasi-peak test results.

Note 1: The class B limits of FCC 47 CFR Part 15, Subpart B:2024 is stricter than those ICES-003:2020 for 3 m test distance. Therefore, the former limits are used in following figures and tables.

Note 2: After the pretest on the voltage of DC 2.4 V and DC 3 V, only the data of worst case was shown in the report.

Notes on following tables of radiated emission results and conversions:

QuasiPeak (dB μ V/m): final measurement results by using quasi-peak detector

Corr. (dB): correction factor including: antenna factor, cable loss, and gain of pre-amplifier (if used)

Margin: Limit (dB μ V/m) - QuasiPeak (dB μ V/m)


Prüfbericht - Nr.: CN26DAWC 001

Test Report No.:

Seite 11 von 19

Page 11 of 19

Figure 1: Spectral Diagrams and measurement results, horizontal polarization (30 MHz to 1 GHz)




Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBμV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
31.212500	21.0	120.000	168.0	H	162.0	24.8	19.1	40.0
35.092500	18.5	120.000	110.0	H	138.0	22.6	21.5	40.0
113.420000	14.3	120.000	190.0	H	46.0	18.7	29.2	43.5
134.517500	14.1	120.000	103.0	H	109.0	18.3	29.4	43.5
419.212500	20.3	120.000	200.0	H	-78.0	24.0	25.7	46.0
683.295000	24.2	120.000	100.0	H	-11.0	27.1	21.8	46.0

Prüfbericht - Nr.: CN26DAWC 001
Test Report No.:

Seite 12 von 19
Page 12 of 19

Figure 2: Spectral Diagrams and measurement results, vertical polarization (30 MHz to 1 GHz)



Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBμV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
31.212500	20.9	120.000	120.0	V	12.0	24.8	19.1	40.0
35.941250	18.1	120.000	106.0	V	93.0	22.1	21.9	40.0
60.070000	17.9	120.000	118.0	V	-49.0	12.7	22.1	40.0
107.478750	13.8	120.000	178.0	V	-112.0	18.4	29.7	43.5
148.340000	17.5	120.000	130.0	V	-132.0	17.2	26.0	43.5
545.797500	22.7	120.000	180.0	V	-97.0	26.2	23.4	46.0

Prüfbericht - Nr.: CN26DAWC 001

Test Report No.:

Seite 13 von 19

Page 13 of 19

5.1.2 Radiated emission (Above 1 GHz)

Result:	Passed
----------------	---------------

Date of testing	: 2026-04-17
Port	: Enclosure
Test procedure	: FCC 47 CFR Part 15, Subpart B:2024, ANSI C63.4-2014 and CISPR 16-2-3 ICES-003:2020
Limit	: Above 1 GHz, Peak limit: 74 dB μ V/m; Average limit: 54 dB μ V/m
Frequency range	: 1-18 GHz Note: The highest frequency in the EUT is 2.4 GHz. According to FCC Part 15 subpart B §15.33 (b) (1), the upper frequency for radiated emission measurement is 12 GHz. The actual test frequency is up to 18 GHz.
Bandwidth of EMI receiver for final measurement	: 1000 kHz
Measurement time for final measurement	: 1 s
Test distance	: 3 m
Kind of test site	: Semi-anechoic chamber
Operational mode	: Mode as defined in clause 2.3
Input voltage	: 2*AAA (see Note 1)
Earthing	: No earthing
Ambient condition	: Temperature: 21.1 °C; Relative humidity: 48.4 %
Expanded measurement uncertainty ($k=2$)	: 5.08 dB The minimum margin to the limit is 6.2 dB at 17988.843750 MHz. The margin is higher than expanded measurement uncertainty.
Test setup photo	: Photograph 2 of Attachment 1

The radiated disturbance test was carried out in a semi-anechoic chamber. The test distance from the receiving antenna to the EUT is 3 m. The normalized site attenuation of the semi-anechoic chamber is regularly calibrated to ensure the radiated disturbance test results are valid. During the test, the EUT was placed on a poly table, which is 0.8 m high. The wooden table was rotated 360° around and the antenna was varied from 1 m to 4 m to find the maximum disturbance. The test was performed with the antenna both in its horizontal and vertical polarizations.

The following figures and tables were those measured by an automatic measurement system. The final test was performed with peak detector and average detector at those critical frequencies during the preview test. In the following figure, “**x**” means measurement results with peak detector and “**+**” means measurement results with average detector.

Note 1: After the pretest on the voltage of DC 2.4 V and DC 3 V, only the data of worst case was shown in the report.

Prüfbericht - Nr.: CN26DAWC 001

Test Report No.:

Seite 14 von 19

Page 14 of 19

Notes on following tables of radiated emission results and conversions:

Peak (dB μ V/m): final measurement results by using peak detector

Average (dB μ V/m): final measurement results by using average detector

Corr. (dB): correction factor including: antenna factor, cable loss, and gain of pre-amplifier (if used)


Margin: Limit PK (dB μ V/m) - Peak (dB μ V/m)

Limit CAV (dB μ V/m) – Average (dB μ V/m)

Prüfbericht - Nr.: CN26DAWC 001
Test Report No.:

Seite 15 von 19
Page 15 of 19

Figure 3: Spectral Diagrams and measurement results, 1-18 GHz, horizontal polarization




Final Peak measurement results:

Frequency (MHz)	MaxPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBμV/m)
1082.000000	32.9	1000.0	1000.000	130.0	H	18.0	-19.9	41.1	74.0
2203.500000	35.7	1000.0	1000.000	110.0	H	26.0	-15.7	38.3	74.0
5026.000000	41.3	1000.0	1000.000	168.0	H	113.0	-10.8	32.7	74.0
7146.500000	46.4	1000.0	1000.000	200.0	H	172.0	-5.3	27.6	74.0
14472.000000	52.3	1000.0	1000.000	100.0	H	-32.0	2.7	21.7	74.0
17984.500000	59.5	1000.0	1000.000	130.0	H	-11.0	11.8	14.5	74.0

Final Average measurement results:

Frequency (MHz)	Average (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBμV/m)
1082.000000	22.0	1000.0	1000.000	130.0	H	18.0	-19.9	32.1	54.0
2203.500000	24.4	1000.0	1000.000	110.0	H	26.0	-15.7	29.6	54.0
5026.000000	28.8	1000.0	1000.000	168.0	H	113.0	-10.8	25.2	54.0
7146.500000	35.6	1000.0	1000.000	200.0	H	172.0	-5.3	18.4	54.0
14472.000000	41.4	1000.0	1000.000	100.0	H	-32.0	2.7	12.6	54.0
17984.500000	47.7	1000.0	1000.000	130.0	H	-11.0	11.8	6.4	54.0

Figure 4: Spectral Diagrams and measurement results, 1-18 GHz, vertical polarization



Final Peak measurement results:

Frequency (MHz)	MaxPeak (dB μ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dB μ V/m)
1332.031250	32.9	1000.0	1000.000	120.0	V	-12.0	-18.7	41.1	74.0
2746.750000	36.8	1000.0	1000.000	113.0	V	-78.0	-15.2	37.2	74.0
3603.656250	38.1	1000.0	1000.000	200.0	V	-46.0	-14.1	35.9	74.0
7120.000000	45.5	1000.0	1000.000	120.0	V	-103.0	-5.0	28.5	74.0
13895.031250	51.6	1000.0	1000.000	130.0	V	41.0	1.1	22.4	74.0
17988.843750	59.0	1000.0	1000.000	100.0	V	-89.0	11.9	15.0	74.0

Final Average measurement results:

Frequency (MHz)	Average (dB μ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dB μ V/m)
1332.031250	21.9	1000.0	1000.000	120.0	V	-12.0	-18.7	32.1	54.0
2746.750000	24.7	1000.0	1000.000	113.0	V	-78.0	-15.2	29.3	54.0
3603.656250	25.5	1000.0	1000.000	200.0	V	-46.0	-14.1	28.5	54.0
7120.000000	34.8	1000.0	1000.000	120.0	V	-103.0	-5.0	19.2	54.0
13895.031250	39.4	1000.0	1000.000	130.0	V	41.0	1.1	14.6	54.0
17988.843750	47.8	1000.0	1000.000	100.0	V	-89.0	11.9	6.2	54.0

Prüfbericht - Nr.: CN26DAWC 001
Test Report No.:

Seite 17 von 19
Page 17 of 19

6 Photographs of the Test Set-Up

Refer to the test setup file.

Prüfbericht - Nr.: CN26DAWC 001

Test Report No.:

Seite 18 von 19

Page 18 of 19

7 List of Test and Measurement Instruments

Equip. no.	Equipment name	Model	Serial no.	Manufacturer	Cal. date	Due date
EMC-S-032	EMI measurement software	EMC32-MEB (10.60.20)	100697	Rohde & Schwarz	N/A	N/A
EMC-C-155	BiLog antenna	CBL 6112D	40530	Teseq	2025-03-24	2026-09-24
EMC-C-121	Thermohygrometer	608-H1	1241320265	testo	2025-06-05	2026-06-05
EMC-C-066	EMI test receiver	ESCI	100280	Rohde & Schwarz	2025-09-28	2026-09-28
EMC-C-001	3 m semi-anechoic chamber	SAC3	FJ129002	Frankonia	2023-12-03	2026-12-03
EMC-C-175	Preamplifier	EMC051845SE	980612	EMCI Taiwan	2025-07-11	2026-07-11
EMC-C-161	Spectrum analyser	FSV40	101258	Rohde & Schwarz	2025-07-11	2026-07-11
EMC-C-019	Double ridged horn antenna	BBHA 9120 D	9120D-433	Schwarzbeck	2025-02-28	2026-08-28

Prüfbericht - Nr.: CN26DAWC 001
Test Report No.:

Seite 19 von 19
Page 19 of 19

8 List of Figures

Figure 1: Spectral Diagrams and measurement results, horizontal polarization (30 MHz to 1 GHz)	11
Figure 2: Spectral Diagrams and measurement results, vertical polarization (30 MHz to 1 GHz)	12
Figure 3: Spectral Diagrams and measurement results, 1-18 GHz, horizontal polarization.....	15
Figure 4: Spectral Diagrams and measurement results, 1-18 GHz, vertical polarization.....	16

End of test report