

Prüfbericht-Nr.: Test report no.:	CN26V7ST 001	Auftrags-Nr.: Order no.:	326173638	Seite 1 von 40 Page 1 of 40
Kunden-Referenz-Nr.: Client reference no.:	1288983	Auftragsdatum: Order date:	2026-02-24	
Auftraggeber: Client:	IKEA of Sweden AB Box 702, SE-343 81 Älmhult, Sweden			
Prüfgegenstand: Test item:	Remote Control (Scroll Wheel)			
Bezeichnung / Typ-Nr.: Identification / Type no.:	E2704			
Auftrags-Inhalt: Order content:	Test Report			
Prüfgrundlage: Test specification:	FCC CFR47 Part 15, Subpart C Section 15.247 RSS-Gen Issue 5, Amendment 2, February 2021 RSS-247 Issue 4, July 24, 2025			
Wareneingangsdatum: Date of sample receipt:	2026-03-26	Refer to photo document.		
Prüfmuster-Nr.: Test sample no.:	A004235068-004			
Prüfzeitraum: Testing period:	2026-05-13 ~ 2026-05-22			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:	X <u>Hongfei Wu</u> Signed by: Hongfei Wu		genehmigt von: authorized by:	X <u>Weidong Wang</u> Signed by: Weidong Wang
Datum: Date:	2026-06-11		Datum: Date:	2026-06-11
Stellung / Position:	Sachverständige(r)/Expert		Stellung / Position:	Sachverständige(r)/Expert
Sonstiges / Other:	FCC ID: FHO-E2704 IC: 10912A-E2704 HVIN: E2704 PMN: BILRESA This report is for Zigbee.			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
* Legend:	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.: CN26V7ST 001
Test report no.:

Seite 2 von 40
Page 2 of 40

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 6dB & 99% BANDWIDTH

RESULT: Pass

5.1.3 OUTPUT POWER

RESULT: Pass

5.1.4 POWER SPECTRAL DENSITY

RESULT: Pass

5.1.5 CONDUCTED BAND EDGE AND OUT-OF BAND EMISSIONS

RESULT: Pass

5.2.1 CONDUCTED EMISSION

RESULT: N/A

5.3.1 RADIATED BAND-EDGE

RESULT: Pass

5.3.2 RADIATED SPURIOUS EMISSION

RESULT: Pass

Contents

1.	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS.....	5
2.	TEST SITES	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	7
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY	8
3.	GENERAL PRODUCT INFORMATION.....	9
3.1	PRODUCT FUNCTION AND INTENDED USE	9
3.2	RATINGS AND SYSTEM DETAILS.....	9
3.3	INDEPENDENT OPERATION MODES.....	9
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	10
4.	TEST SET-UP AND OPERATION MODES.....	11
4.1	PRINCIPLE OF CONFIGURATION SELECTION	11
4.2	TEST OPERATION AND TEST SOFTWARE.....	11
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	11
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	12
5.	TEST RESULTS	13
5.1	CONDUCTED TESTING AT ANTENNA PORT	13
5.1.1	<i>Antenna Requirement.....</i>	<i>13</i>
5.1.2	<i>6dB & 99% Bandwidth.....</i>	<i>15</i>
5.1.3	<i>Output Power</i>	<i>21</i>
5.1.4	<i>Power Spectral Density</i>	<i>23</i>
5.1.5	<i>Conducted Band Edge and out-of Band Emissions.....</i>	<i>27</i>
5.2	EMISSION IN THE FREQUENCY RANGE UP TO 30MHz.....	29
5.2.1	<i>Conducted Emission.....</i>	<i>29</i>
5.3	EMISSION IN THE FREQUENCY RANGE ABOVE 30MHz	30
5.3.1	<i>Radiated Band-Edge</i>	<i>30</i>
5.3.2	<i>Radiated Spurious Emission.....</i>	<i>33</i>
6.	LIST OF TABLES	40
7.	LIST OF FIGURES	40

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

2. Test Sites

2.1 Test Facilities

TÜV Rheinland (Shanghai) Co., Ltd.

Workshop 14, North Half of Workshop 10 and Workshop 16, Pingqian (Taicang) Modern Industrial Park, No.525, Yuewang Lingang South Road, Shaxi, Taicang, Jiangsu, China

The used test equipment is in accordance with CISPR 16 for measurement of radio interference.

The Federal Communications Commission has reviewed the technical characteristics of the radiated and conducted emission facility, and has found these test facilities to be in compliance with the requirements of section 2.948 of the FCC rules. The description of the test facility is listed under FCC registration number 930979.

The Innovation, Science and Economic Development Canada has reviewed the technical characteristics of the radiated and conducted emission facility, and has found these test facilities to be in compliance. The description of the test facility is listed under chambers filing number 33038.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Equip.	Description	Model	Manufacturer	Due Date
EMC-C-196	Wireless connectivity tester	CMW270	Rohde & Schwarz	2027-08-09
EMC-C-302	Signal generator	SMB100B (6 GHz)	Rohde & Schwarz	2026-11-27
EMC-C-303	Vector Signal generator	SMW200A	Rohde & Schwarz	2026-11-27
EMC-C-304	OSP	OSP-B157W8	Rohde & Schwarz	2026-12-17
EMC-C-161	Spectrum analyser	FSV40	Rohde&Schwarz	2026-07-11
EMC-C-019	Double ridged horn antenna	BBHA 9120 D	Schwarzbeck	2026-08-28
EMC-C-066	EMI test receiver	ESCI	Rohde&Schwarz	2026-09-28
EMC-C-068	Broadband horn antenna	BBHA 9170	Schwarzbeck	2028-06-18
EMC-C-155	BiLog antenna	CBL 6112D	Teseq	2026-09-24
EMC-C-175	Preamplifier	EMC051845SE	EMCI Taiwan	2026-07-11
EMC-C-176	Preamplifier	EMC184045SE	EMCI Taiwan	2026-07-11
EMC-C-001	3 m semi-anechoic chamber	SAC3	Frankonia	2026-12-03
software				
EMC-S-036	RF measurement software	WMS32-WB (11.40.00)	Rohde&Schwarz	NA
EMC-S-032	EMI measurement software	EMC32-E+ (10.60.20)	Rohde&Schwarz	NA

2.3 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

Table 2: Measurement Uncertainty

Measurement Type	Frequency	Uncertainty
Antenna Port Conducted Emission	< 1GHz	±0.39dB
	> 1GHz	±0.68dB
Conducted Emission	150kHz - 30MHz	±2.33dB
Radiated Emission	9kHz - 30MHz	±2.93dB
	30MHz - 1GHz	±5.34dB
	> 1GHz	±5.40dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT (Equipment Under Test) is a Remote Control (Scroll Wheel) which support Bluetooth Low Enegy, Zigbee and Thread.

The aim of this report is to evaluate RF character of Zigbee of the EUT.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Description of EUT	
Product Name:	Remote Control (Scroll Wheel)
Model No.:	E2704
Test Voltage:	DC 3V
RF Technical:	1) BLE 2) Zigbee 3) Thread
Technical Specification of Zigbee	
Frequency Range:	2405~2480MHz
Modulation Type:	OQPSK
Antenna Type:	Metal Antenna
Antenna Gain:	-0.38 dBi (declared by client)

Note: After the pretest on the voltage of DC 2.4V and DC 3V, only the test result of the worst case is shown in the report.

Table 4: Operation Channel List

RF Channel	Frequency [MHz]	RF Channel	Frequency [MHz]	RF Channel	Frequency [MHz]	RF Channel	Frequency [MHz]
11	2405	15	2425	19	2445	23	2465
12	2410	16	2430	20	2450	24	2470
13	2415	17	2435	21	2455	25	2475
14	2420	18	2440	22	2460	26	2480

3.3 Independent Operation Modes

Test frequencies are lowest channel: 2405 MHz, middle channel: 2445 MHz and highest channel: 2480 MHz

The basic operation modes are:

- A. Zigbee transmitting mode

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10:2020 and ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024+Errata to C63.10a-2024.

Test Software: sscom 5.13.1

Table 5: Power parameter value

Mode	Power Parameter Setting Value
Zigbee	7

4.3 Special Accessories and Auxiliary Equipment

Table 6: Special Accessories

Accessories	Parameter
RF Cable between the antenna port and test system	Cable loss: 0.5dB

Note: The RF cable used in the test was provided by

- ☒ Client
☐ Test Lab

And the cable loss has been factored in the related test.

Table 7: Auxiliary Equipment

Equipment	Brand	Model
Laptop	Lenovo	21AJ-S57N0J

Prüfbericht - Nr.: CN26V7ST 001
Test Report No.

Seite 12 von 40
Page 12 of 40

4.4 Countermeasures to achieve EMC Compliance

Null.

5. Test Results

5.1 Conducted Testing at Antenna Port

5.1.1 Antenna Requirement

RESULT:**Pass**

According to the manufacturer declared, the EUT has one internal Metal antenna, the directional gain of antenna is -0.38 dBi and the antenna is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Table 8: Antenna Requirement

FCC 15.203 – Antenna Requirement 1		
Requirement:	No antenna other than that furnished by the responsible party shall be used with the device	
Results:	Antenna type:	Metal Antenna
Verdict:	Pass	

FCC 15.204 – Antenna Requirement 2		
Requirement:	An intentional radiator may be operated only with the antenna with which it is authorized. If an antenna is marketed with the intentional radiator, it shall be of a type which is authorized with the intentional radiator.	
Results:	Only one Metal antenna can be used	
Verdict:	Pass	

RSS-Gen 6.4 – External Control		
Requirement:	The device shall not have any external controls accessible to the user that enable it to be adjusted, selected or programmed to operate in violation of the regulatory requirements, including RSS-Gen and the applicable RSSs	
Results:	The device does not have any transmitter external controls accessible to the user that can be adjusted and operated in violation of the limits of this standard.	
Verdict:	PASS	

RSS-Gen 6.8 – Antenna Requirement

Requirement: When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

Results:

a) Antenna Type:	Metal Antenna
b) Manufacture:	N/A
c) Model No.:	N/A
d) Gain with reference to an isotropic radiator:	-0.38 dBi

Verdict: PASS

5.1.2 6dB & 99% Bandwidth**RESULT:****Pass**

Date of testing	:	2026-05-13
Ambient temperature	:	21.3°C
Relative humidity	:	49.5%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(a)(2) RSS-247 Issue 4, July 24, 2025, Clause 6.3.1(a) RSS-Gen Issue 5, Amendment 2, February 2021, Clause 6.7
Test procedure	:	ANSI C63.10:2020 ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024+Errata to C63.10a-2024
Test voltage	:	DC 3V
Test modes applied	:	A


6dB Bandwidth, 2405MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2405.000000	1.500000	0.500000	---	2404.225000	2405.725000

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2405.000000	4.9	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40200 GHz	2.40200 GHz
Stop Frequency	2.40800 GHz	2.40800 GHz
Span	6.000 MHz	6.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	120	~ 120
Sweptime	18.984 µs	AUTO
Reference Level	20.000 dBm	20.000 dBm
Attenuation	40.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	25 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.09 dB	0.50 dB


6dB Bandwidth, 2445MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2445.000000	1.500000	0.500000	---	2444.275000	2445.775000

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2445.000000	4.7	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44200 GHz	2.44200 GHz
Stop Frequency	2.44800 GHz	2.44800 GHz
Span	6.000 MHz	6.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	120	~ 120
Sweeptime	18.984 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	21 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.44 dB	0.50 dB


6dB Bandwidth, 2480MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	1.450000	0.500000	---	2479.275000	2480.725000

(continuation of the "6 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2480.000000	4.5	PASS

6 dB Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47700 GHz	2.47700 GHz
Stop Frequency	2.48300 GHz	2.48300 GHz
Span	6.000 MHz	6.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	120	~ 120
Sweeptime	18.984 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	29 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.00 dB	0.50 dB


Prüfbericht - Nr.: CN26V7ST 001
Test Report No.
Seite 19 von 40
Page 19 of 40
99% Occupied Channel Bandwidth, 2405MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2405.000000	2.040000	---	---	2403.987500	2406.027500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2405.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40200 GHz	2.40200 GHz
Stop Frequency	2.40800 GHz	2.40800 GHz
Span	6.000 MHz	6.000 MHz
RBW	30.000 kHz	>= 30.000 kHz
VBW	100.000 kHz	>= 90.000 kHz
SweepPoints	400	~ 400
Sweptime	63.216 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	46 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.21 dB	0.30 dB


99% Occupied Channel Bandwidth, 2445MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2445.000000	2.040000	---	---	2443.987500	2446.027500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2445.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44200 GHz	2.44200 GHz
Stop Frequency	2.44800 GHz	2.44800 GHz
Span	6.000 MHz	6.000 MHz
RBW	30.000 kHz	>= 30.000 kHz
VBW	100.000 kHz	>= 90.000 kHz
SweepPoints	400	~ 400
Sweeptime	63.216 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	33 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.05 dB	0.30 dB


99% Occupied Channel Bandwidth, 2480MHz

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	2.055000	---	---	2478.987500	2481.042500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2480.000000	PASS

99 % Bandwidth


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47700 GHz	2.47700 GHz
Stop Frequency	2.48300 GHz	2.48300 GHz
Span	6.000 MHz	6.000 MHz
RBW	30.000 kHz	>= 30.000 kHz
VBW	100.000 kHz	>= 90.000 kHz
SweepPoints	400	~ 400
Sweeptime	63.216 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	44 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.30 dB

5.1.3 Output Power

RESULT:**Pass**

Date of testing : 2026-05-13
Ambient temperature : 21.3°C
Relative humidity : 49.5%
Atmospheric pressure : 101kPa
Test requirement : FCC Part 15.247(b)(3)
RSS-247 Issue 4, July 24, 2025, Clause 6.3.2
Test procedure : ANSI C63.10:2020
ANSI C63.10-2020+Cor. 1-2023+C63.10a-
2024+Errata to C63.10a-2024
Test voltage : DC 3V
Test modes applied : A

Table 9: Peak Output Power

Frequency [MHz]	Peak Conducted Output Power [dBm]	Limit [dBm]
2405	7.3	30
2445	7.4	30
2480	6.8	30

Note:

EIRP=Conducted Output Power + Antenna Gain (-0.38dBi), which is far below the 4 W (36dBm).

5.1.4 Power Spectral Density


RESULT:**Pass**

Date of testing	:	2026-05-13
Ambient temperature	:	21.3°C
Relative humidity	:	49.5%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(e) RSS-247 Issue 4, July 24, 2025, Clause 6.3.1(b)
Test procedure	:	ANSI C63.10:2020 ANSI C63.10-2020+Cor. 1-2023+C63.10a- 2024+Errata to C63.10a-2024
Test voltage	:	DC 3V
Test modes applied	:	A

Power Spectral Density, 2405MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2405.000000	2404.567500	1.124	8.0	PASS

Peak Power Spectral Density



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40388 GHz	2.40388 GHz
Stop Frequency	2.40613 GHz	2.40613 GHz
Span	2.250 MHz	2.250 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	450	~ 450
Sweptime	2.250 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	44 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.21 dB	0.50 dB

Power Spectral Density, 2445MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2445.000000	2444.567500	1.143	8.0	PASS

Peak Power Spectral Density



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44388 GHz	2.44388 GHz
Stop Frequency	2.44613 GHz	2.44613 GHz
Span	2.250 MHz	2.250 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	450	~ 450
SweepTime	2.250 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	30 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.37 dB	0.50 dB

Power Spectral Density, 2480MHz

DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2480.000000	2479.625000	-0.057	8.0	PASS

Peak Power Spectral Density


Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47891 GHz	2.47891 GHz
Stop Frequency	2.48109 GHz	2.48109 GHz
Span	2.175 MHz	2.175 MHz
RBW	10.000 kHz	<= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	435	~ 435
Sweptime	2.180 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	62 / max. 150	max. 150
Stable	2 / 2	2
Max Stable Difference	0.08 dB	0.50 dB

5.1.5 Conducted Band Edge and out-of Band Emissions

RESULT:

Pass

Date of testing	:	2026-05-13
Ambient temperature	:	21.3°C
Relative humidity	:	49.5%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(d) RSS-247 Issue 4, July 24, 2025, Clause 6.6
Test procedure	:	ANSI C63.10:2020 ANSI C63.10-2020+Cor. 1-2023+C63.10a- 2024+Errata to C63.10a-2024
Test voltage	:	DC 3V
Test modes applied	:	A

Figure 1: Reference level




Figure 2: Conducted Spurious Emission





Figure 3: Conducted Band Edge



5.2 Emission in the Frequency Range up to 30MHz

5.2.1 Conducted Emission

RESULT:**N/A**

Date of testing	:	/
Ambient temperature	:	/
Relative humidity	:	/
Atmospheric pressure	:	/
Test requirement	:	FCC Part 15.207 (a) RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.8
Test procedure	:	ANSI C63.10:2020 ANSI C63.10-2020+Cor. 1-2023+C63.10a- 2024+Errata to C63.10a-2024
Test voltage	:	/
Test modes applied	:	/

Note: This product is power by battery, so it is not applicable for this test.

5.3 Emission in the Frequency Range above 30MHz


5.3.1 Radiated Band-Edge

RESULT:**Pass**

Date of testing	:	2026-05-22
Ambient temperature	:	20.5°C
Relative humidity	:	48.6%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(d) FCC Part 15.205(a) FCC Part 15.209(a) RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.9 RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.10 RSS-247 Issue 4, July 24, 2025, Clause 6.6
Test procedure	:	ANSI C63.10:2020 ANSI C63.10-2020+Cor. 1-2023+C63.10a- 2024+Errata to C63.10a-2024
Test voltage	:	DC 3V
Test modes applied	:	A

Figure 4: Radiated Band-Edge, 2405MHz, H

XXY- 2310~ 2410 BE 1-18GHz_HL050_FSV40_Pre-10-YUNFANG


Figure 5: Radiated Band-Edge, 2405MHz, V

XXY- 2310~ 2410 BE 1-18GHz_HL050_FSV40_Pre-10-YUNFANG




Figure 6: Radiated Band-Edge, 2480MHz, H

XXY-2470° 2500 BE_1-18GHz_HL050_FSV40_Pre-10-YUNFANG





Figure 7: Radiated Band-Edge, 2480MHz, V

XXY-2470° 2500 BE_1-18GHz_HL050_FSV40_Pre-10-YUNFANG




5.3.2 Radiated Spurious Emission**RESULT:****Pass**

Date of testing	:	2026-05-22
Ambient temperature	:	20.5°C
Relative humidity	:	48.6%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(d) FCC Part 15.209(a) RSS-Gen Issue 5, Amendment 2, February 2021, Clause 8.9 RSS-247 Issue 4, July 24, 2025, Clause 6.6
Test procedure	:	ANSI C63.10:2020 ANSI C63.10-2020+Cor. 1-2023+C63.10a- 2024+Errata to C63.10a-2024
Test voltage	:	DC 3V
Test modes applied	:	A

Note:

For the frequency range from 18GHz to 25GHz, no emission was found.

Figure 8: Radiated Spurious Emission, 2405MHz


Limit and Margin
QP


Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
31.091250	20.8	H	24.8	19.2	40.0
41.640000	14.5	H	18.9	25.5	40.0
128.091250	14.0	H	18.6	29.5	43.5
252.857500	21.0	H	19.7	25.0	46.0
302.691250	28.1	H	20.8	17.9	46.0
306.571250	26.3	H	20.4	19.8	46.0
329.608750	23.4	H	21.4	22.7	46.0
32.303750	19.9	V	24.1	20.1	40.0
132.941250	22.5	V	18.4	21.1	43.5
317.726250	17.2	V	20.7	28.8	46.0
421.637500	19.9	V	24.0	26.1	46.0
487.355000	21.3	V	25.2	24.7	46.0
664.380000	24.5	V	26.6	21.5	46.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1329.181818	39.2	H	-18.7	34.8	74.0
2264.363636	39.9	H	-15.6	34.1	74.0
4809.727273	50.2	H	-11.2	23.8	74.0
8006.500000	47.4	H	-3.3	26.6	74.0
10569.843750	48.9	H	-1.3	25.1	74.0
17986.593750	59.0	H	11.9	15.0	74.0
1594.818182	38.8	V	-18.9	35.2	74.0
1941.454546	39.2	V	-18.1	34.8	74.0
4812.181818	54.2	V	-11.2	19.8	74.0
7889.625000	47.2	V	-3.9	26.8	74.0
9620.062500	48.1	V	-4.4	25.9	74.0
17981.093750	59.6	V	11.8	14.4	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1329.181818	28.2	H	-18.7	25.8	54.0
2264.363636	29.7	H	-15.6	24.3	54.0
4809.727273	45.8	H	-11.2	8.2	54.0
8006.500000	37.6	H	-3.3	16.4	54.0
10569.843750	38.3	H	-1.3	15.7	54.0
17986.593750	48.6	H	11.9	5.4	54.0
1594.818182	32.5	V	-18.9	21.5	54.0
1941.454546	28.0	V	-18.1	26.1	54.0
4812.181818	48.5	V	-11.2	5.5	54.0
7889.625000	36.8	V	-3.9	17.2	54.0
9620.062500	40.4	V	-4.4	13.6	54.0
17981.093750	48.7	V	11.8	5.3	54.0

Figure 9: Radiated Spurious Emission, 2445MHz


Limit and Margin
QP


Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
31.212500	20.7	H	24.8	19.3	40.0
36.911250	17.4	H	21.5	22.6	40.0
111.722500	14.3	H	18.7	29.2	43.5
230.305000	17.8	H	17.3	28.2	46.0
309.845000	26.6	H	20.2	19.4	46.0
317.605000	27.3	H	20.7	18.7	46.0
30.000000	21.7	V	25.4	18.3	40.0
36.790000	17.5	V	21.6	22.5	40.0
148.340000	18.3	V	17.2	25.3	43.5
416.302500	19.9	V	24.0	26.1	46.0
532.217500	30.0	V	25.0	16.0	46.0
723.671250	27.0	V	28.7	19.0	46.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1786.000000	37.7	H	-18.8	36.3	74.0
2199.454546	38.1	H	-15.7	35.9	74.0
4890.181818	49.0	H	-11.1	25.0	74.0
8012.343750	47.8	H	-3.3	26.2	74.0
11489.375000	49.4	H	-1.5	24.6	74.0
17979.031250	59.4	H	11.8	14.6	74.0
1860.181818	41.7	V	-18.5	32.3	74.0
2260.272727	42.2	V	-15.6	31.8	74.0
4889.909091	52.8	V	-11.1	21.2	74.0
7337.500000	45.6	V	-6.2	28.5	74.0
9778.187500	46.9	V	-3.9	27.1	74.0
17987.625000	59.9	V	11.9	14.2	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1786.000000	27.5	H	-18.8	26.5	54.0
2199.454546	29.2	H	-15.7	24.8	54.0
4890.181818	45.7	H	-11.1	8.3	54.0
8012.343750	37.5	H	-3.3	16.6	54.0
11489.375000	37.9	H	-1.5	16.1	54.0
17979.031250	48.0	H	11.8	6.0	54.0
1860.181818	29.2	V	-18.5	24.8	54.0
2260.272727	29.6	V	-15.6	24.4	54.0
4889.909091	47.9	V	-11.1	6.1	54.0
7337.500000	36.7	V	-6.2	17.3	54.0
9778.187500	38.4	V	-3.9	15.6	54.0
17987.625000	48.8	V	11.9	5.2	54.0

Figure 10: Radiated Spurious Emission, 2480MHz


Limit and Margin
QP

Frequency (MHz)	QuasiPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
30.606250	21.1	H	25.1	18.9	40.0
34.850000	18.3	H	22.7	21.7	40.0
244.006250	20.7	H	19.1	25.3	46.0
265.710000	21.3	H	21.2	24.7	46.0
301.357500	26.8	H	20.9	19.2	46.0
320.393750	27.9	H	21.0	18.1	46.0
31.212500	20.7	V	24.8	19.3	40.0
35.213750	18.2	V	22.5	21.8	40.0
133.062500	19.7	V	18.4	23.9	43.5
532.217500	26.0	V	25.0	20.0	46.0
579.868750	23.2	V	26.8	22.8	46.0
666.562500	27.0	V	26.6	19.0	46.0

PK

Frequency (MHz)	MaxPeak (dBµV/m)	Pol	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBµV/m)
1596.727273	36.4	H	-18.9	37.6	74.0
2250.181818	37.9	H	-15.6	36.1	74.0
4962.181818	46.5	H	-11.0	27.5	74.0
7968.687500	47.4	H	-3.4	26.6	74.0
11507.250000	48.6	H	-1.4	25.4	74.0
17995.875000	60.4	H	12.0	13.6	74.0
1816.545455	41.8	V	-18.7	32.2	74.0
1863.454546	43.3	V	-18.5	30.7	74.0
4960.000000	47.8	V	-11.0	26.2	74.0
7435.875000	46.0	V	-5.8	28.0	74.0
10589.781250	49.6	V	-1.1	24.4	74.0
17996.218750	59.6	V	12.0	14.4	74.0

AV

Frequency (MHz)	Average (dBµV/m)	Pol	Corr. (dB/m)	Margin - AVG (dB)	Limit - AVG (dBµV/m)
1596.727273	29.4	H	-18.9	24.6	54.0
2250.181818	28.3	H	-15.6	25.7	54.0
4962.181818	41.0	H	-11.0	13.0	54.0
7968.687500	37.0	H	-3.4	17.0	54.0
11507.250000	38.3	H	-1.4	15.8	54.0
17995.875000	47.9	H	12.0	6.1	54.0
1816.545455	33.2	V	-18.7	20.8	54.0
1863.454546	34.1	V	-18.5	19.9	54.0
4960.000000	43.8	V	-11.0	10.2	54.0
7435.875000	36.9	V	-5.8	17.1	54.0
10589.781250	38.4	V	-1.1	15.7	54.0
17996.218750	47.9	V	12.0	6.1	54.0

6. List of Tables

Table 1: List of Test and Measurement Equipment	7
Table 2: Measurement Uncertainty	8
Table 3: Technical Specification of EUT	9
Table 4: Operation Channel List	9
Table 5: Power parameter value	11
Table 6: Special Accessories	11
Table 7: Auxiliary Equipment	11
Table 8: Antenna Requirement	13
Table 9: Peak Output Power	22

7. List of Figures

Figure 1: Reference level	27
Figure 2: Conducted Spurious Emission	28
Figure 3: Conducted Band Edge	28
Figure 4: Radiated Band-Edge, 2405MHz, H	31
Figure 5: Radiated Band-Edge, 2405MHz, V	31
Figure 6: Radiated Band-Edge, 2480MHz, H	32
Figure 7: Radiated Band-Edge, 2480MHz, V	32
Figure 8: Radiated Spurious Emission, 2405MHz	34
Figure 9: Radiated Spurious Emission, 2445MHz	36
Figure 10: Radiated Spurious Emission, 2480MHz	38