

STATEMENT ON EXPOSURE TO ELECTROMAGNETIC FIELDS

EQUIPMENT

Type of equipment:	Zigbee radio module
Type / Model:	ICC-A-1
Manufacturer:	IKEA of Sweden AB
By request of:	IKEA of Sweden AB

STANDARD

EN 62479
47 CFR §1.1310
RSS-102 Issue 5
Radiation Protection Standard for Maximum Exposure Levels to Radiofrequency fields – 3
kHz to 300 GHz
AS/NZS 2772.1

CONDITIONS

Operating frequency range is 2405-2480 MHz.

Highest output power to antenna is +12.60 dBm.

Antenna gain is -3.6 dBi.

A test separation distance of 5 mm is used for handheld/portable applications.

A test separation distance of 20 cm is used for mobile applications.

Maximum (worst case) duty cycle is 22.4%

This Statement of Compliance is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Statement. Only the Client is authorized to permit copying or distribution of this Statement of Compliance. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
Telephone +46 8 750 00 00, Fax +46 8 750 60 30

www.intertek.se

Registered in Sweden: No: SE556024059901, Registered office: As address

CALCULATIONS**EIRP:**

$$+12.60 \text{ dBm} + (-3.6) \text{ dB} = +9.0 \text{ dBm}$$

Conversion dBm to W:

$$\text{Conducted:} \quad 1 \text{ mW} * 10^{(12.60 \text{ dBm}/10)} = 18.2 \text{ mW}$$

$$\text{EIRP:} \quad 1 \text{ mW} * 10^{(9.0 \text{ dBm}/10)} = 7.9 \text{ mW}$$

Time averaged maximum power:

$$\text{Conducted:} \quad 18.2 \text{ mW} * 0.224 = 4.13 \text{ mW} \approx 5 \text{ mW}$$

$$\text{EIRP:} \quad 7.9 \text{ mW} * 0.224 = 1.79 \text{ mW} \approx 2 \text{ mW}$$

Power density S:

$$5 \text{ mm separation distance:} \quad S \left[\frac{\text{W}}{\text{m}^2} \right] = \frac{\text{DC} \times \text{EIRP}}{4 \times \pi \times R^2} = \frac{0.224 \times 0.0079}{4 \times \pi \times 0.005^2} = 5.71$$

$$20 \text{ cm separation distance:} \quad S \left[\frac{\text{W}}{\text{m}^2} \right] = \frac{\text{DC} \times \text{EIRP}}{4 \times \pi \times R^2} = \frac{0.224 \times 0.0079}{4 \times \pi \times 0.20^2} = 0.004$$

This Statement of Compliance is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Statement. Only the Client is authorized to permit copying or distribution of this Statement of Compliance. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
Telephone +46 8 750 00 00, Fax +46 8 750 60 30

www.intertek.se

Registered in Sweden: No: SE556024059901, Registered office: As address

LIMITS & EVALUATIONS:

Standard	Reference for limit	Limit	Unit	Values	Result
EN 62479	EN 62479 ¹	40	mW	2.0	PASS
CFR 47 §1.1310	KDB 447498 D01 ²	7.5	NA	0.64	PASS
	CFR 47 §1.1310 ³	10	W/m ²	0.004	PASS
RSS-102 issue 5 (2015)	RSS-102 issue 5 (2015) ⁴	10	mW	5.0	PASS
	RSS-102 issue 5 (2015) ⁵	2700	mW	2.0	PASS
Radiation Protection Standard for Maximum Exposure Levels to Radiofrequency fields – 3 kHz to 300 GHz	Radiation Protection Standard for Maximum Exposure Levels to Radiofrequency fields – 3 kHz to 300 GHz ⁶	10	W/m ²	5.71	PASS
AS/NZS 2772.1	AS/NZS 2772.2 ⁷	20	mW	2.0	PASS

1. Table A.1: For general public and limbs exposure.
2. Section 4.3.1, 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz
3. (e) Table 1 – Limits for maximum permissible exposure. For frequency range 1500 – 100 000 MHz and general population/uncontrolled exposure the maximum allowed power density is $1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$
4. Section 2.5.2: at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834} \text{ W}$ (adjusted for tune-up tolerance), where f is in MHz

This Statement of Compliance is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Statement. Only the Client is authorized to permit copying or distribution of this Statement of Compliance. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
Telephone +46 8 750 00 00, Fax +46 8 750 60 30

www.intertek.se

Registered in Sweden: No: SE556024059901, Registered office: As address

5. Section 2.5.1, Table 1: 4 mW at 2450 MHz. For limb-worn devices where the 10 gram value applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of 2.5
6. Table 7: For general public and 2 GHz- 300 GHz the equivalent plane wave power flux density is: 10
7. Section 3.7.3: In some circumstances an RF exposure evaluation may not be required. This is the case with low-power devices whose nominal average RF radiated power does not exceed 20 mW and which do not produce exceptionally high instantaneous fields.

Intertek Semko AB, Radio & EMC

Date of issue: 2017-06-14



Issued by: Daniel Nilsson

This Statement of Compliance is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Statement. Only the Client is authorized to permit copying or distribution of this Statement of Compliance. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
Telephone +46 8 750 00 00, Fax +46 8 750 60 30

www.intertek.se

Registered in Sweden: No: SE556024059901, Registered office: As address