



LCIE

Bluetooth Low Energy Template: Release March 25th, 2021

TEST REPORT

N°: 174550-771868-B (FILE#2835864)

Version : 02

Subject

**Radio spectrum matters
tests according to standards:
47 CFR Part 15.247 & RSS-247 Issue 2 & RSS-Gen Issue 5**

Issued to

MICHELIN NORTH AMERICA (US) INC.
One Parkway South
29615 – GREENVILLE

Apparatus under test

- ↗ Product
- ↗ Trade mark
- ↗ Manufacturer
- ↗ Model under test
- ↗ Serial number
- ↗ FCC ID
- ↗ IC

**Tire Mounted Sensor
Michelin
Manufacture Française des Pneumatiques Michelin
TMS AL-01
05&07&04&06
FI5TMSAL01
5056A-TMSAL01**

Conclusion

See Test Program chapter

Test date

October 7, 2021 to October 8, 2021

Test location

Moirans

FCC Test site

FR0008 - 197516

ISED Test site

FR0008 - 6500A

Sample receipt date

October 22, 2021

Composition of document

50 pages

Document issued on

November 4, 2021

**Written by :
Mounir BOUAMARA
Tests operator**

**Approved by :
Anthony MERLIN
Technical manager**



This document shall not be reproduced, except in full, without the written approval of the LCIE. This document contains results related only to the items tested. It does not imply the conformity of the whole production to the items tested. Unless otherwise specified or rule defined by the test method, the decision of conformity doesn't take into account the uncertainty of measures. This document doesn't anticipate any certification decision.

LCIE

Laboratoire Central des Industries Electriques
Une société de Bureau Veritas

ZI Centr'alp
170 rue de Chatagnon
38430 Moirans FRANCE

Tél : +33 4 76 07 36 36
contact@lcie.fr
www.lcie.fr



PUBLICATION HISTORY

Version	Date	Author	Modification
01	November 4, 2021	Mounir BOUAMARA	Creation of the document
02	November 4, 2021	Mounir BOUAMARA	Modification of recipient p1

Each new edition of this test report replaces and cancels the previous edition. The control of the old editions of report is under responsibility of client.



SUMMARY

1.	TEST PROGRAM	4
2.	EQUIPMENT UNDER TEST: CONFIGURATION (DECLARED BY PROVIDER)	5
3.	OCCUPIED BANDWIDTH.....	9
4.	6DB EMISSION BANDWIDTH	12
5.	MAXIMUM CONDUCTED OUTPUT POWER	15
6.	POWER SPECTRAL DENSITY	19
7.	UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS AT THE BAND EDGE	22
8.	UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS.....	25
9.	UNWANTED EMISSIONS IN RESTRICTED FREQUENCY BANDS	28
10.	UNCERTAINTIES CHART	50

1. TEST PROGRAM

References

- 47 CFR Part 15.247
- RSS 247 Issue 2
- RSS Gen Issue 5
- KDB 558074 D01 DTS Meas Guidance v05r02
- ANSI C63.10-2013

Radio requirement:

Clause (47CFR Part 15.247 & RSS-247 Issue 2 & RSS-Gen Issue 5) Test Description	Test result - Comments
Occupied Bandwidth	☒ PASS ☐ FAIL ☐ NA ☐ NP(1)
6dB Bandwidth	☒ PASS ☐ FAIL ☐ NA() ☐ NP(1)
Duty Cycle	☐ PASS ☐ FAIL ☒ NA ☐ NP(1)
Maximum Conducted Output Power	☒ PASS ☐ FAIL ☐ NA ☐ NP(1)
Power Spectral Density	☒ PASS ☐ FAIL ☐ NA ☐ NP(1)
Conducted Spurious Emission at the Band Edge	☒ PASS ☐ FAIL ☐ NA() ☐ NP(1)
Unwanted Emissions into Non-Restricted Frequency Bands	☒ PASS ☐ FAIL ☐ NA() ☐ NP(1)
AC Power Line Conducted Emission	☐ PASS ☐ FAIL ☒ NA(2) ☐ NP(1)
Unwanted Emissions into Restricted Frequency Bands	☒ PASS ☐ FAIL ☐ NA ☐ NP(1)
Receiver Radiated emissions	☐ PASS ☐ FAIL ☒ NA ☐ NP(1)
This table is a summary of test report, see conclusion of each clause of this test report for detail.	

(1): Limited program

(2): EUT not directly or indirectly connected to the AC Power Public Network

PASS: EUT complies with standard's requirement

FAIL: EUT does not comply with standard's requirement

NA: Not Applicable

NP: Test Not Performed

2. EQUIPMENT UNDER TEST: CONFIGURATION (DECLARED BY PROVIDER)

2.1. HARDWARE IDENTIFICATION (EUT AND AUXILIARIES):

Equipment under test (EUT):

Michelin TMS AL-01

Serial Number: 05&07&04&06



Equipment Under Test

Power supply:

During all the tests, EUT is supplied by V_{nom} : 3.3 VDC

For measurement with different voltage, it will be presented in test method.

Name	Type	Rating	Reference / Sn	Comments
Supply1	☐ AC ☐ DC ☒ Battery	3.3		

Inputs/outputs - Cable:

Access	Type	Length used (m)	Declared <3m	Shielded	Under test	Comments
No input or output						

Equipment information:

Bluetooth LE Type:	☒ BLE	☐ v4.1	☐ v4.2	☐ v5.0
Frequency band:	[2400 – 2483.5] MHz			
Spectrum Modulation:	☒ DSSS (Tested like it)			
Number of Channel:	40			
Spacing channel:	2MHz			
Channel bandwidth:	☒ 1MHz		☐ 2MHz	
Antenna Type:	☒ Integral	☐ External	☐ Dedicated	
Antenna connector:	☐ Yes	☐ No	☒ Temporary for test	
Transmit chains:	1			
	Single antenna			
	Gain: 0dBi			
Antenna requirements §15.203	The transmitter uses an integral antenna and it permanently connected			
Type of equipment:	☒ Stand-alone	☐ Plug-in	☐ Combined	
Duty cycle:	☒ Continuous duty	☐ Intermittent duty	☐ 100% duty	
Equipment type:	☒ Production model		☐ Pre-production model	
Operating temperature range:	Tmin:	☐ -20°C	☐ 0°C	☒ -40°C
	Tnom:	20°C		
	Tmax:	☐ 35°C	☐ 55°C	☒ 125°C
Type of power source:	☐ AC power supply	☐ DC power supply	☒ Battery	
Operating voltage range:	Vnom:	☐ 230V/50Hz	☒ 3.3Vdc	



CHANNEL PLAN			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
Cmin: 0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
Cmid: 12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	Cmax: 39	2480

DATA RATE			
Available	Data Rate (Mbps)	Modulation Type	Worst Case Modulation
☐	0.25	GFSK	☐
☒	1	GFSK	☒
☐	2	GFSK	☐

2.2. RUNNING MODE

Test mode	Description of test mode
Test mode 1	Permanent emission with modulation on a fixed channel in the data rate that produced the highest power
Test mode 2	Permanent reception
Test	Running mode
Occupied Bandwidth	☒ Test mode 1 (1) ☐ Alternative test mode()
6dB Bandwidth	☒ Test mode 1 (1) ☐ Alternative test mode()
Duty Cycle	☐ Test mode 1 (1) ☐ Alternative test mode()
Maximum Conducted Output Power	☒ Test mode 1 (1) ☐ Alternative test mode()
Power Spectral Density	☒ Test mode 1 (1) ☐ Alternative test mode()
Conducted Spurious Emission at the Band Edge	☒ Test mode 1 (1) ☐ Alternative test mode()
Unwanted Emissions into Non-Restricted Frequency Bands	☒ Test mode 1 (1) ☐ Alternative test mode()
AC Power Line Conducted Emission	☐ Test mode 1 (1) ☐ Alternative test mode()
Unwanted Emissions into Restricted Frequency Bands	☒ Test mode 1 (1) ☐ Alternative test mode()

- (1) Following commands with the specific test software "X" are used to set the product:
- See document "X"(provided by customer) for the command used during test.

Hardware information		
Software (if applicable):	V. :	Not communicated

2.3. EQUIPMENT MODIFICATION

☒ None ☐ Modification:

3. OCCUPIED BANDWIDTH

3.1. TEST CONDITIONS

Test performed by : Mounir BOUAMARA
Date of test : October 7, 2021 to October 8, 2021
Ambient temperature : 22 °C
Relative humidity : 39 %

3.2. TEST SETUP

- The Equipment under Test is installed:

- ☐ On a table
- ☒ In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:


- ☒ Conducted Method
- ☐ Radiated Method

- Test Procedure:


- ☒ RSS-Gen Issue 5 § 6.7
- ☐ ANSI C63.10 § 6.9.2

Measurement Procedure:

- a) RBW shall be in the range of 1% to 5% of the anticipated occupied bandwidth
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW
- c) SPAN = Capture all products of the modulation process
- d) Detector = Peak.
- e) Trace mode = max hold.
- f) Sweep = auto couple.
- g) Allow the trace to stabilize.
- h) OBW 99% function of spectrum analyzer used



Test set up of Occupied Bandwidth



Photograph for Occupied bandwidth

3.3. LIMIT

None


3.4. TEST EQUIPMENT LIST

TEST EQUIPMENT USED					
Description	Manufacturer	Model	Identifier	Cal_Date	Cal_Due
Attenuator 10dB	AEROFLEX	—	A7122267	08/21	08/23
Full Anechoic Room	SIEPEL	—	D3044024		
Multimeter - CEM	FLUKE	87	A1240251	03/21	03/23
Power supply DC	METRIX	AX503	A7042307		
SMA 1.5m	SUCOFLEX	18GHz	A5329863	04/21	04/22
SMA 1.5m	SUCOFLEX	18GHz	A5329864	04/21	04/22
Spectrum analyzer	ROHDE & SCHWARZ	FSV 30	A4060051	09/20	09/22
Thermo-hygrometer	TESTO	608-H1	B4204120	12/20	12/22
Thermo-hygrometer (PM1/2/3)	KIMO	HQ 210	B4206022	01/21	01/23

Note: In our quality system, the test equipment calibration due is more & less 2 months

3.5. RESULTS

1Mbits/s



3.6. CONCLUSION

Occupied Channel Bandwidth measurement performed on the sample of the product Michelin TMS AL-01, SN: 05&07&04&06, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247 & RSS-GEN ISSUE 5** limits.

4. 6dB EMISSION BANDWIDTH

4.1. TEST CONDITIONS

Test performed by : Mounir BOUAMARA
Date of test : October 7, 2021 to October 8, 2021
Ambient temperature : 22 °C
Relative humidity : 39 %

4.2. TEST SETUP

- The Equipment under Test is installed:

- ☐ On a table
- ☒ In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:


- ☒ Conducted Method
- ☐ Radiated Method

- Test Procedure:


- ☒ KDB 558074 D01 DTS Meas Guidance v05r02 § 8.2

Measurement Procedure:

1. Set resolution bandwidth (RBW) = 100kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. Compare the resultant bandwidth with the RBW setting of the analyzer.



Test set up of 6dB Emission Bandwidth



Photograph for 6dB emission bandwidth

4.3. LIMIT

The 6dB bandwidth shall be at least 500kHz


4.4. TEST EQUIPMENT LIST

TEST EQUIPMENT USED					
Description	Manufacturer	Model	Identifier	Cal_Date	Cal_Due
Attenuator 10dB	AEROFLEX	—	A7122267	08/21	08/23
Full Anechoic Room	SIEPEL	—	D3044024		
Multimeter - CEM	FLUKE	87	A1240251	03/21	03/23
Power supply DC	METRIX	AX503	A7042307		
SMA 1.5m	SUCOFLEX	18GHz	A5329863	04/21	04/22
SMA 1.5m	SUCOFLEX	18GHz	A5329864	04/21	04/22
Spectrum analyzer	ROHDE & SCHWARZ	FSV 30	A4060051	09/20	09/22
Thermo-hygrometer	TESTO	608-H1	B4204120	12/20	12/22
Thermo-hygrometer (PM1/2/3)	KIMO	HQ 210	B4206022	01/21	01/23

Note: In our quality system, the test equipment calibration due is more & less 2 months

4.5. RESULTS

1Mbits/s



4.6. CONCLUSION

6dB Emission Bandwidth measurement performed on the sample of the product Michelin TMS AL-01, SN: 05&07&04&06, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247 & RSS 247 ISSUE 2** limits.



5. MAXIMUM CONDUCTED OUTPUT POWER

5.1. TEST CONDITIONS

Test performed by : Mounir BOUAMARA
Date of test : October 7, 2021 to October 8, 2021
Ambient temperature : 22 °C
Relative humidity : 39 %

5.2. TEST SETUP

- The Equipment under Test is installed:

- ☐ On a table
- ☒ In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:

- ☒ Conducted Method
- ☐ Radiated Method

- Test Procedure:

- ☒ KDB 558074 D01 DTS Meas Guidance v05r02 § 8.3.1.1


This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the RBW $\geq$ DTS bandwidth.
- b) Set VBW $\geq 3 \times$ RBW.
- c) Set span $\geq 3 \times$ RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.


- ☐ KDB 558074 D01 DTS Meas Guidance v05r02 § 8.3.1.2

This procedure may be used when the maximum available RBW of the measurement instrument is less than the DTS bandwidth.

- a) Set the RBW = 1 MHz.
- b) Set the VBW $\geq 3 \times$ RBW
- c) Set the span $\geq 1.5 \times$ DTS bandwidth.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges



Test set up of Maximum Conducted Output Power



Photograph for Maximum Conducted Output Power

5.3. LIMIT

Maximum Conducted Output power:
 2400MHz-2483.5MHz: Shall not exceed 30dBm
 Limits are reduced by G-6dBi if Overall Antenna Gain above 6dBi


5.4. TEST EQUIPMENT LIST

TEST EQUIPMENT USED					
Description	Manufacturer	Model	Identifier	Cal_Date	Cal_Due
Attenuator 10dB	AEROFLEX	—	A7122267	08/21	08/23
Full Anechoic Room	SIEPEL	—	D3044024		
Multimeter - CEM	FLUKE	87	A1240251	03/21	03/23
Power supply DC	METRIX	AX503	A7042307		
SMA 1.5m	SUCOFLEX	18GHz	A5329863	04/21	04/22
SMA 1.5m	SUCOFLEX	18GHz	A5329864	04/21	04/22
Spectrum analyzer	ROHDE & SCHWARZ	FSV 30	A4060051	09/20	09/22
Thermo-hygrometer	TESTO	608-H1	B4204120	12/20	12/22
Thermo-hygrometer (PM1/2/3)	KIMO	HQ 210	B4206022	01/21	01/23

Note: In our quality system, the test equipment calibration due is more & less 2 months

5.5. RESULTS

1Mbits/s



5.6. CONCLUSION

Maximum Conducted Output Power measurement performed on the sample of the product Michelin TMS AL-01, SN: 05&07&04&06, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247 & RSS 247 ISSUE 2** limits.

6. POWER SPECTRAL DENSITY

6.1. TEST CONDITIONS

Test performed by : Mounir BOUAMARA
Date of test : October 7, 2021 to October 8, 2021
Ambient temperature : 22 °C
Relative humidity : 39 %

6.2. TEST SETUP

- The Equipment Under Test is installed:


- ☒ On a table
☐ In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:


- ☒ Conducted Method
☐ Radiated Method

- Test Procedure:

- ☒ KDB 558074 D01 DTS Meas Guidance v05r02 § 8.4 (Method PKPSD)
- Set analyzer center frequency to DTS channel center frequency.
 - Set the span to 1.5 times the DTS bandwidth.
 - Set the RBW to: 3 kHz.
 - Set the VBW $\geq 3 \times$ RBW.
 - Detector = peak.
 - Sweep time = auto couple.
 - Trace mode = max hold.
 - Allow trace to fully stabilize.
 - Use the peak marker function to determine the maximum amplitude level within the RBW.
 - If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test set up of Power Spectral Density



Photograph for Power Spectral Density

6.3. LIMIT

Power Spectral Density:
 2400MHz-2483.5MHz: Shall not exceed 8dBm/3kHz
 Limits are reduced by G-6dBi if Overall Antenna Gain above 6dBi


6.4. TEST EQUIPMENT LIST

TEST EQUIPMENT USED					
Description	Manufacturer	Model	Identifier	Cal_Date	Cal_Due
Attenuator 10dB	AEROFLEX	—	A7122267	08/21	08/23
Full Anechoic Room	SIEPEL	—	D3044024		
Multimeter - CEM	FLUKE	87	A1240251	03/21	03/23
Power supply DC	METRIX	AX503	A7042307		
SMA 1.5m	SUCOFLEX	18GHz	A5329863	04/21	04/22
SMA 1.5m	SUCOFLEX	18GHz	A5329864	04/21	04/22
Spectrum analyzer	ROHDE & SCHWARZ	FSV 30	A4060051	09/20	09/22
Thermo-hygrometer	TESTO	608-H1	B4204120	12/20	12/22
Thermo-hygrometer (PM1/2/3)	KIMO	HQ 210	B4206022	01/21	01/23

Note: In our quality system, the test equipment calibration due is more & less 2 months

6.5. RESULTS

1Mbits/s



6.6. CONCLUSION

Power Spectral Density measurement performed on the sample of the product Michelin TMS AL-01, SN: 05&07&04&06, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247 & RSS 247 ISSUE 2** limits.

7. UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS AT THE BAND EDGE

7.1. TEST CONDITIONS

Test performed by : Mounir BOUAMARA
Date of test : October 7, 2021 to October 8, 2021
Ambient temperature : 22 °C
Relative humidity : 39 %

7.2. TEST SETUP

- The Equipment Under Test is installed:


- ☐ On a table
- ☒ In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:


- ☒ Conducted Method
- ☐ Radiated Method

- Test Procedure:

- ☒ KDB 558074 D01 DTS Meas Guidance v05r02 § 8.5



Test set up of Unwanted Emissions into Non-Restricted Frequency Bands at the Band Edge



Photograph for Unwanted Emission into non-restricted frequency bands at the band edge

7.3. LIMIT

All Spurious Emissions must be at least 20dB below the Fundamental Radiator Level at the Band Edge Edge “2400MHz & 2483,5MHz”


7.4. TEST EQUIPMENT LIST

TEST EQUIPMENT USED					
Description	Manufacturer	Model	Identifier	Cal_Date	Cal_Due
Attenuator 10dB	AEROFLEX	—	A7122267	08/21	08/23
Full Anechoic Room	SIEPEL	—	D3044024		
Multimeter - CEM	FLUKE	87	A1240251	03/21	03/23
Power supply DC	METRIX	AX503	A7042307		
SMA 1.5m	SUCOFLEX	18GHz	A5329863	04/21	04/22
SMA 1.5m	SUCOFLEX	18GHz	A5329864	04/21	04/22
Spectrum analyzer	ROHDE & SCHWARZ	FSV 30	A4060051	09/20	09/22
Thermo-hygrometer	TESTO	608-H1	B4204120	12/20	12/22
Thermo-hygrometer (PM1/2/3)	KIMO	HQ 210	B4206022	01/21	01/23

Note: In our quality system, the test equipment calibration due is more & less 2 months

7.5. RESULTS

1Mbits/s



7.6. CONCLUSION

Unwanted Emission into non-restricted frequency bands at the band edge measurement performed on the sample of the product Michelin TMS AL-01, SN: 05&07&04&06, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247 & RSS 247 ISSUE 2** limits.

8. UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS

8.1. TEST CONDITIONS

Test performed by : Mounir BOUAMARA
Date of test : October 7, 2021 to October 8, 2021
Ambient temperature : 22 °C
Relative humidity : 39 %

8.2. TEST SETUP

- The Equipment under Test is installed:


- ☒ On a table
- ☐ In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:


- ☒ Conducted Method
- ☐ Radiated Method

- Test Procedure:

- ☒ KDB 558074 D01 DTS Meas Guidance v05r02 § 8.5



Test set up of Unwanted Emissions into Non-Restricted Frequency Bands



Photograph for Unwanted Emission into non-restricted frequency bands

8.3. LIMIT

All Spurious Emissions must be at least 20 below the Fundamental Radiator Level


8.4. TEST EQUIPMENT LIST

TEST EQUIPMENT USED					
Description	Manufacturer	Model	Identifier	Cal_Date	Cal_Due
Attenuator 10dB	AEROFLEX	—	A7122269	09/20	03/22
Cable Measure	—	36G	A5329604	04/21	04/22
Multimeter - CEM	FLUKE	87	A1240251	03/21	03/23
Power supply DC	METRIX	AX503	A7042307		
Thermo-hygrometer	TESTO	608-H1	B4204120	12/20	12/22
Thermo-hygrometer (PM1/2/3)	KIMO	HQ 210	B4206022	01/21	01/23
BAT EMC	NEXIO	v3.19.1.23	L1000115		
Spectrum analyzer	ROHDE & SCHWARZ	FSU 26	A4060058	09/21	09/23

Note: In our quality system, the test equipment calibration due is more & less 2 months

8.5. RESULTS

1Mbits/s



Frequency (MHz)	Level (dBm)	Level (dBc)	Limit (dBc)
2402.00	-1.5		
4803.37	-61.15	59.65	20
87.74	-66.41	64.91	20
2426.00	-8.5		
7278.4	-63.2	54.7	20
1888.23	-58.18	49.68	20
832.71	-61.05	52.55	20
2480.00	-1.1		
7439.56	-63.38	62.28	20
160.038	-67.58	66.48	20

8.6. CONCLUSION

Unwanted Emission into non-restricted frequency bands measurement performed on the sample of the product Michelin TMS AL-01, SN: 05&07&04&06, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247 & RSS 247 ISSUE 2** limits.

9. UNWANTED EMISSIONS IN RESTRICTED FREQUENCY BANDS

9.1. TEST CONDITIONS

Test performed by : Mounir BOUAMARA
 Date of test : October 7, 2021 to October 8, 2021
 Ambient temperature : 22 °C
 Relative humidity : 39 %

9.2. TEST SETUP

The product has been tested according to ANSI C63.10 (2013) and FCC part15 subpart C.

Test is performed in parallel, perpendicular and ground parallel axis with a loop antenna below 30MHz. Measurement bandwidth was 200Hz below 150kHz and 9kHz between 150kHz & 30MHz. The level has been maximised by the turntable rotation of 360 degrees range on all axis of EUT used in normal configuration. Antenna height was 1m. The EUT is placed **in a semi-anechoic chamber**. Distance between measuring antenna and the EUT is **3m**.


Test is performed in horizontal (H) and vertical (V) polarization with **bilog** between 30MHz & 1GHz and with a horn antenna above 1GHz. Measurement bandwidth was 120kHz below 1GHz and 1MHz above 1GHz. The level has been maximised by the turntable rotation of 360 degrees range on all axis of EUT used in normal configuration. The EUT is placed at 1.5m high above 1GHz and at 0.8m high under 1GHz. The EUT is placed **in a full anechoic chamber** above 1GHz and **on an open area test site** from 30MHz to 1GHz. Distance between measuring antenna and the EUT is **3m**.


The height antenna is varied from 1m to 4m from 30MHz to 1GHz and above 1GHz is:

☐ On mast, varied from 1m to 4m



☒ Fixed and centered on the EUT (EUT smaller than the beamwidth of the measurement antenna, ANSI C63.10 §6.6.5)

Frequency list has been created with anechoic chamber pre-scan results.





Test set up of Unwanted Emissions in Restricted Frequency Bands in semi anechoic chamber



Test Set up for radiated measurement in open area test site





Photo Setup : anechoic chamber (XY axis)






Photo Setup : anechoic chamber (Z axis)



Photo Setup – OATS

Photograph for Unwanted Emission in restricted frequency bands

9.3. LIMIT

Measure at 300m		
Frequency range	Level	Detector
9kHz-490kHz	67.6dBµV/m /F(kHz)	QPeak
Measure at 30m		
Frequency range	Level	Detector
490kHz-1.705MHz	87.6dBµV/m /F(kHz)	QPeak
1.705MHz-30MHz	29.5dBµV/m	QPeak

Measure at 10m		
Frequency range	Level	Detector
30MHz to 88MHz	29.5dB μ V/m	QPeak
88MHz to 216MHz	33dB μ V/m	QPeak
216MHz to 960MHz	35.5B μ V/m	QPeak
960MHz to 1000MHz	43.5dB μ V/m	QPeak
Above 1000MHz	63.5dB μ V/m	Peak
	43.5dB μ V/m	Average
Measure at 3m		
Frequency range	Level	Detector
30MHz to 88MHz	40dB μ V/m	QPeak
88MHz to 216MHz	43.5dB μ V/m	QPeak
216MHz to 960MHz	46B μ V/m	QPeak
960MHz to 1000MHz	54dB μ V/m	QPeak
Above 1000MHz	74dB μ V/m	Peak
	54dB μ V/m	Average

9.4. TEST EQUIPMENT LIST

TEST EQUIPMENT USED					
Description	Manufacturer	Model	Identifier	Cal_Date	Cal_Due
Amplifier 9kHz - 40GHz	LCIE SUD EST	—	A7102082	06/20	06/22
Antenna Bi-log	AH System	SAS-521-7	C2040180	02/21	02/23
Antenna horn 18GHz	EMCO	3115	C2042029	09/18	09/21*
BAT EMC	NEXIO	v3.19.1.23	L1000115		
CABLE N 3m	—	-	A5329206	07/20	07/22
Cable SMA 40GHz 40cm	WITHWAVE	W101-SM1-0.4M	A5329979	04/21	04/22
Comb EMR HF	YORK	CGE01	A3169114		
Emission Cable (SMA 1m)	TELEDYNE	26GHz	A5329874	10/20	10/21
Emission Cable (SMA 3.3m)	TELEDYNE	26GHz	A5329875	10/20	10/21
Emission Cable <1GHz (Ampl <-> Cage)	-	18GHz	A5329907	08/20	08/21
Filter Matrice	LCIE SUD EST	Combined filters	A7484078	09/20	09/21*
Multimeter - CEM	FLUKE	87	A1240251	03/21	03/23
Power supply DC	METRIX	AX503	A7042308		
Rehausse Table C3	LCIE	—	F2000507		
Rehausse Table C3	LCIE	—	F2000511		
Semi-Anechoic chamber #3 (BF)	SIEPEL	—	D3044017_BF	12/19	12/22
Semi-Anechoic chamber #3 (VSWR)	SIEPEL	—	D3044017_VSWR	12/19	12/22
Spare C3 Cable Measure	TELEDYNE	26GHz	A5329681	09/20	09/22
Spectrum analyzer	ROHDE & SCHWARZ	FSU 26	A4060058	09/21	09/23
Table C3	LCIE	—	F2000461		



TEST EQUIPMENT USED					
Description	Manufacturer	Model	Identifier	Cal_Date	Cal_Due
Thermo-hygrometer (C3)	OREGON	BAR206	B4204078	02/21	02/23
Thermo-hygrometer (PM1/2/3)	KIMO	HQ 210	B4206022	01/21	01/23
Turntable chamber (Cage#3)	ETS Lingren	Model 2165	F2000371		
Turntable controller (Cage#3)	ETS Lingren	Model 2090	F2000444		
Antenna horn 40GHz	SCHWARZBECK	BBHA 9170	C2042028	09/18	09/21*
Antenna Loop	ELECTRO-METRICS	EM-6879	C2040052	06/19	06/22

*Under derogation


Note: In our quality system, the test equipment calibration due is more & less 2 months

9.5. DIVERGENCE, ADDITION OR SUPPRESSION ON THE TEST SPECIFICATION


☒ None ☐ Divergence:

9.6. RESULTS

Results in the frequency band [0.009-30] MHz:




No significant frequency observed, the margin >10dB.




No significant frequency observed, the margin >10dB.

Results in the frequency band [30-1000] MHz: Worst case presented



No significant frequency observed, the margin >10dB.




No significant frequency observed, the margin >10dB.

QUALIFICATION (30MHz-1GHz): 10 meters measurement on the Open Area Test Site.
 Frequency list has been created with semi-anechoic chamber pre-scan results.
 Measurements are performed using a QUASI-PEAK detection.

Test Frequency (MHz)	Meter Reading dB(μV)	Detector (Pk/QP/Av)	Polarity (V/H)	Azimuth (Degrees)	Antenna Height (cm)	Transducer Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
166	-5	QP	H	0°	250	19.4	31.9	43.5	-11.6	Worst case

Note: Measure have been done at 10m distance and corrected according to requirements of 15.209.e)
 ($M@3m = M@10m + 10.5dB$)


Results in the frequency band [1-14] GHz: (All tilt positions: 0°, 30°, 60°, 90°, 120°, 150°)



Frequency (MHz)	Average (dBµV/m)	Lim.Average (dBµV/m)	Average-Lim.Average (dB)	Commentaire	Polarization	Correction (dB)
4079.761	46.5	54.0	-7.5	Horizontal	Horizontal	39.9
13905.950	47.8	54.0	-6.2	Horizontal	Horizontal	-7.7
7205.600	47.3	54.0	-6.7	Vertical	Vertical	-17.6


Frequency (MHz)	Peak (dBµV/m)	Lim.Peak (dBµV/m)	Peak-Lim.Peak (dB)	Commentaire	Polarization	Correction (dB)
4079.761	58.6	74.0	-15.4	Horizontal	Horizontal	39.9
13905.950	58.8	74.0	-15.2	Horizontal	Horizontal	-7.7
7205.600	53.4	74.0	-20.6	Vertical	Vertical	-17.6

RADIATED EMISSIONS




Frequency (MHz)	Average (dBμV/m)	Lim.Average (dBμV/m)	Average-Lim.Average (dB)	Commentaire	Polarization	Correction (dB)
7439.300	45.1	54.0	-8.9	Vertical	Vertical	-17.0
13950.600	46.8	54.0	-7.2	Vertical	Vertical	-7.4

Frequency (MHz)	Peak (dBμV/m)	Lim.Peak (dBμV/m)	Peak-Lim.Peak (dB)	Commentaire	Polarization	Correction (dB)
7439.300	53.1	74.0	-20.9	Vertical	Vertical	-17.0
13950.600	59.0	74.0	-15.0	Vertical	Vertical	-7.4




Frequency (MHz)	Average (dBμV/m)	Lim.Average (dBμV/m)	Average-Lim.Average (dB)	Commentaire	Polarization	Correction (dB)
7440.250	46.6	54.0	-7.4	Horizontal	Horizontal	-17.0
13904.050	47.4	54.0	-6.6	Horizontal	Horizontal	-7.7
4010.797	46.7	54.0	-7.3	Vertical	Vertical	39.9

Frequency (MHz)	Peak (dBμV/m)	Lim.Peak (dBμV/m)	Peak-Lim.Peak (dB)	Commentaire	Polarization	Correction (dB)
7440.250	53.7	74.0	-20.3	Horizontal	Horizontal	-17.0
13904.050	59.2	74.0	-14.8	Horizontal	Horizontal	-7.7
4010.797	58.4	74.0	-15.6	Vertical	Vertical	39.9




Frequency (MHz)	Average (dBμV/m)	Lim.Average (dBμV/m)	Average-Lim.Average (dB)	Commentaire	Polarization	Correction (dB)
4194.299	46.6	54.0	-7.4	Horizontal	Horizontal	39.8
7278.750	45.5	54.0	-8.5	Horizontal	Horizontal	-17.5
13921.150	46.2	54.0	-7.8	Horizontal	Horizontal	-7.6

Frequency (MHz)	Peak (dBμV/m)	Lim.Peak (dBμV/m)	Peak-Lim.Peak (dB)	Commentaire	Polarization	Correction (dB)
4194.299	58.5	74.0	-15.5	Horizontal	Horizontal	39.8
7278.750	53.4	74.0	-20.6	Horizontal	Horizontal	-17.5
13921.150	58.2	74.0	-15.8	Horizontal	Horizontal	-7.6



Frequency (MHz)	Average (dBμV/m)	Lim.Average (dBμV/m)	Average-Lim.Average (dB)	Commentaire	Polarization	Correction (dB)
4366.911	46.6	54.0	-7.4	Horizontal	Horizontal	39.8
7205.600	47.6	54.0	-6.4	Horizontal	Horizontal	-17.6
13869.850	47.3	54.0	-6.7	Horizontal	Horizontal	-7.9

Frequency (MHz)	Peak (dBμV/m)	Lim.Peak (dBμV/m)	Peak-Lim.Peak (dB)	Commentaire	Polarization	Correction (dB)
4366.911	58.4	74.0	-15.6	Horizontal	Horizontal	39.8
7205.600	54.0	74.0	-20.0	Horizontal	Horizontal	-17.6
13869.850	58.2	74.0	-15.8	Horizontal	Horizontal	-7.9



Frequency (MHz)	Average (dBµV/m)	Lim.Average (dBµV/m)	Average-Lim.Average (dB)	Commentaire	Polarization	Correction (dB)
4099.120	46.6	54.0	-7.4	Horizontal	Horizontal	39.9
13449.950	46.3	54.0	-7.7	Horizontal	Horizontal	-8.9

Frequency (MHz)	Peak (dBµV/m)	Lim.Peak (dBµV/m)	Peak-Lim.Peak (dB)	Commentaire	Polarization	Correction (dB)
4099.120	58.1	74.0	-15.9	Horizontal	Horizontal	39.9
13449.950	58.0	74.0	-16.0	Horizontal	Horizontal	-8.9




QUALIFICATION (1GHz- 14GHz): The frequency list is created from the results obtained during the pre-characterization in anechoic chamber.

Measurements are performed using a PEAK and AVERAGE detection.


Test Frequency (MHz)	Meter Reading dB(μV)	Detector (Pk/Av)	Polarity (V/H)	Azimuth (Degrees)	Antenna Height (cm)	Transducer Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	The tilt position in degree
7278.750	74.01	Pk	H	0°		-17.49	56.5	74.0	-17.5	0°
7278.750	66.38	Av	H	0°		-17.49	48.9	54.0	-5.1	0°
7206.550	74.51	Pk	V	122°		-17.64	56.9	74.0	-17.1	30°
7206.550	67.38	Av	V	122°		-17.64	49.7	54.0	-4.3	30°




Results in the frequency band [14-26] GHz: (All tilt positions: 0°, 30°, 60°, 90°, 120°, 150°)




No significant frequency observed, the NSA margin >6dB.




No significant frequency observed, the NSA margin >6dB.




No significant frequency observed, the NSA margin >6dB.





No significant frequency observed, the NSA margin >6dB.



No significant frequency observed, the NSA margin >6dB.

QUALIFICATION (14GHz- 26GHz): The frequency list is created from the results obtained during the pre-characterization in anechoic chamber.

Measurements are performed using a PEAK and AVERAGE detection.

Test Frequency (MHz)	Meter Reading dB(μV)	Detector (Pk/Av)	Polarity (V/H)	Azimuth (Degrees)	Antenna Height (cm)	Transducer Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
No significant frequency observed										

9.7. CONCLUSION

Unwanted Emission in restricted frequency bands measurement performed on the sample of the product Michelin TMS AL-01, SN: 05&07&04&06, in configuration and description presented in this test report, show levels **compliant** to the 47 CFR PART 15.247 & RSS 247 ISSUE 2 limits.

10. UNCERTAINTIES CHART

Type de mesure / Kind of measurement	Incertitude élargie laboratoire / Wide uncertainty laboratory (k=2) $\pm x$	Incertitude limite du CISPR / CISPR uncertainty limit $\pm y$
Measurement of conducted disturbances in voltage on the power port	3.29dB	3.4 dB
Measurement of conducted disturbances in voltage on the telecommunication port.	3.26 dB	5dB
Measurement of discontinuous conducted disturbances in voltage	3.33 dB	3.4 dB
Measurement of conducted disturbances in current	2.67 dB	2.9dB
Spurious emission, radiated (Semi anechoic chamber & open test site)	5.60 dB	6 dB
Spurious emission, radiated (Full anechoic chamber above 1GHz)	± 3.8 dB	± 6 dB
Occupied Channel Bandwidth	± 2.8 %	± 5 %
RF power, conducted	± 1.2 dB	± 1.5 dB
Power Spectral Density, Conducted	± 1.7 dB	± 3 dB
Spurious emission, conducted	± 2.3 dB	± 3 dB
Temperature	± 0.75 °C	± 3 °C
Supply Voltages	± 1.7 %	± 3 %

Les valeurs d'incertitudes calculées du laboratoire étant inférieures aux valeurs d'incertitudes limites établies par la norme, la conformité de l'échantillon est établie directement par les niveaux limites applicables. / The uncertainty values calculated by the laboratory are lower than limit uncertainty values defined by the standard. The conformity of the sample is directly established by the applicable limits values.