

RF Exposure Report – Transcore 051181

Test	241119								
Transcore Model: 051181									
FCC IC SAR Eclusion									
4.3.1. Standalone SAR test exclusion considerations									
100 MHz to 6 GHz at separation distance less than or equal to 50 mm									
SAR Test Exclusion Calculator									
Insert values in yellow highlighted boxes to determine SAR Exclusion									
Max Power	4.0500	mW							
Min Separation	5	mm	When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.						
Frequency	0.915	GHz							
Answer	0.8 Must be less than or equal to 3.0 for SAR Exclusion								
KDB 628591 D01 TCB Exclusion List v14 TCBs are excluded from granting if: General Population: The Answer is equal to or greater than 24 (8x threshold) Controlled Use: The Answer is equal to or greater than 60 (20x threshold) and, when published RF exposure KDB procedures are not established for SAR testing or when SAR data is not provided to support compliance.									
Please also note the following: [FCC KDB quote] These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface. [End quote]									
RSS-102 Issue 6									
Table 11: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance									
Frequency (MHz)	≤4 mm (mW)	10 mm (mW)	15 mm (mW)	20 mm (mW)	25 mm (mW)				
≤ 300	45	116	139	163	189				
450	32	71	87	104	124				
835	21	32	41	54	72				
1900	6	10	18	33	57				
2450	3	7	16	32	56				
3500	2	6	15	29	50				
5800	1	5	13	23	32				
Frequency (MHz)	30 mm (mW)	35 mm (mW)	40 mm (mW)	45 mm (mW)	≥50 mm (mW)				
≤ 300	216	246	280	319	362				
450	147	175	208	248	296				
835	96	129	172	228	298				
1900	92	138	194	257	323				
2450	89	128	170	209	245				
3500	72	94	114	134	158				
5800	41	54	74	102	128				
The device operating with 4.05 mW output power and maintaining 5 mm distance complies with the requirements of									