

FCC SAR Test Report


FCC ID: FKGW01R10

Report No. : BTL-FCC SAR-2-2409T090
Equipment : Fully Rugged Tablet PC
Model Name : R10
Brand Name : DURABOOK
Serial Name : R10XXXXXX (X = 0 to 9, A to Z, a to z, or blank)
Applicant : Twinhead International Corporation
Address : 9F, No.550, Ruiguang Rd, Neihu, Taipei, Taiwan 11492
Radio Function : WCDMA Band II, IV, V and LTE Band 2, 4, 5, 7, 12, 13, 14, 25, 26, 41, 48, 66, 71
Standard(s) : **KDB447498 D04** Interim General RF Exposure Guidance v01
KDB616217 D04 SAR for laptop and Tablets v01r02
KDB865664 D01 SAR measurement 100 MHz to 6 GHz v01r04
KDB865664 D02 SAR Reporting v01r02
FCC§2.1093 Radiofrequency radiation exposure evaluation: portable devices
IEEE C95.1:2019 Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz
IEEE Std 1528:2013 Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques

Date of Receipt : Nov. 17, 2025
Date of Test : Dec. 20, 2025 ~ Jan. 11, 2026
Issued Date : Mar. 11, 2026

The above equipment has been tested and found in compliance with the requirement of the above standards by BTL Inc.


Prepared by :



Jimmy Gao, Engineer



Approved by :



Brett Shen, Engineer

BTL Inc.

No.18, Ln. 171, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City 114, Taiwan

Tel: +886-2-2657-3299

Fax: +886-2-2657-3331

Web: www.newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

Table of Contents	Page
1. GENERAL INFORMATION	6
1.1. GENERAL DESCRIPTION OF EUT	6
2. RF EMISSIONS MEASUREMENT	7
2.1. TEST FACILITY	7
2.2. MEASUREMENT UNCERTAINTY	8
2.3. WLAN ANTENNA INFORMATION	10
2.4. THE MAXIMUM SAR-1G VALUES	11
2.5. LABORATORY ENVIRONMENT	11
2.6. MAIN TEST INSTRUMENTS	12
3. SAR MEASUREMENTS SYSTEM CONFIGURATION	13
3.1. SAR MEASUREMENT SETUP	13
3.1.1. TEST SETUP LAYOUT	13
3.2. DASY5 E-FIELD PROBE SYSTEM	14
3.2.1. EX3DV4 PROBE SPECIFICATION	14
3.2.2. E-FIELD PROBE CALIBRATION	15
3.2.3. OTHER TEST EQUIPMENT	16
3.2.4. SCANNING PROCEDURE	17
3.2.5. DATA STORAGE AND EVALUATION	18
3.2.6. DATA EVALUATION BY SEMCAD	19
4. TISSUE-EQUIVALENT LIQUID	21
4.1. TISSUE-EQUIVALENT LIQUID INGREDIENTS	21
4.2. TISSUE-EQUIVALENT LIQUID PROPERTIES	22
5. SYSTEM CHECK	23
5.1. DESCRIPTION OF SYSTEM CHECK	23
5.2. DESCRIPTION OF SYSTEM CHECK	24
6. OPERATIONAL CONDITIONS DURING TEST	25
6.1. GENERAL DESCRIPTION OF TEST PROCEDURES	25
6.2. TEST POSITION ANTENNA LOCATION	25
6.3. TEST POSITION OF PORTABLE DEVICES	25
6.4. TEST POSITION	26
6.4.1. BODY TEST CONFIGURATION	26
7. SAR MEASUREMENT VARIABILITY AND UNCERTAINTY	31
7.1. SAR MEASUREMENT VARIABILITY	31
7.2. WCDMA TEST CONFIGURATION	32
7.3. LTE TEST CONFIGURATION	37
8. POWER REDUCTION BY PROXIMITY SENSING	38
8.1. PROCEDURES FOR DETERMINING PROXIMITY SENSOR TRIGGERING DISTANCES	38
8.2. PROCEDURES FOR DETERMINING ANTENNA AND PROXIMITY SENSOR COVERAGE	39
8.3. PROXIMITY SENSOR STATUS TABLE OF TRIGGER DISTANCE	40
8.4. POWER REDUCTION PER AIR-INTERFACE	41
9. CONDUCTED POWER RESULTS	43

9.1. CONDUCTED POWER MEASUREMENTS OF UMTS BAND	43
9.2. CONDUCTED POWER MEASUREMENTS OF LTE BAND	46
9.3. SAR TEST RESULTS	70
10. SAR TEST RESULTS	71
10.1. BODY SAR TEST RESULTS	71
11. SIMULTANEOUS TRANSMISSION CONDITIONS	74
11.1. STAND-ALONE SAR TEST EXCLUSION	74
11.2. SIMULTANEOUS TRANSMISSION CONDITIONS	75
11.3. ABOUT WWAN/BT/WIFI	76
12. TEST LAYOUT	78

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	2026/1/12
R01	Add Simultaneous transmission conditions	2026/2/13
R02	Add registration number	2026/3/11

1 GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF EUT

Equipment	Fully Rugged Tablet PC		
Model Name	R10		
Brand Name	DURABOOK		
Serial Name	R10XXXXXX (X = 0 to 9, A to Z, a to z, or blank)		
Model Difference	Different model distribute to different area.		
Power Rating	Brand: FSP Model : FSP065-RBBN3 I/P : 100-240V-, 1.5A 50-60Hz O/P : 19.0V 3.42A 65.0W		
Battery Information	Brand: Li-ion Battery Model : DURABOOK Rating :11.4VDC 4400mAh 50.16Wh		
WWAN Module	Sierra / EM7595		
Operation Frequency	Function	Band	Frequency (MHz)
	WCDMA	UMTS Band II	TX : 1850 - 1910
		UMTS Band IV	TX : 1710 - 1755
		UMTS Band V	TX : 824 - 849
	LTE	LTE Band 2	TX : 1850 - 1910
		LTE Band 4	TX : 1710 - 1755
		LTE Band 5	TX : 824 - 849
		LTE Band 7	TX : 2500 - 2570
		LTE Band 12	TX : 699 - 716
		LTE Band 13	TX : 777 - 787
		LTE Band 14	TX : 788 - 798
		LTE Band 25	TX : 1850 - 1915
		LTE Band 26	TX : 814 - 849
		LTE Band 41	TX : 2496 - 2690
		LTE Band 48	TX : 3550 - 3700
		LTE Band 66	TX : 1710 - 1780
		LTE Band 71	TX : 663 - 698
Test Model	R10		
Sample Status	Engineering Sample		
EUT Modification(s)	N/A		

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc. The test data, data evaluation, and equipment configuration contained in our test report were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO/IEC 17025 quality assessment standard and technical standard(s).

2 RF EMISSIONS MEASUREMENT

2.1 TEST FACILITY

The test locations stated below are under the TAF Accreditation Number 0659.

The test facilities used to collect the test data in this report is **SAR Test room** at the location of No. 68-1, Ln. 169, Sec.2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan.
(FCC RN:674415)(FCC DN:TW0659)

☒ SAR 01

☐ SAR 02

☐ SAR 03

2.2 MEASUREMENT UNCERTAINTY

Uncertainty Budget for Frequency range of 300 MHz to 3 GHz

Error Description	Uncertainty Value ($\pm$ %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)	V_i V_{eff}
Measurement System								
Probe Calibration	5.5	Normal	1	1	1	± 5.5 %	± 5.5 %	∞
Axial Isotropy of the probe	4.7	Rectangular	$\sqrt{3}$	0.7	0.7	± 1.9 %	± 1.9 %	∞
Hemispherical Isotropy of the probe	9.6	Rectangular	$\sqrt{3}$	0.7	0.7	± 3.9 %	± 3.9 %	∞
Boundary Effect	1	Rectangular	$\sqrt{3}$	1	1	± 0.6 %	± 0.6 %	∞
Probe Linearity	4.7	Rectangular	$\sqrt{3}$	1	1	± 2.7 %	± 2.7 %	∞
System Detection Limit	1	Rectangular	$\sqrt{3}$	1	1	± 0.6 %	± 0.6 %	∞
Modulation response	2.4	Rectangular	$\sqrt{3}$	1	1	± 1.4 %	± 1.4 %	∞
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Response Time	0.8	Rectangular	$\sqrt{3}$	1	1	± 0.5 %	± 0.5 %	∞
Integration Time	2.6	Rectangular	$\sqrt{3}$	1	1	± 1.5 %	± 1.5 %	∞
RF Ambient Noise	3	Rectangular	$\sqrt{3}$	1	1	± 1.7 %	± 1.7 %	∞
RF Ambient Reflections	3	Rectangular	$\sqrt{3}$	1	1	± 1.7 %	± 1.7 %	∞
Probe Positioner Mechanical Tolerance	0.02	Rectangular	$\sqrt{3}$	1	1	± 0.0 %	± 0.0 %	∞
Probe Positioning with respect to Phantom Shell	0.4	Rectangular	$\sqrt{3}$	1	1	± 0.2 %	± 0.2 %	∞
Max SAR Eval	2	Rectangular	$\sqrt{3}$	1	1	± 1.2 %	± 1.2 %	∞
Test Sample Related								
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	145
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	5
Power drift measurement	5	Rectangular	$\sqrt{3}$	1	1	± 2.9 %	± 2.9 %	∞
Power scaling	0	Rectangular	$\sqrt{3}$	1	1	± 0.0 %	± 0.0 %	∞
Phantom and Tissue Parameters (Physical parameter)								
Phantom Production Tolerances	6.1	Rectangular	$\sqrt{3}$	1	1	± 3.5 %	± 3.5 %	∞
SAR correction	1.9	Rectangular	$\sqrt{3}$	1	0.84	± 1.1 %	± 0.9 %	∞
Liquid Conductivity (mea.)	2.5	Rectangular	$\sqrt{3}$	0.78	0.71	± 1.1 %	± 1.0 %	∞
Liquid Permittivity (mea.)	2.5	Rectangular	$\sqrt{3}$	0.26	0.26	± 0.4 %	± 0.4 %	∞
Temp. unc. - Conductivity	3.4	Rectangular	$\sqrt{3}$	0.78	0.71	± 1.5 %	± 1.4 %	∞
Temp. unc. - Permittivity	0.4	Rectangular	$\sqrt{3}$	0.23	0.26	± 0.1 %	± 0.1 %	∞
Combined Standard Uncertainty (K = 1)						± 10.78 %	± 10.73 %	361
Expanded Uncertainty (K = 2)						± 21.55 %	± 21.46 %	

Uncertainty Budget for Frequency range of 3 GHz to 6 GHz

Error Description	Uncertainty Value ($\pm$ %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)	Vi V _{eff}
Measurement System								
Probe Calibration	6.55	Normal	1	1	1	± 6.6 %	± 6.55 %	∞
Axial Isotropy of the probe	4.7	Rectangular	$\sqrt{3}$	0.7	0.7	± 1.9 %	± 1.9 %	∞
Hemispherical Isotropy of the probe	9.6	Rectangular	$\sqrt{3}$	0.7	0.7	± 3.9 %	± 3.9 %	∞
Boundary Effects	2	Rectangular	$\sqrt{3}$	1	1	± 1.2 %	± 1.2 %	∞
Probe Linearity	4.7	Rectangular	$\sqrt{3}$	1	1	± 2.7 %	± 2.7 %	∞
System Detection Limit	1	Rectangular	$\sqrt{3}$	1	1	± 0.6 %	± 0.6 %	∞
Modulation response	2.4	Rectangular	$\sqrt{3}$	1	1	± 1.4 %	± 1.4 %	∞
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %	∞
Response Time	0.8	Rectangular	$\sqrt{3}$	1	1	± 0.5 %	± 0.5 %	∞
Integration Time	2.6	Rectangular	$\sqrt{3}$	1	1	± 1.5 %	± 1.5 %	∞
RF Ambient Noise	3	Rectangular	$\sqrt{3}$	1	1	± 1.7 %	± 1.7 %	∞
RF Ambient Reflections	3	Rectangular	$\sqrt{3}$	1	1	± 1.7 %	± 1.7 %	∞
Probe Positioner Mechanical Tolerance	0.04	Rectangular	$\sqrt{3}$	1	1	± 0.0 %	± 0.0 %	∞
Probe Positioning with respect to Phantom Shell	0.8	Rectangular	$\sqrt{3}$	1	1	± 0.5 %	± 0.5 %	∞
Max.SAR Eval	4	Rectangular	$\sqrt{3}$	1	1	± 2.3 %	± 2.3 %	∞
Test Sample Related								
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %	145
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %	5
Power Drift	5.0	Rectangular	$\sqrt{3}$	1	1	± 2.9 %	± 2.9 %	∞
Power scaling	0	Rectangular	$\sqrt{3}$	1	1	± 0.0 %	± 0.0 %	∞
Phantom and Setup								
Phantom Production Tolerances	6.6	Rectangular	$\sqrt{3}$	1	1	± 3.8 %	± 3.8 %	∞
SAR correction	1.9	Rectangular	$\sqrt{3}$	1	0.84	± 1.1 %	± 0.9 %	
Liquid Conductivity (mea.)	2.5	Rectangular	$\sqrt{3}$	0.78	0.71	± 1.1 %	± 1.0 %	∞
Liquid Permittivity (mea.)	2.5	Rectangular	$\sqrt{3}$	0.26	0.26	± 0.4 %	± 0.4 %	∞
Temp. unc. - Conductivity	3.4	Rectangular	$\sqrt{3}$	0.78	0.71	± 1.5 %	± 1.4 %	∞
Temp. unc. - Permittivity	0.4	Rectangular	$\sqrt{3}$	0.23	0.26	± 0.1 %	± 0.1 %	∞
Combined Standard Uncertainty (K = 1)						± 11.66 %	± 11.62 %	361
Expanded Uncertainty (K = 2)						± 23.33 %	± 23.24 %	

2.3. WLAN ANTENNA INFORMATION

Antenna	Manufacture	P/N	Type	Connector	Gain (dBi)	Note
Main	WGT	22+600911+00	PIFA	I-PEX	-3.28	UMTS-Band II
					-3.27	UMTS-Band IV
					-3.24	UMTS-Band V
					-3.28	LTE Band 2
					-3.27	LTE Band 4
					-3.24	LTE Band 5
					-4.67	LTE Band 7
					-4.85	LTE Band 12
					-4.57	LTE Band 13
					-3.29	LTE Band 14
					-3.28	LTE Band 25
					-3.24	LTE Band 26
					-4.67	LTE Band 41
					-7.48	LTE Band 48
					-3.27	LTE Band 66
					-5.22	LTE Band 71
Aux	WGT	22+600913+00	PIFA	I-PEX	-	RX only

The above Antenna information are derived from the antenna data sheet provided by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible

2.4. THE MAXIMUM SAR-1G VALUES

Mode	Distance(mm)	Highest Body Reported SAR-1g(W/kg)
UMTS Band II	0	1.013
UMTS Band IV	0	1.093
UMTS Band V	0	1.151
LTE Band 2/25	0	1.197
LTE Band 4/66	0	1.187
LTE Band 5/26	0	1.160
LTE Band 7	0	1.165
LTE Band 12	0	1.036
LTE Band 13	0	1.103
LTE Band 14	0	0.983
LTE Band 41	0	1.003
LTE Band 48	0	0.611
LTE Band 71	0	0.918

Note:

1.The device is in compliance with Specific Absorption Rate(SAR)for general population uncontrolled exposure limits according to the FCC rule §2.1093, the ANSI C95.1:2019/IEEE C95.1:2019, the NCRP Report Number 86 for uncontrolled environment and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528:2013.

2.5. LABORATORY ENVIRONMENT

Temperature	Min. = 18°C, Max. = 25°C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2.6. MAIN TEST INSTRUMENTS

Item	Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Interval
1	DASY5	Speag	DASY 5 (Version 52.10.4.1535)	N/A	N/A	N/A
2	Data Acquisition Electronics	Speag	DAE4	1486	Jun. 24, 2025	1 Year
3	E-field Probe	Speag	EX3DV4	7369	May. 21, 2025	1 Year
4	System Validation Dipole	Speag	D750V3	1145	Jun. 3, 2025	3 Year
5	System Validation Dipole	Speag	D835V2	4d084	Apr. 18, 2024	3 Year
6	System Validation Dipole	Speag	D1800V2	2d210	Jun. 11, 2025	3 Year
7	System Validation Dipole	Speag	D1900V2	5d208	Jun. 3, 2025	3 Year
8	System Validation Dipole	Speag	D2600V2	1111	Jun. 3, 2025	3 Year
9	System Validation Dipole	Speag	D3700V2	1065	Aug. 15, 2023	3 Year
10	ELI4 Phantom	Speag	ELI4 Phantom V5.0	1240	N/A	N/A
11	Vector network analyzer	keysight	P5007A	MY58100505	Feb. 25, 2025	1 Year
12	MXG Vector Signal Generator	Agilent	N5182B	MY51350711	Feb. 21, 2025	1 Year
13	Wideband Radio Communication Tester	R&S	CMW500	154121	Jun. 25, 2025	1 Year
14	Spectrum Analyzer	R&S	FSP 40	100129	Mar. 27, 2025	1 Year
15	Peak Power Analyzer	Keysight	8990B	MY51000517	Mar. 16, 2025	1 Year
16	Power Sensor	Keysight	N1923A	MY58310005	Mar.18, 2025	1 Year
17	Dielectric Probe Kit	Agilent	85070E	2593	N/A	N/A
18	Power Amplifier	EMCI	EMC053035	980869	N/A	N/A
19	Thermometer	PA	TA298	h001	Mar. 11, 2025	1 Year
20	Directional Coupler	Woken	50W Coupler	DOM5CIW3E2	N/A	N/A
21	Attenuator	Woken	WATT-518FS-10	N/A	N/A	N/A

Remark: "N/A" denotes no model name, serial No. or calibration specified.


3 SAR MEASUREMENTS SYSTEM CONFIGURATION

3.1 SAR MEASUREMENT SETUP

The DASY5 system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. A unit to operate the optical surface detector which is connected to the EOC.
5. The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.
6. The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows.
7. DASY5 software and SEMCAD data evaluation software.
8. Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
9. The generic twin phantom enabling the testing of left-hand and right-hand usage.
10. The device holder for handheld mobile phones.
11. Tissue simulating liquid mixed according to the given recipes.
12. System validation dipoles allowing to validate the proper functioning of the system.

3.1.1 TEST SETUP LAYOUT




3.2 DASY5 E-FIELD PROBE SYSTEM

The SAR measurements were conducted with the dosimetric probe EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.

3.2.1 EX3DV4 PROBE SPECIFICATION

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB
Dimensions	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Distance from probe tip to dipole centers: 1.0 mm



EX3DV4 E-field Probe

3.2.2 E-FIELD PROBE CALIBRATION

Each probe is calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy was evaluated and found to be better than $\pm 0.25\text{dB}$. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a wave guide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$\text{SAR} = C \frac{\Delta T}{\Delta t}$$

Where: Δt = Exposure time (30 seconds),

C = Heat capacity of tissue (brain or muscle),

ΔT = Temperature increase due to RF exposure.

Or
$$\text{SAR} = \frac{|E|^2 \sigma}{\rho}$$

Where: σ = Simulated tissue conductivity,

ρ = Tissue density (kg/m^3).

3.2.3 OTHER TEST EQUIPMENT

3.2.3.1. DEVICE HOLDER FOR TRANSMITTERS

Construction: Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.) It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner. The extension is fully compatible with the Twin SAM, ELI4 and SAM v6.0 Phantoms.

Material: POM, Acrylic glass, Foam


3.2.3.2 PHANTOM

Model	ELI4 Phantom	
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
Shell Thickness	2±0.1 mm	
Filling Volume	Approx. 30 liters	
Dimensions	Length: 600 mm ; Width: 190mm Height: adjustable feet	
Available	Special	

Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Shell Thickness	2 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length:1000mm; Width: 500mm Height: adjustable feet	
Available	Special	

3.2.4 SCANNING PROCEDURE

The SAR test against the head and body-worn phantom was carried out as follow:



After an area scan has been done at a fixed distance of 1.4mm from the surface of the phantom on the source side, a 3D scan is set up around the location of the maximum spot SAR. First, a point within the scan area is visited by the probe and a SAR reading taken at the start of testing. At the end of testing, the probe is returned to the same point and a second reading is taken. Comparison between these start and end readings enables the power drift during measurement to be assessed.

Above is the scanning procedure flow chart and table from the IEEE1528 standard.

This is the procedure for which all compliant testing should be carried out to ensure that all variations of the device position and transmission behavior are tested.

3.2.5 DATA STORAGE AND EVALUATION

3.2.5.1 DATA STORAGE

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension "DAE4". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm²], [dBre], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

3.2.6 DATA EVALUATION BY SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	Sensitivity	Normi, a _{i0} , a _{i1} , a _{i2}
	Conversion factor	ConvF _i
	Diode compression point	Dcp _i
Device parameters:	Frequency	f
	Crest factor	cf
Media parameters:	Conductivity	
	Density	

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot cf / dcp_i$$

With	V _i = compensated signal of channel i	(i = x, y, z)
	U _i = input signal of channel i	(i = x, y, z)
	cf = crest factor of exciting field	(DASY parameter)
	dcp _i = diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E-field probes: } E_i = (V_i / \text{Norm}_i \cdot \text{ConvF})^{1/2}$$

$$\text{H-field probes: } H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1} f + a_{i2} f^2) / f$$

With V_i = compensated signal of channel i ($i = x, y, z$)

Norm_i = sensor sensitivity of channel i ($i = x, y, z$)
[mV/(V/m)²] for E-field Probes

ConvF = sensitivity enhancement in solution

a_{ij} = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E_i = electric field strength of channel i in V/m

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{\text{tot}} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$\text{SAR} = (E_{\text{tot}})^2 \cdot \sigma / (\rho \cdot 1000)$$

With SAR = local specific absorption rate in mW/g

E_{tot} = total field strength in V/m
= conductivity in [mho/m] or [Siemens/m]
= equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{\text{pwe}} = E_{\text{tot}}^2 / 3770 \text{ or } P_{\text{pwe}} = H_{\text{tot}}^2 \cdot 37.7$$

With P_{pwe} = equivalent power density of a plane wave in mW/cm²

E_{tot} = total field strength in V/m

H_{tot} = total magnetic field strength in A/m

4 TISSUE-EQUIVALENT LIQUID

4.1 TISSUE-EQUIVALENT LIQUID INGREDIENTS

The liquid is consisted of water, salt and Glycol, Sugar, Preventol and Cellulose. The liquid has previously been proven to be suited for worst-case. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values. The below table shows the detail solution. It's satisfying the latest tissue dielectric parameters requirements proposed by the IEC 62209.

Composition of the Tissue Equivalent Matter

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether	Oxidized Mineral Oil
Head 750	0.2	-	0.2	1.5	56.0	-	42.1	-	-
Head 835	0.2	-	0.2	1.5	57.0	-	41.2	-	-
Head 1800	-	44.5	-	0.3	-	-	55.2	-	-
Head 1900	-	44.5	-	0.2	-	-	55.3	-	-
Head 2600	-	45.1	-	0.1	-	-	54.8	-	-
Head 3500	-	8.0	-	0.2	-	20.0	71.8	-	-

4.2 TISSUE-EQUIVALENT LIQUID PROPERTIES

Dielectric Performance of Tissue Simulating Liquid

Tissue Verification									
Date	Tissue Type	Frequency (MHz)	Conductivity (σ)	Permittivity (ϵ_r)	Targeted Conductivity (σ)	Targeted Permittivity (ϵ_r)	Deviation Conductivity (σ) (%)	Deviation Permittivity (ϵ_r) (%)	Limit (%) ± 5
2025/11/22	Head	750	0.90	40.99	0.89	41.94	0.18	-2.27	± 5
2025/11/26	Head	750	0.89	43.52	0.89	41.94	-0.83	3.75	± 5
2025/12/1	Head	750	0.88	42.21	0.89	41.94	-1.05	0.64	± 5
2025/12/4	Head	750	0.91	43.55	0.89	41.94	1.52	3.83	± 5
2025/11/24	Head	835	0.92	42.07	0.91	41.55	0.82	1.24	± 5
2025/12/2	Head	835	0.93	43.12	0.91	41.55	1.92	3.76	± 5
2026/1/11	Head	835	0.92	42.14	0.91	41.55	0.82	1.40	± 5
2025/11/27	Head	1800	1.46	41.38	1.40	40.00	4.57	3.45	± 5
2025/12/2	Head	1800	1.43	41.29	1.40	40.00	2.43	3.22	± 5
2025/11/20	Head	1900	1.40	38.88	1.40	40.00	-0.21	-2.81	± 5
2025/12/2	Head	1900	1.39	40.45	1.40	40.00	-0.86	1.13	± 5
2026/1/11	Head	1900	1.40	39.36	1.40	40.00	-0.29	-1.60	± 5
2025/11/21	Head	2600	1.94	39.55	1.96	39.01	-0.92	1.39	± 5
2025/11/25	Head	2600	1.95	39.92	1.96	39.01	-0.77	2.32	± 5
2025/12/4	Head	2600	1.99	40.60	1.96	39.01	1.28	4.08	± 5
2025/11/28	Head	3700	3.07	35.89	3.12	37.70	-1.46	-4.80	± 5
2025/12/4	Head	3700	3.07	37.84	3.12	37.70	-1.59	0.36	± 5

Note:

- 1)The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.
- 2)KDB 865664 was ensured to be applied for probe calibration frequencies greater than or equal to 50MHz of the EUT frequencies.
- 3)The above measured tissue parameters were used in the DASY software to perform interpolation via the DASY software to determine actual dielectric parameters at the test frequencies. The SAR test plots may slightly differ from the table above since the DASY rounds to three significant digits.
- 4) According to FCC TCB workshop April, 2019 RF Exposure Procedures Update(Effective February 19,2019, FCC has permitted the use of single head-tissue simulating liquid specified in IEEE 62209-1- for all SAR tests.

5 SYSTEM CHECK


5.1 DESCRIPTION OF SYSTEM CHECK

The manufacturer calibrates the probes annually. Dielectric parameters of the tissue simulants were measured every day using the dielectric probe kit and the network analyzer. A system check measurement was made following the determination of the dielectric parameters of the simulant, using the dipole validation kit. A power level of 250 mW(below 3GHz) or 100mW(3-6GHz), which was placed under the flat section of the twin SAM phantom. The system check results (dielectric parameters and SAR values) are given in the 6.2.

System check results have to be equal or near the values determined during dipole calibration with the relevant liquids and test system ($\pm 10\%$).

System check is performed regularly on all frequency bands where tests are performed with the DASY5 system.

System Check Set-up



System Check photo



5.2 DESCRIPTION OF SYSTEM CHECK

System Check in Tissue Simulating Liquid

The system check is performed for verifying the accuracy of the complete measurement system and performance of the software. The system check is performed with tissue equivalent material according to IEEE P1528 (described above). The following table shows system check results for all frequency bands and tissue liquids used during the tests.

Date	System Dipole			Target 1g [W/kg]	Measured 1g [W/kg]	Normalized to 1W 10g[W/kg]	Deviation [%]	Limited [%]
	Type	Serial No.	Liquid					
2025/11/22	D750V3	1145	Head	8.55	2.01	8.04	-5.96	± 10
2025/11/26	D750V3	1145	Head	8.55	2.15	8.60	0.58	± 10
2025/12/1	D750V3	1145	Head	8.55	2.22	8.88	3.86	± 10
2025/12/4	D750V3	1145	Head	8.55	2.09	8.36	-2.22	± 10
2025/11/24	D835V2	4d120	Head	9.77	2.38	9.52	-2.56	± 10
2025/12/2	D835V2	4d120	Head	9.77	2.46	9.84	0.72	± 10
2026/1/11	D835V2	4d120	Head	9.77	2.39	9.56	-2.15	± 10
2025/11/27	D1800V2	2d210	Head	38.20	9.64	38.56	0.94	± 10
2025/12/2	D1800V2	2d210	Head	38.20	9.73	38.92	1.88	± 10
2025/11/20	D1900V2	5d208	Head	40.20	10.00	40.00	-0.50	± 10
2025/12/2	D1900V2	5d208	Head	40.20	9.69	38.76	-3.58	± 10
2026/1/11	D1900V2	5d208	Head	40.20	9.88	39.52	-1.69	± 10
2025/11/21	D2600V2	1077	Head	56.10	14.70	58.80	4.81	± 10
2025/11/25	D2600V2	1077	Head	56.10	14.80	59.20	5.53	± 10
2025/12/4	D2600V2	1077	Head	56.10	13.80	55.20	-1.60	± 10
2025/11/28	D3700V2	1065	Head	67.70	6.40	64.00	-5.47	± 10
2025/12/4	D3700V2	1065	Head	67.70	7.08	70.80	4.58	± 10

6.1 GENERAL DESCRIPTION OF TEST PROCEDURES

6.2 TEST POSITION ANTENNA LOCATION



Minimum Separation Distance					
P-Sensor	Mode	Antenna	Position	Distance (mm)	Evaluation Test
on	WWAN	Main	Edge1	3.00	Yes
			Edge2	23.05	Yes
			Edge3	190.89	No
			Edge4	152.62	No
			Rear	5.00	Yes
off	WWAN	Main	Edge1	13.00	Yes
			Edge2	33.05	Yes
			Rear	15.00	Yes

6.4 TEST POSITION

6.4.1 BODY TEST CONFIGURATION

The SAR Exclusion Threshold in KDB 447498 D01 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an EUT edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned adjacent the phantom and the edge containing the antenna positioned perpendicular to the phantom.

SAR test reduction and exclusion guidance

(1) The SAR exclusion threshold for is defined by the following equation:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

P-Sensor on

Mode	Ant	Position	Distance (mm)	f (MHz)	Max Power(dBm)	Max Power(mW)	SAR Exclusion threshold(mW)	Test required
UMTS Band II	Main	Raer	5.00	1880	19.00	79.43	3	Yes
UMTS Band IV	Main	Raer	5.00	1732.6	19.00	79.43	3	Yes
UMTS Band V	Main	Raer	5.00	836.4	22.50	177.83	9	Yes

Mode	Ant	Position	Distance (mm)	f (MHz)	Max Power(dBm)	Max Power(mW)	SAR Exclusion threshold(mW)	Test required
UMTS Band II	Main	Edge 1	3.00	1880	19.00	79.43	3	Yes
UMTS Band IV	Main	Edge 1	3.00	1732.6	19.00	79.43	3	Yes
UMTS Band V	Main	Edge 1	3.00	836.4	22.50	177.83	9	Yes

Mode	Ant	Position	Distance (mm)	f (MHz)	Max Power(dBm)	Max Power(mW)	SAR Exclusion threshold(mW)	Test required
UMTS Band II	Main	Edge 2	23.05	1880	19.00	79.43	26	Yes
UMTS Band IV	Main	Edge 2	23.05	1732.6	19.00	79.43	26	Yes
UMTS Band V	Main	Edge 2	23.05	836.4	22.50	177.83	44	Yes

Mode	Ant	Position	Distance (mm)	f (MHz)	Max Power(dBm)	Max Power(mW)	SAR Exclusion threshold(mW)	Test required
LTE Band 2/25	Main	Rear	5.00	1880	19.50	89.13	3	Yes
LTE Band 4/66	Main	Rear	5.00	1745	18.50	70.79	3	Yes
LTE Band 5/26	Main	Rear	5.00	836.5	23.00	199.53	9	Yes
LTE Band 7	Main	Rear	5.00	2535	21.00	125.89	3	Yes
LTE Band 12	Main	Rear	5.00	707.5	22.50	177.83	9	Yes
LTE Band 13	Main	Rear	5.00	782	22.50	177.83	9	Yes
LTE Band 14	Main	Rear	5.00	793	22.50	177.83	9	Yes
LTE Band 41	Main	Rear	5.00	2593	22.50	177.83	3	Yes
LTE Band 48	Main	Rear	5.00	3625	22.00	158.49	2	Yes
LTE Band 71	Main	Rear	5.00	680.5	20.50	112.20	9	Yes

Mode	Ant	Position	Distance (mm)	f (MHz)	Max Power(dBm)	Max Power(mW)	SAR Exclusion threshold(mW)	Test required
LTE Band 2/25	Main	Edge1	3.00	1880	19.50	89.13	3	Yes
LTE Band 4/66	Main	Edge1	3.00	1745	18.50	70.79	3	Yes
LTE Band 5/26	Main	Edge1	3.00	836.5	23.00	199.53	9	Yes
LTE Band 7	Main	Edge1	3.00	2535	21.00	125.89	3	Yes
LTE Band 12	Main	Edge1	3.00	707.5	22.50	177.83	9	Yes
LTE Band 13	Main	Edge1	3.00	782	22.50	177.83	9	Yes
LTE Band 14	Main	Edge1	3.00	793	22.50	177.83	9	Yes
LTE Band 41	Main	Edge1	3.00	2593	22.50	177.83	3	Yes
LTE Band 48	Main	Edge1	3.00	3625	22.00	158.49	2	Yes
LTE Band 71	Main	Edge1	3.00	680.5	20.50	112.20	9	Yes

Mode	Ant	Position	Distance (mm)	f (MHz)	Max Power(dBm)	Max Power(mW)	SAR Exclusion threshold(mW)	Test required
LTE Band 2/25	Main	Edge2	23.05	1880	19.50	89.13	44	Yes
LTE Band 4/66	Main	Edge2	23.05	1745	18.50	70.79	44	Yes
LTE Band 5/26	Main	Edge2	23.05	836.5	23.00	199.53	66	Yes
LTE Band 7	Main	Edge2	23.05	2535	21.00	125.89	38	Yes
LTE Band 12	Main	Edge2	23.05	707.5	22.50	177.83	66	Yes
LTE Band 13	Main	Edge2	23.05	782	22.50	177.83	66	Yes
LTE Band 14	Main	Edge2	23.05	793	22.50	177.83	66	Yes
LTE Band 41	Main	Edge2	23.05	2593	22.50	177.83	38	Yes
LTE Band 48	Main	Edge2	23.05	3625	22.00	158.49	32	Yes
LTE Band 71	Main	Edge2	23.05	680.5	20.50	112.20	66	Yes

P-Sensor off

Mode	Ant	Position	Distance (mm)	f (MHz)	Max Power(dBm)	Max Power(mW)	SAR Exclusion threshold(mW)	Test required
UMTS Band II	Main	Raer	15.00	1880	23.50	223.87	26	Yes
UMTS Band IV	Main	Raer	15.00	1732.6	24.00	251.19	26	Yes
UMTS Band V	Main	Raer	15.00	836.4	23.50	223.87	44	Yes

Mode	Ant	Position	Distance (mm)	f (MHz)	Max Power(dBm)	Max Power(mW)	SAR Exclusion threshold(mW)	Test required
UMTS Band II	Main	Edge 1	13.00	1880	23.50	223.87	12	Yes
UMTS Band IV	Main	Edge 1	13.00	1732.6	24.00	251.19	12	Yes
UMTS Band V	Main	Edge 1	13.00	836.4	23.50	223.87	25	Yes

Mode	Ant	Position	Distance (mm)	f (MHz)	Max Power(dBm)	Max Power(mW)	SAR Exclusion threshold(mW)	Test required
UMTS Band II	Main	Edge 2	33.05	1880	23.50	223.87	92	Yes
UMTS Band IV	Main	Edge 2	33.05	1732.6	24.00	251.19	92	Yes
UMTS Band V	Main	Edge 2	33.05	836.4	23.50	223.87	116	Yes

Mode	Ant	Position	Distance (mm)	f (MHz)	Max Power(dBm)	Max Power(mW)	SAR Exclusion threshold(mW)	Test required
LTE Band 2/25	Main	Rear	15.00	1880	24.00	251.19	26	Yes
LTE Band 4/66	Main	Rear	15.00	1745	24.00	251.19	26	Yes
LTE Band 5/26	Main	Rear	15.00	836.5	24.00	251.19	44	Yes
LTE Band 7	Main	Rear	15.00	2535	24.00	251.19	22	Yes
LTE Band 12	Main	Rear	15.00	707.5	23.50	223.87	44	Yes
LTE Band 13	Main	Rear	15.00	782	23.50	223.87	44	Yes
LTE Band 14	Main	Rear	15.00	793	23.50	223.87	44	Yes
LTE Band 41	Main	Rear	15.00	2593	23.50	223.87	22	Yes
LTE Band 48	Main	Rear	15.00	3625	23.00	199.53	18	Yes
LTE Band 71	Main	Rear	15.00	680.5	23.50	223.87	44	Yes

Mode	Ant	Position	Distance (mm)	f (MHz)	Max Power(dBm)	Max Power(mW)	SAR Exclusion threshold(mW)	Test required
LTE Band 2/25	Main	Edge1	13.00	1880	24.00	251.19	12	Yes
LTE Band 4/66	Main	Edge1	13.00	1745	24.00	251.19	12	Yes
LTE Band 5/26	Main	Edge1	13.00	836.5	24.00	251.19	25	Yes
LTE Band 7	Main	Edge1	13.00	2535	24.00	251.19	10	Yes
LTE Band 12	Main	Edge1	13.00	707.5	23.50	223.87	25	Yes
LTE Band 13	Main	Edge1	13.00	782	23.50	223.87	25	Yes
LTE Band 14	Main	Edge1	13.00	793	23.50	223.87	25	Yes
LTE Band 41	Main	Edge1	13.00	2593	23.50	223.87	10	Yes
LTE Band 48	Main	Edge1	13.00	3625	23.00	199.53	8	Yes
LTE Band 71	Main	Edge1	13.00	680.5	23.50	223.87	25	Yes

Mode	Ant	Position	Distance (mm)	f (MHz)	Max Power(dBm)	Max Power(mW)	SAR Exclusion threshold(mW)	Test required
LTE Band 2/25	Main	Edge2	33.05	1880	24.00	251.19	92	Yes
LTE Band 4/66	Main	Edge2	33.05	1745	24.00	251.19	92	Yes
LTE Band 5/26	Main	Edge2	33.05	836.5	24.00	251.19	116	Yes
LTE Band 7	Main	Edge2	33.05	2535	24.00	251.19	83	Yes
LTE Band 12	Main	Edge2	33.05	707.5	23.50	223.87	116	Yes
LTE Band 13	Main	Edge2	33.05	782	23.50	223.87	116	Yes
LTE Band 14	Main	Edge2	33.05	793	23.50	223.87	116	Yes
LTE Band 41	Main	Edge2	33.05	2593	23.50	223.87	83	Yes
LTE Band 48	Main	Edge2	33.05	3625	23.00	199.53	71	Yes
LTE Band 71	Main	Edge2	33.05	680.5	23.50	223.87	116	Yes

7 SAR MEASUREMENT VARIABILITY AND UNCERTAINTY

7.1 SAR MEASUREMENT VARIABILITY

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

The detailed repeated measurement results are shown in Section 9.

7.2 WCDMA TEST CONFIGURATION

1. Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the procedures description in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all "1s" for WCDMA/HSDPA or applying the required inner loop power control procedure to maintain maximum output power while HSUPA is active. Result for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HSDPA, HSPA)

Should be tabulated in the SAR report. All configuration that are not supported by the DUT or cannot be measured due to technical or equipment limitation should be clearly identified.

2. WCDMA

(1). Head SAR Measurements

SAR for Head exposure configurations in voice mode is measured using a 12.2 kbps RMC with TPC bits configured to all "1s". SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2 kbps AMR is less than ¼ dB higher than that measured in 12.2 kbps RMC. Otherwise SAR is measured on the maximum output channel in 12.2 kbps AMR with 3.4 kbps SRB (signalling radio bearer) using the exposure configuration that results in the highest SAR in 12.2 kbps RMC for that RF channel.

(2). Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits configured to all "1s". SAR for other spreading codes and multiple DPDCHn, when supported by the EUT, are not required when the maximum average outputs of each RF channel, for each spreading code and DPDCHn configuration, are less than ¼ dB higher than those measured in 12.2 kbps RMC.

3. HSDPA

SAR for body exposure configurations is measured according to the "Body SAR Measurements" procedures of 3G device. In addition, body SAR is also measured for HSDPA when the maximum average outputs of each RF channel with HSDPA active is at ¼ dB higher than that measured without HSDPA using 12.2 kbps RMC or the maximum SAR 12.2 kbps RMC is above 75% of the SAR limit. Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, using the highest body SAR configuration in 12.2 kbps RMC without HSDPA.

HSDPA should be configured according to UE category of a test device. The number of HS-DSCH/HS-PDSCHs, HAPRQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission condition, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4ms with a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. The β_c and β_d gain factors for DPCCH and DPDCH were set according to the values in the

below table, β_{hs} for HS-DPCCH is set automatically to the correct value when ΔACK , $\Delta NACK$,

$\Delta CQI = 8$. The variation of the β_c / β_d ratio causes a power reduction at sub-tests 2 - 4.

Sub-test ^o	β_c ^o	β_d ^o	β_d (SF) ^o	β_c / β_d ^o	β_{hs} (1) ^o	CM(dB)(2) ^o	MPR (dB) ^o
1 ^o	2/15 ^o	15/15 ^o	64 ^o	2/15 ^o	4/15 ^o	0.0 ^o	0 ^o
2 ^o	12/15(3) ^o	15/15(3) ^o	64 ^o	12/15(3) ^o	24/15 ^o	1.0 ^o	0 ^o
3 ^o	15/15 ^o	8/15 ^o	64 ^o	15/8 ^o	30/15 ^o	1.5 ^o	0.5 ^o
4 ^o	15/15 ^o	4/15 ^o	64 ^o	15/4 ^o	30/15 ^o	1.5 ^o	0.5 ^o

Note 1: ΔACK , $\Delta NACK$ and $\Delta CQI = 8$ $A_{hs} = \beta_{hs} / \beta_c = 30/15$ $\beta_{hs} = 30/15 * \beta_c$ ^o

Note 2: CM=1 for $\beta_c / \beta_d = 12/15$, $\beta_{hs} / \beta_c = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.^o

Note 3: For subtest 2 the β_c / β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$ ^o

The measurements were performed with a Fixed Reference Channel (FRC) and H-Set 1 QPSK.

Settings of required H-Set 1 QPSK acc. to 3GPP 34.121

Parameter	Value
Nominal average inf. bit rate	534 kbit/s
Inter-TTI Distance	3 TTI"s
Number of HARQ Processes	2 Processes
Information Bit Payload	3202 Bits
MAC-d PDU size	336 Bits
Number Code Blocks	1 Block
Binary Channel Bits Per TTI	4800 Bits
Total Available SMLs in UE	19200 SMLs
Number of SMLs per HARQ Process	9600 SMLs
Coding Rate	0.67
Number of Physical Channel Codes	5

HSDPA UE category

HS-DSCH Category	Maximum HS-DSCH Codes Received	Minimum Inter-TTI Interval	Maximum HS-DSCH Transport Block Bits/HS-DSCH TTI	Total Soft Channel Bits
1	5	3	7298	19200
2	5	3	7298	28800
3	5	2	7298	28800
4	5	2	7298	38400
5	5	1	7298	57600
6	5	1	7298	67200
7	10	1	14411	115200
8	10	1	14411	134400
9	15	1	25251	172800
10	15	1	27952	172800
11	5	2	3630	14400
12	5	1	3630	28800
13	15	1	34800	259200
14	15	1	42196	259200
15	15	1	23370	345600
16	15	1	27952	345600

4. HSUPA

SAR for Body exposure configurations is measured according to the "Body SAR Measurements" procedures of 3G device. When the maximum output power is $\leq \frac{1}{4}$ dB higher than the primary mode or when the SAR of the primary mode is scaled by the ratio of specified maximum output power and SAR is $\leq 75\%$ SAR Limit, SAR measurement is not required for the secondary mode.

The 3G SAR test reduction procedures is applied to HSPA(HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures for the highest reported body exposure SAR configuration in 12.2 kbps RMC.

Due to inner loop power control requirements in HSUPA, a commercial communication test set should be used for the output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSDPA should be configured according to the values indicated below as well as other applicable procedures described in the "WCDMA Handset" and „Release 5 HSDPA Data Device" sections of 3G device.

Subtests for WCDMA Release 6 HSUPA

WCDMA General Settings	Mode	HSPA	HSPA	HSPA	HSPA	HSPA
	Subtest	1	2	3	4	5
	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	15/15
	β_{ec}	209/225	12/15	30/15	2/15	24/15
	β_c/β_d	11/15	6/15	9/15	2/15	15/15
	β_{hs}	22/15	12/15	30/15	4/15	30/15
	β_{ed}	1309/225	94/75	47/15	56/75	134/15
	CM (dB)	1	3	2	3	1
	MPR (dB)	0	2	1	2	0

HSUPA UE category

UE E-DCH Category	Maximum E-DCH Codes Transmitted	Number of HARQ Processes	E-DCH TTI(ms)	Minimum Spreading Factor	Maximum E-DCH Transport Block Bits	Max Rate (Mbps)
1	1	4	10	4	7110	0.7296
2	2	8	2	4	2798	1.4592
	2	4	10	4	14484	
3	2	4	10	4	14484	1.4592
4	2	8	2	2	5772	2.9185
	2	4	10	2	20000	2.00
5	2	4	10	2	20000	2.00
6 (No DPDCH)	4	8	10	2SF2&2SF4	11484	5.76
	4	4	2		20000	2.00
7 (No DPDCH)	4	8	2	2SF2&2SF4	22996	?
	4	4	10		20000	?

NOTE: When 4 codes are transmitted in parallel, two codes shall be transmitted with SF2 and two with SF4. UE categories 1 to 6 support QPSK only. UE category 7 supports QPSK and 16QAM. (TS25.306-7.3.0).

5. DC-HSDPA

In DC-HSDPA implementation of this device, the uplink parameters are the same as HSDPA. No additional channels and modulations (16 QAM, and 64 QAM) are supported in uplink. The difference is only in the downlink parameters, where two carriers are supported. HSDPA settings were used on uplink.

For Rel. 8 DC-HSDPA apply the four subtests from HSDPA Release 5 except use fixed reference channel H-Set 12 for DC-HSDPA. And we can apply the same SAR test exclusion criteria used for Rel. 6 HSPA for Rel. 7 HSPA+ and Rel. 8 DC-HSDPA. That is, if the HSPA, HSPA+, or the DC-HSDPA maximum output is not more than 0.25 dB higher than WCDMA, SAR measurement for those modes is not required.

The following tests were completed according to procedures in section 7.3.13 of 3GPP TS 34.108 v9.5.0. A summary of these settings are illustrated below:

Downlink Physical Channels are set as per 3GPP TS34.121-1 v9.0.0 E.5.0
Levels for HSDPA connection setup

Parameter During Connection setup	Unit	Value
P-CPICH_Ec/lor	dB	-10
P-CCPCH and SCH_Ec/lor	dB	-12
PICH_Ec/lor	dB	-15
HS-PDSCH	dB	off
HS-SCCH_1	dB	off
DPCH_Ec/lor	dB	-5
OCNS_Ec/lor	dB	-3.1

Call is set up as per 3GPP TS34.108 v9.5.0 sub clause 7.3.13

The configurations of the fixed reference channels for HSDPA RF tests are described in 3GPP TS 34.121, annex C for FDD and 3GPP TS 34.122.

The measurements were performed with a Fixed Reference Channel (FRC) H-Set 12 with QPSK

Parameter	Value
Nominal average inf. bit rate	60 kbit/s
Inter-TTI Distance	1 TTI"s
Number of HARQ Processes	6 Processes
Information Bit Payload	120 Bits
Number Code Blocks	1 Block
Binary Channel Bits Per TTI	960 Bits
Total Available SMLs in UE	19200 SMLs
Number of SMLs per HARQ Process	3200 SMLs
Coding Rate	0.15
Number of Physical Channel Codes	1

Note:

1. The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table above.
2. Maximum number of transmission is limited to 1,i.e.,retransmission is not allowed. The redundancy and constellation version 0 shall be used.




Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)

The following 4 Sub-tests for HSDPA were completed according to Release 5 procedures. A summary of subtest settings are illustrated below:

Sub-test ^o	β_c ^o	β_d ^o	β_d (SF) ^o	β_c/β_d ^o	$\beta_{hs}(1)$ ^o	CM(dB)(2) ^o	MPR (dB) ^o
1 ^o	2/15 ^o	15/15 ^o	64 ^o	2/15 ^o	4/15 ^o	0.0 ^o	0 ^o
2 ^o	12/15(3) ^o	15/15(3) ^o	64 ^o	12/15(3) ^o	24/15 ^o	1.0 ^o	0 ^o
3 ^o	15/15 ^o	8/15 ^o	64 ^o	15/8 ^o	30/15 ^o	1.5 ^o	0.5 ^o
4 ^o	15/15 ^o	4/15 ^o	64 ^o	15/4 ^o	30/15 ^o	1.5 ^o	0.5 ^o

Note 1: ΔACK , $\Delta NACK$ and $\Delta CQI=8$ $A_{hs}=\beta_{hs}/\beta_c=30/15$ $\beta_{hs}=30/15*\beta_c$

Note 2: CM=1 for $\beta_c/\beta_d=12/15$, $\beta_{hs}/\beta_c=24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 3: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c=11/15$ and $\beta_d=15/15$

Up commands are set continuously to set the UE to Max power.

Note:

- 1.The Dual Carriers transmission only applies to HSDPA physical channels
- 2.The Dual Carriers belong to the same Node and are on adjacent carriers.
- 3.The Dual Carriers do not support MIMO to serve UEs configured for dual cell operation
- 4.The Dual Carriers operate in the same frequency band .
- 5.The device doesn't support the modulation of 16QAM in uplink but 64QAM in downlink for DC-HSDPA mode.
- 6.The device doesn't support carrier aggregation for it just can operate in Release 8.

7.3 LTE TEST CONFIGURATION

Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR. The RS CMW500 was used for LTE output power measurements and SAR testing. Max power control was used so the UE transmits with maximum output power during SAR testing. SAR must be measured with the maximum TTI(transmit time interval) supported by the device in each LTE configuration.

1)Spectrum Plots for RB configurations

A properly configured base station simulator was used for LTE output power measurements and SAR testing. Therefore, spectrum plots for RB configurations were not required to be included in this report.

2) MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3-6.2.5 under Table 6.2.3-1.

3)A-MPR

A-MPR(Additional MPR) has been disabled for all SAR tests by using Network Signaling Value of "NS=01"on the base station simulator.

4)SAR test requirements

The LTE SAR test is choice the max power mode and start with the max power channel.

A) Largest channel bandwidth standalone SAR test requirements

i) QPSK with 1 RB allocation

When the SAR is ≤ 1 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the 10-g SAR of a required test channel is > 1.8 W/kg, SAR is required for all three RB offset configurations for that required test channel.

8 POWER REDUCTION BY PROXIMITY SENSING

A proximity sensor for power reduction is implemented in this device to address RF exposure compliance when the cellular antenna is positioned close to the user's body. The sensor's mechanical structure is designed to fit within the enclosure design used in this device and also extended around the edge and top of the antenna element in order to optimize sensitivity in these orientations. This design combines the antenna printed directly on a plastic part and proximity sensor FPC (Flexible Printed Circuit) bonded together into one piece. According to KDB 616217 D04 SAR for laptop and tablets v01r02)

8.1 PROCEDURES FOR DETERMINING PROXIMITY SENSOR TRIGGERING DISTANCES

The following procedures should be applied to determine proximity sensor triggering distances for the back surface and individual edges of a tablet. Conducted power is monitored qualitatively to identify the general triggering characteristics and recorded quantitatively, versus spacing, as required by the procedures. Unless there is built-in test software that reports the triggering conditions and enables the power levels to be confirmed separately, monitoring of conducted power during the triggering tests typically requires internal access to the antenna ports inside the tablet, which may interfere with the triggering tests.

1. The relevant transmitter should be set to operate at its normal maximum output power.
2. The entire back surface or edge of the tablet is positioned below a flat phantom filled with the required tissue-equivalent medium, and positioned at least 20 mm further than the distance that triggers power reduction.
3. It should be ensured that the cables required for power measurements are not interfering with the proximity sensor. Cable losses should be properly compensated to report the measured power results.
4. The back surface or edge is moved toward the phantom in 3 mm steps until the sensor triggers.
5. The back surface or edge is then moved back (further away) from the phantom by at least 5 mm or until maximum output power is returned to the normal maximum level.
6. The back surface or edge is again moved toward the phantom, but in 1 mm steps, until it is at least 5 mm past the triggering point or touching the phantom. If 1 mm resolution is not suitable for the sensor triggering sensitivity, a KDB inquiry should be submitted to determine alternative test configurations.
7. If the tablet is not touching the phantom, it is moved in 3 mm steps until it touches the phantom to confirm that the sensor remains triggered and the maximum power stays reduced.
8. The process is then reversed by moving the tablet away from the phantom according to steps 4) to 7), to determine triggering release, until it is at least 10 mm beyond the point that triggers the return of normal maximum power.
9. The measured output power within ± 5 mm of the triggering points, or until the tablet is touching the phantom, for movements to and from the phantom should be tabulated in the SAR report.
10. If the sensor design and implementation allow additional variations for triggering distance tolerances, multiple samples should be tested to determine the most conservative distance required for SAR evaluation.
11. To ensure all production units are compliant, it is generally necessary to reduce the triggering distance determined from the triggering tests by 1 mm, or more if it is necessary, and use the smallest distance for movements to and from the phantom, minus 1 mm, as the sensor triggering distance for determining the SAR measurement distance.

8.2 PROCEDURES FOR DETERMINING ANTENNA AND PROXIMITY SENSOR COVERAGE

The sensing regions are usually limited to areas near the sensor element. If a sensor is spatially offset from the antenna(s), it is necessary to verify sensor triggering for conditions where the antenna is next to the user but the sensor is laterally further away to ensure sensor coverage is sufficient for reducing the power to maintain compliance. The following are used to determine if additional SAR measurements may be necessary due to sensor and antenna offset. 25 These procedures do not apply and are not required for configurations where the antenna and sensor are collocated and the peak SAR location is overlapping with the sensor.

1. The back surface or edge of the tablet is positioned at a test separation distance less than or equal to the distance required for back surface or edge triggering, with both the antenna and sensor pad located at least 20 mm laterally outside the edge (boundary) of the phantom, along the direction of maximum antenna and sensor offset. For the back surface, if the direction of maximum offset is not aligned with the tablet coordinates (physical edges) the tablet test position would not be aligned with the phantom coordinates (orientations). Each applicable tablet edge should be positioned perpendicularly to the phantom to determine sensor coverage. For antennas and/or sensors located near the corner of a tablet, both adjacent edges must be considered.
2. The similar sequence of steps applied to determine sensor triggering distance in section 6.2 are used to verify back surface and edge sensor coverage by moving the tablet (sensor and antenna) horizontally toward the phantom while maintaining the same vertical separation between the back surface or edge and the phantom.
3. After the exact location where triggering of power reduction is determined, with respect to the sensor and antenna, the tablet movement should be continued, in 3 mm increments, until both the sensor and antenna(s) are fully under the phantom and at least 20 mm inside the phantom edge.
4. The process is then repeated from the opposite direction, starting at the other end of the maximum antenna and sensor offset, by rotating the tablet 180° along the vertical axis.
5. The triggering points should be documented graphically, with the antenna and sensor clearly identified, along with all relevant dimensions.

If the subsequently measured peak SAR location for the antenna is not between the triggering points, established by the sensor coverage tests from opposite ends of the antenna and sensor, additional SAR tests may be required for conditions where only part of the back surface or edge of a tablet corresponding to the antenna is in proximity to the user and the sensor may not be triggering as desired. A KDB inquiry must be submitted by the test lab to determine if additional tests are required and the proper test configurations to use for testing. This may include situations where the sensor coverage region is too small for the antenna, the sensor is located too far away from the antenna, the sensor location is insufficient to cover multiple antennas or the antenna is at the corner of a tablet etc.

8.3 PROXIMITY SENSOR STATUS TABLE OF TRIGGER DISTANCE

As per the KDB 616217 D04 SAR for laptop and tablets v01r02, section 6.2, the following procedure is used to determine the triggering distances.



Proximity Sensor Status Table when DUT is moving towards the phantom


Distance to the DUT (mm)	Proximity Sensor Status – Rear	Proximity Sensor Status – Edge1	Proximity Sensor Status – Edge2
30	OFF	OFF	OFF
27	OFF	OFF	OFF
25	OFF	OFF	OFF
24	OFF	OFF	OFF
23	OFF	OFF	OFF
22	OFF	OFF	OFF
21	OFF	OFF	OFF
20	OFF	OFF	OFF
19	OFF	OFF	OFF
18	OFF	OFF	OFF
17	OFF	OFF	OFF
16	OFF	OFF	OFF
15	OFF	OFF	OFF
14	OFF	OFF	OFF
13	OFF	OFF	OFF
12	OFF	OFF	OFF
11	OFF	OFF	OFF
10	ON	ON	ON
9	ON	ON	ON
8	ON	ON	ON
7	ON	ON	ON
6	ON	ON	ON
5	ON	ON	ON
4	ON	ON	ON
3	ON	ON	ON
2	ON	ON	ON
1	ON	ON	ON
0	ON	ON	ON

Note: When the Sensor fails, the system output power will transmit at the lowest power

8.4 POWER REDUCTION PER AIR-INTERFACE

The following graphs show the power level and the distance from the DUT to the flat phantom for the Bottom.





9 CONDUCTED POWER RESULTS

9.1 CONDUCTED POWER MEASUREMENTS OF UMTS BAND

P-sensor off

Band	UMTS Band II Average Conducted Power(dBm)			
Tx Channel	Max. Tune-up power (dBm)	9262	9400	9538
Rx Channel		9662	9800	9938
Frequency(MHz)		1852.40MHz	1880.0MHz	1907.6MHz
RMC 12.2K	23.50	23.38	23.45	23.41
HSDPA Subtest-1	23.50	23.35	23.36	23.36
HSDPA Subtest-2	23.00	22.87	22.94	22.91
HSDPA Subtest-3	22.50	22.36	22.41	22.39
HSDPA Subtest-4	22.50	22.35	22.41	22.38
HSUPA Subtest-1	23.50	23.32	23.43	23.39
HSUPA Subtest-2	21.50	21.35	21.40	21.37
HSUPA Subtest-3	22.50	22.36	22.45	22.39
HSUPA Subtest-4	21.50	21.34	21.44	21.38
HSUPA Subtest-5	23.50	23.35	23.37	23.38

P-sensor on

Band	UMTS Band II Average Conducted Power(dBm)			
Tx Channel	Max. Tune-up power (dBm)	9262	9400	9538
Rx Channel		9662	9800	9938
Frequency(MHz)		1852.40MHz	1880.0MHz	1907.6MHz
RMC 12.2K	19.00	18.75	18.89	18.87
HSDPA Subtest-1	19.00	18.74	18.84	18.82
HSDPA Subtest-2	18.50	18.24	18.39	18.31
HSDPA Subtest-3	18.00	17.72	17.87	17.84
HSDPA Subtest-4	18.00	17.72	17.84	17.85
HSUPA Subtest-1	19.00	18.73	18.81	18.86
HSUPA Subtest-2	17.00	16.75	16.89	16.86
HSUPA Subtest-3	18.00	17.72	17.86	17.86
HSUPA Subtest-4	17.00	16.74	16.85	16.83
HSUPA Subtest-5	19.00	18.70	18.87	18.86

P-sensor off

Band	UMTS Band IV Average Conducted Power(dBm)			
Tx Channel	Max. Tune-up power (dBm)	1312	1413	1513
Rx Channel		1537	1638	1738
Frequency(MHz)		1712.4MHz	1732.6MHz	1752.6MHz
RMC 12.2K	24.00	23.39	23.65	23.47
HSDPA Subtest-1	24.00	23.30	23.56	23.42
HSDPA Subtest-2	23.50	22.82	23.10	22.91
HSDPA Subtest-3	23.00	22.34	22.65	22.43
HSDPA Subtest-4	23.00	22.34	22.64	22.43
HSUPA Subtest-1	24.00	23.38	23.61	23.41
HSUPA Subtest-2	22.00	21.38	21.63	21.45
HSUPA Subtest-3	23.00	22.38	22.65	22.46
HSUPA Subtest-4	22.00	21.39	21.65	21.42
HSUPA Subtest-5	24.00	23.37	23.60	23.45

P-sensor on

Band	UMTS Band IV Average Conducted Power(dBm)			
Tx Channel	Max. Tune-up power (dBm)	1312	1413	1513
Rx Channel		1537	1638	1738
Frequency(MHz)		1712.4MHz	1732.6MHz	1752.6MHz
RMC 12.2K	19.00	18.40	18.76	18.55
HSDPA Subtest-1	19.00	18.32	18.75	18.54
HSDPA Subtest-2	18.50	17.87	18.24	18.05
HSDPA Subtest-3	18.00	17.39	17.75	17.52
HSDPA Subtest-4	18.00	17.37	17.74	17.52
HSUPA Subtest-1	19.00	18.38	18.75	18.50
HSUPA Subtest-2	17.00	16.35	16.73	16.54
HSUPA Subtest-3	18.00	17.36	17.72	17.52
HSUPA Subtest-4	17.00	16.38	16.75	16.54
HSUPA Subtest-5	19.00	18.37	18.69	18.54

P-sensor off

Band	UMTS Band V Average Conducted Power(dBm)			
Tx Channel	Max. Tune-up power (dBm)	4132	4182	4233
Rx Channel		4357	4407	4458
Frequency(MHz)		826.4MHz	836.4MHz	846.6MHz
RMC 12.2K	23.50	23.41	23.48	23.46
HSDPA Subtest-1	23.50	23.32	23.40	23.40
HSDPA Subtest-2	23.00	22.90	22.91	22.95
HSDPA Subtest-3	22.50	22.39	22.45	22.44
HSDPA Subtest-4	22.50	22.38	22.47	22.45
HSUPA Subtest-1	23.50	23.37	23.45	23.42
HSUPA Subtest-2	21.50	21.36	21.46	21.44
HSUPA Subtest-3	22.50	22.38	22.45	22.42
HSUPA Subtest-4	21.50	21.37	21.43	21.43
HSUPA Subtest-5	23.50	23.35	23.44	23.42

P-sensor on

Band	UMTS Band V Average Conducted Power(dBm)			
Tx Channel	Max. Tune-up power (dBm)	4132	4182	4233
Rx Channel		4357	4407	4458
Frequency(MHz)		826.4MHz	836.6MHz	846.6MHz
RMC 12.2K	22.50	22.44	22.49	22.46
HSDPA Subtest-1	22.50	22.36	22.44	22.43
HSDPA Subtest-2	22.00	21.87	21.95	21.92
HSDPA Subtest-3	21.50	21.42	21.47	21.43
HSDPA Subtest-4	21.50	21.41	21.44	21.43
HSUPA Subtest-1	22.50	22.42	22.46	22.41
HSUPA Subtest-2	20.50	20.41	20.44	20.41
HSUPA Subtest-3	21.50	21.43	21.45	21.41
HSUPA Subtest-4	20.50	20.39	20.46	20.42
HSUPA Subtest-5	22.50	22.38	22.46	22.39

9.2 CONDUCTED POWER MEASUREMENTS OF LTE BAND

LTE Band 2/25

P-sensor off

LTE B2/25/BW=1.4M		Average Conducted Power(dBm)				LTE B2/25/BW=3M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			26047/1850.7	26340/1880	26683/1914.3				26055/1851.5	26340/1880	26675/1913.5
QPSK	1/0	24.00	23.10	23.10	23.02	QPSK	1/0	24.00	23.14	23.17	23.06
	1/2	24.00	23.02	23.13	22.97		1/7	24.00	23.10	23.20	23.03
	1/5	24.00	23.02	23.05	23.03		1/14	24.00	23.08	23.12	23.08
	3/0	23.00	21.99	22.09	21.92		8/0	23.00	22.05	22.17	21.97
	3/1	23.00	22.00	22.12	22.03		8/4	23.00	22.07	22.19	22.08
	3/2	23.00	22.03	22.13	21.94		8/7	23.00	22.10	22.18	21.99
	5/0	23.00	22.08	22.15	22.02		15/0	23.00	22.13	22.19	22.07
16QAM	1/0	23.00	22.01	22.13	21.98	16QAM	1/0	23.00	22.08	22.20	22.03
	1/2	23.00	22.03	22.10	22.05		1/7	23.00	22.11	22.17	22.10
	1/5	23.00	21.99	22.17	21.98		1/14	23.00	22.05	22.21	22.03
	3/0	22.00	21.00	21.06	20.89		8/0	22.00	21.05	21.11	20.94
	3/1	22.00	20.97	21.03	20.96		8/4	22.00	21.04	21.07	21.01
	3/2	22.00	20.97	21.18	21.03		8/7	22.00	21.03	21.24	21.08
	5/0	22.00	21.03	21.12	20.99		15/0	22.00	21.09	21.16	21.04
64QAM	1/0	22.00	21.00	21.07	20.99	64QAM	1/0	22.00	21.07	21.15	21.04
LTE B2/25/BW=5M		Average Conducted Power(dBm)				LTE B2/25/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			26065/1852.5	26340/1880	26665/1912.5				26090/1855	26340/1880	26640/1910
QPSK	1/0	24.00	23.21	23.23	23.13	QPSK	1/0	24.00	23.28	23.28	23.17
	1/12	24.00	23.16	23.25	23.10		1/24	24.00	23.21	23.30	23.15
	1/24	24.00	23.15	23.17	23.15		1/49	24.00	23.22	23.22	23.19
	12/0	23.00	22.09	22.22	22.05		25/0	23.00	22.17	22.27	22.12
	12/6	23.00	22.13	22.24	22.14		25/12	23.00	22.20	22.29	22.21
	12/11	23.00	22.17	22.23	22.07		25/24	23.00	22.22	22.28	22.12
	25/0	23.00	22.21	22.24	22.13		50/0	23.00	22.25	22.29	22.19
16QAM	1/0	23.00	22.13	22.25	22.08	16QAM	1/0	23.00	22.20	22.30	22.15
	1/12	23.00	22.16	22.22	22.16		1/24	23.00	22.23	22.28	22.21
	1/24	23.00	22.11	22.26	22.10		1/49	23.00	22.15	22.32	22.15
	12/0	22.00	21.10	21.16	21.02		25/0	22.00	21.15	21.23	21.10
	12/6	22.00	21.11	21.15	21.08		25/12	22.00	21.15	21.22	21.13
	12/11	22.00	21.10	21.31	21.14		25/24	22.00	21.16	21.36	21.19
	25/0	22.00	21.15	21.22	21.09		50/0	22.00	21.19	21.29	21.16
64QAM	1/0	22.00	21.09	21.16	21.10	64QAM	1/0	22.00	21.17	21.24	21.15

LTE B2/25/BW=15M		Average Conducted Power(dBm)				LTE B2/25/BW=20M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			26115/1857.5	26340/1880	26615/1907.5				26140/1860	26340/1880	26590/1905
QPSK	1/0	24.00	23.32	23.33	23.25	QPSK	1/0	24.00	23.34	23.42	23.31
	1/37	24.00	23.27	23.35	23.21		1/49	24.00	23.30	23.39	23.29
	1/74	24.00	23.27	23.29	23.24		1/99	24.00	23.29	23.38	23.27
	36/0	23.00	22.22	22.32	22.18		50/0	23.00	22.28	22.35	22.24
	36/18	23.00	22.25	22.36	22.28		50/24	23.00	22.30	22.39	22.29
	36/35	23.00	22.27	22.35	22.20		50/49	23.00	22.29	22.37	22.27
	75/0	23.00	22.30	22.34	22.26		100/0	23.00	22.32	22.38	22.29
16QAM	1/0	23.00	22.25	22.37	22.21	16QAM	1/0	23.00	22.31	22.39	22.27
	1/37	23.00	22.28	22.33	22.22		1/49	23.00	22.31	22.36	22.28
	1/74	23.00	22.20	22.38	22.21		1/99	23.00	22.28	22.39	22.28
	36/0	22.00	21.20	21.29	21.18		50/0	22.00	21.29	21.37	21.26
	36/18	22.00	21.20	21.29	21.17		50/24	22.00	21.29	21.34	21.24
	36/35	22.00	21.21	21.38	21.24		50/49	22.00	21.27	21.40	21.27
	75/0	22.00	21.24	21.35	21.24		100/0	22.00	21.30	21.39	21.26
64QAM	1/0	22.00	21.22	21.31	21.20	64QAM	1/0	22.00	21.29	21.36	21.25

P-sensor on

LTE B2/25/BW=1.4M		Average Conducted Power(dBm)				LTE B2/25/BW=3M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			26047/1850.7	26340/1880	26683/1914.3				26055/1851.5	26340/1880	26675/1913.5
QPSK	1/0	19.50	19.10	19.22	19.05	QPSK	1/0	19.50	19.12	19.28	19.08
	1/2	19.50	18.96	19.22	19.11		1/7	19.50	19.03	19.26	19.17
	1/5	19.50	19.06	19.17	19.01		1/14	19.50	19.07	19.21	19.08
	3/0	18.50	18.04	18.14	17.96		8/0	18.50	18.08	18.22	18.01
	3/1	18.50	17.99	18.14	18.03		8/4	18.50	18.04	18.19	18.12
	3/2	18.50	17.97	18.09	18.00		8/7	18.50	18.04	18.12	18.08
	5/0	18.50	18.06	18.04	18.07		15/0	18.50	18.11	18.11	18.11
16QAM	1/0	18.50	18.01	18.19	18.01	16QAM	1/0	18.50	18.09	18.20	18.04
	1/2	18.50	18.02	18.11	18.06		1/7	18.50	18.11	18.18	18.12
	1/5	18.50	17.91	18.19	18.11		1/14	18.50	17.97	18.25	18.14
	3/0	17.50	16.94	17.11	17.04		8/0	17.50	17.01	17.14	17.13
	3/1	17.50	17.02	17.11	17.01		8/4	17.50	17.05	17.16	17.09
	3/2	17.50	17.02	17.16	17.00		8/7	17.50	17.05	17.21	17.03
	5/0	17.50	16.97	17.16	17.11		15/0	17.50	17.05	17.23	17.13
64QAM	1/0	17.50	17.02	17.07	17.10	64QAM	1/0	17.50	17.07	17.11	17.15
LTE B2/25/BW=5M		Average Conducted Power(dBm)				LTE B2/25/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			26065/1852.5	26340/1880	26665/1912.5				26090/1855	26340/1880	26640/1910
QPSK	1/0	19.50	19.15	19.31	19.16	QPSK	1/0	19.50	19.19	19.37	19.19
	1/12	19.50	19.08	19.32	19.18		1/24	19.50	19.12	19.35	19.24
	1/24	19.50	19.12	19.28	19.13		1/49	19.50	19.20	19.30	19.15
	12/0	18.50	18.10	18.24	18.09		25/0	18.50	18.18	18.26	18.14
	12/6	18.50	18.11	18.25	18.15		25/12	18.50	18.19	18.29	18.23
	12/11	18.50	18.06	18.19	18.16		25/24	18.50	18.12	18.28	18.18
	25/0	18.50	18.14	18.20	18.14		50/0	18.50	18.17	18.26	18.15
16QAM	1/0	18.50	18.10	18.29	18.11	16QAM	1/0	18.50	18.19	18.30	18.19
	1/12	18.50	18.16	18.26	18.20		1/24	18.50	18.18	18.31	18.21
	1/24	18.50	18.05	18.27	18.18		1/49	18.50	18.11	18.28	18.19
	12/0	17.50	17.08	17.21	17.14		25/0	17.50	17.12	17.28	17.22
	12/6	17.50	17.11	17.24	17.10		25/12	17.50	17.13	17.29	17.14
	12/11	17.50	17.13	17.25	17.11		25/24	17.50	17.19	17.29	17.16
	25/0	17.50	17.10	17.27	17.16		50/0	17.50	17.15	17.33	17.22
64QAM	1/0	17.50	17.09	17.20	17.18	64QAM	1/0	17.50	17.13	17.26	17.22

LTE B2/25/BW=15M		Average Conducted Power(dBm)				LTE B2/25/BW=20M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			26115/1857.5	26340/1880	26615/1907.5				26140/1860	26340/1880	26590/1905
QPSK	1/0	19.50	19.21	19.40	19.24	QPSK	1/0	19.50	19.30	19.42	19.32
	1/37	19.50	19.20	19.38	19.29		1/49	19.50	19.26	19.39	19.30
	1/74	19.50	19.23	19.32	19.19		1/99	19.50	19.25	19.38	19.28
	36/0	18.50	18.23	18.30	18.17		50/0	18.50	18.24	18.34	18.25
	36/18	18.50	18.21	18.31	18.28		50/24	18.50	18.26	18.39	18.30
	36/35	18.50	18.21	18.36	18.23		50/49	18.50	18.25	18.37	18.28
	75/0	18.50	18.24	18.32	18.21		100/0	18.50	18.28	18.38	18.30
16QAM	1/0	18.50	18.20	18.37	18.26	16QAM	1/0	18.50	18.27	18.39	18.28
	1/37	18.50	18.24	18.33	18.23		1/49	18.50	18.27	18.36	18.29
	1/74	18.50	18.16	18.36	18.25		1/99	18.50	18.24	18.39	18.29
	36/0	17.50	17.17	17.33	17.23		50/0	17.50	17.25	17.37	17.27
	36/18	17.50	17.19	17.33	17.18		50/24	17.50	17.22	17.34	17.25
	36/35	17.50	17.20	17.32	17.20		50/49	17.50	17.23	17.40	17.28
	75/0	17.50	17.19	17.35	17.24		100/0	17.50	17.26	17.39	17.27
64QAM	1/0	17.50	17.18	17.31	17.24	64QAM	1/0	17.50	17.25	17.36	17.26

LTE Band 4/66

P-sensor off

LTE B4/66/BW=1.4M			Average Conducted Power(dBm)			LTE B4/66/BW=3M			Average Conducted Power(dBm)		
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			131979/1710.7	132322/1745	132665/1779.3				131987/1711.5	132322/1745	132657/1778.5
QPSK	1/0	24.00	23.31	23.41	23.19	QPSK	1/0	24.00	23.39	23.43	23.21
	1/2	24.00	23.31	23.36	23.04		1/7	24.00	23.36	23.42	23.06
	1/5	24.00	23.22	23.45	23.03		1/14	24.00	23.26	23.46	23.12
	3/0	23.00	22.27	22.27	22.07		8/0	23.00	22.31	22.33	22.13
	3/1	23.00	22.35	22.32	22.20		8/4	23.00	22.37	22.37	22.23
	3/2	23.00	22.24	22.29	21.99		8/7	23.00	22.30	22.33	22.06
	5/0	23.00	22.31	22.37	22.07		15/0	23.00	22.38	22.39	22.09
16QAM	1/0	23.00	22.34	22.31	22.10	16QAM	1/0	23.00	22.39	22.37	22.18
	1/2	23.00	22.26	22.32	22.07		1/7	23.00	22.35	22.39	22.14
	1/5	23.00	22.31	22.33	22.14		1/14	23.00	22.38	22.41	22.17
	3/0	22.00	21.26	21.27	21.07		8/0	22.00	21.30	21.33	21.15
	3/1	22.00	21.30	21.39	21.08		8/4	22.00	21.35	21.42	21.12
	3/2	22.00	21.26	21.34	21.07		8/7	22.00	21.28	21.42	21.13
	5/0	22.00	21.30	21.32	21.04		15/0	22.00	21.36	21.40	21.11
64QAM	1/0	22.00	21.33	21.27	21.12	64QAM	1/0	22.00	21.35	21.35	21.16
LTE B4/66/BW=5M			Average Conducted Power(dBm)			LTE B4/66/BW=10M			Average Conducted Power(dBm)		
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			131997/1712.5	132322/1745	132647/1777.5				132022/1715	132322/1745	132622/1775
QPSK	1/0	24.00	23.44	23.48	23.23	QPSK	1/0	24.00	23.49	23.56	23.25
	1/12	24.00	23.43	23.49	23.07		1/24	24.00	23.45	23.54	23.16
	1/24	24.00	23.33	23.50	23.19		1/49	24.00	23.37	23.52	23.23
	12/0	23.00	22.32	22.41	22.15		25/0	23.00	22.37	22.46	22.21
	12/6	23.00	22.45	22.45	22.24		25/12	23.00	22.49	22.49	22.29
	12/11	23.00	22.37	22.38	22.14		25/24	23.00	22.44	22.46	22.18
	25/0	23.00	22.46	22.48	22.12		50/0	23.00	22.50	22.52	22.17
16QAM	1/0	23.00	22.46	22.41	22.23	16QAM	1/0	23.00	22.47	22.48	22.25
	1/12	23.00	22.40	22.44	22.18		1/24	23.00	22.47	22.46	22.20
	1/24	23.00	22.46	22.48	22.24		1/49	23.00	22.50	22.51	22.26
	12/0	22.00	21.39	21.40	21.21		25/0	22.00	21.46	21.48	21.28
	12/6	22.00	21.40	21.43	21.19		25/12	22.00	21.42	21.46	21.22
	12/11	22.00	21.36	21.47	21.21		25/24	22.00	21.39	21.49	21.23
	25/0	22.00	21.41	21.45	21.18		50/0	22.00	21.44	21.53	21.20
64QAM	1/0	22.00	21.40	21.37	21.20	64QAM	1/0	22.00	21.47	21.42	21.25

LTE B4/66/BW=15M		Average Conducted Power(dBm)				LTE B4/66/BW=20M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			132047/1717.5	132322/1745	132597/1772.5				132072/1720	132322/1745	132572/1770
QPSK	1/0	24.00	23.53	23.59	23.33	QPSK	1/0	24.00	23.59	23.63	23.36
	1/37	24.00	23.54	23.55	23.25		1/49	24.00	23.58	23.61	23.29
	1/74	24.00	23.46	23.53	23.31		1/99	24.00	23.54	23.57	23.35
	36/0	23.00	22.44	22.51	22.26		50/0	23.00	22.52	22.56	22.31
	36/18	23.00	22.51	22.56	22.31		50/24	23.00	22.55	22.60	22.34
	36/35	23.00	22.51	22.49	22.25		50/49	23.00	22.56	22.58	22.32
	75/0	23.00	22.51	22.54	22.26		100/0	23.00	22.57	22.57	22.30
16QAM	1/0	23.00	22.53	22.57	22.27	16QAM	1/0	23.00	22.58	22.60	22.32
	1/37	23.00	22.53	22.51	22.21		1/49	23.00	22.56	22.58	22.29
	1/74	23.00	22.51	22.56	22.29		1/99	23.00	22.53	22.60	22.33
	36/0	22.00	21.51	21.56	21.30		50/0	22.00	21.57	21.57	21.33
	36/18	22.00	21.46	21.52	21.27		50/24	22.00	21.54	21.55	21.29
	36/35	22.00	21.48	21.57	21.30		50/49	22.00	21.52	21.60	21.34
	75/0	22.00	21.51	21.59	21.23		100/0	22.00	21.55	21.60	21.31
64QAM	1/0	22.00	21.50	21.49	21.33	64QAM	1/0	22.00	21.54	21.57	21.35

P-sensor on

LTE B4/66/BW=1.4M			Average Conducted Power(dBm)			LTE B4/66/BW=3M			Average Conducted Power(dBm)		
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			131979/1710.7	132322/1745	132665/1779.3				131987/1711.5	132322/1745	132657/1778.5
QPSK	1/0	18.50	18.07	18.17	18.01	QPSK	1/0	18.50	18.15	18.19	18.09
	1/2	18.50	17.93	18.11	17.94		1/7	18.50	18.01	18.20	18.00
	1/5	18.50	18.12	18.22	17.98		1/14	18.50	18.18	18.24	18.03
	3/0	17.50	17.11	17.16	17.00		8/0	17.50	17.13	17.22	17.08
	3/1	17.50	17.05	17.15	17.00		8/4	17.50	17.09	17.17	17.08
	3/2	17.50	17.00	17.11	17.07		8/7	17.50	17.04	17.15	17.12
	5/0	17.50	17.08	17.12	17.04		15/0	17.50	17.16	17.16	17.09
16QAM	1/0	17.50	16.97	17.20	16.92	16QAM	1/0	17.50	17.02	17.26	17.00
	1/2	17.50	17.10	17.10	16.99		1/7	17.50	17.14	17.14	17.08
	1/5	17.50	17.09	17.17	17.15		1/14	17.50	17.11	17.20	17.17
	3/0	16.50	16.06	16.12	16.07		8/0	16.50	16.14	16.20	16.12
	3/1	16.50	16.08	16.15	15.92		8/4	16.50	16.12	16.18	15.99
	3/2	16.50	16.10	16.15	15.99		8/7	16.50	16.18	16.21	16.07
	5/0	16.50	16.05	16.21	16.02		15/0	16.50	16.11	16.25	16.07
64QAM	1/0	16.50	16.03	16.21	16.00	64QAM	1/0	16.50	16.11	16.27	16.03
LTE B4/66/BW=5M			Average Conducted Power(dBm)			LTE B4/66/BW=10M			Average Conducted Power(dBm)		
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			131997/1712.5	132322/1745	132647/1777.5				132022/1715	132322/1745	132622/1775
QPSK	1/0	18.50	18.21	18.26	18.15	QPSK	1/0	18.50	18.25	18.31	18.17
	1/12	18.50	18.10	18.29	18.08		1/24	18.50	18.19	18.35	18.12
	1/24	18.50	18.21	18.31	18.10		1/49	18.50	18.23	18.35	18.18
	12/0	17.50	17.18	17.28	17.09		25/0	17.50	17.19	17.35	17.16
	12/6	17.50	17.10	17.23	17.13		25/12	17.50	17.18	17.26	17.15
	12/11	17.50	17.10	17.22	17.19		25/24	17.50	17.14	17.28	17.23
	25/0	17.50	17.23	17.19	17.14		50/0	17.50	17.24	17.28	17.19
16QAM	1/0	17.50	17.08	17.29	17.05	16QAM	1/0	17.50	17.14	17.37	17.10
	1/12	17.50	17.18	17.21	17.15		1/24	17.50	17.19	17.25	17.16
	1/24	17.50	17.16	17.29	17.19		1/49	17.50	17.18	17.31	17.21
	12/0	16.50	16.15	16.27	16.13		25/0	16.50	16.20	16.31	16.19
	12/6	16.50	16.14	16.20	16.06		25/12	16.50	16.18	16.24	16.09
	12/11	16.50	16.23	16.28	16.09		25/24	16.50	16.26	16.31	16.15
	25/0	16.50	16.19	16.30	16.08		50/0	16.50	16.23	16.35	16.17
64QAM	1/0	16.50	16.17	16.32	16.06	64QAM	1/0	16.50	16.20	16.36	16.14

LTE B4/66/BW=15M		Average Conducted Power(dBm)				LTE B4/66/BW=20M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			132047/1717.5	132322/1745	132597/1772.5				132072/1720	132322/1745	132572/1770
QPSK	1/0	18.50	18.30	18.40	18.22	QPSK	1/0	18.50	18.35	18.44	18.30
	1/37	18.50	18.24	18.36	18.19		1/49	18.50	18.28	18.42	18.25
	1/74	18.50	18.27	18.40	18.21		1/99	18.50	18.30	18.42	18.26
	36/0	17.50	17.24	17.41	17.22		50/0	17.50	17.29	17.42	17.27
	36/18	17.50	17.23	17.33	17.22		50/24	17.50	17.31	17.41	17.28
	36/35	17.50	17.21	17.33	17.25		50/49	17.50	17.30	17.39	17.26
	75/0	17.50	17.31	17.32	17.26		100/0	17.50	17.33	17.40	17.28
16QAM	1/0	17.50	17.23	17.40	17.18	16QAM	1/0	17.50	17.30	17.41	17.26
	1/37	17.50	17.26	17.33	17.21		1/49	17.50	17.32	17.42	17.27
	1/74	17.50	17.22	17.40	17.23		1/99	17.50	17.27	17.41	17.27
	36/0	16.50	16.28	16.32	16.22		50/0	16.50	16.30	16.39	16.26
	36/18	16.50	16.25	16.32	16.14		50/24	16.50	16.29	16.38	16.23
	36/35	16.50	16.29	16.40	16.20		50/49	16.50	16.33	16.42	16.23
	75/0	16.50	16.30	16.36	16.20		100/0	16.50	16.31	16.41	16.25
64QAM	1/0	16.50	16.24	16.38	16.16	64QAM	1/0	16.50	16.30	16.40	16.24

LTE Band 5/26
P-sensor off

LTE B5/26/BW=1.4M		Average Conducted Power(dBm)				LTE B5/26/BW=3M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			26722/817.2	26915/836.5	27033/848.3				26730/818	26915/836.5	27025/847.5
QPSK	1/0	24.00	23.34	23.44	23.36	QPSK	1/0	24.00	23.39	23.45	23.42
	1/2	24.00	23.25	23.33	23.35		1/7	24.00	23.34	23.38	23.42
	1/5	24.00	23.21	23.39	23.31		1/14	24.00	23.28	23.46	23.37
	3/0	23.00	22.28	22.44	22.39		8/0	23.00	22.29	22.46	22.41
	3/1	23.00	22.29	22.39	22.42		8/4	23.00	22.36	22.41	22.46
	3/2	23.00	22.25	22.36	22.39		8/7	23.00	22.32	22.43	22.42
	5/0	23.00	22.35	22.44	22.29		15/0	23.00	22.39	22.45	22.34
16QAM	1/0	23.00	22.38	22.38	22.35	16QAM	1/0	23.00	22.43	22.41	22.43
	1/2	23.00	22.29	22.40	22.32		1/7	23.00	22.38	22.46	22.40
	1/5	23.00	22.25	22.31	22.26		1/14	23.00	22.29	22.38	22.28
	3/0	22.00	21.33	21.39	21.31		8/0	22.00	21.34	21.42	21.32
	3/1	22.00	21.25	21.35	21.33		8/4	22.00	21.30	21.40	21.37
	3/2	22.00	21.32	21.29	21.43		8/7	22.00	21.38	21.38	21.47
	5/0	22.00	21.32	21.40	21.32		15/0	22.00	21.35	21.46	21.35
64QAM	1/0	22.00	21.25	21.36	21.36	64QAM	1/0	22.00	21.31	21.45	21.42
LTE B/26/BW=5M		Average Conducted Power(dBm)				LTE B5/26/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			26740/819	26915/836.5	27015/846.5				26765/821.5	26915/836.5	26990/844
QPSK	1/0	24.00	23.41	23.51	23.44	QPSK	1/0	24.00	23.47	23.60	23.52
	1/12	24.00	23.42	23.44	23.46		1/24	24.00	23.47	23.50	23.49
	1/24	24.00	23.37	23.49	23.42		1/49	24.00	23.44	23.52	23.44
	12/0	23.00	22.33	22.50	22.46		25/0	23.00	22.40	22.54	22.47
	12/6	23.00	22.40	22.46	22.47		25/12	23.00	22.47	22.53	22.53
	12/11	23.00	22.39	22.47	22.44		25/24	23.00	22.45	22.51	22.51
	25/0	23.00	22.41	22.47	22.41		50/0	23.00	22.46	22.48	22.48
16QAM	1/0	23.00	22.44	22.44	22.47	16QAM	1/0	23.00	22.47	22.53	22.48
	1/12	23.00	22.39	22.51	22.43		1/24	23.00	22.42	22.56	22.45
	1/24	23.00	22.35	22.40	22.34		1/49	23.00	22.43	22.48	22.41
	12/0	22.00	21.37	21.50	21.39		25/0	22.00	21.45	21.52	21.46
	12/6	22.00	21.38	21.49	21.45		25/12	22.00	21.43	21.51	21.47
	12/11	22.00	21.40	21.45	21.50		25/24	22.00	21.48	21.53	21.53
	25/0	22.00	21.42	21.52	21.43		50/0	22.00	21.49	21.56	21.47
64QAM	1/0	22.00	21.39	21.47	21.45	64QAM	1/0	22.00	21.42	21.54	21.47

LTE B5/26/BW=15M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			26790/824	26915/836.5	26965/841.5
QPSK	1/0	24.00	23.55	23.62	23.56
	1/37	24.00	23.54	23.54	23.53
	1/74	24.00	23.51	23.60	23.51
	36/0	23.00	22.48	22.59	22.54
	36/18	23.00	22.52	22.59	22.54
	36/35	23.00	22.52	22.58	22.53
	75/0	23.00	22.50	22.56	22.52
16QAM	1/0	23.00	22.54	22.56	22.51
	1/37	23.00	22.48	22.57	22.49
	1/74	23.00	22.49	22.54	22.49
	36/0	22.00	21.51	21.56	21.53
	36/18	22.00	21.50	21.58	21.51
	36/35	22.00	21.52	21.59	21.54
	75/0	22.00	21.51	21.60	21.49
64QAM	1/0	22.00	21.49	21.56	21.55

LTE Band 5/26

P-sensor on

LTE B5/26/BW=1.4M		Average Conducted Power(dBm)				LTE B5/26/BW=3M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			26722/817.2	26915/836.5	27033/848.3				26730/818	26915/836.5	27025/847.5
QPSK	1/0	23.00	22.29	22.43	22.29	QPSK	1/0	23.00	22.37	22.50	22.38
	1/2	23.00	22.09	22.37	22.31		1/7	23.00	22.13	22.41	22.33
	1/5	23.00	22.10	22.40	22.27		1/14	23.00	22.16	22.46	22.34
	3/0	22.00	21.14	21.41	21.32		8/0	22.00	21.18	21.47	21.35
	3/1	22.00	21.20	21.39	21.30		8/4	22.00	21.21	21.43	21.33
	3/2	22.00	21.09	21.33	21.25		8/7	22.00	21.18	21.41	21.29
	5/0	22.00	21.17	21.33	21.28		15/0	22.00	21.21	21.39	21.31
16QAM	1/0	22.00	21.12	21.35	21.24	16QAM	1/0	22.00	21.20	21.39	21.31
	1/2	22.00	21.18	21.38	21.24		1/7	22.00	21.20	21.47	21.27
	1/5	22.00	21.12	21.35	21.30		1/14	22.00	21.17	21.43	21.34
	3/0	21.00	20.09	20.34	20.30		8/0	21.00	20.13	20.38	20.35
	3/1	21.00	20.16	20.31	20.21		8/4	21.00	20.22	20.39	20.29
	3/2	21.00	20.12	20.37	20.30		8/7	21.00	20.21	20.44	20.39
	5/0	21.00	20.26	20.32	20.32		15/0	21.00	20.27	20.36	20.38
64QAM	1/0	21.00	20.20	20.40	20.22	64QAM	1/0	21.00	20.23	20.46	20.29
LTE B/26/BW=5M		Average Conducted Power(dBm)				LTE B5/26/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			26740/819	26915/836.5	27015/846.5				26765/821.5	26915/836.5	26990/844
QPSK	1/0	23.00	22.38	22.55	22.39	QPSK	1/0	23.00	22.40	22.59	22.48
	1/12	23.00	22.21	22.47	22.36		1/24	23.00	22.27	22.51	22.43
	1/24	23.00	22.23	22.48	22.42		1/49	23.00	22.28	22.55	22.45
	12/0	22.00	21.24	21.48	21.39		25/0	22.00	21.31	21.52	21.44
	12/6	22.00	21.24	21.51	21.36		25/12	22.00	21.32	21.55	21.42
	12/11	22.00	21.25	21.43	21.35		25/24	22.00	21.31	21.48	21.42
	25/0	22.00	21.26	21.40	21.37		50/0	22.00	21.31	21.47	21.39
16QAM	1/0	22.00	21.25	21.46	21.35	16QAM	1/0	22.00	21.34	21.51	21.41
	1/12	22.00	21.24	21.54	21.34		1/24	22.00	21.28	21.55	21.42
	1/24	22.00	21.25	21.45	21.38		1/49	22.00	21.26	21.50	21.45
	12/0	21.00	20.19	20.45	20.40		25/0	21.00	20.28	20.49	20.42
	12/6	21.00	20.27	20.46	20.37		25/12	21.00	20.30	20.48	20.45
	12/11	21.00	20.29	20.52	20.42		25/24	21.00	20.36	20.54	20.48
	25/0	21.00	20.34	20.45	20.40		50/0	21.00	20.35	20.54	20.43
64QAM	1/0	21.00	20.30	20.51	20.36	64QAM	1/0	21.00	20.34	20.52	20.40

LTE B5/26/BW=15M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			26790/824	26915/836.5	26965/841.5
QPSK	1/0	23.00	22.42	22.61	22.53
	1/37	23.00	22.35	22.59	22.48
	1/74	23.00	22.37	22.59	22.49
	36/0	22.00	21.40	21.57	21.50
	36/18	22.00	21.38	21.58	21.49
	36/35	22.00	21.37	21.56	21.49
	75/0	22.00	21.37	21.53	21.47
16QAM	1/0	22.00	21.37	21.54	21.49
	1/37	22.00	21.36	21.59	21.50
	1/74	22.00	21.34	21.57	21.46
	36/0	21.00	20.35	20.56	20.49
	36/18	21.00	20.36	20.53	20.50
	36/35	21.00	20.38	20.59	20.50
	75/0	21.00	20.40	20.55	20.48
64QAM	1/0	21.00	20.37	20.57	20.48

LTE Band 7

P-sensor off

LTE B7/BW=5M		Average Conducted Power(dBm)				LTE B7/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			20775/2502.5	21100/2535	21425/2567.5				20800/2505	21100/2535	21400/2565
QPSK	1/0	24.00	23.48	23.66	23.55	QPSK	1/0	24.00	23.51	23.74	23.63
	1/12	24.00	23.42	23.68	23.53		1/24	24.00	23.51	23.72	23.62
	1/24	24.00	23.41	23.67	23.56		1/49	24.00	23.50	23.74	23.60
	12/0	23.00	22.46	22.60	22.60		25/0	23.00	22.50	22.67	22.62
	12/6	23.00	22.41	22.67	22.55		25/12	23.00	22.50	22.70	22.64
	12/11	23.00	22.43	22.73	22.55		25/24	23.00	22.50	22.74	22.60
	25/0	23.00	22.41	22.57	22.58		50/0	23.00	22.49	22.65	22.62
16QAM	1/0	23.00	22.37	22.67	22.55	16QAM	1/0	23.00	22.45	22.69	22.57
	1/12	23.00	22.44	22.62	22.50		1/24	23.00	22.47	22.64	22.54
	1/24	23.00	22.41	22.69	22.58		1/49	23.00	22.49	22.71	22.62
	12/0	22.00	21.35	21.59	21.54		25/0	22.00	21.44	21.68	21.62
	12/6	22.00	21.45	21.63	21.51		25/12	22.00	21.49	21.71	21.59
	12/11	22.00	21.41	21.68	21.59		25/24	22.00	21.45	21.74	21.62
	25/0	22.00	21.45	21.61	21.57		50/0	22.00	21.50	21.68	21.59
64QAM	1/0	22.00	21.39	21.60	21.54	64QAM	1/0	22.00	21.46	21.66	21.61
LTE B7/BW=15M		Average Conducted Power(dBm)				LTE B7/BW=20M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			20825/2507.5	21100/2535	21375/2562.5				20850/2510	21100/2535	21350/2560
QPSK	1/0	24.00	23.57	23.82	23.67	QPSK	1/0	24.00	23.63	23.84	23.76
	1/37	24.00	23.57	23.76	23.69		1/49	24.00	23.59	23.81	23.75
	1/74	24.00	23.52	23.76	23.66		1/99	24.00	23.56	23.78	23.69
	36/0	23.00	22.58	22.75	22.67		50/0	23.00	22.60	22.82	22.74
	36/18	23.00	22.55	22.77	22.70		50/24	23.00	22.59	22.81	22.74
	36/35	23.00	22.58	22.77	22.68		50/49	23.00	22.59	22.80	22.71
	75/0	23.00	22.53	22.72	22.70		100/0	23.00	22.61	22.81	22.72
16QAM	1/0	23.00	22.53	22.77	22.64	16QAM	1/0	23.00	22.59	22.81	22.72
	1/37	23.00	22.52	22.73	22.62		1/49	23.00	22.60	22.79	22.69
	1/74	23.00	22.52	22.74	22.66		1/99	23.00	22.56	22.81	22.73
	36/0	22.00	21.50	21.73	21.66		50/0	22.00	21.58	21.80	21.72
	36/18	22.00	21.52	21.72	21.63		50/24	22.00	21.59	21.77	21.69
	36/35	22.00	21.48	21.75	21.68		50/49	22.00	21.56	21.80	21.71
	75/0	22.00	21.58	21.76	21.66		100/0	22.00	21.60	21.81	21.71
64QAM	1/0	22.00	21.51	21.73	21.66	64QAM	1/0	22.00	21.58	21.78	21.70

P-sensor on

LTE B7/BW=5M		Average Conducted Power(dBm)				LTE B7/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			20775/2502.5	21100/2535	21425/2567.5				20800/2505	21100/2535	21400/2565
QPSK	1/0	21.00	20.45	20.75	20.61	QPSK	1/0	21.00	20.50	20.84	20.64
	1/12	21.00	20.49	20.75	20.55		1/24	21.00	20.51	20.77	20.61
	1/24	21.00	20.40	20.74	20.57		1/49	21.00	20.48	20.78	20.65
	12/0	20.00	19.46	19.78	19.54		25/0	20.00	19.51	19.82	19.57
	12/6	20.00	19.50	19.69	19.52		25/12	20.00	19.53	19.74	19.55
	12/11	20.00	19.44	19.73	19.53		25/24	20.00	19.52	19.79	19.60
	25/0	20.00	19.49	19.78	19.52		50/0	20.00	19.53	19.81	19.59
16QAM	1/0	20.00	19.51	19.77	19.57	16QAM	1/0	20.00	19.56	19.79	19.60
	1/12	20.00	19.46	19.70	19.52		1/24	20.00	19.53	19.77	19.57
	1/24	20.00	19.44	19.71	19.51		1/49	20.00	19.52	19.79	19.57
	12/0	19.00	18.44	18.72	18.48		25/0	19.00	18.47	18.73	18.50
	12/6	19.00	18.44	18.64	18.53		25/12	19.00	18.52	18.70	18.56
	12/11	19.00	18.38	18.74	18.48		25/24	19.00	18.47	18.82	18.52
	25/0	19.00	18.49	18.72	18.57		50/0	19.00	18.55	18.80	18.59
64QAM	1/0	19.00	18.36	18.64	18.43	64QAM	1/0	19.00	18.44	18.70	18.49
LTE B7/BW=15M		Average Conducted Power(dBm)				LTE B7/BW=20M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			20825/2507.5	21100/2535	21375/2562.5				20850/2510	21100/2535	21350/2560
QPSK	1/0	21.00	20.57	20.88	20.70	QPSK	1/0	21.00	20.64	20.92	20.71
	1/37	21.00	20.54	20.83	20.63		1/49	21.00	20.61	20.90	20.69
	1/74	21.00	20.51	20.85	20.68		1/99	21.00	20.56	20.87	20.69
	36/0	20.00	19.57	19.84	19.64		50/0	20.00	19.62	19.87	19.67
	36/18	20.00	19.57	19.82	19.61		50/24	20.00	19.60	19.89	19.69
	36/35	20.00	19.57	19.81	19.64		50/49	20.00	19.63	19.86	19.68
	75/0	20.00	19.60	19.83	19.67		100/0	20.00	19.62	19.88	19.69
16QAM	1/0	20.00	19.62	19.87	19.67	16QAM	1/0	20.00	19.63	19.90	19.70
	1/37	20.00	19.60	19.82	19.63		1/49	20.00	19.62	19.86	19.68
	1/74	20.00	19.56	19.82	19.61		1/99	20.00	19.58	19.90	19.64
	36/0	19.00	18.55	18.81	18.58		50/0	19.00	18.60	18.87	18.66
	36/18	19.00	18.53	18.79	18.60		50/24	19.00	18.59	18.85	18.65
	36/35	19.00	18.52	18.87	18.61		50/49	19.00	18.59	18.90	18.69
	75/0	19.00	18.57	18.85	18.61		100/0	19.00	18.60	18.89	18.66
64QAM	1/0	19.00	18.49	18.77	18.57	64QAM	1/0	19.00	18.57	18.86	18.65

LTE Band 12

P-sensor off

LTE B12/BW=1.4M		Average Conducted Power(dBm)				LTE B12/BW=3M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			23017/699.7	23095/707.5	23173/715.3				23025/700.5	23095/707.5	23165/714.5
QPSK	1/0	23.50	23.09	23.14	23.11	QPSK	1/0	23.50	23.13	23.21	23.15
	1/2	23.50	23.04	23.12	23.06		1/7	23.50	23.12	23.19	23.12
	1/5	23.50	23.02	23.11	23.06		1/14	23.50	23.08	23.18	23.11
	3/0	22.50	22.03	22.07	21.99		8/0	22.50	22.09	22.15	22.04
	3/1	22.50	22.03	22.12	22.06		8/4	22.50	22.10	22.19	22.11
	3/2	22.50	22.03	22.12	22.04		8/7	22.50	22.10	22.17	22.09
	5/0	22.50	22.08	22.14	22.07		15/0	22.50	22.13	22.18	22.12
16QAM	1/0	22.50	22.05	22.12	22.05	16QAM	1/0	22.50	22.12	22.19	22.10
	1/2	22.50	22.04	22.08	22.07		1/7	22.50	22.12	22.15	22.12
	1/5	22.50	22.05	22.14	22.06		1/14	22.50	22.11	22.18	22.11
	3/0	21.50	21.07	21.10	21.00		8/0	21.50	21.12	21.15	21.05
	3/1	21.50	21.04	21.05	21.02		8/4	21.50	21.11	21.09	21.07
	3/2	21.50	21.01	21.12	21.06		8/7	21.50	21.07	21.18	21.11
	5/0	21.50	21.07	21.12	21.04		15/0	21.50	21.13	21.16	21.09
64QAM	1/0	21.50	21.05	21.09	21.04	64QAM	1/0	21.50	21.12	21.17	21.09
LTE B5/BW=5M		Average Conducted Power(dBm)				LTE B12/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			23035/701.5	23095/707.5	23155/713.5				23060/704	23095/707.5	23130/711
QPSK	1/0	23.50	23.20	23.27	23.22	QPSK	1/0	23.50	23.27	23.32	23.26
	1/12	23.50	23.18	23.24	23.19		1/24	23.50	23.23	23.29	23.24
	1/24	23.50	23.15	23.23	23.18		1/49	23.50	23.22	23.28	23.22
	12/0	22.50	22.13	22.20	22.12		25/0	22.50	22.21	22.25	22.19
	12/6	22.50	22.16	22.24	22.17		25/12	22.50	22.23	22.29	22.24
	12/11	22.50	22.17	22.22	22.17		25/24	22.50	22.22	22.27	22.22
	25/0	22.50	22.21	22.23	22.18		50/0	22.50	22.25	22.28	22.24
16QAM	1/0	22.50	22.17	22.24	22.15	16QAM	1/0	22.50	22.24	22.29	22.22
	1/12	22.50	22.17	22.20	22.18		1/24	22.50	22.24	22.26	22.23
	1/24	22.50	22.17	22.23	22.18		1/49	22.50	22.21	22.29	22.23
	12/0	21.50	21.17	21.20	21.13		25/0	21.50	21.22	21.27	21.21
	12/6	21.50	21.18	21.17	21.14		25/12	21.50	21.22	21.24	21.19
	12/11	21.50	21.14	21.25	21.17		25/24	21.50	21.20	21.30	21.22
	25/0	21.50	21.19	21.22	21.14		50/0	21.50	21.23	21.29	21.21
64QAM	1/0	21.50	21.14	21.18	21.15	64QAM	1/0	21.50	21.22	21.26	21.20

P-sensor on

LTE B12/BW=1.4M		Average Conducted Power(dBm)				LTE B12/BW=3M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			23017/699.7	23095/707.5	23173/715.3				23025/700.5	23095/707.5	23165/714.5
QPSK	1/0	22.50	22.28	22.28	22.25	QPSK	1/0	22.50	22.30	22.34	22.29
	1/2	22.50	22.17	22.27	22.24		1/7	22.50	22.25	22.31	22.30
	1/5	22.50	22.18	22.26	22.21		1/14	22.50	22.20	22.30	22.28
	3/0	21.50	21.17	21.24	21.15		8/0	21.50	21.20	21.31	21.19
	3/1	21.50	21.13	21.25	21.17		8/4	21.50	21.18	21.30	21.26
	3/2	21.50	21.17	21.19	21.17		8/7	21.50	21.23	21.22	21.25
	5/0	21.50	21.24	21.16	21.29		15/0	21.50	21.29	21.24	21.33
16QAM	1/0	21.50	21.16	21.28	21.16	16QAM	1/0	21.50	21.24	21.30	21.20
	1/2	21.50	21.18	21.17	21.21		1/7	21.50	21.26	21.24	21.27
	1/5	21.50	21.11	21.31	21.28		1/14	21.50	21.17	21.37	21.30
	3/0	20.50	20.14	20.21	20.17		8/0	20.50	20.22	20.24	20.25
	3/1	20.50	20.21	20.17	20.19		8/4	20.50	20.24	20.21	20.27
	3/2	20.50	20.13	20.28	20.18		8/7	20.50	20.17	20.33	20.22
	5/0	20.50	20.15	20.23	20.24		15/0	20.50	20.23	20.30	20.25
64QAM	1/0	20.50	20.21	20.17	20.21	64QAM	1/0	20.50	20.26	20.22	20.26
LTE B5/BW=5M		Average Conducted Power(dBm)				LTE B12/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			23035/701.5	23095/707.5	23155/713.5				23060/704	23095/707.5	23130/711
QPSK	1/0	22.50	22.33	22.37	22.36	QPSK	1/0	22.50	22.37	22.43	22.39
	1/12	22.50	22.30	22.37	22.31		1/24	22.50	22.33	22.40	22.37
	1/24	22.50	22.24	22.37	22.33		1/49	22.50	22.32	22.39	22.35
	12/0	21.50	21.23	21.34	21.27		25/0	21.50	21.31	21.36	21.32
	12/6	21.50	21.25	21.36	21.29		25/12	21.50	21.33	21.40	21.37
	12/11	21.50	21.25	21.29	21.33		25/24	21.50	21.32	21.38	21.35
	25/0	21.50	21.31	21.32	21.36		50/0	21.50	21.35	21.39	21.37
16QAM	1/0	21.50	21.25	21.38	21.26	16QAM	1/0	21.50	21.34	21.40	21.35
	1/12	21.50	21.32	21.32	21.35		1/24	21.50	21.34	21.37	21.36
	1/24	21.50	21.26	21.38	21.34		1/49	21.50	21.31	21.40	21.36
	12/0	20.50	20.29	20.31	20.27		25/0	20.50	20.32	20.38	20.34
	12/6	20.50	20.30	20.30	20.29		25/12	20.50	20.32	20.35	20.32
	12/11	20.50	20.25	20.37	20.30		25/24	20.50	20.30	20.41	20.35
	25/0	20.50	20.28	20.34	20.28		50/0	20.50	20.33	20.40	20.34
64QAM	1/0	20.50	20.28	20.30	20.29	64QAM	1/0	20.50	20.32	20.37	20.33

LTE Band 13

P-sensor off

LTE B13/BW=5M		Average Conducted Power(dBm)				LTE B13/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			23205/779.5	23230/782	23255/784.5					23230/782	
QPSK	1/0	23.50	23.36	23.32	23.38	QPSK	1/0	23.50		23.40	
	1/12	23.50	23.30	23.30	23.31		1/24	23.50		23.37	
	1/24	23.50	23.29	23.28	23.27		1/49	23.50		23.34	
	12/0	22.50	22.34	22.29	22.33		25/0	22.50		22.38	
	12/6	22.50	22.26	22.26	22.25		25/12	22.50		22.32	
	12/11	22.50	22.28	22.29	22.33		25/24	22.50		22.36	
	25/0	22.50	22.28	22.27	22.27		50/0	22.50		22.32	
16QAM	1/0	22.50	22.35	22.34	22.33	16QAM	1/0	22.50		22.37	
	1/12	22.50	22.30	22.28	22.27		1/24	22.50		22.34	
	1/24	22.50	22.36	22.35	22.32		1/49	22.50		22.37	
	12/0	21.50	21.28	21.28	21.31		25/0	21.50		21.35	
	12/6	21.50	21.28	21.31	21.28		25/12	21.50		21.33	
	12/11	21.50	21.32	21.30	21.28		25/24	21.50		21.36	
	25/0	21.50	21.31	21.35	21.33		50/0	21.50		21.37	
64QAM	1/0	21.50	21.26	21.30	21.31	64QAM	1/0	21.50		21.33	

P-sensor on

LTE B13/BW=5M		Average Conducted Power(dBm)				LTE B13/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			23205/779.5	23230/782	23255/784.5					23230/782	
QPSK	1/0	22.50	22.33	22.36	22.37	QPSK	1/0	22.50		22.41	
	1/12	22.50	22.37	22.35	22.33		1/24	22.50		22.39	
	1/24	22.50	22.29	22.28	22.28		1/49	22.50		22.36	
	12/0	21.50	21.32	21.37	21.34		25/0	21.50		21.39	
	12/6	21.50	21.32	21.36	21.31		25/12	21.50		21.38	
	12/11	21.50	21.37	21.35	21.33		25/24	21.50		21.39	
	25/0	21.50	21.31	21.35	21.29		50/0	21.50		21.37	
16QAM	1/0	21.50	21.33	21.30	21.29	16QAM	1/0	21.50		21.38	
	1/12	21.50	21.29	21.30	21.34		1/24	21.50		21.35	
	1/24	21.50	21.27	21.29	21.30		1/49	21.50		21.36	
	12/0	20.50	20.34	20.29	20.32		25/0	20.50		20.36	
	12/6	20.50	20.32	20.26	20.34		25/12	20.50		20.35	
	12/11	20.50	20.38	20.34	20.35		25/24	20.50		20.39	
	25/0	20.50	20.35	20.31	20.34		50/0	20.50		20.36	
64QAM	1/0	20.50	20.28	20.30	20.33	64QAM	1/0	20.50		20.35	

LTE Band 14

P-sensor off

LTE B14/BW=5M		Average Conducted Power(dBm)				LTE B14/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			23305/790.5	23330/793	23355/795.5					23330/793	
QPSK	1/0	23.50	23.39	23.352	23.35	QPSK	1/0	23.50		23.42	
	1/12	23.50	23.37	23.35	23.36		1/24	23.50		23.39	
	1/24	23.50	23.32	23.29	23.28		1/49	23.50		23.36	
	12/0	22.50	22.31	22.30	22.35		25/0	22.50		22.38	
	12/6	22.50	22.35	22.35	22.33		25/12	22.50		22.39	
	12/11	22.50	22.29	22.36	22.28		25/24	22.50		22.37	
	25/0	22.50	22.37	22.34	22.35		50/0	22.50		22.39	
16QAM	1/0	22.50	22.35	22.27	22.32	16QAM	1/0	22.50		22.36	
	1/12	22.50	22.35	22.33	22.35		1/24	22.50		22.37	
	1/24	22.50	22.29	22.31	22.34		1/49	22.50		22.35	
	12/0	21.50	21.37	21.34	21.33		25/0	21.50		21.38	
	12/6	21.50	21.30	21.30	21.32		25/12	21.50		21.39	
	12/11	21.50	21.31	21.33	21.35		25/24	21.50		21.38	
	25/0	21.50	21.27	21.27	21.26		50/0	21.50		21.35	
64QAM	1/0	21.50	21.27	21.29	21.34	64QAM	1/0	21.50		21.36	

P-sensor on

LTE B14/BW=5M		Average Conducted Power(dBm)				LTE B14/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			23305/790.5	23330/793	23355/795.5					23330/793	
QPSK	1/0	22.50	22.41	22.43	22.45	QPSK	1/0	22.50		22.47	
	1/12	22.50	22.39	22.40	22.38		1/24	22.50		22.45	
	1/24	22.50	22.40	22.39	22.37		1/49	22.50		22.42	
	12/0	21.50	21.38	21.38	21.41		25/0	21.50		21.43	
	12/6	21.50	21.39	21.36	21.36		25/12	21.50		21.44	
	12/11	21.50	21.41	21.34	21.38		25/24	21.50		21.42	
	25/0	21.50	21.41	21.41	21.43		50/0	21.50		21.46	
16QAM	1/0	21.50	21.35	21.35	21.36	16QAM	1/0	21.50		21.42	
	1/12	21.50	21.36	21.34	21.39		1/24	21.50		21.41	
	1/24	21.50	21.37	21.40	21.35		1/49	21.50		21.43	
	12/0	20.50	20.40	20.39	20.35		25/0	20.50		20.42	
	12/6	20.50	20.39	20.35	20.38		25/12	20.50		20.41	
	12/11	20.50	20.43	20.43	20.40		25/24	20.50		20.45	
	25/0	20.50	20.35	20.33	20.33		50/0	20.50		20.39	
64QAM	1/0	20.50	20.40	20.36	20.38	64QAM	1/0	20.50		20.41	

LTE Band 41
P-sensor off

LTE B41/BW=5M		Average Conducted Power(dBm)				LTE B41/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			39675/2488.5	40620/2593	41565/2687.5				39700/2501	40620/2593	41540/2685
QPSK	1/0	23.50	23.29	23.23	22.21	QPSK	1/0	23.50	23.31	23.28	22.26
	1/12	23.50	23.24	23.24	22.19		1/24	23.50	23.27	23.29	22.21
	1/24	23.50	23.26	23.32	22.19		1/49	23.50	23.29	23.34	22.24
	12/0	22.50	22.21	22.15	21.05		25/0	22.50	22.25	22.22	21.09
	12/6	22.50	22.26	22.27	21.19		25/12	22.50	22.29	22.30	21.22
	12/11	22.50	22.23	22.20	21.14		25/24	22.50	22.30	22.22	21.23
	25/0	22.50	22.24	22.19	21.16		50/0	22.50	22.26	22.23	21.17
16QAM	1/0	22.50	22.18	22.21	21.23	16QAM	1/0	22.50	22.24	22.25	21.29
	1/12	22.50	22.20	22.29	21.37		1/24	22.50	22.26	22.30	21.41
	1/24	22.50	22.22	22.22	21.49		1/49	22.50	22.24	22.31	21.57
	12/0	21.50	21.25	21.28	20.19		25/0	21.50	21.26	21.29	20.22
	12/6	21.50	21.15	21.14	20.28		25/12	21.50	21.21	21.20	20.31
	12/11	21.50	21.21	21.18	20.30		25/24	21.50	21.25	21.21	20.32
	25/0	21.50	21.21	21.22	19.97		50/0	21.50	21.23	21.30	20.01
64QAM	1/0	21.50	21.18	21.25	20.10	64QAM	1/0	21.50	21.26	21.27	20.17
LTE B41/BW=15M		Average Conducted Power(dBm)				LTE B41/BW=20M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			39725/2503.5	40620/2593	41515/2682.5				39750/2506	40620/2593	41490/2680
QPSK	1/0	23.50	23.34	23.36	22.28	QPSK	1/0	23.50	23.40	23.43	22.31
	1/37	23.50	23.34	23.37	22.30		1/49	23.50	23.36	23.42	22.33
	1/74	23.50	23.32	23.36	22.30		1/99	23.50	23.33	23.41	22.38
	36/0	22.50	22.28	22.29	21.17		50/0	22.50	22.35	22.38	21.24
	36/18	22.50	22.33	22.36	21.28		50/24	22.50	22.36	22.42	21.33
	36/35	22.50	22.32	22.31	21.31		50/49	22.50	22.35	22.39	21.36
	75/0	22.50	22.34	22.32	21.25		100/0	22.50	22.38	22.40	21.29
16QAM	1/0	22.50	22.28	22.32	21.35	16QAM	1/0	22.50	22.34	22.39	21.39
	1/37	22.50	22.29	22.33	21.44		1/49	22.50	22.37	22.37	21.51
	1/74	22.50	22.28	22.38	21.61		1/99	22.50	22.37	22.40	21.63
	36/0	21.50	21.32	21.37	20.24		50/0	21.50	21.35	21.40	20.25
	36/18	21.50	21.29	21.29	20.36		50/24	21.50	21.38	21.36	20.38
	36/35	21.50	21.29	21.27	20.37		50/49	21.50	21.33	21.37	20.41
	75/0	21.50	21.31	21.37	20.09		100/0	21.50	21.39	21.40	20.17
64QAM	1/0	21.50	21.32	21.28	20.25	64QAM	1/0	21.50	21.35	21.36	20.34

P-sensor on

LTE B41/BW=5M		Average Conducted Power(dBm)				LTE B41/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			39675/2488.5	40620/2593	41565/2687.5				39700/2501	40620/2593	41540/2685
QPSK	1/0	22.50	22.26	22.34	21.28	QPSK	1/0	22.50	22.32	22.41	21.30
	1/12	22.50	22.29	22.25	21.16		1/24	22.50	22.31	22.31	21.24
	1/24	22.50	22.12	22.37	21.12		1/49	22.50	22.20	22.38	21.20
	12/0	21.50	21.25	21.24	21.17		25/0	21.50	21.28	21.30	21.21
	12/6	21.50	21.28	21.32	20.24		25/12	21.50	21.32	21.38	20.31
	12/11	21.50	21.18	21.26	20.14		25/24	21.50	21.26	21.29	20.22
	25/0	21.50	21.21	21.36	20.23		50/0	21.50	21.23	21.38	20.26
16QAM	1/0	21.50	21.16	21.14	20.16	16QAM	1/0	21.50	21.24	21.21	20.23
	1/12	21.50	21.30	21.23	20.20		1/24	21.50	21.32	21.28	20.23
	1/24	21.50	21.21	21.26	20.17		1/49	21.50	21.23	21.28	20.24
	12/0	20.50	20.23	20.23	19.15		25/0	20.50	20.24	20.28	19.22
	12/6	20.50	20.21	20.26	19.21		25/12	20.50	20.27	20.33	19.23
	12/11	20.50	20.16	20.32	19.21		25/24	20.50	20.22	20.39	19.27
	25/0	20.50	20.22	20.34	19.26		50/0	20.50	20.24	20.36	19.28
64QAM	1/0	20.50	20.19	20.25	19.15	64QAM	1/0	20.50	20.25	20.31	19.23
LTE B41/BW=15M		Average Conducted Power(dBm)				LTE B41/BW=20M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			39725/2503.5	40620/2593	41515/2682.5				39750/2506	40620/2593	41490/2680
QPSK	1/0	22.50	22.36	22.43	21.35	QPSK	1/0	22.50	22.40	22.46	21.38
	1/37	22.50	22.37	22.40	21.26		1/49	22.50	22.39	22.44	21.35
	1/74	22.50	22.26	22.40	21.28		1/99	22.50	22.34	22.41	21.36
	36/0	21.50	21.29	21.38	21.25		50/0	21.50	21.37	21.42	20.39
	36/18	21.50	21.36	21.39	20.34		50/24	21.50	21.37	21.43	20.35
	36/35	21.50	21.33	21.37	20.25		50/49	21.50	21.36	21.40	20.32
	75/0	21.50	21.30	21.40	20.31		100/0	21.50	21.35	21.44	20.35
16QAM	1/0	21.50	21.28	21.30	20.30	16QAM	1/0	21.50	21.37	21.39	20.34
	1/37	21.50	21.35	21.36	20.25		1/49	21.50	21.38	21.40	20.33
	1/74	21.50	21.27	21.36	20.29		1/99	21.50	21.34	21.42	20.31
	36/0	20.50	20.31	20.33	19.27		50/0	20.50	20.36	20.41	19.32
	36/18	20.50	20.31	20.36	19.27		50/24	20.50	20.35	20.42	19.32
	36/35	20.50	20.29	20.41	19.28		50/49	20.50	20.36	20.43	19.31
	75/0	20.50	20.27	20.44	19.30		100/0	20.50	20.36	20.45	19.32
64QAM	1/0	20.50	20.31	20.38	19.25	64QAM	1/0	20.50	20.34	20.41	19.29

LTE Band 48
P-sensor off

LTE B48/BW=5M		Average Conducted Power(dBm)				LTE B48/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			55265/3552.5	55990/3625	56715/3697.5				55290/3555	55990/3625	56690/3695
QPSK	1/0	23.00	22.50	22.63	22.63	QPSK	1/0	23.00	22.53	22.71	22.71
	1/12	23.00	22.44	22.65	22.61		1/24	23.00	22.53	22.69	22.70
	1/24	23.00	22.43	22.64	22.64		1/49	23.00	22.52	22.71	22.68
	12/0	22.00	21.48	21.57	21.68		25/0	22.00	21.52	21.64	21.70
	12/6	22.00	21.43	21.64	21.63		25/12	22.00	21.52	21.67	21.72
	12/11	22.00	21.45	21.70	21.63		25/24	22.00	21.52	21.71	21.68
	25/0	22.00	21.43	21.54	21.66		50/0	22.00	21.51	21.62	21.70
16QAM	1/0	22.00	21.39	21.64	21.63	16QAM	1/0	22.00	21.47	21.66	21.65
	1/12	22.00	21.46	21.59	21.58		1/24	22.00	21.49	21.61	21.62
	1/24	22.00	21.43	21.66	21.66		1/49	22.00	21.51	21.68	21.70
	12/0	21.00	20.37	20.56	20.62		25/0	21.00	20.46	20.65	20.70
	12/6	21.00	20.47	20.60	20.59		25/12	21.00	20.51	20.68	20.67
	12/11	21.00	20.43	20.65	20.67		25/24	21.00	20.47	20.71	20.70
	25/0	21.00	20.47	20.58	20.65		50/0	21.00	20.52	20.65	20.67
64QAM	1/0	21.00	20.41	20.57	20.62	64QAM	1/0	21.00	20.48	20.63	20.69
LTE B48/BW=15M		Average Conducted Power(dBm)				LTE B48/BW=20M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			55315/3557.5	55990/3625	56665/3692.5				55340/3560	55990/3625	56640/3690
QPSK	1/0	23.00	22.59	22.79	22.75	QPSK	1/0	23.00	22.65	22.81	22.84
	1/37	23.00	22.59	22.73	22.77		1/49	23.00	22.61	22.78	22.83
	1/74	23.00	22.54	22.73	22.74		1/99	23.00	22.58	22.75	22.77
	36/0	22.00	21.60	21.72	21.75		50/0	22.00	21.62	21.79	21.82
	36/18	22.00	21.57	21.74	21.78		50/24	22.00	21.61	21.78	21.82
	36/35	22.00	21.60	21.74	21.76		50/49	22.00	21.61	21.77	21.79
	75/0	22.00	21.55	21.69	21.78		100/0	22.00	21.63	21.78	21.80
16QAM	1/0	22.00	21.55	21.74	21.72	16QAM	1/0	22.00	21.61	21.78	21.80
	1/37	22.00	21.54	21.70	21.70		1/49	22.00	21.62	21.76	21.77
	1/74	22.00	21.54	21.71	21.74		1/99	22.00	21.58	21.78	21.81
	36/0	21.00	20.52	20.70	20.74		50/0	21.00	20.60	20.77	20.80
	36/18	21.00	20.54	20.69	20.71		50/24	21.00	20.61	20.74	20.77
	36/35	21.00	20.50	20.72	20.76		50/49	21.00	20.58	20.77	20.79
	75/0	21.00	20.60	20.73	20.74		100/0	21.00	20.62	20.78	20.79
64QAM	1/0	21.00	20.53	20.70	20.74	64QAM	1/0	21.00	20.60	20.75	20.78

P-sensor on

LTE B48/BW=5M		Average Conducted Power(dBm)				LTE B48/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			55265/3552.5	55990/3625	56715/3697.5				55290/3555	55990/3625	56690/3695
QPSK	1/0	22.00	21.70	21.76	21.76	QPSK	1/0	22.00	21.75	21.85	21.79
	1/12	22.00	21.74	21.76	21.70		1/24	22.00	21.76	21.78	21.76
	1/24	22.00	21.65	21.75	21.72		1/49	22.00	21.73	21.79	21.80
	12/0	21.00	20.71	20.79	21.69		25/0	21.00	20.76	20.83	21.72
	12/6	21.00	20.75	20.70	20.67		25/12	21.00	20.78	20.75	20.70
	12/11	21.00	20.69	20.74	20.68		25/24	21.00	20.77	20.80	20.75
	25/0	21.00	20.74	20.79	20.67		50/0	21.00	20.78	20.82	20.74
16QAM	1/0	21.00	20.76	20.78	20.72	16QAM	1/0	21.00	20.81	20.80	20.75
	1/12	21.00	20.71	20.71	20.67		1/24	21.00	20.78	20.78	20.72
	1/24	21.00	20.69	20.72	20.66		1/49	21.00	20.77	20.80	20.72
	12/0	20.00	19.69	19.73	19.63		25/0	20.00	19.72	19.74	19.65
	12/6	20.00	19.69	19.65	19.68		25/12	20.00	19.77	19.71	19.71
	12/11	20.00	19.63	19.75	19.63		25/24	20.00	19.72	19.83	19.67
	25/0	20.00	19.74	19.73	19.72		50/0	20.00	19.80	19.81	19.74
64QAM	1/0	20.00	19.61	19.65	19.58	64QAM	1/0	20.00	19.69	19.71	19.64
LTE B48/BW=15M		Average Conducted Power(dBm)				LTE B48/BW=20M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			55315/3557.5	55990/3625	56665/3692.5				55340/3560	55990/3625	56640/3690
QPSK	1/0	22.00	21.82	21.89	21.85	QPSK	1/0	22.00	21.89	21.93	21.86
	1/37	22.00	21.79	21.84	21.78		1/49	22.00	21.86	21.91	21.84
	1/74	22.00	21.76	21.86	21.83		1/99	22.00	21.81	21.88	21.84
	36/0	21.00	20.82	20.85	21.79		50/0	21.00	20.87	20.88	21.82
	36/18	21.00	20.82	20.83	20.76		50/24	21.00	20.85	20.90	20.84
	36/35	21.00	20.82	20.82	20.79		50/49	21.00	20.88	20.89	20.83
	75/0	21.00	20.85	20.84	20.82		100/0	21.00	20.87	20.89	20.84
16QAM	1/0	21.00	20.87	20.88	20.82	16QAM	1/0	21.00	20.88	20.91	20.85
	1/37	21.00	20.85	20.83	20.78		1/49	21.00	20.87	20.87	20.83
	1/74	21.00	20.81	20.83	20.76		1/99	21.00	20.83	20.91	20.79
	36/0	20.00	19.80	19.82	19.73		50/0	20.00	19.85	19.88	19.81
	36/18	20.00	19.78	19.80	19.75		50/24	20.00	19.84	19.86	19.80
	36/35	20.00	19.77	19.88	19.76		50/49	20.00	19.84	19.91	19.84
	75/0	20.00	19.82	19.86	19.76		100/0	20.00	19.85	19.90	19.81
64QAM	1/0	20.00	19.74	19.78	19.72	64QAM	1/0	20.00	19.82	19.87	19.80

LTE Band 71

P-sensor off

LTE B71/BW=5M		Average Conducted Power(dBm)				LTE B71/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			133147/665.5	133297/680.5	133447/695.5				133172/668	133297/680.5	133422/693
QPSK	1/0	23.50	23.16	23.22	23.16	QPSK	1/0	23.50	23.19	23.30	23.24
	1/12	23.50	23.10	23.24	23.14		1/24	23.50	23.19	23.28	23.23
	1/24	23.50	23.09	23.23	23.17		1/49	23.50	23.18	23.30	23.21
	12/0	22.50	22.14	22.16	22.21		25/0	22.50	22.18	22.23	22.23
	12/6	22.50	22.09	22.23	22.16		25/12	22.50	22.18	22.26	22.25
	12/11	22.50	22.11	22.29	22.16		25/24	22.50	22.18	22.30	22.21
	25/0	22.50	22.09	22.13	22.19		50/0	22.50	22.17	22.21	22.23
16QAM	1/0	22.50	22.05	22.23	22.16	16QAM	1/0	22.50	22.13	22.25	22.18
	1/12	22.50	22.12	22.18	22.11		1/24	22.50	22.15	22.20	22.15
	1/24	22.50	22.09	22.25	22.19		1/49	22.50	22.17	22.27	22.23
	12/0	21.50	21.03	21.15	21.15		25/0	21.50	21.12	21.24	21.23
	12/6	21.50	21.13	21.19	21.12		25/12	21.50	21.17	21.27	21.20
	12/11	21.50	21.09	21.24	21.20		25/24	21.50	21.13	21.30	21.23
	25/0	21.50	21.13	21.17	21.18		50/0	21.50	21.18	21.24	21.20
64QAM	1/0	19.50	19.14	19.18	19.24	64QAM	1/0	19.50	19.19	19.25	19.26
LTE B71/BW=15M		Average Conducted Power(dBm)				LTE B71/BW=20M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			133197/670.5	133297/680.5	133397/690.5				133222/673	133297/680.5	133372/688
QPSK	1/0	23.50	23.25	23.38	23.28	QPSK	1/0	23.50	23.31	23.40	23.37
	1/37	23.50	23.25	23.32	23.30		1/49	23.50	23.27	23.37	23.36
	1/74	23.50	23.20	23.32	23.27		1/99	23.50	23.24	23.34	23.30
	36/0	22.50	22.26	22.31	22.28		50/0	22.50	22.28	22.38	22.35
	36/18	22.50	22.23	22.33	22.31		50/24	22.50	22.27	22.37	22.35
	36/35	22.50	22.26	22.33	22.29		50/49	22.50	22.27	22.36	22.32
	75/0	22.50	22.21	22.28	22.31		100/0	22.50	22.29	22.37	22.33
16QAM	1/0	22.50	22.21	22.33	22.25	16QAM	1/0	22.50	22.27	22.37	22.33
	1/37	22.50	22.20	22.29	22.23		1/49	22.50	22.28	22.35	22.30
	1/74	22.50	22.20	22.30	22.27		1/99	22.50	22.24	22.37	22.34
	36/0	21.50	21.18	21.29	21.27		50/0	21.50	21.26	21.36	21.33
	36/18	21.50	21.20	21.28	21.24		50/24	21.50	21.27	21.33	21.30
	36/35	21.50	21.16	21.31	21.29		50/49	21.50	21.24	21.36	21.32
	75/0	21.50	21.26	21.32	21.28		100/0	21.50	21.28	21.37	21.29
64QAM	1/0	21.50	21.19	21.29	21.27	64QAM	1/0	21.50	21.26	21.34	21.31

P-sensor on

LTE B71/BW=5M		Average Conducted Power(dBm)				LTE B71/BW=10M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			133147/665.5	133297/680.5	133447/695.5				133172/668	133297/680.5	133422/693
QPSK	1/0	20.50	20.27	20.32	20.31	QPSK	1/0	20.50	20.32	20.41	20.34
	1/12	20.50	20.31	20.32	20.25		1/24	20.50	20.33	20.34	20.31
	1/24	20.50	20.22	20.31	20.27		1/49	20.50	20.30	20.35	20.35
	12/0	19.50	19.28	19.35	20.24		25/0	19.50	19.33	19.39	20.27
	12/6	19.50	19.32	19.26	19.22		25/12	19.50	19.35	19.31	19.25
	12/11	19.50	19.26	19.30	19.23		25/24	19.50	19.34	19.36	19.30
	25/0	19.50	19.31	19.35	19.22		50/0	19.50	19.35	19.38	19.29
16QAM	1/0	19.50	19.33	19.34	19.27	16QAM	1/0	19.50	19.38	19.36	19.30
	1/12	19.50	19.28	19.27	19.22		1/24	19.50	19.35	19.34	19.27
	1/24	19.50	19.26	19.28	19.21		1/49	19.50	19.34	19.36	19.27
	12/0	18.50	18.26	18.29	18.18		25/0	18.50	18.29	18.30	18.20
	12/6	18.50	18.26	18.21	18.23		25/12	18.50	18.34	18.27	18.26
	12/11	18.50	18.20	18.31	18.18		25/24	18.50	18.29	18.39	18.22
	25/0	18.50	18.31	18.29	18.27		50/0	18.50	18.37	18.37	18.29
64QAM	1/0	18.50	18.18	18.21	18.13	64QAM	1/0	18.50	18.26	18.27	18.19
LTE B71/BW=15M		Average Conducted Power(dBm)				LTE B71/BW=20M		Average Conducted Power(dBm)			
Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)			Modulation	RB Size/Offset	Max. Tune-up (dBm)	Channel/Frequency(MHz)		
			133197/670.5	133297/680.5	133397/690.5				133222/673	133297/680.5	133372/688
QPSK	1/0	20.50	20.39	20.45	20.40	QPSK	1/0	20.50	20.46	20.49	20.41
	1/37	20.50	20.36	20.40	20.33		1/49	20.50	20.43	20.47	20.39
	1/74	20.50	20.33	20.42	20.38		1/99	20.50	20.38	20.44	20.39
	36/0	19.50	19.40	19.41	20.34		50/0	19.50	19.42	19.44	19.37
	36/18	19.50	19.37	19.39	19.31		50/24	19.50	19.40	19.43	19.39
	36/35	19.50	19.38	19.38	19.34		50/49	19.50	19.45	19.45	19.38
	75/0	19.50	19.42	19.40	19.37		100/0	19.50	19.40	19.42	19.39
16QAM	1/0	19.50	19.44	19.44	19.37	16QAM	1/0	19.50	19.45	19.47	19.40
	1/37	19.50	19.42	19.39	19.33		1/49	19.50	19.44	19.43	19.38
	1/74	19.50	19.38	19.39	19.31		1/99	19.50	19.40	19.47	19.34
	36/0	18.50	18.37	18.38	18.28		50/0	18.50	18.42	18.44	18.36
	36/18	18.50	18.35	18.36	18.30		50/24	18.50	18.41	18.42	18.35
	36/35	18.50	18.34	18.44	18.31		50/49	18.50	18.41	18.47	18.39
	75/0	18.50	18.39	18.42	18.31		100/0	18.50	18.42	18.46	18.36
64QAM	1/0	18.50	18.31	18.34	18.27	64QAM	1/0	18.50	18.39	18.43	18.35

9.3 SAR TEST RESULTS

General Notes:

1. Per KDB447498 D04, all measurement SAR results are scaled to the maximum tune-up tolerance limit to demonstrate compliant.
2. Per KDB447498 D04, testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is: ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz. When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel must be used.
3. Per KDB865664 D01, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg; if the deviation among the repeated measurement is $\leq 20\%$, and the measured SAR < 1.45 W/kg, only one repeated measurement is required.

WLAN Notes:

1. For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other (remaining) test positions. Otherwise, SAR is evaluated at the subsequent highest peak SAR position until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 for 2.4GHz WIFI single transmission chain operations, the highest measured maximum output power Channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 7.1.4 for more information.
3. Justification for test configurations for WLAN per KDB Publication 248227 for 5GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed power. Other transmission mode was not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2W/kg. See Section 7.1.4 for more information.

10 SAR TEST RESULTS

10.1 BODY SAR TEST RESULTS

SAR test results of WWAN

WCDMA

Body SAR											
P-sensor	Band	Mode	channel	distance (mm)	Ant	Test Position	Max Tune-up Power (dBm)	AVG Power (dBm)	SAR 1g	Reported SAR 1g	Note
on	UMTS Bnad II	RMC12.2K	9400	0	Main	Edge 1	19.00	18.89	0.266	0.273	
off		RMC12.2K	9400	9		Edge 1	23.50	23.45	0.388	0.392	
on		RMC12.2K	9400	0		Edge 2	19.00	18.89	0.049	0.050	
off		RMC12.2K	9400	9		Edge 2	23.50	23.45	0.061	0.062	
on		RMC12.2K	9400	0		Rear	19.00	18.89	0.920	0.944	
		RMC12.2K	9262	0		Rear	19.00	18.75	0.843	0.893	1
		RMC12.2K	9538	0		Rear	19.00	18.87	0.983	1.013	1
off		RMC12.2K	9400	9		Rear	23.50	23.45	0.636	0.643	
on	UMTS Bnad IV	RMC12.2K	1413	0	Main	Edge 1	19.00	18.76	0.268	0.283	
off		RMC12.2K	1413	9		Edge 1	24.00	23.65	0.369	0.400	
on		RMC12.2K	1413	0		Edge 2	19.00	18.76	0.059	0.062	
off		RMC12.2K	1413	9		Edge 2	24.00	23.65	0.070	0.076	
on		RMC12.2K	1413	0		Rear	19.00	18.76	0.974	1.029	
		RMC12.2K	1312	0		Rear	19.00	18.40	0.952	1.093	1
		RMC12.2K	1513	0		Rear	19.00	18.55	0.880	0.976	1
off		RMC12.2K	1413	9		Rear	24.00	23.65	0.626	0.679	
on	UMTS Bnad V	RMC12.2K	4182	0	Main	Edge 1	22.50	22.49	0.253	0.254	
off		RMC12.2K	4182	9		Edge 1	23.50	23.48	0.797	0.801	
on		RMC12.2K	4182	0		Edge 2	22.50	22.49	0.117	0.117	
off		RMC12.2K	4182	9		Edge 2	23.50	23.48	0.033	0.033	
on		RMC12.2K	4182	0		Rear	22.50	22.49	1.130	1.133	
		RMC12.2K	4132	0		Rear	22.50	22.44	1.100	1.115	1
		RMC12.2K	4233	0		Rear	22.50	22.46	1.140	1.151	1
		RMC12.2K	4233	0		Rear	22.50	22.46	1.050	1.060	2
off	RMC12.2K	4182	9	Rear	23.50	23.48	0.494	0.496			

Note:

- Highest reported SAR is > 0.8 W/kg. Added second highest power channel for this test position.
- Repeated measurements are required only when the measured SAR is ≥ 0.80 W/kg. If the measured SAR values are < 1.45 W/kg with $\leq 20\%$ variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. Original SAR = 1.140 W/kg, therefore second times repeat SAR is required.
Repeat SAR = 1.050 W/kg < 1.45 W/kg
SAR variation= -7.89%

LTE

Body SAR															
P-sensor	Band	Mode	channel	RB	Offset	distance (mm)	Ant	Test Position	Max Tune-up Power (dbm)	AVG Power (dbm)	SAR 1g	Reported SAR 1g	Note		
on	LTE Band 2/5	QPSK20M	26340	1	0	0	Main	Edge 1	19.50	19.42	0.273	0.278			
		QPSK20M	26340	50	0	0		Edge 1	18.50	18.34	0.308	0.320			
		off	QPSK20M	26340	1	0		9	Edge 1	24.00	23.42	0.277	0.317		
QPSK20M		26340	50	0	9	Edge 1		23.00	22.35	0.251	0.292				
on		QPSK20M	26340	1	0	0		Edge 2	19.50	19.42	0.128	0.130			
QPSK20M		26340	50	0	0	Edge 2		18.50	18.34	0.117	0.121				
off		QPSK20M	26340	1	0	9		Edge 2	24.00	23.42	0.072	0.082			
QPSK20M		26340	50	0	9	Edge 2		23.00	22.35	0.067	0.078				
on		QPSK20M	26340	1	0	0		Rear	19.50	19.42	1.050	1.070			
		QPSK20M	26140	1	0	0		Rear	19.50	19.30	0.968	1.014	1		
		QPSK20M	26590	1	0	0		Rear	19.50	19.32	1.110	1.157	1		
		QPSK20M	26340	50	0	0		Rear	18.50	18.34	1.110	1.152			
		QPSK20M	26140	50	0	0		Rear	18.50	18.24	1.010	1.072	1		
		QPSK20M	26590	50	0	0		Rear	18.50	18.25	1.130	1.197	1		
		QPSK20M	26590	50	0	0		Rear	18.50	18.25	0.950	1.006	2		
		QPSK20M	26340	100	0	0		Rear	18.50	18.38	1.090	1.121	1		
off		QPSK20M	26340	1	0	9		Rear	24.00	23.42	0.477	0.545			
QPSK20M		26340	50	0	9	Rear		23.00	22.35	0.415	0.482				
on		QPSK20M	132322	1	0	0		Edge 1	18.50	18.44	0.255	0.259			
		QPSK20M	132322	50	0	0		Edge 1	17.50	17.42	0.254	0.259			
off		QPSK20M	132322	1	0	9		Edge 1	24.00	23.63	0.378	0.412			
QPSK20M		132322	50	0	9	Edge 1		23.00	22.56	0.374	0.414				
on		QPSK20M	132322	1	0	0		Edge 2	18.50	18.44	0.051	0.052			
QPSK20M		132322	50	0	0	Edge 2		17.50	17.42	0.048	0.048				
off	QPSK20M	132322	1	0	9	Edge 2	24.00	23.63	0.098	0.107					
QPSK20M	132322	50	0	9	Edge 2	23.00	22.56	0.086	0.095						
on	LTE Band 4/66	QPSK20M	132322	1	0	0	Rear	18.50	18.44	0.823	0.834				
		QPSK20M	132072	1	0	0	Rear	18.50	18.35	0.956	0.990	1			
		QPSK20M	132572	1	0	0	Rear	18.50	18.30	0.920	0.963	1			
		QPSK20M	132322	50	0	0	Rear	17.50	17.42	0.822	0.837				
		QPSK20M	132072	50	0	0	Rear	17.50	17.29	0.947	0.994	1			
		QPSK20M	132572	50	0	0	Rear	17.50	17.27	0.931	0.982	1			
		QPSK20M	132322	100	0	0	Rear	17.50	17.40	0.837	0.856	1			
		QPSK20M	132322	1	0	9	Rear	24.00	23.63	0.771	0.840				
		QPSK20M	132072	1	0	9	Rear	24.00	23.59	1.080	1.187	1			
		QPSK20M	132572	1	0	9	Rear	24.00	23.36	0.973	1.127	1			
		QPSK20M	132322	50	0	9	Rear	23.00	22.56	0.750	0.830				
		QPSK20M	132072	50	0	9	Rear	23.00	22.52	0.897	1.002	1			
off	QPSK20M	132572	50	0	9	Rear	23.00	22.31	0.817	0.958	1				
QPSK20M	132322	100	0	9	Rear	23.00	22.57	0.759	0.838	1					
on	LTE Band 5/26	QPSK15M	26915	1	0	0	Main	Edge 1	23.00	22.61	0.930	1.017			
		QPSK15M	26865	1	0	0		Edge 1	23.00	22.42	0.938	1.072	1		
		QPSK15M	26965	1	0	0		Edge 1	23.00	22.53	0.914	1.018	1		
		QPSK15M	26915	36	0	0		Edge 1	22.00	21.57	0.930	1.027			
		QPSK15M	26865	36	0	0		Edge 1	22.00	21.40	0.976	1.121	1		
		QPSK15M	26965	36	0	0		Edge 1	22.00	21.50	0.908	1.019	1		
		QPSK15M	26915	75	0	0		Edge 1	22.00	21.53	0.918	1.023	1		
		off	QPSK15M	26915	1	0		9	Edge 1	24.00	23.62	0.549	0.599		
		QPSK15M	26915	36	0	9		Edge 1	23.00	22.59	0.432	0.475			
		on	QPSK15M	26915	1	0		0	Edge 2	23.00	22.61	0.103	0.113		
		QPSK15M	26915	36	0	0		Edge 2	22.00	21.57	0.105	0.116			
		off	QPSK15M	26915	1	0		9	Edge 2	24.00	23.62	0.046	0.050		
QPSK15M		26915	36	0	9	Edge 2		23.00	22.59	0.038	0.041				
on		QPSK15M	26915	1	0	0		Rear	23.00	22.61	0.976	1.068			
		QPSK15M	26865	1	0	0		Rear	23.00	22.42	0.983	1.123	1		
		QPSK15M	26965	1	0	0		Rear	23.00	22.53	0.964	1.074	1		
		QPSK15M	26915	36	0	0		Rear	22.00	21.57	0.988	1.091			
		QPSK15M	26865	36	0	0		Rear	22.00	21.40	1.010	1.160	1		
		QPSK15M	26965	36	0	0		Rear	22.00	21.50	0.975	1.094	1		
		QPSK15M	26915	75	0	0		Rear	22.00	21.53	0.981	1.093	1		
		QPSK15M	26915	1	0	9		Rear	24.00	23.62	0.448	0.489			
on		QPSK15M	26915	36	0	9		Rear	23.00	22.59	0.359	0.395			
on		LTE Band 7	QPSK20M	21100	1	0		0	Main	Edge 1	21.00	20.92	0.337	0.343	
			QPSK20M	21100	50	0		0		Edge 1	20.00	19.87	0.359	0.370	
	off		QPSK20M	21100	1	0	9	Edge 1		24.00	23.84	0.410	0.425		
	QPSK20M		21100	50	0	9	Edge 1	23.00		22.82	0.346	0.361			
	on		QPSK20M	21100	1	0	0	Edge 2		21.00	20.92	0.070	0.072		
	QPSK20M		21100	50	0	0	Edge 2	20.00		19.87	0.078	0.080			
	off		QPSK20M	21100	1	0	9	Edge 2		24.00	23.84	0.033	0.034		
	QPSK20M		21100	50	0	9	Edge 2	23.00		22.82	0.028	0.030			
	on		QPSK20M	21100	1	0	0	Rear		21.00	20.92	0.919	0.936		
			QPSK20M	20850	1	0	0	Rear		21.00	20.64	0.772	0.839	1	
			QPSK20M	21350	1	0	0	Rear		21.00	20.71	1.050	1.123	1	
			QPSK20M	21100	50	0	0	Rear		20.00	19.87	0.965	0.994		
QPSK20M		20850	50	0	0	Rear	20.00	19.62	0.819	0.894	1				
QPSK20M		21350	50	0	0	Rear	20.00	19.67	1.080	1.165	1				
QPSK20M		21100	100	0	0	Rear	20.00	19.88	0.945	0.971	1				
QPSK20M		21100	1	0	9	Rear	24.00	23.84	0.261	0.271					
on	QPSK10M	21100	50	0	9	Rear	23.00	22.82	0.259	0.270					
on	LTE Band 12	QPSK10M	23095	1	0	0	Main	Edge 1	22.50	22.43	0.710	0.722			
		QPSK10M	23095	25	0	0		Edge 1	21.50	21.36	0.763	0.788			
		off	QPSK10M	23095	1	0		9	Edge 1	23.50	23.32	0.327	0.341		
		QPSK10M	23095	25	0	9		Edge 1	22.50	22.25	0.280	0.297			
		on	QPSK10M	23095	1	0		0	Edge 2	22.50	22.43	0.137	0.139		
		QPSK10M	23095	25	0	0		Edge 2	21.50	21.36	0.144	0.149			
		off	QPSK10M	23095	1	0		9	Edge 2	23.50	23.32	0.065	0.085		
		QPSK10M	23095	25	0	9		Edge 2	22.50	22.25	0.067	0.071			
		on	QPSK10M	23095	1	0		0	Rear	22.50	22.43	0.892	0.906		
			QPSK10M	23060	1	0		0	Rear	22.50	22.37	0.848	0.874	1	
			QPSK10M	23130	1	0		0	Rear	22.50	22.39	0.939	0.963	1	
			QPSK10M	23095	25	0		0	Rear	21.50	21.36	0.957	0.988		
QPSK10M	23060		25	0	0	Rear	21.50	21.31	0.918	0.959	1				
QPSK10M	23130		25	0	0	Rear	21.50	21.32	0.994	1.036	1				
QPSK10M	23095		50	0	0	Rear	21.50	21.39	0.981	1.006	1				
QPSK10M	23095		1	0	9	Rear	23.50	23.32	0.362	0.377					
on	QPSK10M	23095	25	0	9	Rear	22.50	22.25	0.298	0.316					
on	LTE Band 13	QPSK10M	23230	1	0	0	Main	Edge 1	22.50	22.41	0.931	0.950			
		off	QPSK10M	23230	25	0		0	Edge 1	21.50	21.39	0.980	1.005		
		QPSK10M	23230	50	0	0		Edge 1	21.50	21.37	1.020	1.051			
		QPSK10M	23230	1	0	9		Edge 1	23.50	23.40	0.648	0.663			
		on	QPSK10M	23230	25	0		9	Edge 1	22.50	22.38	0.554	0.570		
		QPSK10M	23230	1	0	0		Edge 2	22.50	22.41	0.201	0.205			
		off	QPSK10M	23230	25	0		0	Edge 2	21.50	21.39	0.166	0.170		
		QPSK10M	23230	1	0	9		Edge 2	23.50	23.40	0.327	0.335			
		on	QPSK10M	23230	25	0		9	Edge 2	22.50	22.38	0.280	0.288		
		QPSK10M	23230	1	0	0		Rear	22.50	22.41	0.979	0.999			
		off	QPSK10M	23230	25	0		0	Rear	21.50	21.39	1.050	1.077		
		QPSK10M	23230	50	0	0		Rear	21.50	21.37	1.070	1.103	1		
QPSK10M	23230	1	0	9	Rear	23.50	23.40	0.054	0.055						
QPSK10M	23230	25	0	9	Rear	22.50	22.38	0.052	0.053						

Body SAR														
P-sensor	Band	Mode	channel	RB	Offset	distance (mm)	Ant	Test Position	Max Tune-up Power (dBm)	AVG Power	SAR 1g	Reported SAR 1g	Note	
on	LTE Band 14	QPSK10M	23330	1	0	0	Main	Edge 1	22.50	22.47	0.899	0.905		
		QPSK10M	23330	25	0	0		Edge 1	21.50	21.43	0.905	0.920		
		QPSK10M	23330	50	0	0		Edge 1	21.50	21.46	0.937	0.946	1	
off		QPSK10M	23330	1	0	9		Edge 1	23.50	23.42	0.456	0.464		
QPSK10M		23330	25	0	9	Edge 1		22.50	22.38	0.368	0.378			
on		QPSK10M	23330	1	0	0		Edge 2	22.50	22.47	0.130	0.131		
QPSK10M		23330	25	0	0	Edge 2		21.50	21.43	0.106	0.108			
off		QPSK10M	23330	1	0	9		Edge 2	23.50	23.42	0.050	0.050		
QPSK10M		23330	25	0	9	Edge 2		22.50	22.38	0.050	0.052			
on		QPSK10M	23330	1	0	0		Rear	22.50	22.47	0.927	0.933		
QPSK10M		23330	25	0	0	Rear		21.50	21.43	0.933	0.948			
off		QPSK10M	23330	50	0	0		Rear	21.50	21.46	0.974	0.983	1	
QPSK10M	23330	1	0	9	Rear	23.50	23.42	0.398	0.405					
QPSK10M	23330	25	0	9	Rear	22.50	22.38	0.327	0.336					
on	LTE Band 41	QPSK20M	40620	1	0	0	Main	Edge 1	22.50	22.46	0.349	0.352		
QPSK20M		40620	50	0	0	Edge 1		21.50	21.42	0.363	0.370			
off		QPSK20M	40620	1	0	9		Edge 1	23.50	23.43	0.233	0.237		
QPSK20M		40620	50	0	9	Edge 1		22.50	22.38	0.192	0.197			
on		QPSK20M	40620	1	0	0		Edge 2	22.50	22.46	0.082	0.082		
QPSK20M		40620	50	0	0	Edge 2		21.50	21.42	0.090	0.092			
off		QPSK20M	40620	1	0	9		Edge 2	23.50	23.43	0.026	0.027		
QPSK20M		40620	50	0	9	Edge 2		22.50	22.38	0.032	0.033			
on		QPSK20M	40620	1	0	0		Rear	22.50	22.46	0.809	0.816		
		QPSK20M	39750	1	0	0		Rear	22.50	22.40	0.477	0.488	1	
		QPSK20M	41490	1	0	0		Rear	22.50	21.38	0.775	1.003	1	
		QPSK20M	40620	50	0	0		Rear	21.50	21.42	0.723	0.736		
	QPSK20M	39750	50	0	0	Rear	21.50	21.37	0.513	0.529	1			
	QPSK20M	41490	50	0	0	Rear	21.50	20.39	0.758	0.979	1			
off	QPSK20M	40620	100	0	0	Rear	21.50	21.44	0.860	0.872	1			
QPSK20M	40620	1	0	9	Rear	23.50	23.43	0.245	0.249					
QPSK20M	40620	50	0	9	Rear	22.50	22.38	0.207	0.213					
on	LTE Band 48	QPSK20M	55990	1	0	0	Main	Edge 1	22.00	21.93	0.113	0.115		
QPSK20M		55990	50	0	0	Edge 1		21.00	20.88	0.118	0.121			
off		QPSK20M	55990	1	0	9		Edge 1	23.00	22.81	0.051	0.053		
QPSK20M		55990	50	0	9	Edge 1		22.00	21.79	0.041	0.043			
on		QPSK20M	55990	1	0	0		Edge 2	22.00	21.93	0.016	0.017		
QPSK20M		55990	50	0	0	Edge 2		21.00	20.88	0.016	0.016			
off		QPSK20M	55990	1	0	9		Edge 2	23.00	22.81	0.002	0.002		
QPSK20M		55990	50	0	9	Edge 2		22.00	21.79	0.004	0.004			
on		QPSK20M	55990	1	0	0		Rear	22.00	21.93	0.584	0.593		
QPSK20M		55990	50	0	0	Rear		21.00	20.88	0.594	0.611			
off		QPSK20M	55990	1	0	9		Rear	23.00	22.81	0.116	0.121		
QPSK20M		55990	50	0	9	Rear		22.00	21.79	0.094	0.098			
on	LTE Band 71	QPSK20M	133297	1	0	0	Main	Edge 1	20.50	20.49	0.907	0.909		
		QPSK20M	133222	1	0	0		Edge 1	20.50	20.46	0.704	0.711	1	
		QPSK20M	133372	1	0	0		Edge 1	20.50	20.41	0.801	0.818	1	
		QPSK20M	133297	50	0	0		Edge 1	19.50	19.44	0.905	0.918		
		QPSK20M	133222	50	0	0		Edge 1	19.50	19.42	0.853	0.869	1	
		QPSK20M	133372	50	0	0		Edge 1	19.50	19.37	0.619	0.638	1	
		QPSK20M	133297	100	0	0		Edge 1	19.50	19.42	0.744	0.758	1	
		off	QPSK20M	133297	1	0		9	Edge 1	23.50	23.40	0.304	0.311	
		QPSK20M	133297	50	0	9		Edge 1	22.50	22.38	0.275	0.283		
		on	QPSK20M	133297	1	0		0	Edge 2	20.50	20.49	0.029	0.029	
		QPSK20M	133297	50	0	0		Edge 2	19.50	19.44	0.026	0.027		
		off	QPSK20M	133297	1	0		9	Edge 2	23.50	23.40	0.015	0.015	
QPSK20M	133297	50	0	9	Edge 2	22.50	22.38	0.018	0.018					
on	QPSK20M	133297	1	0	0	Rear	20.50	20.49	0.573	0.574				
QPSK20M	133297	50	0	0	Rear	19.50	19.44	0.628	0.637					
off	QPSK20M	133297	1	0	9	Rear	23.50	23.40	0.292	0.299				
QPSK20M	133297	50	0	9	Rear	22.50	22.38	0.240	0.247					

Note:

1. Highest reported SAR is > 0.8 W/kg. Added second highest power channel for this test position.
2. Repeated measurements are required only when the measured SAR is ≥ 0.80 W/kg. If the measured SAR values are < 1.45 W/kg with $\leq 20\%$ variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns.

Original SAR = 1.12 W/kg, therefore second times repeat SAR is required.

Repeat SAR = 0.950 W/kg < 1.45 W/kg

SAR variation= -15.93% < 20%

11. SIMULTANEOUS TRANSMISSION CONDITIONS

11.1. STAND-ALONE SAR TEST EXCLUSION

SAR compliance for simultaneous transmission must be considered when the maximum duration of overlapping transmissions, including network hand-offs, is greater than 30 seconds. This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis.

The Simultaneous Transmission Possibilities of this device are as below:

No.	Configuration	Body
1	WWAN + WiFi2.4G	Yes
2	WWAN + BT	Yes
3	WWAN + WiFi5G	Yes
4	WWAN + WiFi6G	Yes
5	WiFi2.4G(Main) +BT	Yes
6	WiFi5G(Main) + BT	Yes
7	WiFi6G(Main) + BT	Yes
8	WiFi2.4G(Main) + WiFi2.4G(Aux)	Yes
9	WiFi5G(Main) + WiFi5G(Aux)	Yes
10	WiFi6G(Main) + WiFi 6G(Aux)	Yes

Note:

- 1.UMTS & LTE share the same antenna and can't transmit simultaneously.
- 2.For the WLAN test result that we reference WLAN report BTL-FCC SAR-1-2409T090 R00 (WLAN FCC ID: FKGR1001).

11.2. SIMULTANEOUS TRANSMISSION CONDITIONS

KDB 447498 D04 General RF Exposure Guidance v01, introduces a new formula for calculating the SAR to Peak Location Ratio (SPLSR) between pairs of simultaneously transmitting antennas:

$$SPLSR = (SAR_1 + SAR_2)^{1.5} / R_i$$

Where:

SAR₁ is the highest Reported or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition

SAR₂ is the highest Reported or estimated SAR for the second of a pair of simultaneous transmitting antennas, in the same test operating mode and exposure condition as the first

R_i is the separation distance between the pair of simultaneous transmitting antennas. When the SAR is measured, for both antennas in the pair, it is determined by the actual x, y and z coordinates in the 1-g SAR for each SAR peak location, based on the extrapolated and interpolated result in the zoom scan measurement, using the formula of $[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$

A new threshold of 0.04 is also introduced in the KDB. Thus, in order for a pair of simultaneous transmitting antennas with the sum of 1-g SAR > 1.6 W/kg to qualify for exemption from Simultaneous Transmission SAR measurements, it has to satisfy the condition of:

$$(SAR_1 + SAR_2)^{1.5} / R_i \leq 0.04$$

11.3. ABOUT WWAN/BT/WIFI

Test Position SAR1g(W/kg)	Rear	Edge1	Edge2	Edge3	Edge4
UMTS Bnad II	1.013	0.392	0.062		
UMTS Bnad IV	1.093	0.400	0.076		
UMTS Bnad V	1.151	0.801	0.117		
LTE Band 2/25	1.197	0.320	0.130		
LTE Band 4/66	1.187	0.414	0.107		
LTE Band 5/26	1.160	1.121	0.116		
LTE Band 7	1.165	0.425	0.080		
LTE Band 12	1.036	0.788	0.149		
LTE Band 13	1.103	1.051	0.335		
LTE Band 14	0.983	0.946	0.131		
LTE Band 41	1.003	0.370	0.092		
LTE Band 48	0.611	0.121	0.017		
LTE Band 71	0.637	0.918	0.029		
WLAN 2.4G WiFi_Main	1.115				0.783
WLAN 2.4G WiFi_Aux	1.181		1.069		
UNII_1 & 2a WiFi_Main	1.006				1.139
UNII_1 & 2a WiFi_Aux	0.929		1.081		
UNII_2c WiFi_Main	0.930				1.089
UNII_2c WiFi_Aux	1.100		0.930		
UNII_3 WiFi_Main	1.067				1.152
UNII_3 WiFi_Aux	1.108		0.860		
UNII_4 WiFi_Main	0.965				1.087
UNII_4 WiFi_Aux	1.146		0.869		
UNII_5 WiFi_Main	0.382				0.196
UNII_5 WiFi_Aux	0.319		0.224		
UNII_6 WiFi_Main	0.402				0.326
UNII_6 WiFi_Aux	0.325		0.233		
UNII_7 WiFi_Main	0.429				0.308
UNII_7 WiFi_Aux	0.378		0.212		
UNII_8 WiFi_Main	0.387				0.242
UNII_8 WiFi_Aux	0.294		0.166		
Bluetooth_DH5	0.683		0.682		
BLE_2M	0.554		0.544		

Test Position SAR _{1g} (W/kg)	Rear	Edge1	Edge2	Edge3	Edge4
WWAN+WLAN MAX $\sum$ SAR _{10g}	2.378	1.121	1.416		1.152
WWAN+BT MAX $\sum$ SAR _{10g}	1.880	1.121	1.017		
WLAN_Main+WLAN_Aux MAX $\sum$ SAR _{10g}	2.261		1.081		1.152
WLAN+BT MAX $\sum$ SAR _{10g}	1.798		1.763		1.152

Note:

1. MAX. $\sum$ SAR_{1g}= 2.378 W/Kg>1.6 W/Kg, so Peak location SAR are required.
2. For the WLAN test result that we reference WLAN report BTL-FCC SAR-1-2409T090 R00 (WLAN FCC ID: FKGR1001).
3. Peak location SAR are 0.02 that refer Appendix E.

12. TEST LAYOUT

Specific Absorption Rate Test Layout




Liquid depth in the flat Phantom ($\geq 15\text{cm}$ depth)

HSL(750MHz)




HSL(900MHz)



HSL(1750-2600MHz)



HSL(3500MHz)



Appendix A. SAR Plots of System Verification

(Pls See BTL-FCC SAR-2-2409T090_Appendix A.)

Appendix B. SAR Plots of SAR Measurement

(Pls See BTL-FCC SAR-2-2409T090_Appendix B.)

Appendix C. Calibration Certificate

(Pls See BTL-FCC SAR-2-2409T090_Appendix C.)

Appendix D. Photographs of the Test Set-Up

(Pls See BTL-FCC SAR-2-2409T090_Appendix D.)

Appendix E. SAR SPLSR

(Pls See BTL-FCC SAR-2-2409T090_Appendix E.)

End of Test Report