

FCC TEST REPORT

for

CISPR PUB. 22 Class B

Equipment : VGA CARD
Model No. : A4-S3S4SD-A7-L
FCC ID : FQIS3S4SD
Filing Type : Original Grant
Applicant : JOYTECH COMPUTER CO., LTD.
3F, No. 1, ALLEY2, SZU-WEI LANE,
CHUNG CHENG RD., HSIN TIEN CITY,
TAIPEI HSIEN, TAIWAN, R.O.C.

- The test result refers exclusively to the test presented test model / sample.
- Without the written authorization of the test lab., the Test Report may not be copied.
- **Certificate or Test Report must not be used by the applicant to claim the product in this test report endorsement by NVLAP or any agency of U.S. government.**

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

Table of Contents

CERTIFICATE OF COMPLIANCE	3
1. General Description of Equipment under Test	4
1.1. Applicant	4
1.2. Manufacturer	4
1.3. Basic Description of Equipment under Test	4
1.4. Feature of Equipment under Test	4
2. Test Configuration of Equipment under Test	5
2.1. Test Manner	5
2.2. Description of Test System	5
2.3. Connection Diagram of Test System	7
3. Test Software	8
4. General Information of Test	9
4.1. Test Facility	9
4.2. Standard for Methods of Measurement	9
4.3. Test in Compliance with	9
4.4. Frequency Range Investigated	9
4.5. Test Distance	9
5. Test of Conducted Powerline	10
5.1. Major Measuring Instruments	10
5.2. Test Procedures	11
5.3. Typical Test Setup Layout of Conducted Powerline	12
5.4. Test Result of AC Powerline Conducted Emission	13
5.5. Photographs of Conducted Powerline Test Configuration	16
6. Test of Radiated Emission	20
6.1. Major Measuring Instruments	20
6.2. Test Procedures	21
6.3. Typical Test Setup Layout of Radiated Emission	22
6.4. Test Result of Radiated Emission	23
6.5. Photographs of Radiated Emission Test Configuration	26
7. Antenna Factor & Cable Loss	28
8. List of Measuring Equipments Used	29



CERTIFICATE OF COMPLIANCE


for

CISPR PUB. 22 Class B

Equipment : VGA CARD
Model No. : A4-S3S4SD-A7-L
FCC ID : FQIS3S4SD
Applicant : JOYTECH COMPUTER CO., LTD.
3F, No. 1, ALLEY2, SZU-WEI LANE,
CHUNG CHENG RD., HSIN TIEN CITY,
TAIPEI HSIEN, TAIWAN, R.O.C.

I **HEREBY** CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4 - 1992** and the energy emitted by this equipment was **passed CISPR PUB. 22** both radiated and conducted emission class B limits. Testing was carried out on Jun. 15, 1999 at **SPORTON International Inc.** LAB. in Lin Kou.

 *Jun 22, 1999*
W. L. Huang
General Manager

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

1. General Description of Equipment under Test

1.1. Applicant

JOYTECH COMPUTER CO., LTD.
3F, No. 1, ALLEY2, SZU-WEI LANE, CHUNG CHENG RD.,
HSIN TIEN CITY, TAIPEI HSIEN, TAIWAN, R.O.C.

1.2. Manufacturer

Same as 1.1.

1.3. Basic Description of Equipment under Test

Equipment : VGA CARD
Model No. : A4-S3S4SD-A7-L
FCC ID : FQIS3S4SD
Trade Name : JOYTECH
Power Supply Type : N/A
Power Cord : N/A

1.4. Feature of Equipment under Test

- High-performance 3D Acceleration
- Single-pass multiple textures
- Hardware bump mapping
- High quality up/down scalar
- Hardware subpicture blending and highlights
- 24-bit digital interface for panel encoders (TMDS Transmitter)
- Support for all resolution up to SXGA at 1024x768@60Hz
- VGA resolution up to 1600x1200 85Hz

2. Test Configuration of Equipment under Test

2.1. Test Manner

- a. The EUT has been associated with personal computer and peripherals pursuant to ANSI C63.4-1992 and configuration operated in a manner which tended to maximize its emission characteristics in a typical application.
- b. The HITACHI Monitor, DELL PS/2 Keyboard, PRIMAX PS/2 Mouse, HP Printer, ACEEX Modem, COMPAQ LCD-Monitor and EUT were connected to the FIC PC for EMI test.
- c. The Following display resolution were investigated during the compliance test:
 1. Horizontal frequency (640x480 to 1,600x1,200, 31.5 KHz to 109 KHz)
 2. Vertical frequency (60 Hz to 100 Hz)
- d. According to the above tests, we listed the following display modes as the worst cases:
 1. 1,024x768 (non-interlanced 48 KHz), refresh rate 60 Hz ;CRT+LCD.
 2. 1,280x1,024 (non-interlanced 109 KHz), refresh rate 100 Hz ; CRT ONLY.
 3. 1,600x1,200 (non-interlanced 106 KHz), refresh rate 85 Hz ; CRT ONLY.
- e. Frequency range investigated: conduction 150 KHz to 30 MHz, radiation 30 MHz to 2000MHz.

2.2. Description of Test System

Support Unit 1. -- Personal Computer (FIC)

FCC ID	: N/A
Model No.	: P2L97
Power Supply Type	: Switching
Power Cord	: Non-Shielded
Serial No.	: SP0006
Data Cable	: Shielded, 360 degree via metal backshells
Remark	: This support device was tested to comply with FCC standards and authorized under a declaration of conformity.

Support Unit 2. -- Monitor (HITACHI)

FCC ID	: N/A
Model No.	: CM753ET
Serial No.	: SP0176
Power Supply Type	: Switching
Power Cord	: Non-Shielded
Data Cable	: Shielded, 360 degree via metal backshells, 1.15m
Remark	: This support device was tested to comply with FCC standards and authorized under a declaration of conformity.

Support Unit 3. -- PS/2 Keyboard (DELL)
 FCC ID : GYUM92SK
 Model No. : AT101(DE8M)
 Serial No. : SP0054
 Data Cable : Shielded, 360 degree via metal backshells, 1.9m


Support Unit 4. -- PS/2 Mouse (PRIMAX)
 FCC ID : EMJMU5JQ
 Model No. : MUS9J
 Serial No. : SP0045
 Data Cable : Shielded, 360 degree via metal backshells, 1.7m

Support Unit 5. -- Modem (ACEEX)
 FCC ID : IFAXDM1414
 Model No. : DM1414
 Power Supply Type : Linear
 Power Cord : Non-Shielded
 Serial No. : SP0059
 Data Cable : Braided-Shielded, 360 degree via metal backshells, 1.15m

Support Unit 6. -- LCD-Monitor (COMPAQ)
 FCC ID : N/A
 Model No. : FP500(306)
 Serial No. : SP0049
 Data Cable : Shielded, 1.7m
 Remark : This support device was tested to comply with FCC standards and authorized under a declaration of conformity.

Support Unit 7. -- PRINTER (HP)
 FCC ID : B94C2642X
 Model No. : DESK JET 400
 Serial No. : SP1040
 Data Cable : Shielded, 360 degree via metal backshells, 1.35m
 Power Supply Type : Linear, Adapter
 Power Cord : Non-shielded

2.3. Connection Diagram of Test System



1. The I/O cable is connected from PC to the support unit 5.
2. The I/O cable is connected from EUT to the support unit 6.
3. The I/O cable is connected from PC to the support unit 3.
4. The I/O cable is connected from EUT to the support unit 2.
5. The Power Cord is connected from Adapter to the support unit 6.
6. The I/O cable is connected from PC to the support unit 4.
7. The I/O cable is connected from PC to the support unit 7.

3. Test Software

Two executive program, EMITEST.EXE & WINFCC.EXE under WIN 98, which generate a complete line of continuously repeating " H " pattern were used as the test software.

The programs were executed as follows :

- a. Turn on the power of all equipment.
- b. The PC reads the test program from the floppy disk drive and runs it.
- c. The PC sends " H " messages to the monitor, and the monitor displays " H " patterns on the screen.
- d. The PC sends " H " messages to the printer, then the printer prints them on the paper.
- e. The PC sends " H " messages to the modem.
- f. The PC sends " H " messages to the internal Hard Disk, and the Hard Disk reads and writes the message.
- g. Repeat the steps from b to f.

4. General Information of Test

4.1. Test Facility

This test was carried out by SPORTON International Inc. in an openarea test site.
Openarea Test Site Location : No. 30-2, Lin 6, Diing-Fwu Tsuen, Lin-Kou-Hsiang,
Taipei Hsien, Taiwan, R.O.C.
TEL : 886-2-2601-1640
FAX : 886-2-2601-1695

4.2. Standard for Methods of Measurement

ANSI C63.4-1992

4.3. Test in Compliance with

CISPR PUB. 22 Class B

4.4. Frequency Range Investigated

- a. Conduction: from 150 kHz to 30 MHz
- b. Radiation : from 30 MHz to 2,000 MHz

4.5. Test Distance

The test distance of radiated emission from antenna to EUT is 10 M.

5. Test of Conducted Powerline

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 115 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-1992 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 5.3. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.


5.1. Major Measuring Instruments

- Test Receiver (HP 8591EM)
 - Attenuation 0 dB
 - Start Frequency 0.15 MHz
 - Stop Frequency 30 MHz
 - Step MHz 0.007 MHz
 - IF Bandwidth 9 KHz

5.2. Test Procedures

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c. All the support units are connect to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 150 kHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- i. If the emission level of the EUT in peak mode was 6 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 6 dB margin will be retested one by one using the quasi-peak method and reported.

5.3. Typical Test Setup Layout of Conducted Powerline



5.4. Test Result of AC Powerline Conducted Emission


5.4.1. Test mode : 1024x768 48K/60Hz (CRT+LCD)

- Temperature : 26°C
- Relative Humidity : 47 %
- Test Date : Jun. 15, 1999

The Conducted Emission test was passed at minimum margin

NEUTRAL 0.243 MHz / 45.00 dBuV.

Freq. (MHz)	Line or Neutral	Meter Reading				Limits				Margin	
		Q.P. (dBuV)	A.V. (dBuV)	Q.P. (uV)	A.V. (uV)	Q.P. (dBuV)	A.V. (dBuV)	Q.P. (uV)	A.V. (uV)	Q.P. (dB)	A.V. (dB)
0.219	L	45.40	44.90	186.21	175.79	62.86	52.86	1389.44	439.38	-17.46	-7.96
0.243	L	44.10	43.30	160.32	146.22	61.98	51.98	1256.06	397.20	-17.88	-8.68
0.280	L	40.20	40.00	102.33	100.00	60.80	50.80	1096.99	346.90	-20.60	-10.80
0.219	N	45.50	45.00	188.36	177.83	62.84	52.84	1386.47	438.44	-17.34	-7.84
0.243	N	45.00	44.30	177.83	164.06	61.98	51.98	1256.05	397.20	-16.98	-7.68
0.280	N	39.90	39.60	98.86	95.50	60.80	50.80	1096.67	346.80	-20.90	-11.20

Test Engineer : 
PETER WANG

FCC TEST REPORT

Report No. : F961107


5.4.2. Test mode : 1280x1024 109K/100Hz (CRT ONLY)

- Temperature : 26°C
- Relative Humidity : 47 %
- Test Date : Jun. 15, 1999

The Conducted Emission test was passed at minimum margin**LINE 0.241 MHz / 45.10 dBuV.**

Freq. (MHz)	Line or Neutral	Meter Reading				Limits				Margin	
		Q.P. (dBuV)	A.V. (dBuV)	Q.P. (uV)	A.V. (uV)	Q.P. (dBuV)	A.V. (dBuV)	Q.P. (uV)	A.V. (uV)	Q.P. (dB)	A.V. (dB)
0.217	L	45.80	45.30	194.98	184.08	62.92	52.92	1399.95	442.70	-17.12	-7.62
0.241	L	45.10	44.50	179.89	167.88	62.06	52.06	1267.90	400.94	-16.96	-7.56
0.279	L	40.50	39.30	105.93	92.26	60.84	50.84	1102.02	348.49	-20.34	-11.54
0.217	N	45.70	45.20	192.75	181.97	62.92	52.92	1399.95	442.70	-17.22	-7.72
0.241	N	44.30	43.60	164.06	151.36	62.07	52.07	1269.51	401.45	-17.77	-8.47
0.279	N	40.80	39.60	109.65	95.50	60.84	50.84	1102.02	348.49	-20.04	-11.24

Test Engineer :


PETER WANG

FCC TEST REPORT

Report No. : F961107


5.4.3. Test mode : 1600x1200 106K/85Hz (CRT ONLY)

- Temperature : 26°C
- Relative Humidity : 47 %
- Test Date : Jun. 15, 1999

The Conducted Emission test was passed at minimum margin**LINE0.167 MHz / 46.40 dBuV.**

Freq. (MHz)	Line or Neutral	Meter Reading				Limits				Margin	
		Q.P. (dBuV)	A.V. (dBuV)	Q.P. (uV)	A.V. (uV)	Q.P. (dBuV)	A.V. (dBuV)	Q.P. (uV)	A.V. (uV)	Q.P. (dB)	A.V. (dB)
0.217	L	46.50	37.80	211.35	77.62	62.94	52.94	1403.60	443.86	-16.44	-15.14
0.242	L	44.30	35.40	164.06	58.88	62.03	52.03	1263.44	399.54	-17.73	-16.63
0.340	L	37.90	28.10	78.52	25.41	59.20	49.20	911.88	288.36	-21.30	-21.10
0.167	N	46.40	37.80	208.93	77.62	65.11	55.11	1801.62	569.72	-18.71	-17.31
0.242	N	44.30	35.40	164.06	58.88	62.03	52.03	1263.44	399.54	-17.73	-16.63
0.340	N	37.70	28.00	76.74	25.12	59.20	49.20	911.89	288.36	-21.50	-21.20


Test Engineer :


PETER WANG

6.2. Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 10 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a half wave dipole and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 6 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 6 dB margin will be repeated one by one using the quasi-peak method and reported.

6.3. Typical Test Setup Layout of Radiated Emission



6.4. Test Result of Radiated Emission

6.4.1. Test mode : 1024x768 48K/60Hz (CRT+LCD)

- Test Distance : 10 M
- Temperature : 28°C
- Relative Humidity : 73 %
- Test Date : Jun. 11, 1999
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

The Radiated Emission test was passed at minimum margin

227.200 MHz / 26.96 dBuV (HORIZONTAL) Antenna Height 2.8 Meter, Turntable Degree 145 °.

Frequency (MHz)	Polarity	Antenna Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Limits		Emission (dBuV/m)	Level (uV/m)	Margin (dB)
					(dBuV/m)	(uV/m)			
65.043	V	5.54	0.90	19.03	30.00	31.62	25.47	18.77	-4.53
227.200	V	11.09	1.63	13.95	30.00	31.62	26.67	21.55	-3.33
178.860	H	9.30	1.49	15.52	30.00	31.62	26.31	20.68	-3.69
196.212	H	8.88	1.48	14.98	30.00	31.62	25.34	18.49	-4.66
211.200	H	9.77	1.57	14.82	30.00	31.62	26.16	20.32	-3.84
227.200	H	11.09	1.63	14.24	30.00	31.62	26.96	22.28	-3.04

Test Engineer : Terry Chang
Terry Chang

FCC TEST REPORT

Report No. : F961107

6.4.2. Test mode : 1280x1024 109K/100Hz (CRT ONLY)

- Test Distance : 10 M
- Temperature : 28°C
- Relative Humidity : 73 %
- Test Date : Jun. 11, 1999
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

The Radiated Emission test was passed at minimum margin**118.057 MHz / 24.10 dBuV (VERTICAL) Antenna Height 1.3 Meter, Turntable Degree 69 °.**

Frequency (MHz)	Polarity	Antenna Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Limits		Emission (dBuV/m)	Level (uV/m)	Margin (dB)
					(dBuV/m)	(uV/m)			
60.794	V	5.52	0.98	15.58	30.00	31.62	22.08	12.71	-7.92
72.385	V	6.10	0.96	16.19	30.00	31.62	23.25	14.54	-6.75
83.284	V	8.08	0.96	11.13	30.00	31.62	20.17	10.20	-9.83
118.057	V	12.48	1.20	10.42	30.00	31.62	24.10	16.03	-5.90
118.576	H	5.55	0.90	17.63	30.00	31.62	24.08	16.00	-5.92
358.415	H	13.81	2.19	11.47	37.00	70.79	27.47	23.63	-9.53

Test Engineer : Terry Chang
Terry Chang

FCC TEST REPORT

Report No. : F961107

6.4.3. Test mode : 1600x1200 106K/85Hz (CRT ONLY)

- Test Distance : 10 M
- Temperature : 28°C
- Relative Humidity : 73 %
- Test Date : Jun. 11, 1999
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

The Radiated Emission test was passed at minimum margin**57.284 MHz / 24.65 dBuV (VERTICAL) Antenna Height 1.5 Meter, Turntable Degree 211 °.**

Frequency (MHz)	Polarity	Antenna Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Limits		Emission (dBuV/m)	Level (uV/m)	Margin (dB)
					(dBuV/m)	(uV/m)			
57.284	V	6.23	0.88	17.54	30.00	31.62	24.65	17.08	-5.35
70.136	V	5.56	0.90	16.78	30.00	31.62	23.24	14.52	-6.76
85.360	V	8.45	1.00	11.62	30.00	31.62	21.07	11.31	-8.93
401.453	V	15.58	2.11	11.65	37.00	70.79	29.34	29.31	-7.66
114.770	H	12.27	1.20	10.04	30.00	31.62	23.51	14.98	-6.49
400.656	H	15.57	2.10	11.09	37.00	70.79	28.76	27.42	-8.24

Test Engineer : Terry Chang
Terry Chang

7. Antenna Factor & Cable Loss

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)
30	17.9	0.6
35	16.1	0.7
40	14.0	0.7
45	10.5	0.8
50	7.9	0.7
55	6.7	0.8
60	5.5	1.0
65	5.5	0.9
70	5.6	0.9
75	6.5	1.0
80	7.5	0.9
85	8.5	1.0
90	9.4	1.0
95	10.4	1.1
100	11.5	1.1
110	12.1	1.2
120	12.6	1.2
130	12.0	1.3
140	11.6	1.3
150	10.5	1.3
160	10.5	1.4
170	9.8	1.4
180	9.2	1.5
190	9.0	1.6
200	8.8	1.4
220	10.5	1.7
240	12.2	1.5
260	13.1	1.8
280	13.2	1.8
300	13.4	1.9
320	13.4	1.9
340	13.4	2.0
360	13.9	2.2
380	14.9	2.1
400	15.6	2.1
450	16.4	2.3
500	16.6	2.5
550	19.7	2.4
600	19.3	2.8
650	20.0	2.9
700	19.5	2.9
750	18.5	2.7
800	17.8	3.5
850	18.3	3.3
900	20.5	3.2
950	21.4	4.5
1000	21.2	3.5
2000	31.57	6.2

8. List of Measuring Equipments Used

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver (site 2)	HP	8591EM	3710A01187	9 KHz - 18 GHz	Sep. 18, 1998	Conduction
LISN (EUT) (site 2)	Telemeter	NNB-2/16Z	98009	50 ohm / 50 uH	Jan. 22, 1999	Conduction
LISN (Support Unit) (site 2)	EMCO	3810/2NM	9703-1839	50 ohm / 50 uH	Jul. 06, 1998	Conduction
Amplifier (Site 5)	HP	87405A	3207A01437	10MHz -3.0GHz	June 26, 1998	Radiation
Spectrum Analyzer (Site 5)	HP	8594A	3051A00172	9KHz -2.9GHz	Apr. 18, 1999	Radiation
Bilog Antenna (Site 5)	CHASE	CBL6112A	2287	30MHz -2GHz	Jan. 07, 1999	Radiation
Half-wave dipole antenna (Site 5)	EMCO	3121C	9705-1285	28 M - 1GHz	May 19, 1999	Radiation
Turn Table (site 5)	EMCO	2080	9711-2021	0 ~ 360 degree	N/A	Radiation
Antenna Mast (site 5)	EMCO	2075	9711-2115	1 m- 4 m	N/A	Radiation



D700701

SPORTON LAB.

Certificate No:

CERTIFICATE OF COMPLIANCE

Authorized under Declaration of Conformity
according to

47 CFR, Part 2 and Part 15 of the FCC Rules

Equipment Under Test : **PERSONAL COMPUTER**

Model No. : **P2L97**

Applicant : **FIRST INTERNATIONAL COMPUTER INC.**

6F, Formosa Plastics Rear Building 201,
Tung Hwa N. Rd., Taipei, Taiwan, R.O.C.



CERTIFY THAT:

THE MEASUREMENTS SHOWN IN THIS TEST REPORT WERE MADE IN
ACCORDANCE WITH THE PROCEDURES GIVEN IN **ANSI C63.4 - 1992**
AND THE ENERGY EMITTED BY THIS EQUIPMENT WAS **PASSED** BOTH
RADIATED AND CONDUCTED EMISSIONS CLASS B LIMITS. THE TESTING
WAS COMPLETED ON **SEP. 02, 1997** AT **SPORTON INTERNATIONAL**
INC. LAB. IN NEI HWU.

W. L. Huang OCT 02, 97

W. L. Huang

GENERAL MANAGER

6. Test of Radiated Emission

Radiated emissions from 30 MHz to 2,000 MHz were measured with a bandwidth of 120 kHz according to the methods defines in ANSI C63.4-1992. The EUT was placed on a nonmetallic stand in the open-field site, 0.8 meter above the ground plane, as shown in section 6.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.

6.1. Major Measuring Instruments

- Amplifier (HP 87405A)
 - Attenuation 0 dB
 - RF Gain 20 dB
 - Signal Input 10 MHz to 3 GHz

- Spectrum Analyzer (HP 8594A)
 - Attenuation 0 dB
 - Start Frequency 30 MHz
 - Stop Frequency 2000 MHz
 - Resolution Bandwidth 1 MHz
 - Video Bandwidth 1 MHz
 - Signal Input 9 KHz to 2.9 GHz

- Quasi-Peak Adapter (HP 8594A)
 - Resolution Bandwidth 120 KHz
 - Frequency Band 30 MHz to 1 GHz
 - Quasi-Peak Detector ON for Quasi-Peak Mode
OFF for Peak Mode